



index.qmd x

Render on Save ABC 🔍 Render ⚙️

+c ⬆️ ⬆️ Run ⌂ Publish

Source Visual Outline

```
1 ---
2 title: "Reproducible Report: Lincoln Weather Analysis"
3 format: html
4 ---
5
6 ## Lincoln, NE 2016 Temperature Distribution
7
8 ### Overview
9
10 This Quarto document demonstrates how to integrate external data, R code, and advanced visualizations
11 into a single, seamless report. We are using the built-in lincoln_weather dataset from the ggridges
12 package to explore the distribution of mean daily temperatures throughout the year 2016.
13 Ridge Plot Visualization
14
15 ```{r}
16 # Load necessary visualization and data libraries
17 library(ggplot2)
18 library(ggribes)
19 library(viridis)
20
21 # Load the data, which is included in the ggridges package
22 lincoln_weather <- ggribes::lincoln_weather
23
24 # Generate the plot
25 ggplot(
26   lincoln_weather,
27   # Use after_stat(x) for the fill aesthetic, representing the temperature gradient
28   aes(x = 'Mean Temperature [F]', y = 'Month', fill = after_stat(x))
29 ) +
30   geom_density_ridges_gradient(scale = 3, rel_min_height = 0.01) +
31   scale_fill_viridis(name = "Temp [F]", option = "C")
```

12:1 Overview ↕ Quarto ↕

index.qmd &gt; Lincoln, NE 2016 Temperature Distribution &gt; Overview

```
1 ---
2 title: "Reproducible Report: Lincoln Weather Analysis"
3 format: html
4 ---
5
6 ## Lincoln, NE 2016 Temperature Distribution
7
8 ### Overview
9
10 This Quarto document demonstrates how to integrate external data, R code, and
11 advanced visualizations into a single, seamless report. We are using the
12 built-in lincoln_weather dataset from the ggribes package to explore the
13 distribution of mean daily temperatures throughout the year 2016.
14 Ridge Plot Visualization
15
16 > Run Cell
17 ```{r}
18 # Load necessary visualization and data libraries
19 library(ggplot2)
20 library(ggribes)
21 library(viridis)
22
23 # Load the data, which is included in the ggribes package
24 lincoln_weather <- ggribes::lincoln_weather
25
26 # Generate the plot
27 ggplot(
28   lincoln_weather,
29   # Use after_stat(x) for the fill aesthetic, representing the temperature
30   # gradient
31   aes(x = `Mean Temperature [F]`, y = `Month`, fill = after_stat(x))
32 ) +
33   geom_density_ridges_gradient(scale = 3, rel_min_height = 0.01) +
34   scale_fill_viridis(name = "Temp. [F]", option = "C") +
```



quarto®














A solid blue circle with a white capital letter 'R' centered inside it.

R






```

1
2 title: "Reproducible Report: Lincoln Weather Analysis"
3 format: html
4 ---
5
6 ## Lincoln, NE 2016 Temperature Distribution
7
8 ### Overview
9
10 This Quarto document demonstrates how to integrate external data, R code, and advanced visualizations
11 into a single, seamless report. We are using the built-in lincoln_weather dataset from the ggridges
12 package to explore the distribution of mean daily temperatures throughout the year 2016.
13 Ridge Plot Visualization
14
15 ```{r}
16 # Load necessary visualization and data libraries
17 library(ggplot2)
18 library(ggridges)
19 library(viridis)
20
21 # Load the data, which is included in the ggridges package
22 lincoln_weather <- ggridges::lincoln_weather
23
24 # Generate the plot
25 ggplot(
26   lincoln_weather,
27   # Use after_stat(x) for the fill aesthetic, representing the temperature gradient
28   aes(x = 'Mean Temperature [F]', y = 'Month', fill = after_stat(x))
29 ) +
30   geom_density_ridges_gradient(scale = 3, rel_min_height = 0.01) +
31   scale_fill_viridis(name = "Temp. [F]", option = "C")
32 ```

```



```

1 ---
2 title: "Reproducible Report: Lincoln Weather Analysis"
3 format: html
4 ---
5
6 ## Lincoln, NE 2016 Temperature Distribution
7
8 ### Overview
9
10 This Quarto document demonstrates how to integrate external data, R code, and
11 advanced visualizations into a single, seamless report. We are using the
12 built-in lincoln_weather dataset from the ggridges package to explore the
13 distribution of mean daily temperatures throughout the year 2016.
14 Ridge Plot Visualization
15
16 > Run Cell
17 ```{r}
18 # Load necessary visualization and data libraries
19 library(ggplot2)
20 library(ggridges)
21 library(viridis)
22
23 # Load the data, which is included in the ggridges package
24 lincoln_weather <- ggridges::lincoln_weather
25
26 # Generate the plot
27 ggplot(
28   lincoln_weather,
29   # Use after_stat(x) for the fill aesthetic, representing the temperature
30   gradient
31   aes(x = 'Mean Temperature [F]', y = 'Month', fill = after_stat(x))
32 ) +
33   geom_density_ridges_gradient(scale = 3, rel_min_height = 0.01) +
34   scale_fill_viridis(name = "Temp. [F]", option = "C") +

```



Environment History Connections Tutorial

Files Plots Packages Help Viewer Presentation

Edit Publish

## Reproducible Report: Lincoln Weather Analysis

### Lincoln, NE 2016 Temperature Distribution

#### Overview

This Quarto document demonstrates how to integrate external data, R code, and advanced visualizations into a single, seamless report. We are using the built-in lincoln\_weather dataset from the ggridges package to explore the distribution of mean daily temperatures throughout the year 2016. Ridge Plot Visualization

```
# Load necessary visualization and data libraries
library(ggplot2)
library(ggridges)
library(viridis)
```

Loading required package: viridisLite

```
# Load the data, which is included in the ggridges package
lincoln_weather <- ggridges::lincoln_weather

# Generate the plot
ggplot(
  lincoln_weather,
  # Use after_stat(x) for the fill aesthetic, representing the temperature
  aes(x = `Mean Temperature [F]`, y = `Month`, fill = after_stat(x))
) +
  geom_density_ridges_gradient(scale = 3, rel_min_height = 0.01) +
  scale_fill_viridis(name = "Temp. [F]", option = "C") +
  labs(
    title = "Monthly Mean Temperature Distributions in Lincoln NE (2016)",
    subtitle = "Higher density indicates more days at that specific temperature",
  ) +
```

SESSION CONNECTIONS HELP VIEWER

← → ↺ http://localhost:5801/ Zoom: (Auto) ⌵ ⌵

## Reproducible Report: Lincoln Weather Analysis

### Lincoln, NE 2016 Temperature Distribution

#### Overview

This Quarto document demonstrates how to integrate external data, R code, and advanced visualizations into a single, seamless report. We are using the built-in lincoln\_weather dataset from the ggridges package to explore the distribution of mean daily temperatures throughout the year 2016. Ridge Plot Visualization

```
# Load necessary visualization and data libraries
library(ggplot2)
library(ggridges)
library(viridis)
```

Loading required package: viridisLite

```
# Load the data, which is included in the ggridges package
lincoln_weather <- ggridges::lincoln_weather

# Generate the plot
ggplot(
  lincoln_weather,
  # Use after_stat(x) for the fill aesthetic, representing the temperature gradient
  aes(x = `Mean Temperature [F]`, y = `Month`, fill = after_stat(x))
) +
  geom_density_ridges_gradient(scale = 3, rel_min_height = 0.01) +
  scale_fill_viridis(name = "Temp. [F]", option = "C") +
  labs(
    title = "Monthly Mean Temperature Distributions in Lincoln NE (2016)",
    subtitle = "Higher density indicates more days at that specific temperature.",
  ) +
  theme_ridges() +
  theme(plot.title.position = "plot")
```

Picking joint bandwidth of 3.37

#### Monthly Mean Temperature Distributions in Lincoln NE (2016)

Higher density indicates more days at that specific temperature.

Ln 39, Col 1 Spaces: 4 UTF-8 LF Quarto