



**Part Number :** [480372100](#)

**Product Description :** Universal Serial Bus (USB)  
Shielded I/O Plug, Type A, Right-Angle, Surface Mount,  
Straight Tab 4.80mm, 0.76µm Gold (Au) Plating, PCB  
Thickness 1.60mm, Tape on Reel Package, Lead-Free

**Series Number :** 48037

**Status :** Active

**Product Category :** I/O Connectors



## Documents and Resources

### Drawings

[480372100 sd.pdf](#)

[PK-48037-210-002.pdf](#)

### 3D Models and Design Files

[STEP AP242](#)

[SOLIDWORKS](#)

[Creo](#)

[Symbol and Footprint \(Multi-Format\)](#)

### Specifications

[PS-48037-001-001.pdf](#)

[TS-48037-001-001.pdf](#)

## Product Environment Compliance

### Compliance

|                    |                                                                                                         |
|--------------------|---------------------------------------------------------------------------------------------------------|
| GADSL/IMDS         | Compliant with Exemption 33                                                                             |
| China RoHS         |  per SJ/T 11365-2006 |
| EU ELV             | Not Relevant                                                                                            |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21                                                                          |
| REACH SVHC         | Not Contained per D(2025)7771-DC (04 Feb 2026)                                                          |
| EU RoHS            | Compliant per EU 2015/863                                                                               |

Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest

- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

---

**Part Details**

**General**

|                |                                                                                                                                                                                           |
|----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Status         | Active                                                                                                                                                                                    |
| Category       | I/O Connectors                                                                                                                                                                            |
| Series         | 48037                                                                                                                                                                                     |
| Description    | Universal Serial Bus (USB)<br>Shielded I/O Plug, Type A, Right-Angle, Surface Mount, Straight Tab 4.80mm, 0.76µm Gold (Au) Plating, PCB Thickness 1.60mm, Tape on Reel Package, Lead-Free |
| Application    | Wire-to-Board                                                                                                                                                                             |
| Comments       | Straight Tab 4.80mm                                                                                                                                                                       |
| Component Type | Plug                                                                                                                                                                                      |
| Product Name   | USB                                                                                                                                                                                       |
| Standard       | USB 2.0                                                                                                                                                                                   |
| Type           | A                                                                                                                                                                                         |
| UPC            | 822350302760                                                                                                                                                                              |

**Electrical**

|                               |             |
|-------------------------------|-------------|
| Current - Maximum per Contact | 1.5A        |
| Shielded                      | Yes         |
| Shield Type                   | Full Shield |

|                   |               |
|-------------------|---------------|
| Voltage - Maximum | 150V AC (RMS) |
|-------------------|---------------|

## Physical

|                                |                       |
|--------------------------------|-----------------------|
| Circuits (Loaded)              | 4                     |
| Circuits (maximum)             | 4                     |
| Color - Resin                  | Black                 |
| Gender                         | Male                  |
| Keying to Mating Part          | Yes                   |
| Lock to Mating Part            | Yes                   |
| Material - Metal               | Brass                 |
| Material - Plating Mating      | Gold                  |
| Material - Plating Termination | Tin                   |
| Mounting Style                 | Top-Mount             |
| Net Weight                     | 1.908/g               |
| Number of Rows                 | 1                     |
| Orientation                    | Right Angle           |
| Packaging Type                 | Embossed Tape on Reel |
| Panel Mount                    | Yes                   |
| PCB Locator                    | Yes                   |
| PCB Retention                  | Yes                   |
| PCB Thickness - Recommended    | 1.60mm                |
| Pitch - Mating Interface       | 2.00mm, 2.50mm        |
| Pitch - Termination Interface  | 2.00mm, 2.50mm        |
| Plating min - Mating           | 0.762µm               |
| Polarized to Mating Part       | Yes                   |
| Polarized to PCB               | Yes                   |
| Ports                          | 1                     |
| Temperature Range - Operating  | -20° to +85°C         |
| Termination Interface Style    | Surface Mount         |
| Waterproof / Dustproof         | No                    |

---

## Mates With / Use With

### Mates with Part(s)

| Description | Part Number |
|-------------|-------------|
|-------------|-------------|

|            |                       |
|------------|-----------------------|
| Mates With | USB Type A Receptacle |
|------------|-----------------------|

---

This document was generated on Jun 28, 2026