

```
<ri:Resource xsi:type="vs:CatalogService">
  <title>Example Data For Identifiers in VOResource</title>
  <identifier>ivo://org.gavo.dc/hsoy/q/q</identifier>
  <altIdentifier>doi:10.555/fictional-resource</altIdentifier>
  <curation>
    <publisher>E.X Ample Data Providers</publisher>
    <creator altIdentifier="https://orcid.org/0000-0001-2345-6789">
      <name>Uthor, A.</name>
    </creator>
    <contact>...</contact>
  </curation>
  <content>
    ...
    <source format="bibcode">2018ivoa.spec.0625P</source>
    <relationship>
      <relationshipType>IsDerivedFrom</relationshipType>
      <relatedResource altIdentifier="doi:10.555/fi
        >Generic non-VO data</relatedResource>
      </relationship>
    </content>
  </ri:Resource>
```

The diagram illustrates the following annotations:

- The VO-internal IVOID** points to the `<identifier>` tag.
- A DOI describing the full record** points to the `<altIdentifier>` tag.
- An ORCID for an author** points to the `altIdentifier` attribute of the `<creator>` tag.
- A Bibcode to cite** points to the `<source format="bibcode">` tag.
- A DOI for VO-external data** points to the `altIdentifier` attribute of the `<relatedResource>` tag.