



Git rules

1) each PR should be independent, it should be created from `develop` branch, and ONLY from `develop`

2) `master` or `main` is ONLY for init commit and production. while development ONLY init commit should be on master. Even if you work alone in a repo

3) delete your remote branches if they are not in use

4) PR rules:

PR rules

5) Commit rules:

Commit naming rules

6) Review:

- At least once a day send a PR link to your project chat, tag your team members, and Liudmyla

Stick to these rules if you want three PRs to pass the test and not have to redo the work :)

How do I add a template to a project?

1. Create a new directory `.github` with the file `pull_request_template.md` in the root directory.
2. In the created file `.github/pull_request_template.md` add the following rules:

Describe your changes

- I did an awesome feature.

Issue ticket code (and/or) and link

- [Link to JIRA ticket](#https://ticket-url)

General

- [] Assigned myself to the PR
- [] Assigned the appropriate labels to the PR
- [] Assigned the appropriate reviewers to the PR
- [] Updated the documentation
- [] Performed a self-review of my code
- [] Types for input and output parameters
- [] Don't have "any" on my code
- [] Used the try/catch pattern for error handling
- [] Don't have magic numbers
- [] Compare only with constants not with strings
- [] No ternary operator inside the ternary operator
- [] Don't have commented code
- [] no links in the code, env links should be in env file (for example: server url), constant links (for example default avatar URL) should be in constant file.
- [] Used camelCase for variables and functions
- [] Date and time formats are on the constants
- [] Functions are public only if it's used outside the class
- [] No hardcoded values
- [] covered by tests
- [] Check your commit messages meet the [conventional commit format](https://www.conventionalcommits.org/en/v1.0.0/).

Frontend

- [] Components and business logic are separated
- [] Colors, Font Size, and Font Name is on the theme or in the constants
- [] No text in the components, use i18n approach
- [] No inline styles
- [] Imports are absolute

- [] Attach a screenshot if PR has visual changes.

Backend

- [] Swagger documentation updated
- [] Database requests are optimized and not redundant
- [] Unit tests written
- [] use ConfigService instead of process.env
- [] use transactions if there is a call chain that mutates data in different tables
- [] use @index decorator for frequently requested data

Pr checklist:

1.1 Common

1.1.1 types for input and output params

1.1.2 no `any`, should be also added to eslint rules

1.1.3 try/catch for any async function

1.1.4 no `magic` numbers

1.1.5 compare only with constants not with strings

(instead of `user === 'admin'`, better `user === roles.admin`)

1.1.6 no ternary operator inside ternary operator (bad example: `question ? first: second ? third: fourth`)

1.1.7 avoid similar types with duplicating by generics

1.1.8 no `console.log` in pr

1.1.9 .env file should be in .gitignore

1.1.10 delete commented code if it's not part of documentation

1.1.11 no links in the code, env links should be in env file (for example: server url), constant links (for example default avatar URL) should be in constant file

1.1.12 `constants` and `function` names should be lowercase.

1.1.13 no dates format in the code (like `"dd/MM/yyyy"`), move it in global constant variable

1.1.14 import rules. imports should come in a specific order: node modules, absolute path, relative path

1.1.15 strings should be in the constant variable. Example: instead of '15 3 * * *',
const EACH_DAY_15h_15min = '15 3 * * *'

1.2 Backend

1.2.1 swagger for each endpoint. add in the documentation, different types of responses.

on a successful response (2xx), on unsuccessful response (4xx, 5xx)

1.2.2 less requests to db, all data should be taken with one query

1.2.3 `public` in method use only is use function externally

1.2.4 use ConfigService instead of `process.env`

1.2.5 use `@`@index`` decorator for frequently requested data

1.2.6 use transactions if there is a call chain that mutates data in different tables

1.2.7. add a set of rules for nestjs to the .eslint config file. It helps to prevent bugs and confusing moments

1.2.8 use REST API Naming Convention for endpoints.

P.S: more information about RESTful API design by Microsoft

1.2.9 use 'UUIDs' for primary key, **to prevent Enumeration Attacks.**

1.3 Frontend|Mobile

1.3.1 split component and logic (move logic to custom hook file)

1.3.2 colors, font size, and font name should be in the theme or in the constants

1.3.3 no text in the components, use i18n approach, even if you have only one language for now

1.3.4 inline styles prohibited

1.3.5 import should be absolute. instead of `../../components/myComponent` should be `components/myComponent`

