Наконечник-вилка для ISO-пневмоцилиндров Серия GKM



Номер для заказа

Типоразмер	C55	C85, C76	C95, C96,CP96			
8	_	– GKM4-8				
10						
12 16	_	GKM6-12	_			
20	GKM8-16	GKM8-16	_			
	GKM8-16-YCLIP	GKM8-16-YCLIP	_			
25	GKM8-16	GKM10-20	_			
	GKM8-16-YCLIP	GKM10-20-YPIN	_			
32	GKM10-20	GKM10-20A	GKM10-20			
	GKM10-20-YPIN	_	GKM10-20-YPIN			
40	GKM10-20	GKM12-24A	GKM12-24			
	GKM10-20-YPIN	_	GKM12-24-YPIN			
50	GKM12-24	_	GKM16-32			
	GKM12-24-YPIN	_	GKM16-32-YPIN			

Типоразмер							
	C55	C85, C76	C95, C96,CP96				
63	GKM12-24	_	GKM16-32				
	GKM12-24-YPIN	_	GKM16-32-YPIN				
80	GKM16-32	_	GKM20-40				
	GKM16-32-YPIN	_	GKM20-40-YPIN				
100	GKM16-32	_	GKM20-40				
	GKM16-32-YPIN	_	GKM20-40-YPIN				
125	_	_	GKM30-54				
	_	_	GKM30-54-YPIN				
160	_	_	GKM35-54				
	_	_	GKM35-54-YPIN				
200	_	_	GKM35-54				
	_	_	GKM35-54-YPIN				
250	_	_	GKM40-84				

^{*} В комплект поставки входит шплинт с шайбой. Для исполнения -YPIN: шплинт и шайба. Для исполнения -YCLIP: шплинт и клипса.

Размеры

Модель	е	b	d	øf _{h11} (вал)	øf нэ (отв.)	l1	с (мин.)	а (макс.)
GKM4-8	M4	4	16	4	4	-	8	8
GKM6-12	M6	6	24	6	6	_	12	12
GKM8-16	M8 x 1.25	8	32 (30)	8	8	_	16	16
GKM8-16-YCLIP						(40)	(15)	
GKM10-20	M10 x 1.25	10	40	10	10	52	20	20
GKM10-20-YPIN								(19)
GKM10-20A	M10	10	40	10	10	52	20	20
GKM12-24	M12 x 1.25	12	48	12	12	62	24	24
GKM12-24-YPIN								(25.4)
GKM12-24A	M12	12	48	12	12	62	24	24
GKM16-32	M16 x 1.5	16	64	16	16	83	32	32
GKM16-32-YPIN								
GKM20-40	M20 x 1.5	20	80	20	20	105	40	40
GKM20-40-YPIN								(44.4)
GKM30-54	M27 x 2.0	30	110	30	30	148	54	55
GKM30-54-YPIN								
GKM35-54 ¹	M36 x 2.0	35	144	35	35	201	54	70
GKM35-54-YPIN						(191)	(72)	
GKM40-84	M42 x 2	40	168	40	40	245	84	85

Øf h11

^{*} В круглых скобках () приведены значения для исполнений -YPIN (либо YCLIP).