Swirl Jet Diffuser STD/STD1





Description
Swirl jet diffuser with radial fixed blades **STD/STD1**.

Application
Supply/ exhaust of the air flow


Characteristics
Recommended for rooms between 2.60 to 4.00 meters in height.
Depending on the technical and architectural requirements, the diffuser is produced with round or rectangular front **R/C.**
Blade design, radial layout and swirl action, result in a high level induction rate.
The diffuser should be embedded into the ceiling to ensure a stable horizontal discharge of air.
The diffuser is supplied with seals, screw fastening and masking plastic lid.

Accessories
Insulated/Non-insulated adapter **ADP IZ/N**.


Materials and finishing
Pickled steel sheet electrostatic field painted white RAL 9016.
Other RAL colors available on request.

Technical design


STD-R




STD-C



STD1-R



STD1-C



Assembly method
Paneled ceiling 600 x 600 mm mounting, fitted with a central screw M6 x 100 mm.

Selection table STD/STD1

STD-R / STD-C

Air flow (m^3/h)	595 x 595 / D595	
	Ak [m^2]	0.0367
300	Veff[m/s] X [m] NR [dB(A)] △Pt [pa]	2.27 1.80 22.00 22.00
450	Veff[m/s] X [m] NR [dB(A)] △Pt [pa]	3.41 3.30 25.00 30.00
500	Veff[m/s] X [m] NR [dB(A)] △Pt [pa]	3.78 3.90 35.00 33.00
600	Veff[m/s] X [m] NR [dB(A)] △Pt [pa]	4.54 4.80 45.00 38.00
700	Veff[m/s] X [m] NR [dB(A)] △Pt [pa]	5.30 5.70 64.00 43.00
800	Veff[m/s] X [m] NR [dB(A)] △Pt [pa]	6.06 6.10 79.00 49.00

STD1-R / STD1-C

Air flow (m^3/h)	595 x 595 /D595	
	Ak [m^2]	0.058
300	Veff[m/s] X [m] NR [dB(A)] △Pt [pa]	1.44 2.60 - 8.00
450	Veff[m/s] X [m] NR [dB(A)] △Pt [pa]	2.16 3.80 15.00 18.00
500	Veff[m/s] X [m] NR [dB(A)] △Pt [pa]	2.39 4.20 18.00 20.00
600	Veff[m/s] X [m] NR [dB(A)] △Pt [pa]	2.87 5.00 26.10 26.00
700	Veff[m/s] X [m] NR [dB(A)] △Pt [pa]	3.35 5.70 35.00 32.00
800	Veff[m/s] X [m] NR [dB(A)] △Pt [pa]	3.83 6.70 44.70 36.00

Annotation

* Ak [m²] - Free surface
* Veff[m/s] - Air velocity inside the diffuser
* X [m] - Air jet length
* NR [dB(A)] - Noise level without the room attenuation
* ΔPt [pa] - Pressure loss

Order codes

Type	-	R/C	+	ADP IZ/N	/	O
STD **STD1**		Rectangular \ Circular		Insulated/ Non-insulated adapter		**0** Painted white RAL 9016 **R** Other RAL paints