Circular Valve VN/VLB/VLA



Description
Stainless steel circular valve for exhaust/supply of the air flow.

Application
Supply/ exhaust of the airflow


Characteristics
VN - Circular valve with adjustable central cone for air flow adjustments.
- Mounting frame with mounting holes and clips provided
VLA - Exterior valve with blades, 1.5 x 1.5 mm mesh and sealing gasket.
- Clips on the connector and mounting holes on the outer frame
VLB - Exterior valve with 10 x 10 mm mesh and sealing gasket.
- Clips on the connector and mounting holes on the outer frame.


Materials and finishing
Stainless steel, natural finish.

Assembly Methods
Mounting with screw and/or using the clamp located at the connection/framework.


Technical design


VLA





VLB





Type	Ø1	Ø2	H
VN	100	140	50
	125	170	50
	150	218	63
	160	218	63
	200	298	80
VLA	100	147	50
	125	187	50
	150	210	61
	160	210	64
	200	270	73
VLB	100	147	50
	125	187	50
	150	210	61
	160	210	64
	200	270	73

Selection table VN, VLA, VLB

VN						
Air flow (m^3/h)	Dimensions (mm)	100	125	150	160	200
30	X [m]	0.21				
	ΔPt [pa]	14.00				
40	X [m]	0.42	0.32			
	ΔPt [pa]	27.00	12.00			
60	X [m]	0.75	0.45	0.30	0.20	
	ΔPt [pa]	50.00	25.00	3.00	2.00	
80	X [m]	1.10	0.70	0.50	0.43	
	ΔPt [pa]	95.00	55.00	1.00	9.00	
130	X [m]		1.50	1.00	0.95	1.2
	ΔPt [pa]		125.00	25.00	25.00	45.00
190	X [m]			1.80	1.70	1.7
	ΔPt [pa]			56.00	50.00	60.00
220	X [m]					2.10
	ΔPt [pa]					120.00

VLA				
Air flow (m^3/h)	Dimensions (mm)	100	125	150
30	Veff[m/s]	1.00	0.80	
	ΔPt [pa]	6.50	5.00	
60	Veff[m/s]	2.00	1.40	1.00
	ΔPt [pa]	23.00	18.00	7.00
80	Veff[m/s]	3.00	1.90	1.30
	ΔPt [pa]	45.00	27.00	13.00
110	Veff[m/s]	4.00	2.50	1.80
	ΔPt [pa]	90.00	47.00	23.00
140	Veff[m/s]	5.00	3.20	2.20
	ΔPt [pa]	145.00	72.00	34.00
170	Veff[m/s]		3.90	2.70
	ΔPt [pa]		125.00	50.00
180	Veff[m/s]		4.00	2.90
	ΔPt [pa]		137.00	58.00
190	Veff[m/s]		4.20	3.00
	ΔPt [pa]		150.00	67.00
220	Veff[m/s]		5.00	3.50
	ΔPt [pa]		210.00	85.00
250	Veff[m/s]		5.70	4.00
	ΔPt [pa]		240.00	105.00
270	Veff[m/s]		6.00	4.30
	ΔPt [pa]		270.00	115.00
320	Veff[m/s]			5.00
	ΔPt [pa]			170.00
380	Veff[m/s]			6.00
	ΔPt [pa]			250.00

VLB				
Air flow (m^3/h)	Dimensions (mm)	100	125	150
30	Veff[m/s]	1.00	0.80	
	ΔPt [pa]	4.5	5.00	
60	Veff[m/s]	2.00	1.40	1.00
	ΔPt [pa]	15.00	4.00	3.00
80	Veff[m/s]	3.00	1.90	1.30
	ΔPt [pa]	29.00	8.50	5.00
110	Veff[m/s]	4.00	2.50	1.70
	ΔPt [pa]	55.00	15.00	16.00
140	Veff[m/s]	5.00	3.20	2.20
	ΔPt [pa]	90.00	25.00	24.00
170	Veff[m/s]	6.00	3.90	2.70
	ΔPt [pa]	135.00	37.00	37.00
180	Veff[m/s]		4.00	2.90
	ΔPt [pa]		40.00	43.00
190	Veff[m/s]		4.20	3.00
	ΔPt [pa]		45.00	48.00
220	Veff[m/s]		5.00	3.50
	ΔPt [pa]		65.00	63.00
250	Veff[m/s]		5.70	4.00
	ΔPt [pa]		70.00	73.00
270	Veff[m/s]		6.00	4.30
	ΔPt [pa]		85.00	80.00
320	Veff[m/s]			5.00
	ΔPt [pa]			125.00
380	Veff[m/s]			6.00
	ΔPt [pa]			180.00

Annotation

* Veff[m/s] - Air velocity in valve
* ΔPt [pa] - Pressure loss
* X [m] - Length air jet at speed Vk [m/s] = 0.5 m/s

Order codes

Type	/	Dimensions
		Ø
VN VLA VLB		100 125 150 160 200