# **SuiteCRM Analytics**

# **SuiteCRM Data Integration Installation**

Revision: 1.2

www.ivy-is.co.uk

# **Table of Contents**

Prerequisites	.3
Downloading SuiteCRM Data Integration	.3
Manually Build the Package (Cloning from Repo)	.3
Configuring SuiteCRM Data Integration	.4
Installing SuiteCRM Data Integration	.6

### **Prerequisites**

SuiteCRM Data Integration requires the following pre-requisites installed on your server

- · Linux environment
- OpenJDK 8 JRE (Java)
- wget
- unzip
- zip
- Mysql server + an empty MySQL database

### **Downloading SuiteCRM Data Integration**

There are two ways of downloading the SuiteCRM Data Integration:

- <u>Download from SuiteCRM website</u>: a pre-built package containing installation scripts, web server and all the third party open source libraries required.
- Clone the SuiteCRM Data Integration repo: a script to build the SuiteCRM data integration package (generating the same available package via the SuiteCRM website)

# Manually Build the Package (Cloning from Repo)

Clone repo via terminal:

git clone https://github.com/ivylabs/suitecrm-data-integration

Navigate into the newly cloned repository's directory and run:

#### ./build.sh

This should output on your terminal all the files that the solution downloads and zips up into a package.

The end of the script will ask if you wish to delete the installation files.

Would you like to remove the installation files? This will save disk space. [y/N] y

Build is complete!

This will generate a package named "suitecrm-data-integration-server.zip" within the root of your directory. This is the same package available via the SuiteCRM website.

# **Configuring SuiteCRM Data Integration**

After downloading or generating the "suitecrm-data-integration-server.zip" file, Upload and Extract the file on a hosted web server.

Navigate into the newly extracted "suitecrm-data-integration-server" folder and edit the the "install.properties" file:

```
# Java Virtual Memory allocation
JVM SIZE=1024
# SuiteCRM Source Database Connection Details
SUITECRM HOST=127.0.0.1
SUITECRM PORT=3306
SUITECRM DATABASE=suitecrm testdata
SUITECRM USERNAME=suitecrmrootuser
SUITECRM PASSWORD=suitecrmrootuserpassword
# SuiteCRM Analytis Target Database Connection
SUITECRM ANALYTICS HOST=127.0.0.1
SUITECRM ANALYTICS PORT=3306
SUITECRM ANALYTICS DATABASE=suitecrm dwh
SUITECRM ANALYTICS USERNAME=suitecrmrootuser
SUITECRM ANALYTICS PASSWORD=suitecrmrootuserpassword
# Enable SMTP email functionality
SMTP ENABLED=0
# SMTP Server Details
SMTP HOSTNAME=smtp.gmail.com
SMTP PORT=587
SMTP USE AUTHENTICATION=1
SMTP USERNAME=user@suitecrm-analvtics.co.uk
SMTP PASSWORD=password
#SMTP SECURE AUTHENTICATION=
#SMTP<sup>-</sup>SECURE<sup>-</sup>AUTHENTICATION=SSL
SMTP SECURE AUTHENTICATION=TLS
# Email address that SuiteCRM Analytics sends from
SMTP FROM EMAIL ADDRESS=donotreply@suitecrm-analytics.co.uk
SMTP FROM EMAIL NAME=SuiteCRM Analytics
# Email addresses seperated by spaces that error emails are delivered
to
SMTP SEND ERROR EMAILS TO=user@suitecrm-analytics.co.uk
# Set this to 1 or zero. Setting it to 1 means that you will get an email for every sucessful run on the ETL
SMTP SEND SUCCESS EMAILS=1
# Email addresses seperated by spaces that success emails are
delivered to
SMTP SEND SUCCESS EMAILS TO=user@suitecrm-analytics.co.uk
user123@suitecrm-analytics.co.uk
```

These config variables from "*install.properties*" define the connection to your SuiteCRM database to extract information from:

```
# SuiteCRM Source Database Connection Details
SUITECRM_HOST=127.0.0.1
SUITECRM_PORT=3306
SUITECRM_DATABASE=suitecrm_testdata
SUITECRM_USERNAME=suitecrmrootuser
SUITECRM_PASSWORD=suitecrmrootuserpassword
```

Update the above values in your "install.properties" file to reflect the following:

"SUITECRM DATABASE" = The Database name of your SuiteCRM Instance

"SUITECRM\_USERNAME" = The username used to connect to the SuiteCRM Database

"SUITECRM\_PASSWORD" = The password used to connect to the SuiteCRM Database

These config variables define the connection to your SuiteCRM Data Integration to transform and load the extracted SuiteCRM data into:

```
# SuiteCRM Analytics Target Database Connection
SUITECRM_ANALYTICS_HOST=127.0.0.1
SUITECRM_ANALYTICS_PORT=3306
SUITECRM_ANALYTICS_DATABASE=suitecrm_dwh
SUITECRM_ANALYTICS_USERNAME=suitecrmrootuser
SUITECRM_ANALYTICS_PASSWORD=suitecrmrootuser
```

Note: For this step, it is recommended to create a new MySQL database as the SuiteCRM Data Integration Data Warehouse

Update the above values in your "install.properties" file to reflect the following:

"SUITECRM\_ANALYTICS\_DATABASE" = The name of the Database to be used as the SuiteCRM Data Warehouse

"SUITECRM\_ANALYTICS\_USERNAME" = The username used to connect to the Database used as the SuiteCRM Data Warehouse

"SUITECRM\_ANALYTICS\_PASSWORD" = The password used to connect to the Database used as the SuiteCRM Data Warehouse

The SMTP config variables will define the connection to an email mail client to send out notifications on the status of the extraction script (success or failure). These are optional:

```
# Enable SMTP email functionality
SMTP ENABLED=0
# SMTP Server Details
SMTP HOSTNAME=smtp.gmail.com
SMTP PORT=587
SMTP USE AUTHENTICATION=1
SMTP_USERNAME=user@suitecrm-analytics.co.uk
SMTP PASSWORD=password
#SMTP SECURE AUTHENTICATION=
#SMTP_SECURE_AUTHENTICATION=SSL
SMTP SECURE AUTHENTICATION=TLS
# Email address that SuiteCRM Analytics sends from
SMTP FROM EMAIL ADDRESS=donotreply@suitecrm-analytics.co.uk
SMTP FROM EMAIL NAME=SuiteCRM Analytics
# Email addresses seperated by spaces that error emails are delivered
SMTP SEND ERROR EMAILS TO=user@suitecrm-analytics.co.uk
# Set this to 1 or zero. Setting it to 1 means that you will get an email for every sucessful run on the ETL
SMTP SEND SUCCESS EMAILS=1
# Email addresses seperated by spaces that success emails are
delivered to
SMTP SEND SUCCESS EMAILS TO=user@suitecrm-analytics.co.uk
user123@suitecrm-analytics.co.uk
```

# **Installing SuiteCRM Data Integration**

Once the configuration has been defined, now run the setup script in the root of your 'suitecrm-data-integration' directory, using the command:

#### ./setup-suitecrm-data-integration.sh

This will check the connection of your databases and create the tables required to extract your SuiteCRM data.

You will also be asked if you wish to install the **Demo Data**. Selecting **Y** will populate the Data Warehouse with Demo Data llowing you to test the solution. If you wish to run the solution against your live instance of SuiteCRM then type **N** 

Then you can run the SuiteCRM Data Integration script to extract and transform your data:

./run-suitecrm-data-integration.sh

This should output on your terminal all logging referring to the extracting, transforming and loading data into the data warehouse tables.

Note: The above script will process any records that have been added/modified between the previous run and the current system time.

Due to this, it is recommended that both the server in which the Data Warehouse resides and the current system be on the same timezone setting, to allow the smoothest transition of data.

The solution currently extracts data from the following modules:

- Accounts
- Campaigns
- Cases
- Contacts
- Invoices
- Leads
- Opportunities
- Products/Product Categories
- Users
- Custom Fields from Cases, Leads

This is the end of the SuiteCRM Data Integration installation.

If you wish to know more about Pentaho ETL solutions you can visit the Spoon user guide.

This solution includes a pre-packaged spoon client that you can run via terminal:

./data-integration-client.sh