

Universe Reinsurance Platform — Redeployment Quick Reference

Companion to the Work Environment Deployment Specification v2.0 (July 2026) · PM2 + Nginx path, app root
/opt/universe · Confidential — internal IT use only

1 · Standard redeploy — one command

The repository ships the redeploy script. Run it as the application user on the server:

```
ssh <admin>@<server>
cd /opt/universe
./deploy.sh
```

What `deploy.sh` does, in order:

1. Pulls the latest main branch from GitHub.
2. Reinstalls exact dependencies from the lockfiles (`npm ci` for root, client, server).
3. Builds the frontend (`npm run build --prefix client`).
4. Applies pending database migrations (`npm run migrate`) — idempotent, safe to rerun.
5. Reloads the app under PM2 with zero downtime (`npm run cluster:reload`).
6. Runs the seed hook (`npm run seed:deploy`) — see §2. Does nothing unless enabled.

2 · Seed reference variables on redeploy — never contracts

The base catalogue (75 countries, 15 classes of business, 11 brokers, 22 cedant companies, 32 currencies, treaty types, reinsurers) comes from the **migrations** — no variable needed. `SEED_ON_DEPLOY=reference` additionally seeds the Ghana pack: 8 Ghanaian cedants, the GHS currency + USD rate, the Ghana CPI series (2000–2026) the loss-inflation screens need, and 8 CRESTA zones. **It never writes a treaty contract**, and it is idempotent — rows already present are left alone, so rerunning is always safe.

How to set it — Option A (recommended): store it in the app's .env file. The deploy hook reads `/opt/universe/.env` automatically; no restart is needed and it takes effect on the next `./deploy.sh`:

```
cd /opt/universe
nano .env                                # open the environment file...
SEED_ON_DEPLOY=reference                 # ...and add this on its own line, then save
```

```
# or append it without an editor:
echo 'SEED_ON_DEPLOY=reference' >> /opt/universe/.env
```

```
grep SEED_ON_DEPLOY /opt/universe/.env # confirm it appears exactly once
chmod 600 /opt/universe/.env           # keep the file locked down
```

Keep a single `SEED_ON_DEPLOY` line — if one already exists, edit it rather than appending a second. Setting it once is fine even if you rarely redeploy: later deploys just confirm the rows exist and touch nothing.

Option B: one-shot for a single deploy — pass it on the command line and save nothing:

```
SEED_ON_DEPLOY=reference ./deploy.sh
```

Option C: run the top-up by hand any time (no variable at all):

```
cd /opt/universe
SEED_ALLOW_PRODUCTION=1 node server/scripts/seedTestTreaties.js --reference-only
```

Note: with `NODE_ENV=production` a direct run asks for `SEED_ALLOW_PRODUCTION=1` before writing; the deploy hook supplies it automatically once `SEED_ON_DEPLOY` is set. Do **not** use `SEED_ON_DEPLOY=1` or `=reset` on this server — those seed 100 fabricated treaty contracts and are for test/demo databases only.

3 · Manual redeploy — step by step

Identical to `deploy.sh`, for when each step should be run and checked individually:

```
cd /opt/universe
git pull origin main
npm ci && npm ci --prefix client && npm ci --prefix server
npm run build --prefix client
npm run migrate:status --prefix server # review the pending set first
```

```

npm run migrate:up      --prefix server    # apply BEFORE reloading the app
npm run cluster:reload  # zero-downtime PM2 reload
npm run seed:deploy     --prefix server    # reference top-up (per SEED_ON_DEPLOY)

```

4 · Verify after every redeploy

```

npm run cluster:status      # all PM2 workers online
curl -fsS http://127.0.0.1:4000/api/health # {"status":"ok"}
curl -fsS http://127.0.0.1:4000/api/health/db # DB + pool health
pm2 logs universe --lines 50 # clean request logs, no errors

```

Then load the site over HTTPS and log in once. Confirm the reference lookups are present (currency and cedant dropdowns populated).

5 · If something goes wrong

Symptom	Do this
Migration step fails	App keeps running on the old version — nothing was reloaded. Read the error, fix, rerun <code>npm run migrate:up --prefix server</code> , then continue.
Seed step fails after reload	The app is already live; the deploy script exits non-zero so the failure is visible. Rerun <code>npm run seed:deploy --prefix server</code> after fixing the cause.
Seed step prints “skipping”	<code>SEED_ON_DEPLOY</code> is not set in the environment or <code>/opt/universe/.env</code> . Add <code>SEED_ON_DEPLOY=reference</code> .
App down after reload	<code>pm2 logs universe --lines 200</code> for the boot error; <code>pm2 restart ecosystem.config.cjs</code> once fixed.
Fabricated treaties appeared	Someone seeded the full portfolio. Remove it cleanly: <code>node server/scripts/seedTestTreaties.js --reset-only</code> (deletes only rows stamped <code>seed:test-treaties</code>).

August 2026 · Reference: `DEPLOYMENT.md` §9 and `docs/seed-test-treaties.md` in the repository — always confirm against the latest code before relying on this snapshot.