

CS-AML

Control Implementation Guide

Version 0.1.4

Approved Internal Specification Baseline

2026-10-10 · tag v0.1.4-spec

Civil Society Anti-Money Laundering & Financial Intelligence Framework

Generated from the canonical Markdown source. The Markdown file in the repository remains authoritative; change tags such as `[v0.1.x · ...]` are part of the traceability record.

Contents

Document Control	4
1. Purpose and Scope	5
1.1 In scope	5
1.2 Out of scope	5
2. Control Philosophy and External Alignment	5
3. CS-AML Control Model	6
3.1 Control design attributes	6
4. Roles, Accountability, and Segregation of Duties	6
5. Risk-Based Control Profiles	7
6. Control Implementation Lifecycle	7
1. Establish	7
2. Design	7
3. Implement	7
4. Validate	8
5. Test	8
6. Measure	8
7. Improve	8
7. Evidence of Control Operation	8
8. Control Testing Standard	8
8.1 Design effectiveness	8
8.2 Operating effectiveness	8
8.3 Minimum test method	8
8.4 Effectiveness rating	9
9. Detailed Control Implementation Profiles	9
9.1 Governance Controls	9
9.2 Case Management Controls	11
9.3 Sources Controls	13
9.4 Evidence Controls	15
9.5 Entities Controls	16
9.6 Relationships Controls	17
9.7 Assets Controls	18
9.8 Value Flow Controls	19
9.9 Typologies Controls	20
9.10 Hypotheses Controls	21
9.11 Assessment Controls	23
9.12 Privacy Controls	24
9.13 Security Controls	26
9.14 Quality Controls	28
9.15 Dissemination Controls	29
9.16 Audit Controls	30
9.17 Technology Controls	31
10. Cross-Control Implementation Bundles	33
10.1 New case baseline	33
10.2 Sensitive/protected-source case	33
10.3 Entity/graph investigation	33
10.4 Follow-the-value investigation	33
10.5 High-impact adverse product	33
10.6 AI/automation-assisted investigation	33

11. Exceptions and Compensating Controls	33
12. Metrics and Control Effectiveness	34
13. Assurance Programme	34
13.1 First-line self-check	34
13.2 Independent quality review	34
13.3 Periodic control assurance	35
13.4 Triggered assurance	35
14. Implementation Maturity Model	35
15. Minimum Organisational Implementation Plan	35
16. Control Implementation Conformance	35
16.1 Minimum Conformance Evidence Pack	36
17. Traceability to Other CS-AML Documents	36
Annex A — Control Register Template	36
Annex B — Control Test Worksheet	38
Annex C — Exception Record Template	38
Annex D — High-Impact Product Control Checklist	38
Annex E — Reference Lineage	39
E.1 Interpretation notes	39

CS-AML

Control Implementation Guide

Civil Society Anti-Money Laundering & Financial Intelligence Framework

Version 0.1.4 | Implementation Guide (Approved Internal Specification Baseline)

Document status — v0.1.4

Version: 0.1.4 — Approved Internal Specification Baseline (2026-10-10, tag v0.1.4-spec). Supersedes v0.1.3 (2026-10-09, tag v0.1.3-spec). [v0.1.4]

Supersedes: CS-AML Control Implementation Guide v0.1. The DOCX/PDF files in this repository are the unchanged v0.1 baseline (legacy); this Markdown file is the canonical source.

Validation: approved by the product owner as the internal specification baseline on 2026-10-08 (v0.1.1) and 2026-10-09 (v0.1.3) and 2026-10-10 (v0.1.4; decision register and release gates in CHANGELOG.md). The v0.1.3 and v0.1.4 changes come from change requests raised while implementing increments I5-I7 and the post-MVP follow-ups; this is not an independent audit. Acceptance criteria in this document are targets, not evidence that tests have passed.

CS-AML is not an external standard or certification. References to FATF, Wolfsberg, PPATK, UNODC or other bodies do not imply their endorsement.

Changes in 0.1.1: see CHANGELOG.md at the repository root (audit findings A01-A16).

Changes in 0.1.3: change requests CR-I5-01...CR-I7-08 approved by the product owner on 2026-10-09 (CHANGELOG.md, section v0.1.3). Each change is tagged *[v0.1.3 · CR-xx-yy]*.

Changes in 0.1.4: change requests CR-N-01...CR-N-14 approved by the product owner on 2026-10-10 (CHANGELOG.md, section v0.1.4). Each change is tagged *[v0.1.4 · CR-N-xx]*.

Status

This document is a derivative specification of CS-AML Framework v0.1.1 (draft for review). It defines how the minimum CS-AML control catalogue is to be implemented, evidenced, tested, reviewed, and improved. It does not replace applicable law, professional ethics, or organisational policy. The efficacy of these controls has not yet been demonstrated: no design-effectiveness or operating-effectiveness test of any control described here has been recorded. [v0.1.1 · A01]

Document Control

Field	Specification
Document	CS-AML Control Implementation Guide
Version	0.1.4 [v0.1.4]
Status	Approved Internal Specification Baseline (2026-10-10, tag v0.1.4-spec) — derivative implementation guide [v0.1.1 · A01]
Parent	CS-AML Framework v0.1.4 Expanded (Markdown, Documents/CS-AML_Framework_v0.1.4_Expanded.md)
Related specifications	Goals & Non-Goals v0.1.1; Typology Catalogue v0.1.1; Investigation Methodology v0.1.4; Data Model Specification v0.1.4
Primary audience	CSO leadership, investigators, compliance/ethics leads, privacy/security staff, system owners, reviewers, assurance teams
Normative language	SHALL/MUST = mandatory; SHOULD = strongly recommended unless justified; MAY = optional
Control population	26 minimum controls inherited from the CS-AML v0.1 control catalogue
Design objective	Make controls operational, proportionate, auditable, and outcome-focused without turning civil-society investigation into regulated-bank compliance.

1. Purpose and Scope

The CS-AML Control Implementation Guide translates the normative control catalogue into operating controls that a civil-society organisation can actually perform and demonstrate. It defines the expected control objective, implementation pattern, responsible roles, operating evidence, test procedures, common failure modes, and maturity expectations for each minimum control.

Primary implementation principle

A control is not implemented merely because a policy exists. A conforming control requires an assigned owner, an operating process, evidence that the process occurred, and a means to test whether the control materially reduces the risk it was designed to address.

1.1 In scope

- Governance and accountability controls
- Case initiation and lifecycle-gate controls
- Source, evidence, and provenance controls
- Entity, relationship, asset, and value-flow analytical controls
- Typology, hypothesis, assessment, and intelligence-gap controls
- Privacy, retention, and source-protection controls
- Security and access controls
- Quality, dissemination, and audit controls
- Technology, AI, and explainability controls
- Control testing, exceptions, assurance, metrics, and maturity

1.2 Out of scope

- Bank/financial-institution AML regulatory compliance programmes
- Formal STR/SAR filing obligations unless separately applicable
- Law-enforcement covert powers or compelled financial records
- A determination of criminal guilt
- Vendor-specific product configuration
- A requirement to collect more personal or financial data than is necessary for a legitimate civil-society investigation

2. Control Philosophy and External Alignment


CS-AML uses a risk-based implementation philosophy. Controls SHALL be proportionate to the case, data, harm, dissemination, and technology risks involved. Organisations SHOULD prioritise controls that materially improve analytical reliability, rights protection, source safety, and decision usefulness rather than maximising documentation volume.

Outcome orientation

CS-AML borrows the logic of proportionality, prioritisation, and effectiveness from contemporary financial-crime risk management, while adapting it to civil society. The objective is not “more controls”; it is better-supported intelligence with fewer avoidable harms.

The guide is consistent in principle with the FATF emphasis on risk-based and effective AML/CFT systems, the Wolfsberg Group's 2026 articulation of proportionality, prioritisation, and effectiveness, and PPATK's recognition that high-quality information from NGO/CSO and the public can support financial-intelligence analysis. These sources provide context; CS-AML remains a civil-society methodology rather than a financial-institution compliance standard.

3. CS-AML Control Model



3.1 Control design attributes

Attribute	Definition
Control ID	Stable reference identifier from the CS-AML control catalogue.
Objective	The result the control is intended to achieve.
Requirement	The minimum normative rule.
Risk addressed	The error, harm, abuse, or analytical failure controlled.
Owner	Role accountable for design and/or operation.
Frequency/trigger	When the control is performed.
Procedure	Minimum operating steps.
Evidence of operation	Artefacts demonstrating that the control actually ran.
Test procedure	How assurance personnel verify design and operating effectiveness.
Failure modes	Known patterns indicating ineffective or cosmetic implementation.
Exception path	How deviations are approved, time-limited, and compensated.
Metric	Evidence used to understand coverage, timeliness, or outcomes.

4. Roles, Accountability, and Segregation of Duties

Role	Minimum accountability
Governing authority / executive sponsor	Approves organisational adoption, risk tolerance, material exceptions, and assurance responses.
Framework owner	Maintains CS-AML local policy, control catalogue, mappings, and change management.
Case owner	Accountable for legitimate purpose, scope, risk, gates, resources, and closure of a case.
Lead analyst	Directs analysis and ensures provenance, hypotheses, gaps, and confidence are maintained.
Collector / researcher	Obtains and registers information through lawful, approved methods.
Evidence custodian / data steward	Maintains integrity, lineage, storage, retention, and controlled data quality.

Role	Minimum accountability
Privacy / legal / ethics reviewer	Advises on necessity, proportionality, sensitive data, publication risk, and legal constraints.
Security administrator	Implements access, authentication, logging, source compartmentalisation, and incident response.
Peer reviewer / red-team reviewer	Independently challenges evidence, reasoning, alternatives, confidence, and wording.
Product approver	Authorises referral, publication, partner dissemination, or other external release.
Assurance reviewer	Tests control design/operation independently from day-to-day case execution.
Technology/model owner	Owns rules, models, AI integrations, versioning, validation, and technical controls.

Segregation rule

A high-impact adverse assessment SHOULD NOT be authored, independently reviewed, and finally approved by the same individual. Small organisations MAY use documented compensating controls such as cross-organisation peer review or executive review when full role separation is impracticable.

5. Risk-Based Control Profiles

Profile	Typical conditions	Control expectation
P1 — Standard	Ordinary open-source research; limited sensitive data; no protected source; no planned public allegation.	All mandatory controls; streamlined gate and review evidence.
P2 — Sensitive	Sensitive personal/financial data, vulnerable persons, confidential source, significant reputational impact, or cross-border sharing.	Mandatory controls plus privacy/security review, stricter access, enhanced evidence handling, independent peer review.
P3 — High Impact	Public attribution of serious wrongdoing, referral likely to trigger enforcement, protected-source risk, large-scale datasets, high-threat subject, or significant physical/digital safety risk.	Enhanced gate approvals, independent review/red-team, legal/ethics review where appropriate, formal dissemination control, documented disconfirmation, stronger audit and assurance.
P4 — Technology/Automation Enhanced	Material use of AI/ML, large-scale entity resolution, automated scoring, or automated extraction that can influence findings.	P1-P3 as applicable plus TEC-01/02 validation, model/rule cards, human verification, versioning, and performance monitoring.

6. Control Implementation Lifecycle

1. Establish

Approve local CS-AML policy, owner, scope, roles, control catalogue, risk profiles, and exceptions process.

2. Design

Translate each normative control into an operating procedure, system configuration, form/template, and expected evidence.

3. Implement

Train personnel, configure systems, run controls on live or pilot cases, and collect evidence of operation.

4. Validate

Verify that each control exists, can be performed, and maps to the intended risk and framework requirement.

5. Test

Perform design-effectiveness and operating-effectiveness tests on a risk-based sample.

6. Measure

Track coverage, timeliness, exceptions, false-positive/false-association outcomes, privacy events, and review findings.

7. Improve

Remediate failures, simplify redundant controls, strengthen high-value controls, and update for emerging typologies and technology risks.

7. Evidence of Control Operation

Evidence of operation demonstrates that a control actually ran. A policy, template, or configured feature is design evidence; it is not by itself evidence that the control operated on a case.

Evidence class	Examples
Design evidence	Policy, procedure, template, role description, configured workflow, model/rule card.
Operation evidence	Completed charter, source record, hash record, merge decision, gate approval, hypothesis matrix, review sign-off.
System evidence	Audit event, IAM record, immutable log, version record, retention job output, model execution/version.
Outcome evidence	Unsupported relationship removed, overstatement corrected, source identity protected, duplicate entities resolved, dissemination prevented or narrowed.
Assurance evidence	Test sample, finding, rating, remediation plan, retest result.

8. Control Testing Standard

8.1 Design effectiveness

A control is design-effective when, if performed as specified, it is reasonably capable of achieving its control objective and reducing the stated risk without creating disproportionate harm.

8.2 Operating effectiveness

A control is operating-effective when evidence shows it was performed by appropriate personnel, at the required time, on the relevant population, and exceptions were identified and handled.

8.3 Minimum test method

1. Define the control population and period.
2. Select a risk-based sample; include high-impact and exception cases.
3. Inspect evidence of operation and timing.

4. Reperform or independently verify a meaningful portion of the control when feasible.
5. Identify exceptions and determine whether they are isolated or systemic.
6. Rate design and operating effectiveness separately.
7. Assign remediation owner/date and retest material failures.

8.4 Effectiveness rating

Rating	Meaning
Effective	Control is appropriately designed and operated with no material exception.
Effective with improvement	Objective substantially achieved; minor gaps do not materially undermine outcomes.
Partially effective	Control exists but material design/operation gaps reduce reliability.
Ineffective	Control absent, routinely bypassed, or not capable of achieving the objective.
Not applicable	Control legitimately not applicable; rationale and approval recorded.

9. Detailed Control Implementation Profiles

The following profiles are normative implementation guidance for the minimum CS-AML v0.1 control catalogue. Organisations MAY implement different procedures if they achieve the same objective and retain demonstrable evidence of operation.

9.1 Governance Controls

GOV-01 — Accountable ownership

Field	Specification
Control objective	Accountable ownership
Normative requirement	Every case SHALL have an accountable owner.
Risk addressed	Prevent orphaned investigations, ambiguous authority, and decisions without a clearly responsible human.
Primary roles	Case owner; Investigation lead; Governance approver
Default trigger/frequency	At each relevant case event; continuous/system-enforced where technically appropriate.

Implementation requirements

- Create a named Case Owner role at case opening.
- Record owner, deputy, approving manager, and review date in the Case Charter.
- Require transfer-of-ownership records when responsibility changes.
- Ensure the owner has authority to pause, narrow, escalate, or close the case.

Minimum evidence of operation

- Case Charter
- Case register
- Ownership transfer log
- Gate approval records

Assurance test

- Sample open cases and verify a current owner is recorded.
- Compare ownership changes with audit events.
- Interview analysts to confirm decision authority is understood.

Common failure modes

- Cases assigned to teams rather than accountable persons.
- Owner listed but lacking authority.
- Ownership changes without recorded rationale.

Implementation maturity

Baseline: documented and consistently performed. Managed: system-supported, measured, and exceptions tracked. Assured: independently tested with remediation and periodic revalidation. For GOV-01, higher maturity SHALL NOT be achieved by indiscriminate collection or broader surveillance.

GOV-02 — Conflict control

Field	Specification
Control objective	Conflict control
Normative requirement	Material conflicts SHALL be declared and managed.
Risk addressed	Protect analytical independence where personal, organisational, donor, political, financial, or partnership interests could influence investigation decisions.
Primary roles	All investigators; Case owner; Governance approver
Default trigger/frequency	At each relevant case event; continuous/system-enforced where technically appropriate.

Implementation requirements

- Require conflict declarations at intake and before high-impact dissemination.
- Define recusal, secondary review, and transfer procedures.
- Record both actual and reasonably perceived conflicts.
- Do not disclose protected-source identity unnecessarily when assessing conflicts.

Minimum evidence of operation

- Conflict declaration
- Conflict register
- Recusal/mitigation record
- Independent review sign-off

Assurance test

- Review a sample of high-impact cases for conflict declarations.
- Check declared conflicts against mitigation actions.
- Test whether conflicted reviewers were excluded from approvals.

Common failure modes

- No declaration process.
- Conflicts considered only after publication.
- Informal mitigation with no evidence.

Implementation maturity

Baseline: documented and consistently performed. Managed: system-supported, measured, and exceptions tracked. Assured: independently tested with remediation and periodic revalidation. For GOV-02, higher maturity SHALL NOT be achieved by indiscriminate collection or broader surveillance.

9.2 Case Management Controls

CAS-01 — Defined purpose

Field	Specification
Control objective	Defined purpose
Normative requirement	Every case SHALL have a documented investigation question and scope.
Risk addressed	Prevent open-ended surveillance, mission creep, and evidence collection without a defined legitimate purpose.
Primary roles	Case owner; Analyst; Approver
Default trigger/frequency	At each relevant case event; continuous/system-enforced where technically appropriate.

Implementation requirements

- Create an Investigation Charter before substantive collection.
- State the issue, question, subjects, time period, jurisdiction, inclusion/exclusion boundaries, intended outputs, and stop conditions.
- Record material scope changes and require re-approval when risk increases.

Minimum evidence of operation

- Investigation Charter
- Scope-change record
- Investigation question
- Closure decision

Assurance test

- Verify each sampled case has a question framed without presuming guilt.
- Compare collected data with approved scope.
- Inspect scope changes after discovery of new subjects.

Common failure modes

- Question framed as an accusation.
- No geographic/time boundary.
- Collection expands without updated charter.

Implementation maturity

Baseline: documented and consistently performed. Managed: system-supported, measured, and exceptions tracked. Assured: independently tested with remediation and periodic revalidation. For CAS-01, higher maturity SHALL NOT be achieved by indiscriminate collection or broader surveillance.

CAS-02 — Gate approval

Field	Specification
Control objective	Gate approval
Normative requirement	High-risk cases SHALL pass defined lifecycle gates.
Risk addressed	Ensure increasing analytical, privacy, legal, reputational, and safety risk receives proportionate review before the case advances.
Primary roles	Case owner; Privacy/security reviewer; Independent approver
Default trigger/frequency	At each relevant case event; continuous/system-enforced where technically appropriate.

Implementation requirements

- Apply G0-G6 stage gates defined in the Investigation Methodology.
- Define criteria for high-risk cases, including sensitive personal data, protected sources, high-impact allegations, vulnerable persons, and planned public attribution.
- Record gate decision, approver, conditions, and unresolved gaps.

Reference implementation (v0.1.4) [*v0.1.4 · CR-N-03, CR-N-05, CR-N-06, CR-N-07*] High-risk (high-impact) case = risk rating HIGH or CRITICAL, or classification RESTRICTED or SOURCE_PROTECTED (a P3 proxy). For every gate the decider is never the submitter (system-enforced) and is a LEAD or REVIEWER member of the case; for a high-impact case the G0 / G1 decider must not have authored the charter version under approval. Gate approval requires a recent second-factor step-up. The decision record holds approver, rationale, conditions, the bound charter version and the case-status transition; readiness criteria that are data are checked at submission and approval, the rest is reviewer judgement (Framework §5.9). Gates control the case lifecycle (activation, review, closure); collection, assessment finalisation and dissemination keep their own controls. Separate legal / privacy reviewer roles per gate and configuration per organisation or risk tier (P1-P3) are deferred to v0.2.

Minimum evidence of operation

- Gate checklist
- Approval record
- Risk review
- Conditions/waivers

Assurance test

- Trace sample cases through required gates.
- Confirm gate approvals predate the controlled action.
- Check that conditions were resolved or explicitly accepted.

Common failure modes

- Retroactive approvals.
- Same person self-approves high-impact gates.
- Gate used as paperwork only.

Implementation maturity

Baseline: documented and consistently performed. Managed: system-supported, measured, and exceptions tracked. Assured: independently tested with remediation and periodic revalidation. For CAS-02, higher maturity SHALL NOT be achieved by indiscriminate collection or broader surveillance.

9.3 Sources Controls

SRC-01 — Provenance

Field	Specification
Control objective	Provenance
Normative requirement	Material sources SHALL have provenance metadata.
Risk addressed	Allow another analyst to determine where information originated, how it was obtained, when it was accessed, and whether it remains reproducible.
Primary roles	Collector; Analyst; Evidence custodian
Default trigger/frequency	At each relevant case event; continuous/system-enforced where technically appropriate.

Implementation requirements

- Register every material source with source ID, origin, publisher/owner where known, access method, access time, URL/location, archival copy where appropriate, legal/access note, and handling classification.
- Preserve original context and avoid detached screenshots when a fuller record is available.

Minimum evidence of operation

- Source register
- Archived copy
- Collection metadata
- Access/legal note

Assurance test

- Select material claims and trace them to registered sources.
- Verify URLs/locations and access dates are present.
- Check archived copy policy for mutable web content.

Common failure modes

- Screenshots with no URL/date.
- Copied text with no original context.
- Sources referenced only in analyst notes.

Implementation maturity

Baseline: documented and consistently performed. Managed: system-supported, measured, and exceptions tracked. Assured: independently tested with remediation and periodic revalidation. For SRC-01, higher maturity SHALL NOT be achieved by indiscriminate collection or broader surveillance.

SRC-02 — Reliability assessment

Field	Specification
Control objective	Reliability assessment
Normative requirement	Material source reliability SHOULD be assessed separately from information credibility.
Risk addressed	Avoid treating a generally reputable source as proof that every item it contains is accurate, or dismissing useful information solely because the source is unfamiliar.
Primary roles	Analyst; Reviewer
Default trigger/frequency	At each relevant case event; continuous/system-enforced where technically appropriate.

Implementation requirements

- Use the CS-AML source reliability scale A-F and information credibility scale 1-6 where material.
- Document rationale for ratings that materially influence an assessment.
- Reassess when corroboration or contradiction emerges.

Minimum evidence of operation

- Source rating
- Credibility rating
- Rating rationale
- Reassessment history

Assurance test

- Check that source and information ratings are not conflated.
- Review whether high-impact claims rely on weak/unknown sources without corroboration.

Common failure modes

- Everything from official sources marked A1 automatically.
- Anonymous source treated as unreliable without assessing the information.

Implementation maturity

Baseline: documented and consistently performed. Managed: system-supported, measured, and exceptions tracked. Assured: independently tested with remediation and periodic revalidation. For SRC-02, higher maturity SHALL NOT be achieved by indiscriminate collection or broader surveillance.

9.4 Evidence Controls

EVD-01 — Integrity

Field	Specification
Control objective	Integrity
Normative requirement	Critical digital evidence SHOULD be integrity-protected.
Risk addressed	Preserve the ability to demonstrate that critical digital material has not silently changed since collection.
Primary roles	Evidence custodian; Collector; Security administrator
Default trigger/frequency	At each relevant case event; continuous/system-enforced where technically appropriate.

Implementation requirements

- Preserve originals read-only where feasible.
- Compute cryptographic hashes for critical files at acquisition or entry into the evidence store.
- Record acquisition time, collector, source, and hash algorithm.
- Use derivative working copies rather than editing originals.

Minimum evidence of operation

- Hash record
- Original evidence store
- Acquisition log
- Read-only/immutability configuration

Assurance test

- Recompute hashes for a sample.
- Confirm analyst work occurs on derivatives.
- Check that replaced files create new versions rather than overwriting originals.

Common failure modes

- Original PDFs annotated directly.
- No distinction between original and working copy.
- Hashes calculated only at case closure.

Implementation maturity

Baseline: documented and consistently performed. Managed: system-supported, measured, and exceptions tracked. Assured: independently tested with remediation and periodic revalidation. For EVD-01, higher maturity SHALL NOT be achieved by indiscriminate collection or broader surveillance.

EVD-02 — Derivative lineage

Field	Specification
Control objective	Derivative lineage

Field	Specification
Normative requirement	Derived artefacts SHALL link to their originals.
Risk addressed	Ensure extracts, translations, cropped images, parsed tables, OCR text, and analyst-created datasets remain traceable to the source evidence from which they were produced.
Primary roles	Analyst; Evidence custodian
Default trigger/frequency	At each relevant case event; continuous/system-enforced where technically appropriate.

Implementation requirements

- Assign IDs to derivative artefacts.
- Record parent evidence reference, transformation type, tool/version when material, creator, and creation time.
- Do not replace original wording with corrected or translated text without retaining both.

Reference implementation (v0.1.4) [v0.1.4 · CR-N-09, CR-N-10] OCR, text extraction and machine translation produce a DerivedText (Data Model §7.7) and a derivative EvidenceItem linked to its parent (derived_from, derivation_type), with engine, version, model hashes and licence, requester and time. Translations keep the source-language text of every page and the method ("Machine translation", engine, model); a translation is never translated again. All automation engines run offline; evidence content never leaves the host. Reviewed translations need no second reviewer, but the machine-translation label is carried into any intelligence product that uses the translation.

Minimum evidence of operation

- Evidence lineage
- Derivative metadata
- Transformation log

Assurance test

- Trace sample extracts backward to originals.
- Check translations retain source text and translator/method metadata.

Common failure modes

- Orphan spreadsheets.
- OCR text treated as original.
- Translated quotes without source-language text.

Implementation maturity

Baseline: documented and consistently performed. Managed: system-supported, measured, and exceptions tracked. Assured: independently tested with remediation and periodic revalidation. For EVD-02, higher maturity SHALL NOT be achieved by indiscriminate collection or broader surveillance.

9.5 Entities Controls

ENT-01 — Evidence-based resolution

Field	Specification
Control objective	Evidence-based resolution
Normative requirement	Material entity merges SHALL be evidence-based and reversible.
Risk addressed	Prevent false network connections caused by prematurely treating similar names, addresses, identifiers, or profiles as the same person or organisation.
Primary roles	Analyst; Entity reviewer; Data steward
Default trigger/frequency	At each relevant case event; continuous/system-enforced where technically appropriate.

Implementation requirements

- Maintain candidate-match state before merge.
- Record match features, conflicting features, confidence, analyst rationale, and evidence references.
- Support unmerge or superseding decisions without losing history.
- Do not merge solely on common names.

Minimum evidence of operation

- Entity-resolution decision (append-only ResolutionDecision record: merge, unmerge, keep-separate, possible-match or defer) [v0.1.1 · ER]
- Merge history
- Candidate match record
- Evidence links

Assurance test

- Review merged high-impact entities and verify multiple discriminating attributes.
- Test reversibility.
- Search for merges based only on name.

Common failure modes

- One-record-per-name logic.
- Hidden merges.
- Merged entity loses alternate identifiers/provenance.

Implementation maturity

Baseline: documented and consistently performed. Managed: system-supported, measured, and exceptions tracked. Assured: independently tested with remediation and periodic revalidation. For ENT-01, higher maturity SHALL NOT be achieved by indiscriminate collection or broader surveillance.

9.6 Relationships Controls

REL-01 — Relationship proof

Field	Specification
Control objective	Relationship proof

Field	Specification
Normative requirement	Material analytical relationships SHALL link to evidence and carry temporal/confidence metadata.
Risk addressed	Prevent visual graph edges from being mistaken for established relationships merely because they appear connected.
Primary roles	Analyst; Graph/data steward
Default trigger/frequency	At each relevant case event; continuous/system-enforced where technically appropriate.

Implementation requirements

- Represent relationships as first-class records, not display-only edges.
- Record relationship type, endpoints, source/evidence, valid time where known, confidence, status, and analyst.
- Use controlled vocabulary.
- Distinguish asserted, observed, inferred, and disputed relationships where needed.

Minimum evidence of operation

- Relationship record
- Edge provenance
- Graph audit
- Confidence metadata

Assurance test

- Click/trace sample material graph edges to evidence.
- Check historical relationships include valid time.
- Look for unsupported edges created manually in visualisation.

Common failure modes

- Graph edge with no provenance.
- Current director relationship shown as timeless.
- Association inferred from co-occurrence only.

Implementation maturity

Baseline: documented and consistently performed. Managed: system-supported, measured, and exceptions tracked. Assured: independently tested with remediation and periodic revalidation. For REL-01, higher maturity SHALL NOT be achieved by indiscriminate collection or broader surveillance.

9.7 Assets Controls

AST-01 — Attribution distinction

Field	Specification
Control objective	Attribution distinction
Normative requirement	Legal ownership, beneficial ownership, control, use, and association SHALL be represented distinctly.
Risk addressed	Avoid overstating that a subject owns an asset merely because they use, control, finance, occupy, or are associated with it.

Field	Specification
Primary roles	Analyst; Reviewer; Legal/editorial reviewer where applicable
Default trigger/frequency	At each relevant case event; continuous/system-enforced where technically appropriate.

Implementation requirements

- Use separate relationship types for legal title, beneficial interest, control, use/occupancy, financing, and association.
- Record valuation source/date and uncertainty separately from ownership.
- Require stronger review before public statements of beneficial ownership.

Minimum evidence of operation

- Asset record
- Ownership/control records
- Valuation provenance
- Assessment wording

Assurance test

- Compare graph labels with underlying attribution type.
- Review publications for language stronger than recorded evidence.

Common failure modes

- “Associated with” converted to “owns”.
- Asset value presented without date/source.
- Beneficial ownership inferred solely from family relationship.

Implementation maturity

Baseline: documented and consistently performed. Managed: system-supported, measured, and exceptions tracked. Assured: independently tested with remediation and periodic revalidation. For AST-01, higher maturity SHALL NOT be achieved by indiscriminate collection or broader surveillance.

9.8 Value Flow Controls

VAL-01 — Flow epistemic status

Field	Specification
Control objective	Flow epistemic status
Normative requirement	Direct, documented, reconstructed, and hypothetical value flows SHALL be distinguished.
Risk addressed	Prevent analytical reconstruction from being presented as if it were a known bank transaction or verified transfer.
Primary roles	Analyst; Reviewer; UI/data owner
Default trigger/frequency	At each relevant case event; continuous/system-enforced where technically appropriate.

Implementation requirements

- Set flow_class on every material ValueFlow.
- DIRECT requires direct transaction-level evidence; DOCUMENTED requires reliable documentation of the transfer/value movement; RECONSTRUCTED represents analytical linkage from multiple facts; HYPOTHETICAL is a scenario for testing only.
- Use distinct visual styling and narrative language for each class.
- Record amount/date uncertainty explicitly.

Minimum evidence of operation

- ValueFlow record
- Flow-class field
- Evidence links
- Visualisation legend

Assurance test

- Sample flows and verify classification against evidence.
- Check reports/graphs preserve class distinction.
- Review whether hypothetical flows leaked into findings.

Common failure modes

- All arrows look identical.
- Reconstructed contract-to-asset chain called a transfer.
- Estimated values displayed as exact.

Implementation maturity

Baseline: documented and consistently performed. Managed: system-supported, measured, and exceptions tracked. Assured: independently tested with remediation and periodic revalidation. For VAL-01, higher maturity SHALL NOT be achieved by indiscriminate collection or broader surveillance.

9.9 Typologies Controls

TYP-01 — Typology caution

Field	Specification
Control objective	Typology caution
Normative requirement	A typology match SHALL NOT be treated as proof of money laundering or predicate crime.
Risk addressed	Use typologies as structured analytical lenses without converting pattern similarity into a determination of wrongdoing.
Primary roles	Analyst; Peer reviewer
Default trigger/frequency	At each relevant case event; continuous/system-enforced where technically appropriate.

Implementation requirements

- Use the CS-AML Typology Catalogue entry ID and indicator classes.
- Record supporting, contextual, disconfirming indicators and intelligence gaps.
- Require corroboration before assessments above Plausible consistency unless direct authoritative evidence establishes the mechanism.
- Document legitimate alternative explanations.

Minimum evidence of operation

- Typology worksheet
- Indicator map
- Alternative explanation
- Assessment language

Assurance test

- Review a sample of typology matches for disconfirming indicators.
- Search products for deterministic phrases unsupported by adjudicated facts.

Common failure modes

- Single red flag equals typology match.
- Typology label used as allegation.
- No alternatives considered.

Implementation maturity

Baseline: documented and consistently performed. Managed: system-supported, measured, and exceptions tracked. Assured: independently tested with remediation and periodic revalidation. For TYP-01, higher maturity SHALL NOT be achieved by indiscriminate collection or broader surveillance.

9.10 Hypotheses Controls**HYP-01 — Competing explanations**

Field	Specification
Control objective	Competing explanations
Normative requirement	Material investigations SHOULD maintain plausible competing hypotheses.
Risk addressed	Reduce confirmation bias and make analytical reasoning explicit, testable, and reviewable.
Primary roles	Analyst; Peer reviewer
Default trigger/ frequency	At each relevant case event; continuous/system-enforced where technically appropriate.

Implementation requirements

- Create hypothesis records with supporting, contradicting, and unknown evidence.
- Include a legitimate/non-criminal explanation where plausible.
- Update status as evidence changes.
- Avoid deleting rejected hypotheses; retain decision history.

Minimum evidence of operation

- Hypothesis matrix
- Status history
- Evidence links

Assurance test

- Check high-impact cases for more than one plausible hypothesis.
- Verify rejected hypotheses show rationale.

Common failure modes

- Only inculpatory hypothesis exists.
- Hypothesis rewritten after evidence arrives to appear correct.

Implementation maturity

Baseline: documented and consistently performed. Managed: system-supported, measured, and exceptions tracked. Assured: independently tested with remediation and periodic revalidation. For HYP-01, higher maturity SHALL NOT be achieved by indiscriminate collection or broader surveillance.

HYP-02 — Disconfirmation

Field	Specification
Control objective	Disconfirmation
Normative requirement	High-impact adverse findings SHALL document reasonable efforts to find disconfirming evidence.
Risk addressed	Prevent strong conclusions from being produced solely by accumulating confirmatory material.
Primary roles	Lead analyst; Independent reviewer
Default trigger/frequency	At each relevant case event; continuous/system-enforced where technically appropriate.

Implementation requirements

- Define what evidence would weaken or falsify each material hypothesis.
- Perform targeted searches for legitimate explanations, contradictory records, timing inconsistencies, identity mismatches, and alternative controllers/owners.
- Record searches even when no disconfirming evidence is found.

Minimum evidence of operation

- Disconfirmation log
- Search notes
- Hypothesis matrix
- Peer-review checklist

Assurance test

- Inspect high-impact findings for explicit disconfirmation actions.
- Assess whether searches were meaningful rather than ceremonial.

Common failure modes

- “No contradiction found” with no search record.
- Only sources likely to confirm the hypothesis are used.

Implementation maturity

Baseline: documented and consistently performed. Managed: system-supported, measured, and exceptions tracked. Assured: independently tested with remediation and periodic revalidation. For HYP-02, higher maturity SHALL NOT be achieved by indiscriminate collection or broader surveillance.

9.11 Assessment Controls**ASM-01 — Confidence statement**

Field	Specification
Control objective	Confidence statement
Normative requirement	Material assessments SHALL carry an explicit confidence level and basis.
Risk addressed	Communicate the strength and limitations of analytical judgments so readers do not interpret all findings as equally certain.
Primary roles	Analyst; Reviewer
Default trigger/frequency	At each relevant case event; continuous/system-enforced where technically appropriate.

Implementation requirements

- Use controlled confidence levels (e.g., Low/Moderate/High) with documented basis.
- Base confidence on evidence quality, corroboration, inference distance, unresolved contradictions, and intelligence gaps—not merely number of sources.
- Separate confidence in identity, relationship, flow, typology, and overall judgment where materially different.

Minimum evidence of operation

- Assessment record
- Confidence rationale
- Evidence matrix

Assurance test

- Compare confidence level with source quality and gaps.
- Check for high confidence despite unresolved identity or provenance issues.

Common failure modes

- Numeric score with no explanation.
- High confidence because many articles repeat the same claim.

Implementation maturity

Baseline: documented and consistently performed. Managed: system-supported, measured, and exceptions tracked. Assured: independently tested with remediation and periodic revalidation. For ASM-01, higher maturity SHALL NOT be achieved by indiscriminate collection or broader surveillance.

GAP-01 — Explicit unknowns

Field	Specification
Control objective	Explicit unknowns
Normative requirement	Material intelligence gaps SHALL be explicit and linked to affected judgments.
Risk addressed	Make clear what is not known and prevent absence of data from being mistaken for evidence of absence.
Primary roles	Analyst; Reviewer
Default trigger/frequency	At each relevant case event; continuous/system-enforced where technically appropriate.

Implementation requirements

- Maintain a gap register with gap description, impact, priority, possible collection path, legal/ethical constraints, and status.
- Link gaps to hypotheses, assessments, or value flows they affect.
- Carry critical unresolved gaps into intelligence products.

Minimum evidence of operation

- Intelligence Gap Register
- Assessment limitations
- Collection plan

Assurance test

- Select key judgments and verify critical unknowns are visible.
- Check closed gaps have supporting evidence.

Common failure modes

- Unknown source of funds omitted.
- Bank data unavailable but flow written as complete.

Implementation maturity

Baseline: documented and consistently performed. Managed: system-supported, measured, and exceptions tracked. Assured: independently tested with remediation and periodic revalidation. For GAP-01, higher maturity SHALL NOT be achieved by indiscriminate collection or broader surveillance.

9.12 Privacy Controls**PRI-01 — Data minimisation**

Field	Specification
Control objective	Data minimisation
Normative requirement	Sensitive personal data SHALL be necessary, proportionate, and relevant to an approved investigation purpose.
Risk addressed	Limit harm, legal exposure, and surveillance creep by collecting only data that materially serves the investigation.
Primary roles	Case owner; Privacy reviewer; Collector

Field	Specification
Default trigger/frequency	At each relevant case event; continuous/system-enforced where technically appropriate.

Implementation requirements

- Apply necessity/relevance test before collecting or retaining sensitive data.
- Document justification for special-category/sensitive financial or protected-source information.
- Avoid collecting relatives, associates, contacts, or location history merely because technically available.
- Use redaction/pseudonymisation where identity is not required.

Minimum evidence of operation

- Collection decision
- Privacy review
- Data inventory
- Redaction record

Assurance test

- Compare collected sensitive fields with case purpose.
- Sample unrelated persons for documented necessity.
- Check bulk imports for minimisation controls.

Common failure modes

- “May be useful later” as sole justification.
- Whole datasets retained when only a few records are relevant.

Implementation maturity

Baseline: documented and consistently performed. Managed: system-supported, measured, and exceptions tracked. Assured: independently tested with remediation and periodic revalidation. For PRI-01, higher maturity SHALL NOT be achieved by indiscriminate collection or broader surveillance.

PRI-02 — Retention and disposition

Field	Specification
Control objective	Retention and disposition
Normative requirement	Sensitive data SHALL have retention, review, and disposition rules.
Risk addressed	Prevent indefinite accumulation of personal data and ensure closed-case material is retained only for justified periods.
Primary roles	Data steward; Privacy reviewer; Evidence custodian
Default trigger/frequency	At each relevant case event; continuous/system-enforced where technically appropriate.

Implementation requirements

- Assign retention class at ingestion or case association.
- Define review triggers, legal holds, archival criteria, deletion/anonymisation methods, and exceptions.
- Log destruction or irreversible anonymisation.
- Protect evidence that must be preserved from premature deletion.

Minimum evidence of operation

- Retention schedule
- Disposition log
- Legal hold record
- Retention review

Reference implementation (MVP 0.1) [v0.1.3 · CR-I7-01, CR-I7-03, CR-I7-04, CR-I7-05] The retention schedule is the set of RetentionRules (Data Model §16.1), the legal hold record is the LegalHold (§16.2) and the disposition log is the DispositionRecord (§16.3), managed through the retention API (API Specification §20A). Disposition is never automatic: evaluation reports or proposes, the case LEAD (never the proposer) approves, and execution is refused under an active legal hold. MVP 0.1 supports DELETE (stored bytes purged; the record remains as a tombstone with hash and size), ARCHIVE and REVIEW; irreversible anonymisation and whole-case deletion are not available until v0.2, so the “log irreversible anonymisation” requirement has no MVP 0.1 occurrence.

Assurance test

- Identify expired items and verify disposition occurred.
- Review exceptions for approvals and reasons.

Common failure modes

- Everything retained indefinitely.
- Manual deletion with no audit.
- Retention policy exists but no job/workflow implements it.

Implementation maturity

Baseline: documented and consistently performed. Managed: system-supported, measured, and exceptions tracked. Assured: independently tested with remediation and periodic revalidation. For PRI-02, higher maturity SHALL NOT be achieved by indiscriminate collection or broader surveillance.

9.13 Security Controls

SEC-01 — Least privilege

Field	Specification
Control objective	Least privilege
Normative requirement	Access SHALL be role- and need-based.
Risk addressed	Reduce insider risk and unnecessary exposure of sensitive case, source, and personal data.
Primary roles	Security administrator; Case owner; Data owner
Default trigger/ frequency	At each relevant case event; continuous/system-enforced where technically appropriate.

Implementation requirements

- Define roles and data-access attributes.
- Separate ordinary case access from protected-source identity, highly sensitive evidence, and dissemination authority.
- Review access periodically and on role change.
- Use strong authentication and log privileged actions.

Minimum evidence of operation

- Access-control matrix
- IAM configuration
- Access review
- Privileged audit log

Assurance test

- Sample users and compare permissions with role.
- Test terminated/transferred users.
- Review dormant privileged accounts.

Common failure modes

- All investigators are administrators.
- Shared accounts.
- Case access never expires.

Implementation maturity

Baseline: documented and consistently performed. Managed: system-supported, measured, and exceptions tracked. Assured: independently tested with remediation and periodic revalidation. For SEC-01, higher maturity SHALL NOT be achieved by indiscriminate collection or broader surveillance.

SEC-02 — Protected-source compartmentalisation

Field	Specification
Control objective	Protected-source compartmentalisation
Normative requirement	Protected source identities SHALL be compartmentalised from ordinary case material.
Risk addressed	Reduce risk that compromise, sharing, publication, or broad team access reveals whistleblowers or confidential informants.
Primary roles	Source handler; Security administrator; Case owner
Default trigger/frequency	At each relevant case event; continuous/system-enforced where technically appropriate.

Implementation requirements

- Use source aliases in general case records.
- Store identifying data in a restricted compartment with separate permissions.
- Minimise cross-links that expose identity.
- Define controlled re-identification process and emergency disclosure rules.

Minimum evidence of operation

- Restricted source store
- Alias mapping
- Access log
- Re-identification approval

Assurance test

- Verify ordinary analysts cannot retrieve source identity without authorisation.
- Check exports/publication packages for leakage.

Common failure modes

- Source name embedded in filenames.
- Identity repeated in notes and chat.
- Alias mapping stored beside public product.

Implementation maturity

Baseline: documented and consistently performed. Managed: system-supported, measured, and exceptions tracked. Assured: independently tested with remediation and periodic revalidation. For SEC-02, higher maturity SHALL NOT be achieved by indiscriminate collection or broader surveillance.

9.14 Quality Controls**QUA-01 — Independent peer review**

Field	Specification
Control objective	Independent peer review
Normative requirement	High-impact products SHALL be independently reviewed before external dissemination.
Risk addressed	Detect analytical error, unsupported inference, overstatement, privacy harm, and inconsistent application of the framework.
Primary roles	Peer reviewer; Approver; Lead analyst
Default trigger/frequency	At each relevant case event; continuous/system-enforced where technically appropriate.

Implementation requirements

- Define high-impact criteria.
- Reviewer SHALL be sufficiently independent from primary analysis.
- Review provenance, entity resolution, key relationships, flow classification, typology use, alternatives, confidence, gaps, privacy, and wording.
- Material reviewer disagreements SHALL be resolved or recorded.

Minimum evidence of operation

- Peer-review form
- Reviewer comments
- Resolution log
- Approval record

Assurance test

- Reperform selected key judgments from evidence.
- Check reviewer independence and timing.
- Verify disagreements were not silently removed.

Common failure modes

- Copy-editing mistaken for analytical review.
- Reviewer approves without evidence access.

Implementation maturity

Baseline: documented and consistently performed. Managed: system-supported, measured, and exceptions tracked. Assured: independently tested with remediation and periodic revalidation. For QUA-01, higher maturity SHALL NOT be achieved by indiscriminate collection or broader surveillance.

9.15 Dissemination Controls**DIS-01 — Handling and approval**

Field	Specification
Control objective	Handling and approval
Normative requirement	External dissemination SHALL have classification, audience, purpose, and approval recorded.
Risk addressed	Prevent intelligence products from reaching audiences that lack need, context, legal basis, or adequate handling capability.
Primary roles	Product owner; Approver; Security/privacy reviewer
Default trigger/frequency	At each relevant case event; continuous/system-enforced where technically appropriate.

Implementation requirements

- Classify product and define intended audience/use.
- Apply redaction, minimisation, source protection, and caveats appropriate to recipient.
- Record approval, recipient, date, version, transfer method, and restrictions.
- Create separate referral and public versions where necessary.

Minimum evidence of operation

- Dissemination log
- Approved product version
- Recipient restrictions
- Transfer record

Assurance test

- Match sent files to approved hashes/versions.
- Verify recipients and restrictions.
- Check whether superseded drafts were shared.

Common failure modes

- Emailing working files.
- No record of who received which version.
- Same product sent to FIU and published publicly.

Implementation maturity

Baseline: documented and consistently performed. Managed: system-supported, measured, and exceptions tracked. Assured: independently tested with remediation and periodic revalidation. For DIS-01, higher maturity SHALL NOT be achieved by indiscriminate collection or broader surveillance.

9.16 Audit Controls

AUD-01 — Material change auditability

Field	Specification
Control objective	Material change auditability
Normative requirement	Material analytical and evidentiary changes SHOULD be logged.
Risk addressed	Allow reconstruction of how the case changed and who made decisions affecting findings.
Primary roles	System owner; Security; Assurance reviewer
Default trigger/ frequency	At each relevant case event; continuous/system-enforced where technically appropriate.

Implementation requirements

- Audit creation/update/deletion/merge/unmerge of material entities, evidence metadata, relationships, hypotheses, assessments, approvals, dissemination, and access to highly sensitive records.
- Protect logs from routine user alteration.
- Synchronise time sources where practical.

Minimum evidence of operation

- Audit trail
- Version history
- Log-retention policy
- Integrity monitoring

Assurance test

- Trace a sample material change end-to-end.
- Check logs identify actor, time, object, action, and previous/new state where required.

Common failure modes

- Only login events logged.
- Analysts can edit audit logs.
- No history after entity merge.

Implementation maturity

Baseline: documented and consistently performed. Managed: system-supported, measured, and exceptions tracked. Assured: independently tested with remediation and periodic revalidation. For AUD-01, higher maturity SHALL NOT be achieved by indiscriminate collection or broader surveillance.

9.17 Technology Controls

TEC-01 — AI verification

Field	Specification
Control objective	AI verification
Normative requirement	AI-generated material SHALL NOT become a material fact without human verification against authoritative or primary evidence.
Risk addressed	Prevent hallucinated, decontextualised, or misattributed model output from contaminating evidentiary records and assessments.
Primary roles	Analyst; Technology owner; Reviewer
Default trigger/frequency	At each relevant case event; continuous/system-enforced where technically appropriate.

Implementation requirements

- Label AI-assisted outputs.
- Require source-level human verification before a Claim is recorded or a Fact is created through a VerificationDecision. [v0.1.1 · C16]
- Do not permit generative summaries to overwrite original evidence.
- Record model/tool use when material to reproducibility.
- Apply stricter controls to identity resolution, allegation drafting, translation, and extraction from sensitive records.
- Run every automation engine offline (no evidence content to third-party services, no on-line fallback); keep machine output labelled machine-generated and review-required until a person reviews it; a review never creates a Fact. [v0.1.4 · CR-N-09, CR-N-10]

Minimum evidence of operation

- AI-use record
- Verification record
- Source links
- Prompt/output retention where policy permits

Assurance test

- Sample AI-assisted facts and reproduce verification.
- Search for facts whose only provenance is an AI output.

Common failure modes

- LLM answer cited as source.
- AI confidence treated as analytical confidence.
- Unverified OCR/translation used to create a fact without a VerificationDecision. [v0.1.1 · C16]

Implementation maturity

Baseline: documented and consistently performed. Managed: system-supported, measured, and exceptions tracked. Assured: independently tested with remediation and periodic revalidation. For TEC-01, higher maturity SHALL NOT be achieved by indiscriminate collection or broader surveillance.

TEC-02 — Explainable automation

Field	Specification
Control objective	Explainable automation
Normative requirement	Automated scores or models used materially SHOULD be explainable and governed.
Risk addressed	Ensure risk scores, entity matching, anomaly flags, and typology ranking can be understood, challenged, validated, and changed.
Primary roles	Model owner; Analyst; Independent validator
Default trigger/frequency	At each relevant case event; continuous/system-enforced where technically appropriate.

Implementation requirements

- Document purpose, input features/data, output meaning, thresholds, version, known limitations, owner, validation status, and override process.
- Do not use a score as a substitute for assessment.
- Monitor drift and false positives where outcomes are available.

Minimum evidence of operation

- Model/rule card
- Validation record
- Threshold rationale
- Override log
- Performance metrics

Assurance test

- Select material automated outcomes and explain why they occurred.
- Check model version used at decision time.
- Review overrides for patterns.

Common failure modes

- Black-box score with no feature explanation.
- Threshold chosen only to reduce workload.
- Model changes without versioning.

Implementation maturity

Baseline: documented and consistently performed. Managed: system-supported, measured, and exceptions tracked. Assured: independently tested with remediation and periodic revalidation. For TEC-02, higher maturity SHALL NOT be achieved by indiscriminate collection or broader surveillance.

10. Cross-Control Implementation Bundles

10.1 New case baseline

Before substantive collection, assign owner, approve purpose/scope, establish source provenance, confirm necessary/proportionate collection, and restrict access.

| Controls: GOV-01 CAS-01 SRC-01 PRI-01 SEC-01

10.2 Sensitive/protected-source case

Use enhanced gates, protected-source compartmentalisation, stricter access, retention decisions, and auditable handling.

| Controls: GOV-01 CAS-02 PRI-01 PRI-02 SEC-01 SEC-02 AUD-01

10.3 Entity/graph investigation

Every merge, edge, asset attribution, and derived graph element remains evidence-linked and reversible.

| Controls: SRC-01 EVD-02 ENT-01 REL-01 AST-01 AUD-01

10.4 Follow-the-value investigation

Clearly distinguish known transfer evidence from reconstructed economic relationships and carry gaps/confidence into the assessment.

| Controls: VAL-01 REL-01 AST-01 HYP-01 GAP-01 ASM-01

10.5 High-impact adverse product

Require alternative explanations, disconfirmation, explicit confidence/gaps, independent review, and controlled dissemination.

| Controls: GOV-02 CAS-02 TYP-01 HYP-01 HYP-02 ASM-01 GAP-01 QUA-01 DIS-01

10.6 AI/automation-assisted investigation

Verify model outputs against source evidence, preserve lineage/versioning, explain material scores, and independently review high-impact uses.

| Controls: TEC-01 TEC-02 EVD-02 ENT-01 AUD-01 QUA-01

11. Exceptions and Compensating Controls

A control exception is not the absence of a control. It is a documented, risk-accepted deviation from the standard requirement. Exceptions SHALL be narrowly scoped and time-limited.

8. Identify the control and exact requirement not met.
9. Explain operational reason and affected cases/data.
10. Assess analytical, privacy, security, legal, source-safety, and reputational risk.
11. Define compensating control(s).
12. Obtain approval from a role independent of the person requesting the exception where practicable.
13. Set expiry/review date.
14. Record closure, extension, or conversion into a permanent control change.

Not an exception

Convenience, workload, urgency, donor pressure, publication deadlines, or technical difficulty alone do not justify silently bypassing a mandatory control.

Non-waivable invariants [v0.1.1 · A16]

No exception, waiver, or risk acceptance may permit: (1) unauthorized access or authorization bypass; (2) exposure of protected source identity; (3) evidence corruption or loss of provenance/integrity for material records; (4) certainty promotion — e.g. reconstructed or hypothetical flows presented or stored as direct/documented, an insufficient-basis judgement presented as a confidence level, or a claim treated as fact without a recorded verification decision; (5) approval bypass, including external dissemination or export without approval; (6) broken, missing, or editable audit history. Where a system defect produces one of these conditions, the only acceptable path is to disable the affected function with tested evidence that it cannot be reached; the defect itself is not excepted. Exceptions for other requirements remain subject to steps 8–14 above, including a compensating control, independent approval, and an expiry date.

12. Metrics and Control Effectiveness

Metrics SHALL be interpreted as evidence about outcomes, not targets that incentivise surveillance or accusation. Higher case volume, more entities, more alerts, or more typology matches are not measures of success.

Domain	Illustrative measures
Purpose/scope	% cases with approved charter before substantive collection; number of scope-change exceptions.
Provenance	% material facts traceable to registered evidence; orphan derivative rate.
Entity quality	Merge reversal rate; duplicate rate; high-impact merges independently reviewed.
Relationship quality	% material edges with evidence; unsupported-edge defects found in QA.
Value flow	% material flows with explicit flow_class; reconstructed/direct misclassification findings.
Analytical discipline	% high-impact cases with competing hypotheses/disconfirmation; unresolved critical gaps at dissemination.
Privacy	Sensitive records collected without necessity rationale; retention exceptions; privacy incidents.
Security	Excess-access findings; protected-source access events; privileged account review completion.
Quality	Peer-review defect categories; material changes prompted by review; repeat findings.
Technology	AI facts rejected at verification; model overrides; unexplained-score findings.
Dissemination	Unapproved recipients/versions; redaction defects; dissemination withdrawal/correction events.

13. Assurance Programme

13.1 First-line self-check

Case teams perform control completion checks and correct obvious gaps before gate review or dissemination.

13.2 Independent quality review

Peer or specialist reviewers challenge evidence, reasoning, privacy, security, and product wording for high-impact cases.

13.3 Periodic control assurance

An organisational reviewer independent of day-to-day case work tests a sample of controls, documents findings, tracks remediation, and reports systemic issues to leadership.

13.4 Triggered assurance

- material correction or retraction
- source compromise or data breach
- serious unsupported allegation
- repeated entity-resolution errors
- major technology/model change
- external complaint indicating potential rights harm
- material control failure in a partner or shared investigation

14. Implementation Maturity Model

Level	Characteristics
L1 — Defined	Named control owners; baseline policy/templates; minimum records exist; control operation largely manual.
L2 — Managed	Controls integrated into case workflow; risk profiles, gate checks, access, retention, and review operate consistently; exceptions tracked.
L3 — Measured	Control coverage/outcomes are measured; recurring defects analysed; system validations reduce manual errors; independent testing occurs.
L4 — Assured & adaptive	Independent assurance, secure automation, model validation, trend analysis, cross-case learning, partner controls, and documented continuous improvement.

Maturity rule

Higher maturity means better selectivity, provenance, challenge, safety, and decision usefulness—not greater data volume or more intrusive monitoring.

15. Minimum Organisational Implementation Plan

Phase	Minimum deliverables
Phase A — Foundation	Adopt framework; nominate owner; approve roles; define P1-P4 profiles; establish case/source/evidence registers; implement least privilege.
Phase B — Analytical controls	Implement entity resolution, relationship provenance, asset attribution, flow classification, typology worksheets, hypotheses, confidence, and gap registers.
Phase C — Protection & dissemination	Implement protected-source compartmentalisation, retention, high-impact peer review, dissemination logging, and incident response.
Phase D — Assurance & technology	Implement audit events, periodic control testing, AI/model governance, metrics, and remediation tracking.

16. Control Implementation Conformance

An organisation MAY claim conformance with this guide only for a stated scope (for example, a unit, programme, platform, or investigation function) and assessment period.

- All applicable mandatory controls have documented owners and procedures.
- Evidence demonstrates controls operated during the assessment period.
- Material exceptions are recorded, approved, and time-limited, and none covers a non-waivable invariant (§11). [v0.1.1 · A16]
- High-impact cases meet enhanced review requirements.
- A risk-based control test has been completed and material deficiencies have remediation plans.
- The organisation does not claim conformance merely because templates or software features exist.

16.1 Minimum Conformance Evidence Pack

- Control register with owner/status
- Approved local implementation procedures
- Sample case charter and gate records
- Source/evidence provenance records
- Entity merge and relationship provenance records
- Value-flow classification records
- Hypothesis/assessment/gap artefacts
- Privacy and access evidence
- Peer-review and dissemination evidence
- Audit/event history
- Control test results
- Open exceptions and remediation register

17. Traceability to Other CS-AML Documents

Document	Control-guide relationship
Goals & Non-Goals	Defines why controls exist and what CS-AML must not become.
Investigation Methodology	Defines when controls operate across case stages and gates.
Typology Catalogue	Provides structured typology and indicator content governed by TYP-01 and related analytical controls.
Data Model Specification	Defines the canonical objects and metadata that store control evidence, provenance, confidence, privacy, audit, and analytical records.
Technology Architecture (planned)	Will define reference technical components used to implement security, workflow, graph, evidence, audit, model, and reporting controls.

Annex A — Control Register Template

Control ID	Owner	Procedure	Profile	Frequency	Evidence	Status	Last test	Rating	Remediation

Annex B — Control Test Worksheet

Field	Specification
Control ID	
Period / population	
Tester / independence	
Design effectiveness	Effective / Improvement / Partial / Ineffective
Operating effectiveness	Effective / Improvement / Partial / Ineffective
Sample	
Exceptions	
Root cause	
Risk/impact	
Remediation owner/date	
Retest result	

Annex C — Exception Record Template

Field	Specification
Exception ID	
Non-waivable invariant check (confirm the exception does not touch any invariant in §11) [v0.1.1 · A16]	
Control / requirement	
Reason	
Affected scope	
Risk assessment	
Compensating control	
Approver	
Start / expiry	
Review result	

Annex D — High-Impact Product Control Checklist

- ☐ Case purpose/scope current
- ☐ Material facts trace to evidence
- ☐ Entity resolution rechecked
- ☐ Material relationships evidence-linked
- ☐ Asset attribution wording matches evidence
- ☐ Value flows correctly classified
- ☐ Typology not presented as proof
- ☐ Competing hypotheses considered
- ☐ Disconfirming search documented
- ☐ Confidence and basis explicit
- ☐ Critical gaps visible
- ☐ Sensitive data minimised
- ☐ Protected sources protected

- ☐ Independent peer review completed
- ☐ Dissemination version/audience approved

Annex E — Reference Lineage

These external sources provide alignment context rather than direct regulatory obligations for civil-society organisations. CS-AML adapts their risk-based and effectiveness concepts to a rights-respecting investigative setting.

Source	Use in this guide
FATF	FATF Recommendations and 2022 Methodology, as amended June 2026 — risk-based approach and effectiveness principles.
Wolfsberg Group	Guidance on the Risk-Based Approach, June 2026 — proportionality, prioritisation, and effectiveness.
PPATK	Klinik Dumas Special Edition, November 2025 — role and quality of NGO/CSO and public information in supporting financial-intelligence analysis.
CS-AML	Framework v0.1.4 Expanded; Goals & Non-Goals; Typology Catalogue; Investigation Methodology; Data Model Specification.

E.1 Interpretation notes

FATF materials inform the concepts of risk-based implementation and effectiveness. Wolfsberg materials inform proportionality, prioritisation, and outcome focus. PPATK materials support the premise that well-structured NGO/CSO information can contribute to financial-intelligence analysis. None of these references converts CS-AML users into regulated financial institutions or grants investigative powers reserved to competent authorities.