
TECHNICAL DOCUMENTATION

AI agents that can only spend inside your rules.

ChainBrain gives each AI agent its own card: a small program on the blockchain that holds the agent's money and the owner's rules. The agent shops and pays on its own. The card checks every payment, so even a tricked agent can't pay outside the rules.



Above a limit you choose, the card also needs your signature, given on your phone for that one payment.

Money is Mock e-HKD, a test token on a FISCO BCOS blockchain, shown in HK$.

HK$0
lost in 63 attacks, including 8 against a live AI model

25
transactions on a public chain that anyone can open, 9 of them refused attacks

462
automated tests in 7 suites, all passing on 19 October

Try it and check it

Phone app	Web console	Chain explorer	Source code
fisco-phone-production...	fisco-web-production...	fisco-api-.../explorer	github.com/ixgnoy/ChainBrain


All four run on Railway; the phone app opens in any browser. Also in this package: the security self-assessment and the execution evidence.

01 · PROJECT OVERVIEW

The problem, and who it is for


An AI agent that pays for things today gets either a whole wallet or nothing. With the wallet, one tricked instruction can empty it. Without it, the owner approves every payment by hand, and the agent saves no time.

Agent with your wallet



One tricked instruction can send everything.

Agent with a ChainBrain card



At worst it spends that card's balance, with allowed sellers only.

Who it is for

People and small businesses who want an AI agent to buy small things on its own, such as data, reports or news feeds, without watching every step and without handing over their wallet.

Topic F, Agent Wallet

An AI wallet agent that carries out on-chain payments by itself, with risk control. Every payment in this package is a real transaction on a FISCO BCOS chain that judges can open.

What is new

One card per agent

Each agent spends from its own contract with its own balance and rules. A mistake stays inside that card.

Rules checked at the moment of payment

The token asks the card before any money moves. Our server checks first too, but nothing depends on it.

AI that can only make rules stricter

Radar scores sellers, the Sentinel can freeze a card, and memory keeps preferences. None of them can loosen a rule.

An agent that explains a "no"

Every refusal comes back with a reason the agent reads. It tries another seller or tells the owner the one change that would help.


Where to find what is scored

Judging area	Where to look
Task completion, 40%	Execution evidence: 25 transactions on the hosted chain, each with a link and a one-command re-check
Security and compliance, 30%	Security self-assessment: permissions, 63 attacks, data and privacy, known risks. Pages 9 and 10 here
Innovation and interaction, 30%	Pages 6 to 8 here: the agent, the payment path and the card's checks. The apps on page 5

02 · SYSTEM ARCHITECTURE

Architecture, by who you have to trust

Read it top to bottom. The owner's device holds the only key that can change a rule. Our servers run the AI and can be wrong. The chain at the bottom holds the rules and has the final say on every payment.



Arrows show who calls whom. The green line is the only path that changes a card's rules. The Sentinel's key can freeze a card and nothing else. The agent loop calls the wallet tools; the model never sees a key.

Models, tools, data sources and outside services

AI model	Claude Haiku 5.5 through OpenRouter by default. One setting switches to Anthropic's API or to a scripted agent with no model.
Agent tools	7 wallet tools. Only `pay` moves money, and no tool accepts a payee address (page 4).
Payments	x402 version 2: the seller answers HTTP 402 with a price, the agent's signed payment comes back in a header, and a facilitator submits it on chain.
Data sources	Seller content, always wrapped as untrusted; token transfers on the chain, which Radar indexes; an optional risk-label file.
Hosting	Railway: the chain node, the wallet API, the sellers, the web console and the phone app's web build.

02 · SYSTEM ARCHITECTURE

The wallet server

A TypeScript service (Hono on Node 24, with viem and the x402 libraries) runs the agent and checks each payment before it reaches the chain. A second process runs the test sellers. Neither holds an owner's key.

Sign-in and accounts

Password-free sign-in with the owner's key, one agent key per card, rate limits, and saved accounts and events.

Payments

The 7 tools, quotes and settlement over x402, the task check, the dry run, owner co-signs, and the 30 refusal reasons.

The agent

The tool loop, the scripted fallback, the model switch, memory, and turning one sentence into card rules.

Safety

Radar's seller screening and alerts, the Sentinel's hold and freeze, and the judges' attack arena on the real chain.

Routines and onboarding

Standing orders checked every 30 seconds. A new account starts lived-in: two cards make real purchases, one refuses a planted transfer on chain, and a daily routine leaves a co-sign waiting.

Chain access

A read-only explorer and RPC proxy, plus the 8 x402 test sellers with 12 items.

The agent's seven tools

Tool	What it does	Moves money
`get_pocket`	Reads the card's balance, cap, ask-me limit, allowance and what this task has spent	no
`search_sellers`	Lists sellers, items and prices, and whether the card allows each seller	no
`draft_intent`	Shows the owner a fixed Buy / Price / Deadline card and waits up to 10 minutes for a yes	no
`get_quote`	Gets the seller's price and reports the card check, the task check and Radar's score	no
`counter_offer`	Haggles, at most 3 rounds, only on items that have a floor price	no
`ask_owner`	Asks the owner a question, or asks for a co-sign on one quote	no
`pay`	Runs every check on page 7, then settles the quote over x402	yes, only this one

No tool takes a payee address, edits a card, or reaches another card or the owner's main wallet. A tricked model can only choose among quotes the server fetched itself.

Main routes, 42 in all

`POST /v1/challenge`, `/v1/visitors` sign up or sign in

`POST /v1/cards/agent` the next card's agent address

`POST /api/chat` one turn of the agent

`POST /api/approvals/:id` the owner's answer or co-sign

`GET /api/events` the live event stream

`POST /api/rules/compile` one sentence to card rules

`POST /api/arena/straight` the agent key tries the chain directly

`GET /api/radar/screen/:who` a seller's risk score


`GET /explorer` blocks and transactions

`POST /api/faucet` test money for an address

02 · SYSTEM ARCHITECTURE

The apps


The phone app is where the owner works: cards, the agent, co-signing. The web console is where a judge watches each decision and tries to break it. These are screens from the real apps.




Home
the main wallet and one card per job




New card
one sentence becomes the card's rules




Co-sign
one payment, one seller, slide and Face ID



Brain
how each payment was decided



Sentinel
asks for an OK, then freezes the card



Web console, Judges tab: four one-tap attacks (induced transfer, data extraction, privilege escalation, prompt injection), each with its expected result and a box to write your own.

	Phone app
Built with	Expo SDK 57, React Native 0.86
Tabs	Home, Agents, Brain, Activity, Settings
Owner key	made on the phone, kept in its secure storage

	Web console
Built with	React 19, Vite 8, Tailwind 4
Tabs	Live, Brain, Pockets, Sellers, Explorer, Evidence, Judges, Faucet
Owner key	made in the browser, optionally locked by a passkey

Every step on screen

Both apps follow the server's live event stream: the task, the quote, Radar, the dry run, the payment, or the refusal and its reason. Each transaction links to the explorer.

The phone signs only what it can read


A signing guard decodes each request first. It signs sign-in, creating or funding the owner's own card, the owner's controls, and a co-sign that matches the payment on screen. Anything else is refused.

03 · AGENT DESIGN

How the agent understands, plans and remembers

The model plans, compares sellers and talks to the owner. We assume it can be tricked, so the money rules sit in code and on the chain, not in instructions to the model.

One turn of the agent



When something goes wrong

At 24 model calls the turn stops and names any payment made.

If the model fails or has no key, a scripted agent finishes the turn, and the trace says so.

The task the owner confirms

```
Buy: one durian export market report
Price: at most HK$15.00 each, HK$15.00 in total, up to 1 item
Deadline: 2026-10-19 23:59 HKT
```

The model fills in the fields. Code writes the three lines, so the amounts and the deadline shown are never the model's own words. Each quote, co-sign request and payment is then checked against them: confirmed, not expired, price per item, total, number of items.

Models

Setting `LLM_PROVIDER`	Used for every AI feature
openrouter default	Claude Haiku 5.5, or one of four other preset models
anthropic	Opus 5.5 for the agent, Sonnet 5.5 for rules, Haiku 5.5 for memory, Radar and the Sentinel
scripted	No model: a keyword router and fixed parsers

Memory can only tighten

After each turn the model writes a short note per card, up to 30 items. It reads only the owner's words and fixed lines built from wallet events, never seller text. A note that would loosen a limit ("always pay", "raise the cap", "trust this seller") is rejected. Two bad attempts keep the old note.

Rules from one sentence

"HK$5 a week for news, only Exa, ask me above HK$1." The model reads the sentence twice in parallel, and wherever the readings differ, the stricter value wins. The owner sees a draft card with each rule in plain words, and still has to sign it.

The Brain graph


The apps draw the agent's world as a live graph: ChainBrain in the centre, then agents, their cards, and the sellers each card may pay. Every node is a real agent, card or seller, and each line carries a payment count.

Seller text is data, never instructions. Everything a seller returns is wrapped as untrusted content, and fake closing tags are removed. Requests for personal data or for a signature are refused by code. Seller text never reaches memory, the haggler, Radar's summary or the Sentinel's model.

03 · CORE ALGORITHMS

One payment, step by step

"Get me a durian export report, under HK$15, by tonight." Every message from that sentence to the money landing, and where each check runs.



Step	Check	What happens	Refusal reason
7	**At the quote**	The card, the task and Radar are checked and reported, so the agent can change plan early. Nothing is refused yet.	none
12	**Task, Radar, Sentinel**	The price, total, item count and deadline; the seller's risk score; any hold on the card	`PRICE_ABOVE_INTENT` · `COUNTERPARTY_HIGH_RISK` · `SENTINEL_HOLD`
12	**Dry run, then card rules**	The exact transfer runs as a dry run and its result is recorded but never blocks. Then the card's own check is read from the chain	`SELLER_NOT_ALLOWED` · `OVER_CAP` · `NEEDS_OWNER_APPROVAL`
13	**Live price**	The seller's price at payment time must match the quote: network, token, payee, amount	`QUOTE_MISMATCH`
15	**The card, on chain**	The last check, made by the contract when the money moves (page 8)	the transfer reverts


Each refusal carries one of 30 reasons, so the agent can re-plan instead of retrying. A signed payment is valid for 600 seconds and only once. Its one-time number is derived from the confirmed task, so every transfer traces back to it.

03 · CORE ALGORITHMS

The card's checks

The card is a small smart contract. When a payment arrives, the token asks the card whether the signature is valid (the ERC-1271 standard), and the card answers yes only for a transfer inside the owner's rules.

What happens when a payment reaches the chain



One "no" and the token reverts the transfer: no money moves. The owner's co-signature can lift only two limits, the ask-me limit and the allowance. It never lifts a revoke, a freeze, the expiry, the seller list, the cap or the balance.

The rules a card holds

Rule	Who changes it	When broken
Sellers it may pay	the owner	`SELLER_NOT_ALLOWED`
Cap per payment, overall or per seller	the owner	`OVER_CAP`
Ask-me limit	the owner	the owner must co-sign that payment
Allowance per day, week or month, Hong Kong time	the owner	`OVER_PERIOD`, unless the owner co-signs
Expiry date	the owner	`POCKET_EXPIRED`
Freeze	the owner or the Sentinel freezes; only the owner unfreezes	`POCKET_FROZEN`
Revoke, for good	the owner, who can then take the money back	`POCKET_REVOKED`

What the agent and the owner sign

Both sign the same structured message (EIP-712): from this card, to one seller, one amount, one one-time number, one time window. The token is handed both signatures together:

```
abi.encode(to, value, validAfter, validBefore,
           nonce, agentSig, ownerSig)
```

ownerSig is empty when no co-sign is needed. The transfer itself follows EIP-3009, a token transfer anyone can submit once the payer has signed it.

The contracts

Pocket	the card, 216 lines
MockEHKD	the test token, 102 lines
PocketFactory	creates cards, 27 lines
Clock	FISCO's time in seconds, 11 lines

Solidity 0.8.24 with OpenZeppelin 5.4, built and tested with Foundry. Every rule change and payment emits an event anyone can read.

04 · SECURITY DESIGN

Who holds which key

Each key has one limited job. The owner's key is the only one that can change a rule or move money out freely, and it never leaves the owner's device.

Key	Where it lives	Can	Cannot
Owner	The phone's secure storage, or the browser with an optional passkey	Create, fund and edit cards; revoke; unfreeze; take the money back; co-sign one payment	Be seen by the server
Agent, one per card	Derived on the server when needed from a master secret and the card's id; never stored	Sign one exact transfer from its own card to a seller it was quoted	Change a rule, pay a seller not on the list, go past the cap, the allowance or the balance, or sign for someone else's card
Sentinel (guardian)	The server; fixed when the card factory is set up	Freeze a card, giving a reason	Move money, unfreeze, or change any rule
Facilitator	The server	Submit a payment the agent already signed	Spend from a card without the agent's signature
Token issuer	The server	Mint test Mock e-HKD for the faucet and new accounts	Touch any card's rules or balance

If a key is stolen

an agent key
Pays only allowed sellers, under the cap and the allowance. Above the ask-me limit it still needs the owner.

the whole server
The same limits apply to every card. The server's own checks are skipped; the card's are not.

the guardian key
Can freeze cards, which stops payments. The owner unfreezes. No money moves.

an owner key
Full control of that owner's cards, which is why it stays in the device's secure storage.

Signing in without a password

1 **Challenge** — a one-time number, valid 5 minutes → 2 **The device signs** — a login message that says it moves no money → 3 **The server checks** — same key, same account; no password stored → 4 **Session token** — 7 days; only its hash is kept

Every request that acts on a card checks the card's on-chain owner against the signed-in key. Someone else's card answers 403.

A new account gets real test funds on the chain: gas balance and HK$500 of Mock e-HKD, so it can open cards straight away.

Sensitive actions, by tier

Reading needs nothing. Paying inside the rules needs the owner to confirm the task once. Paying above the ask-me limit or the allowance needs the owner's co-sign for that payment. Changing a rule needs the owner's own transaction.

How a card gets its agent

The app asks the server for the next agent address. The owner's key then creates the card with that agent and the chosen rules, and funds it with a plain transfer. A card can only use an agent issued to its own owner.

04 · SECURITY DESIGN

Protection against injection, escalation and leaks

The layers above the card cut down mistakes. The card is the layer that guarantees the limits. The results of 63 attacks, the data map and the known risks are in the separate security self-assessment.

1 · AI agent
can be fooled, holds no key

2 · Seller text wrapped and scanned
data and signature requests refused

3 · Task check
price, total, items, deadline

4 · Radar
seller's money trail: pay, ask, or refuse

5 · Sentinel hold
after odd behaviour, the owner must OK

6 · Signing rule
signs only its own transfer, live price

our servers; skipped if the server is broken

7 · The card contract
exact payment, agent, rules, co-sign

8 · The token
each signed payment works once

on chain: always holds

beside the agent: memory can only tighten

Radar: who is this seller?

Radar indexes every Mock e-HKD transfer and follows a seller's money three hops each way. Labels come from a risk-list file, plus a "flagged" label for any seller that asked for data or a signature.



3 money from a flagged seller · 5 any mixer · 6 drainer or scam, or the seller itself flagged · 7 mixer 25%+ · 8 scam 10%+, darknet, or itself a mixer · 9 sanctioned, or drainer 10%+ · 10 itself sanctioned or a drainer, scam or darknet

Re-screens every 30 seconds; a worse score alerts every card that paid or quoted that seller. The thresholds are a first guess, not yet calibrated.

Sentinel: is this agent hijacked?

Signal	When	Action
Refusal burst	3 or more suspicious refusals in 60 s	freeze
Ghost transfer	money left with no payment event	freeze
Follow-through	a refusal within 120 s of a data request	hold
Probing	2 suspicious refusals in 60 s	watch
Repeated attacks	2 chat attacks in 5 minutes	watch
Fast burn	80% of the budget in the first 20% of the card's life	watch

The guardian can only freeze

A freeze is a transaction from the Sentinel's guardian key, which is set once per card. It can't move money, unfreeze or change a rule. Without that key, a freeze becomes a hold.

The AI can only make it stricter

A second model reads a fixed summary and may raise a watch to a hold or a freeze. It can never lower a decision, and a freeze needs at least 70% confidence.

A dry run that never blocks

Before paying, the wallet runs the exact transfer as a dry run and records "pays" or "refused, because". After settling it shows predicted against actual.

Prompt injection: seller text is data (page 6) and the card holds anyway. Privilege escalation: only the owner's key changes a rule (page 9). Privacy: no name, email or ID is collected, and requests for personal data are refused. All 30 refusal reasons are listed in the self-assessment.

05 · DEPLOYMENT AND TESTING

Three ways to run it

The apps open on the real hosted chain. A built-in demo network runs every scene with no server or internet. A local stack lets anyone run the real code end to end.

default

Hosted, real chain

The apps sign in with the owner's key and talk to the hosted wallet API. Real FISCO transactions, real Mock e-HKD, every hash in the public explorer.

Settings › Demo network

Built-in demo network

A whole simulated world inside the app: a virtual chain, the wallet API, 7 sellers, 3 agents, 12 scenes and two weeks of made-up history. Hashes exist only in the app.

Settings › Server

Your own server


Point either app at any ChainBrain server: one on a local FISCO node, or the dev stack, which runs the real server and contracts with a scripted agent and no API key.

What is real in each mode

	Hosted	Demo network	Dev stack
Chain	FISCO BCOS	in memory, same card rules	FISCO BCOS, local
Contracts	deployed	same check order	fresh deploy per run
Wallet server and tools	real	same logic, in the app	real
x402 payments	real	not run	real
The agent	live model	scripted	scripted
Radar and Sentinel	real	same rules, AI part scripted	real rules, no AI part
Memory	real	scripted	off, needs a model
Owner key	device	device	test keys

Pairing outside agents (Claude, ChatGPT) to a card exists only on the demo network for now.

Linking the phone to the console on the demo network



judge actions go back to the phone: plant an order, force a transfer, hijack, say something

05 · DEPLOYMENT AND TESTING

Chain and deployment

One FISCO BCOS 3.16.4 node runs on Railway with its own explorer and faucet, so anyone can open a transaction, get test money and check a card. FISCO BCOS is the open-source blockchain platform led by WeBank.

Public addresses

Console	fisco-web-production.up.railway.app
Phone app	fisco-phone-production.up.railway.app, in a browser
Explorer	fisco-api-production-85c5.../explorer
Faucet	fisco-api-production-85c5.../faucet, HK$100 a day
Chain RPC	fisco-node-production.up.railway.app
Wallet API	fisco-api-production-85c5.up.railway.app



The hosted explorer, built into the wallet API because FISCO has none: an attempt to move money outside the rules, reverted.

Contracts on the hosted chain

Mock e-HKD	`0x0355c0c5Afe2A35369056FBB854903A4aF07781A`
Card factory	`0x03aB4C311eeE7C3295c63F910D79a07Ffa7A097A`

Chain id 20200, gas price 0. Each card is its own contract made by the factory.

What the RPC gateway fixes

Fee history. Wallets ask for fee data that FISCO doesn't have, so the gateway answers with zeros.

Event logs. Large log queries are split into 5-block windows, up to 5,000 blocks.

Batches. More than 8 calls at once are split, and transaction indexes are repaired.

Funding. FISCO needs a sender to hold some native balance, so a protected route gives it.

Deploying it

On a laptop

```
bash scripts/fisco/setup.sh   # once
bash scripts/fisco/deploy.sh  # deploy, mint
cd server && pnpm sellers     # :4021
cd server && pnpm dev         # :8787
```

On Railway


```
railway up --service fisco-node
railway up --service fisco-api
railway up --service fisco-sellers
railway up --service fisco-web
railway up --service fisco-phone
```

`deploy.sh` funds the keys, deploys the contracts with Foundry and mints HK$10,000 of test money to the issuer. On Railway, the API service does the same at first start.

05 · DEPLOYMENT AND TESTING

Tests, setup and known limits

Every suite below was run on 19 October 2026 on the submitted code. Attack results and live-model runs are in the security self-assessment; every hosted transaction is in the execution evidence.



462 tests, 0 failures Plus 6 agent scenes, which pass 6 of 6 with the scripted agent.

Run the tests

```
cd contracts && forge test
cd server && npx vitest run
cd web && npx vitest run
cd mobile && npm test
cd mobile && node --import tsx \
  --test ../shared/sim/*.test.ts
cd devstack && npx vitest run
python3 -m unittest verify/test_verify.py
```

The server and full-stack suites need the local FISCO node: `bash scripts/fisco/start.sh`.

Settings that matter

Setting	Default, and what it does
`FISCO_RPC`	127.0.0.1:8545, the chain
`LLM_PROVIDER`	openrouter, or anthropic or scripted
`OPENROUTER_API_KEY`	none; without it, the scripted agent
`LLM_MODEL`	claude-haiku-5.5, or a preset
`AGENT_MASTER_KEY`	set once and never change
`SENTINEL_PK`	optional, the freeze-only guardian
`DATA_DIR`	server/.data, accounts and events
`VISITOR_STARTER`	500, HK$ for a new account

`pnpm wallets` writes the other keys to `server/.env`.

How to check our results

- Every hash opens in the hosted explorer.
- The Python verifier reads a card with only the standard library and compares it with what the owner approved.
- One script re-fetches all 25 hosted receipts.
- The console's Evidence tab exports expected against actual for each scene.

Known limits

- Radar's thresholds are a first guess, not calibrated on real data.
- The content scan reads JSON fields. A request written as prose is left to the model and the card.
- Open tasks, quotes, Radar's index and the Sentinel's state reset when the server restarts.
- One FISCO node. The iOS app was tested in the simulator and Expo Go, not as a store build.