

Class 7 Machine Learning 1

Ivy (PID: A15442572)

2/8/2022

#Clustering methods


Find groups (AKA) clusters in my data.

K-means clustering

Make up some data to test with.

```
# Make up some data wiith 2 clear groups
tmp <- c(rnorm(30, mean=3), rnorm(30, mean= -3))
x<- cbind(tmp, rev(tmp))

plot(x)
```



```
k<- kmeans(x, centers=2, nstart=20)
k
```

We can use the dollar syntac to get at the results (components of the returned list).

 k_{size}

Q2. What ‘component’ of your result objects details -cluster size? -cluster assignment/membership? -cluster center?


 k_{size}

```
k$cluster
```

```
k$centers
```

Q3. Plot x colors by the kmeans cluster assignment and add cluster centers as blue points

```
plot(x, col=k$cluster)
points(k$centers, col="blue", pch=15, cex= 2)
```



Hierarchical Clustering

The `hclust()` fnx needs a distance matrix as input not our original data. For this we use the `dist()` fnx.

```
hc<- hclust(dist(x))
hc
```

```
##
## Call:
## hclust(d = dist(x))
##
## Cluster method   : complete
## Distance        : euclidean
## Number of objects: 60
```

```
plot(hc)
abline(h=10, col= "red")
```

```
cutree(hc, h=10)

## [1] 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 2 2 2 2 2 2 2 2
## [39] 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
```

```
cutree(hc, k=2)

## [1] 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 2 2 2 2 2 2 2 2
## [39] 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
```

PCA of UK Food Data

```
url <- "https://tinyurl.com/UK-foods"
x <- read.csv(url, row.names=1)
```

Look at the first bit (the header) of the file:

```
head(x)
```

```
##           England Wales Scotland N.Ireland
## Cheese           105   103       103        66
## Carcass_meat     245   227       242       267
## Other_meat       685   803       750       586
## Fish             147   160       122        93
## Fats_and_oils    193   235       184       209
## Sugars           156   175       147       139
```

How many columns in this dataset:

```
ncol(x)
```

```
## [1] 4
```


Q1. How many rows and columns are in your new data frame named x? What R functions could you use to answer this questions?

```
dim(x)
```

```
## [1] 17  4
```

We can make some plots to try to understand this data a bit more. For example barplots:

```
barplot(as.matrix(x), beside = TRUE )
```



PCA to the rescue

The main base R function for PCA is called 'prcomp()'

```
pca <- prcomp(t(x))
summary(pca)
```


```
## Importance of components:
##               PC1      PC2      PC3      PC4
## Standard deviation  324.1502 212.7478 73.87622 4.189e-14
## Proportion of Variance  0.6744  0.2905  0.03503 0.000e+00
## Cumulative Proportion  0.6744  0.9650  1.00000 1.000e+00
```

What is in this return pca obj?

```
attributes(pca)
```


```
## $names
## [1] "sdev"      "rotation" "center"    "scale"     "x"
##
## $class
## [1] "prcomp"
```

```
plot(pca$x[,1:2], col=c("orange", "red", "blue", "green"), pch=15)
text(pca$x[,1], pca$x[,2], labels=colnames(x))
```



We can look at how the variables contribute to our new PCs by examining the ‘pca\$rotation’ component of our results

```
barplot(pca$rotation[,1], las=2 )
```



PCA of RNA-seq data

Read the data first

```
url2 <- "https://tinyurl.com/expression-CSV"
rna.data <- read.csv(url2, row.names=1)
head(rna.data)
```

```
##          wt1 wt2  wt3  wt4 wt5 ko1 ko2 ko3 ko4 ko5
## gene1    439 458  408  429 420  90  88  86  90  93
## gene2    219 200  204  210 187 427 423 434 433 426
## gene3   1006 989 1030 1017 973 252 237 238 226 210
## gene4    783 792  829  856 760 849 856 835 885 894
## gene5    181 249  204  244 225 277 305 272 270 279
## gene6    460 502  491  491 493 612 594 577 618 638
```

How many genes (how many rows)?

```
nrow(rna.data)
```

```
## [1] 100
```

How many experiments(how many columns)?


```
ncol(rna.data)
```

```
## [1] 10
```

Let's do PCA of this dataset. First take the transpose as that is what the `prcomp()` fnx wants...


```
pca <- prcomp( t(rna.data), scale= TRUE)
summary(pca)
```

```
## Importance of components:
```

```
##              PC1      PC2      PC3      PC4      PC5      PC6      PC7
## Standard deviation  9.6237  1.5198  1.05787  1.05203  0.88062  0.82545  0.80111
## Proportion of Variance 0.9262  0.0231  0.01119  0.01107  0.00775  0.00681  0.00642
## Cumulative Proportion 0.9262  0.9493  0.96045  0.97152  0.97928  0.98609  0.99251
##              PC8      PC9      PC10
## Standard deviation  0.62065  0.60342  3.348e-15
## Proportion of Variance 0.00385  0.00364  0.000e+00
## Cumulative Proportion 0.99636  1.00000  1.000e+00
```


We can make out score plot (AKA PCA plot) from the `'pca$x'`

```
plot(pca$x[,1],pca$x[,2])
```



Make a little color vector to color up our plot by wt and ko.

```
colvec <- c(rep("red", 5), rep("blue", 5))
plot(pca$x[,1],pca$x[,2], col= colvec, pch = 15)
```



```
y <- c(1:5)
z <- c("red", "blue")
cbind(y, z)
```

```
## Warning in cbind(y, z): number of rows of result is not a multiple of vector
## length (arg 2)
```

```
##      y    z
## [1,] "1" "red"
## [2,] "2" "blue"
## [3,] "3" "red"
## [4,] "4" "blue"
## [5,] "5" "red"
```