NATIONAL UNIVERSITY OF SINGAPORE

SCHOOL OF COMPUTING EXAMINATION FOR CS1020

Semester 1: AY2013/14

CS1020 - Data Structures and Algorithms I

Nov 2013	Time	e allowed: 2	hours
Matriculation number:			

INSTRUCTIONS TO CANDIDATES

- 1. This examination paper consists of EIGHTEEN (18) questions and comprises THIRTEEN (13) printed pages.
- 2. This is a **CLOSED BOOK** examination. You are NOT allowed to refer to any material during the exam.
- 3. Fill in your Matriculation Number above clearly with a pen.
- 4. Answer all questions.
- 5. For MCQs (Q1 to Q12), use the OCR form provided. Shade and write down your matriculation number on the OCR form. You must use 2B pencil to shade/write on the OCR form.
- 6. For short questions (Q13 to Q18), write your answers in the space provided. You may use pencil to write your answers.
- 7. You must submit <u>both the OCR form and this document</u>. It is your responsibility to ensure that you have submitted both to the invigilator at the end of the examination.

	EXAMINER	'S USE ONLY	
Section / Question	Possible	Marks	Check
A. MCQs 1-12	36		
B. Q 13	6		
B. Q 14	12		"
B. Q 15	12		
B. Q 16	12		
B. Q 17	13		
B. Q 18	9		
Total	100		

SECTION B (7 Short Questions: 64 Marks)

13. Given the following function where n is an integer,

$$f(n) = \begin{cases} f(n-1) + n - 1 & \text{if } n > 1 \\ 0 & \text{if } n = 1 \end{cases}$$


In trying to implement the function iteratively, a student makes some mistakes. Help him to correct all the mistakes in his codes. You should have the same number of statements as the codes provided.

(6 marks)

Wrong implementation

```
float calculate(n) {
    int result = 0;
    for (i = 2; i < n; i+=2)
        result = result + (i - 1);
    return result;
}
```

your correction





14a. Given the following array,

32	41	12	27	49	87	55	62	38	74
0	1	2	3	4	5	6	7	8	9


If we apply Insertion Sort, Selection Sort and the improved version of Bubble Sort to the array, what will be the content of the array after 3 passes of the respective sorting process?

(6 marks)







Improved Bubble Sort





members according to their age. Propose an efficient sorting algorithm to do club. Take note that the member list is already sorted alphabetically according	I like to sort the the job for the job for the ing to their
hat is the complexity of your sorting algorithm?	(1 mark)
	are organizing some activities for different age groups and hence they would members according to their age. Propose an efficient sorting algorithm to do club. Take note that the member list is already sorted alphabetically according names. Your algorithm should ensure that in the age groups, the names are s

integers are repl on its right, the i	aced by	the n	earest	bigge	er integ	ger on	their i	right.]	lf ther ving a	e is no rray o	bigger integer fintegers
	2	1	4	5	3	6	7	9	4	8]
-11-1 1				l							J
should become	4	4	5	6	6	7	9	9	8	8	
a) Create an O(1	n²) algo	rithm									(4 marks)
b) Create an O(1	ı) algor	ithm									(8 marks)
b) Create an O(r	n) algor	rithm									(8 marks)
b) Create an O(ı	n) algor	rithm									(8 marks)
b) Create an O(ı	n) algor	rithm									(8 marks)
b) Create an O(ı	n) algor	rithm									(8 marks)
b) Create an O(ı	n) algor	rithm									(8 marks)
b) Create an O(ı	n) algor	rithm									(8 marks)
b) Create an O(ı	n) algor	rithm									(8 marks)
b) Create an O(ı	n) algor	rithm									(8 marks)
b) Create an O(ı	n) algor	rithm									(8 marks)
b) Create an O(ı	n) algor	rithm									(8 marks)











b. insert 56, insert 73, insert 29, insert 47, insert 31, insert 95, delete 29, insert 82. Hash function H(key) = key % 13. Use Quadratic probing to resolve collision. (2 marks)




What is the probe sequence when you insert 82?

(1 mark)



c. insert 56, insert 73, insert 39, insert 47, insert 31, insert 99, insert 82.
 Hash function H(key) = key % 11, using G(key) = 9 - key % 9 as secondary hash function to resolve collision. (2 marks)



What can you conclude about the hash function for the given set of keys? (1 marks)




ite a recursive method that tests whether an array, A, is sorted in ascending or ider of the method is given. (4 roughlic static boolean sorted (int [] A, int l, int r) {		^	1	2	2	4	~	_	_	_	_		
ite a recursive method that tests whether an array, A, is sorted in ascending or ider of the method is given. (4 roughlic static boolean sorted (int [] A, int I, int r) {	[<u> </u>	1	7	3	4	5	6	7	8	9	10	7
ite a recursive method that tests whether an array, A, is sorted in ascending or ider of the method is given. (4 roughlic static boolean sorted (int [] A, int I, int r) {	Į						***						_
ite a recursive method that tests whether an array, A, is sorted in ascending or ider of the method is given. (4 roughlic static boolean sorted (int [] A, int I, int r) {													
ite a recursive method that tests whether an array, A, is sorted in ascending or ider of the method is given. (4 roughlic static boolean sorted (int [] A, int I, int r) {				,									
ite a recursive method that tests whether an array, A, is sorted in ascending or ider of the method is given. (4 roughlic static boolean sorted (int [] A, int I, int r) {													
ite a recursive method that tests whether an array, A, is sorted in ascending or ider of the method is given. (4 roughlic static boolean sorted (int [] A, int I, int r) {													
ite a recursive method that tests whether an array, A, is sorted in ascending or ider of the method is given. (4 roughlic static boolean sorted (int [] A, int I, int r) {													
ite a recursive method that tests whether an array, A, is sorted in ascending or ider of the method is given. (4 roughlic static boolean sorted (int [] A, int I, int r) {													
public static boolean sorted (int [] A, int I, int r) {	If the l	oad fa	ctor is	5, wh	at mu	st be d	one af	ter the	integ	er 89 i	s adde	ed?	(1 n
public static boolean sorted (int [] A, int I, int r) {													
public static boolean sorted (int [] A, int I, int r) {	i												
public static boolean sorted (int [] A, int I, int r) {													
public static boolean sorted (int [] A, int I, int r) {													
public static boolean sorted (int [] A, int I, int r) {													
public static boolean sorted (int [] A, int I, int r) {													
public static boolean sorted (int [] A, int l, int r) {													
}	rite a rec	cursive	e meth	nod tha	it tests	wheth	er an	аггау,	A, is s	sorted	in asce		
}	rite a rec	cursive	e meth thod i	od tha	it tests	wheth	er an	array,	A, is s	sorted	in asco		
	ader of t	he me	thod i	s give	n.	·				sorted	in asco		
	ader of t	he me	thod i	s give	n.	·				sorted	in asco		g ord (4 ma
	ader of t	he me	thod i	s give	n.	·				sorted	in asco		
	ader of t	he me	thod i	s give	n.	·				sorted	in asco		
	ader of t	he me	thod i	s give	n.	·				sorted	in asco		
	ader of t	he me	thod i	s give	n.	·				sorted	in asco		
	ader of t	he me	thod i	s give	n.	·				sorted	in asc		
	ader of t	he me	thod i	s give	n.	·				sorted	in asco		
	ader of t	he me	thod i	s give	n.	·				sorted	in asco		
	ader of t	he me	thod i	s give	n.	·				sorted	in asc		
at is the complexity of your algorithm? (1 n	ader of t	he me	thod i	s give	n.	·				sorted	in asco		
at is the complexity of your algorithm? (I n	pub	he me	thod i	s give	n.	·				sorted	in asc		
	pub	he me	thod i	s given	sorted	(int []	A, in			sorted	in asc	((4 m
	pub	he me	thod i	s given	sorted	(int []	A, in			sorted	in asco	(

	or "Odd" or "Same" a			(6 marks)
	istNode head points t			
nemod in 17a a	and print the result retu			(2 marks)
	atic void main (String ode head = createList		eates the linked lis	st
			a and then print th	ne result.
ListN	e your statements to c	call your method in 17	a and alon print a	
ListN	e your statements to c	call your method in 17	a and mon print a	
ListN	e your statements to c	call your method in 17	a and mon print a	

18. The nchoosek algorithm is given below. A partial recursive tree of the algorithm is also given. Complete the next two levels of the recursive tree. (3 marks)

```
int nchoosek(int [] arr, int n, int k) {
    if (n == k) return 1;
    if (k == 0) return 1;
    return nchoosek(arr, n-1, k) + nchoosek(arr, n-1, k-1);
}
```



What is the maximum level of the tree?	(3 marks)

What is the worst case complexity of the algorithm? Give you answer in Big-O. (3 marks)

=== END OF PAPER ====