


By: Justin Ellingwood

Subscribe

Share

Contents ▾



# Installing and Using Ranger, a Terminal File Manager, on a Ubuntu VPS

7

Posted July 12, 2013 99.3k

APPLICATIONS

MISCELLANEOUS

UBUNTU

## Introduction

Ranger is a terminal file manager with vim-like keybindings that uses the ncurses library to provide a powerful interface for your filesystem.

Ranger uses conventions common to both text-based file managers, such as Midnight Commander, and graphical file managers, such as Mac OS X's Finder.

Sign up for our newsletter. Get the latest tutorials on SysAdmin and open source topics.

✕

Sign Up

SCROLL TO TOP

Ranger is in Ubuntu's default repositories. It can be installed easily with apt-get.

We will also install some other applications that allow ranger to preview various file formats effectively.

```
sudo apt-get update
sudo apt-get install ranger caca-utils highlight atool w3m poppler-utils mediainfo
```

Start ranger for a moment and exit. This will allow ranger to create the directory structure for its configuration files:

```
ranger
Q
```

Now ranger has created its configuration directory and we can copy its configuration files with the following command:

```
ranger --copy-config=all
```

```
creating: /home/DemoUser/.config/ranger/apps.py
creating: /home/DemoUser/.config/ranger/commands.py
creating: /home/DemoUser/.config/ranger/rc.conf
creating: /home/DemoUser/.config/ranger/options.py
creating: /home/DemoUser/.config/ranger/scope.sh
```

If you would like to modify the configuration files later, you can locate them in ~/.config/ranger:

```
cd ~/.config/ranger
```

## Using Ranger

Before we begin exploring the features of ranger, it would be helpful to have some example files to look at. Let's acquire some files:

Sign up for our newsletter. Get the latest tutorials on SysAdmin and open source topics.



Sign Up

SCROLL TO TOP

```
wget http://upload.wikimedia.org/wikipedia/commons/4/47/PNG_transparency_demonstrat
wget http://upload.wikimedia.org/wikipedia/commons/4/40/Equipol.gif
wget http://upload.wikimedia.org/wikipedia/commons/f/f8/Cula_Duca.jpg
cp /usr/share/doc/shared-mime-info/* .
tar -czvf zipped.tar.gz README copyright
```

Now start ranger:

```
ranger
```

You should see a three column layout. This type of file tree representation is known as "Miller columns". It is a style that most people today would associate with Mac OS X's "Finder" file manager.

The middle column is the current working directory. In this case, it should be showing your home directory.

The left pane is the current directory's parent directory. The right pane shows a preview (if available) of the file you are currently interacting with in the middle column.

*Ranger showing a zipped text file in its preview pane.*

If you move down the list of example files using the arrow keys, you will see how the preview pane

Sign up for our newsletter. Get the latest tutorials on SysAdmin and open source topics.




Sign Up

SCROLL TO TOP

uncompressed and viewed in the same way. Even the example pdf file is converted to text for our viewing.

If you choose an image file, it is displayed using colored ascii art. The image clarity will depend a lot on your window size. If you expand the window, you should be able to see more detail.



*Ranger showing an ascii representation of an image file in its preview pane.*

## Navigation

Ranger uses many of the same keybindings as "vim". For instance, the movement commands mirror vim closely:

- j = Move down
- k = Move up
- h = Move to parent directory
- gg = Go to the top of the list
- G = Go to the bottom of the list
- <ctrl>-f = Page down
- <ctrl>-b = Page up

Sign up for our newsletter. Get the latest tutorials on SysAdmin and open source topics.



Sign Up

SCROLL TO TOP

- K = Page up 1/2 page
- H = Go back through navigation history
- L = Go forward through navigation history

There are also some directory-specific shortcuts to move to common directories:

- gh = cd ~
- ge = cd /etc
- gu = cd /usr
- gd = cd /dev
- go = cd /opt
- gv = cd /var
- gm = cd /media
- gM = cd /mnt
- gs = cd /srv
- gr = cd /
- gR = cd to ranger's global configuration directory

## Working with Files

Ranger allows you to perform many different operations on files from within its interface. Here are some of the most common:

- i = Display file (useful if you'd like to view a text file in a pager instead of editing it)
- l or E = Open file (opens file in default file-handler)
- r = Open file with... (allows you to choose program to use)
- o = Change sort order (follow by character in menu selection)

Sign up for our newsletter. Get the latest tutorials on SysAdmin and open source topics.



Sign Up

SCROLL TO TOP

- <space> = Select current file
- t = Tag file (you can perform actions on tagged files)
- cw = Rename current file
- /= Search for files
- n = Jump to next match
- N = Jump to previous match
- yy = Yank (copy) file
- dd = Mark file for cut operation
- <delete> = Delete selected file

```

drowan@aws-system: /usr/lib/python2.7/dist-packages/ranger/_init_.py
apt          api
aptsources  *colorchemes
axi          container
chardet      *core
debconf      data
debconf      defaults
python-debian-0.10-1  ext
python-debian-0.10-1  fobject
python-debian-0.10-1  gui
python-debian-0.10-1  README
python-debian-0.10-1  _init_.py -> 1.53 K
python-debian-0.10-1  opt_inst.so
python-debian-0.10-1  opt_pkg.so
python-debian-0.10-1  apt_inst_index
python-debian-0.10-1  chardet-2.0.1-eg
python-debian-0.10-1  debconf.py
python-debian-0.10-1  debconf2.py
python-debian-0.10-1  lib_release.py
python-debian-0.10-1  python_opt-0.5.3-
python-debian-0.10-1  ranger-1.5.2-egg-

# Copyright (C) 2009, 2010, 2011 Rowan Ziebelmann - drowan@lavabit.com
#
# This program is free software: you can redistribute it and/or modify
# it under the terms of the GNU General Public License as published by
# the Free Software Foundation, either version 3 of the License, or
# (at your option) any later version.
#
# This program is distributed in the hope that it will be useful,
# but WITHOUT ANY WARRANTY; without even the implied warranty of
# MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
# GNU General Public License for more details.
#
# You should have received a copy of the GNU General Public License
# along with this program. If not, see <http://www.gnu.org/licenses/>.
#
# A console file manager with VI key bindings.
#
# It provides a minimalist and nice curses interface with a view on the
# directory hierarchy. The secondary task of ranger is to figure out which
# program you want to use to open your files with.
#
# Report as
#
# Information
# _license_ = 'GPL3'
# _version_ = '1.5.2'
# _author_ = '_maintainer_' = 'Rowan Ziebelmann'
# _email_ = 'rowan@lavabit.com'
#
# Constants
# RANGERDIR = os.path.dirname(__file__)
# TICKS_BEFORE_COLLECTING_GARBAGE = 100
# TIME_BEFORE_FILE_BECOMES_GARBAGE = 1200
# MACRO_DELIMITER = '!'
# LOGFILE = '/tmp/ranger_error.log'
# USAGE = '%prog [options] [path/filename]'
# STABLE = True
#
# If the environment variable XDG_CONFIG_HOME is non-empty, CONFDIR is ignored
# and the configuration directory will be $XDG_CONFIG_HOME/ranger instead.
# CONFDIR = '/.config/ranger'

```

*Tagged and selected files in ranger's current working directory.*

## Tabbed Browsing

Ranger also incorporates tabbed functionality to allow multiple viewports into the filesystem. Here are the most common tab control keys:

Sign up for our newsletter. Get the latest tutorials on SysAdmin and open source topics.




Sign Up

SCROLL TO TOP

- <tab> = Next tab
- <shift><tab> = Previous tab

## General Commands

These commands control ranger itself:

- ? = View ranger man page
- 1? = Keybindings help
- 2? = Command help
- 3? = Settings help
- R = Reload current directory
- Q = Quit

## Command Interface

Like vim, ranger also includes a robust command interface. This allows you to manipulate files in more complex ways. The abilities are extensive, so we will only be covering a few:

- != Execute a command from the shell (non-ranger commands)
- := Execute a ranger command
- du = Measure disk usage of current directory
- chmod = Change permissions of current file

There are a number of flags that you can pass to commands to modify the operation of the commands. They should be used with a dash "-" after typing "!" for shell commands or ":" for ranger commands:

- -s = Discard the output of the current command.
- -d = Detach the process and run in the background
- -p = Return the output in ranger's file pager

Sign up for our newsletter. Get the latest tutorials on SysAdmin and open source topics.



Sign Up

SCROLL TO TOP

Ranger also allows you to target specific files by substituting groups of files for command operations. It accomplishes that by using placeholders that will be expanded with the correct files upon execution:

- %f = Substitute highlighted file
- %d = Substitute current directory
- %s = Substitute currently selected files
- %t = Substitute currently tagged files

For example, if we wanted to change the names of multiple files, we could select them all with the space bar. After that, we can type:

```
:bulkrename %s
```

This is a great way to rename multiple files. It gives you every file you'd like to change in a text editor. You simply modify as necessary and then exit out. The file manager will perform your changes when after you confirm.

```
# This file will be executed when you close the editor.  
# Please double-check everything, clear the file to abort.  
mv -vi README 1.README  
mv -vi changelog.Debian.gz 2.changelog.Debian.gz  
mv -vi copyright 3.copyright  
mv -vi shared-mime-info-spec.pdf 4.shared-mime-info-spec.pdf  
mv -vi shared-mime-info-spec.xml.gz 5.shared-mime-info-spec.xml.gz
```

*Renaming with ranger's bulkrename command.*

Ranger allows us to mark different groups of files at the same time. This gives us great flexibility if we want to perform multiple operations based on different criteria.

By Justin Ellingwood

By: Justin Ellingwood

Upvote (7)

 Subscribe

 Share

Sign up for our newsletter. Get the latest tutorials on SysAdmin and open source topics.

×

Sign Up

SCROLL TO TOP



## Spin up an SSD cloud server in under a minute.

Simple setup. Full root access. Straightforward pricing.

**DEPLOY SERVER**

---

### Related Tutorials

How to Install and Configure Magento on Ubuntu 14.04

How To Install and Use Webmin on CentOS 7

How to Install Perlbrew and Manage Multiple Versions of Perl 5 on CentOS 7

How To Build Go Executables for Multiple Platforms on Ubuntu 16.04

How To Install Webmin on Ubuntu 16.04

---

## 4 Comments

Leave a comment...

Sign up for our newsletter. Get the latest tutorials on SysAdmin and open source topics.

×

Sign Up

SCROLL TO TOP

[jirik.chara](#) August 30, 2013

0 Nice article, thanks!

---

[raverunner](#) September 9, 2014

2 Are you referring to the *ncurses* library (as opposed to the *nurses* library) ?

---

[asb](#) MOD September 9, 2014

0 Opps! Fixed. Thanks for catching that!

---

[dosware](#) November 10, 2014

0 I've been using Ranger as my preferred file manager for two years- but only scratched the surface of its capabilities. Somehow I missed so much just browsing the man page (as man pages aren't always an easy read). Your article clearly and concisely enumerates how to accomplish a multitude of tasks- thank you!



This work is licensed under a Creative Commons Attribution-NonCommercial-ShareAlike 4.0 International License.



Sign up for our newsletter. Get the latest tutorials on SysAdmin and open source topics.



Sign Up

SCROLL TO TOP

Sign up for our newsletter. Get the latest tutorials on SysAdmin and open source topics.

Sign Up



[SCROLL TO TOP](#)