

vimrc

```

1 map <F9> :wall! <CR> :!g++ -Wall -Wextra -Wshadow ↵
  Wno-unused-result -o %:r % -std=c++14 -DHOME ↵
  D_GLIBCXX_DEBUG -fsanitize=address <CR>
2 map <F7> :wall! <CR> :!g++ -Wall -Wextra -Wshadow ↵
  Wno-unused-result -o %:r % -std=c++14 -DHOME ↵
  02 <CR>
3 map <F8> :wall! <CR> :!ulimit -s 500000 && ./%:r <CR↵
  >
4
5 inoremap {<CR> {<CR>}<ESC>O
6 map <c-a> ggVG
7
8 set nu
9 set rnu
10 syntax on
11
12 map <c-t> :tabnew <CR>
13 map <c-l> :tabn <CR>
14 map <c-h> :tabp <CR>
15
16 set cin
17 set sw=4
18 set so=99
19 set bs=2
20 set et
21 set sts=4

```

template

```

1 // team : SPb ITMO University 1
2 #include <bits/stdc++.h>
3
4 #define F first
5 #define S second
6 #define pb push_back
7 #define forn(i, n) for(int i = 0 ; (i) < (n) ; ++i)
8 #define eprintf(...) fprintf(stderr, __VA_ARGS__) ,↵
  fflush(stderr)
9 #define sz(a) ((int)(a).size())
10 #define all(a) (a).begin(), a.end()
11 #define pw(x) (1LL<<(x))
12
13 using namespace std;
14
15 typedef long long ll;
16 typedef double dbl;
17 typedef vector<int> vi;
18 typedef pair<int, int> pi;
19
20 const int INF = 1.01e9;
21 const dbl eps = 1e-9;
22
23 /* ——— main part ——— */
24
25
26
27
28
29
30
31 int main()
32 {
33 #define TASK ""
34 #ifdef home
35     assert(freopen(TASK".in", "r", stdin));
36     //assert(freopen(TASK".out", "w", stdout));
37 #endif
38
39
40
41
42
43 #ifdef home
44     eprintf("time = %d ms\n", (int)(clock() * 1000. / ↵
        CLOCKS_PER_SEC));
45 #endif
46     return 0;
47 }

```

crt

```

1 int CRT(int a1, int m1, int a2, int m2)
2 {
3     return (a1 - a2 % m1 + m1) * (1ll)rev(m2, m1) % m1 ↵
        * m2 + a2;
4 }

```

fastIO

```

1 #include <cstdio>
2 #include <algorithm>
3
4 /** Interface */
5
6 inline int readInt();
7 inline int readUInt();
8 inline bool isEof();
9
10 /** Read */
11
12 static const int buf_size = 100000;
13 static char buf[buf_size];
14 static int buf_len = 0, pos = 0;
15
16 inline bool isEof() {
17     if (pos == buf_len) {
18         pos = 0, buf_len = fread(buf, 1, buf_size, stdin↵
        );
19         if (pos == buf_len) return 1;
20     }
21     return 0;
22 }
23
24 inline int getChar() { return isEof() ? -1 : buf[pos↵
    ++]; }
25
26 inline int readChar() {
27     int c = getChar();
28     while (c != -1 && c <= 32) c = getChar();
29     return c;
30 }
31
32 inline int readUInt() {
33     int c = readChar(), x = 0;
34     while ('0' <= c && c <= '9') x = x * 10 + c - '0',↵
        c = getChar();
35     return x;
36 }
37
38 inline int readInt() {
39     int s = 1, c = readChar();
40     int x = 0;
41     if (c == '-') s = -1, c = getChar();
42     while ('0' <= c && c <= '9') x = x * 10 + c - '0',↵
        c = getChar();
43     return s == 1 ? x : -x;
44 }
45
46
47 // 10M int [0..1e9)
48 // cin 3.02
49 // scanf 1.2
50 // cin_sync_with_stdio(false) 0.71
51 // fastRead getchar 0.53
52 // fastRead fread 0.15

```

fft

```

1 namespace fft
2 {
3     const int maxBase = 21;
4     const int maxN = 1 << maxBase;
5
6     struct num
7     {
8         dbl x, y;
9         num() {}

```

```

10     num(dbl xx, dbl yy): x(xx), y(yy) {}
11     num(dbl alp): x(cos(alp)), y(sin(alp)) {}
12 };
13
14 inline num operator + (num a, num b) { return num(←
15     a.x + b.x, a.y + b.y); }
16 inline num operator - (num a, num b) { return num(←
17     a.x - b.x, a.y - b.y); }
18 inline num operator * (num a, num b) { return num(←
19     a.x * b.x - a.y * b.y, a.x * b.y + a.y * b.x); }
20
21 inline num conj(num a) { return num(a.x, -a.y); }
22
23 const dbl PI = acos(-1);
24
25 num root[maxN];
26 int rev[maxN];
27 bool rootsPrepared = false;
28
29 void prepRoots()
30 {
31     if (rootsPrepared) return;
32     rootsPrepared = true;
33     root[1] = num(1, 0);
34     for (int k = 1; k < maxBase; ++k)
35     {
36         num x(2 * PI / pw(k + 1));
37         for (int i = pw(k - 1); i < pw(k); ++i)
38         {
39             root[2 * i] = root[i];
40             root[2 * i + 1] = root[i] * x;
41         }
42     }
43
44 int base, N;
45
46 int lastRevN = -1;
47 void prepRev()
48 {
49     if (lastRevN == N) return;
50     lastRevN = N;
51     forn(i, N) rev[i] = (rev[i >> 1] >> 1) + ((i & ←
52     1) << (base - 1));
53
54 void fft(num *a, num *f)
55 {
56     forn(i, N) f[i] = a[rev[i]];
57     for (int k = 1; k < N; k <= 1) for (int i = 0; ←
58     i < N; i += 2 * k) forn(j, k)
59     {
60         num z = f[i + j + k] * root[j + k];
61         f[i + j + k] = f[i + j] - z;
62         f[i + j] = f[i + j] + z;
63     }
64
65 num a[maxN], b[maxN], f[maxN], g[maxN];
66 ll A[maxN], B[maxN], C[maxN];
67
68 void _multMod(int mod)
69 {
70     forn(i, N)
71     {
72         int x = A[i] % mod;
73         a[i] = num(x & (pw(15) - 1), x >> 15);
74     }
75     forn(i, N)
76     {
77         int x = B[i] % mod;
78         b[i] = num(x & (pw(15) - 1), x >> 15);
79     }
80     fft(a, f);
81     fft(b, g);
82
83     forn(i, N)
84     {
85         int j = (N - i) & (N - 1);
86         num a1 = (f[i] + conj(f[j])) * num(0.5, 0);
87         num a2 = (f[i] - conj(f[j])) * num(0, -0.5);
88         num b1 = (g[i] + conj(g[j])) * num(0.5 / N, 0) ←
89         ;
90         num b2 = (g[i] - conj(g[j])) * num(0, -0.5 / N ←
91         );
92         a[j] = a1 * b1 + a2 * b2 * num(0, 1);
93         b[j] = a1 * b2 + a2 * b1;
94     }
95     fft(a, f);
96     fft(b, g);
97     forn(i, N)
98     {
99         ll aa = f[i].x + 0.5;
100        ll bb = g[i].x + 0.5;
101        ll cc = f[i].y + 0.5;
102        C[i] = (aa + bb % mod * pw(15) + cc % mod * pw ←
103        (30)) % mod;
104    }
105 }
106
107 void prepAB(int n1, int n2)
108 {
109     base = 1;
110     N = 2;
111     while (N < n1 + n2) base++, N <= 1;
112
113     for (int i = n1; i < N; ++i) A[i] = 0;
114     for (int i = n2; i < N; ++i) B[i] = 0;
115
116     prepRoots();
117     prepRev();
118 }
119
120 void mult(int n1, int n2)
121 {
122     prepAB(n1, n2);
123     forn(i, N) a[i] = num(A[i], B[i]);
124     fft(a, f);
125     forn(i, N)
126     {
127         int j = (N - i) & (N - 1);
128         a[i] = (f[j] * f[j] - conj(f[i] * f[i])) * num ←
129         (0, -0.25 / N);
130     }
131     fft(a, f);
132     forn(i, N) C[i] = (ll)round(f[i].x);
133 }
134
135 void multMod(int n1, int n2, int mod)
136 {
137     prepAB(n1, n2);
138     _multMod(mod);
139 }
140
141 int D[maxN];
142
143 void multLL(int n1, int n2)
144 {
145     prepAB(n1, n2);
146
147     int mod1 = 1.5e9;
148     int mod2 = mod1 + 1;
149
150     _multMod(mod1);
151
152     forn(i, N) D[i] = C[i];
153
154     _multMod(mod2);
155
156     forn(i, N)
157     {
158         C[i] = D[i] + (C[i] - D[i] + (ll)mod2) * (ll) ←
159         mod1 % mod2 * mod1;
160     }
161 }
162
163 // HOW TO USE ::
164 // — set correct maxBase
165 // — use mult(n1, n2), multMod(n1, n2, mod) and ←
166 // multLL(n1, n2)
167 // — input : A[], B[]
168 // — output : C[]

```

fftint

```

1 namespace fft
2 {
3     const int mod = 998244353;
4     const int base = 20;
5     const int N = 1 << base;
6     const int ROOT = 646;
7
8     int root[N];
9     int rev[N];
10
11     void init()
12     {

```

```

13     forn(i, N) rev[i] = (rev[i >> 1] >> 1) + ((i & ←
14     1) << (base - 1));
15     int NN = N >> 1;
16     int z = 1;
17     forn(i, NN)
18     {
19         root[i + NN] = z;
20         z = z * (11)ROOT % mod;
21     }
22     for (int i = NN - 1; i > 0; --i) root[i] = root←
23     [2 * i];
24 }
25 void fft(int *a, int *f)
26 {
27     forn(i, N) f[i] = a[rev[i]];
28     for (int k = 1; k < N; k <= 1) for (int i = 0; ←
29     i < N; i += 2 * k) forn(j, k)
30     {
31         int z = f[i + j + k] * (11)root[j + k] % mod;
32         f[i + j + k] = (f[i + j] - z + mod) % mod;
33         f[i + j] = (f[i + j] + z) % mod;
34     }
35 }
36 int A[N], B[N], C[N];
37 int F[N], G[N];
38 void _mult(int eq)
39 {
40     fft(A, F);
41     if (eq) forn(i, N) G[i] = F[i];
42     else fft(B, G);
43     int invN = inv(N);
44     forn(i, N) A[i] = F[i] * (11)G[i] % mod * invN %←
45     mod;
46     reverse(A + 1, A + N);
47     fft(A, C);
48 }
49 void mult(int n1, int n2, int eq = 0)
50 {
51     for (int i = n1; i < N; ++i) A[i] = 0;
52     for (int i = n2; i < N; ++i) B[i] = 0;
53     _mult(eq);
54     //forn(i, n1 + n2) C[i] = 0;
55     //forn(i, n1) forn(j, n2) C[i + j] = (C[i + j] ←
56     A[i] * (11)B[j]) % mod;
57 }
58 }
59 }

```

blackbox

```

1 namespace blackbox
2 {
3     int A[N];
4     int B[N];
5     int C[N];
6
7     int magic(int k, int x)
8     {
9         B[k] = x;
10        C[k] = (C[k] + A[0] * (11)B[k]) % mod;
11        int z = 1;
12        if (k == N - 1) return C[k];
13        while ((k & (z - 1)) == (z - 1))
14        {
15            //mult B[k - z + 1 ... k] x A[z .. 2 * z - 1]
16            forn(i, z) fft::A[i] = A[z + i];
17            forn(i, z) fft::B[i] = B[k - z + 1 + i];
18            fft::multMod(z, z, mod);
19            forn(i, 2 * z - 1) C[k + 1 + i] = (C[k + 1 + i] ←
20            + fft::C[i]) % mod;
21            z <= 1;
22        }
23        return C[k];
24    }
25    // A — constant array
26    // magic(k, x) :: B[k] = x, returns C[k]
27    // !! WARNING !! better to set N twice the size ←
28    needed
29 }

```

halfplaneIntersection

```

1 int getPart(pt v) {
2     return less(0, v.y) || (equal(0, v.y) && less(v.x, ←
3     0));
4 }
5 int cmpV(pt a, pt b) {
6     int partA = getPart(a);
7     int partB = getPart(b);
8     if (partA < partB) return -1;
9     if (partA > partB) return 1;
10    if (equal(0, a * b)) return 0;
11    if (0 < a * b) return -1;
12    return 1;
13 }
14 double planeInt(vector<Line> l) {
15     int n = l.size();
16     sort(all(l), [](Line a, Line b) {
17         int r = cmpV(a.v, b.v);
18         if (r != 0) return r < 0;
19         return a.0 % a.v.rotate() < b.0 % a.v.rotate() ←
20         );
21     });
22     int cur = 0;
23     for (int i = 0; i < n; i++) {
24         int j = i;
25         for (; i < n && cmpV(l[j].v, l[i].v) == 0 && ←
26         cmpV(l[i].v, l[j].v) == 0; i++);
27         l[cur++] = l[i - 1];
28     }
29     n = cur;
30     for (int i = 0; i < n; i++)
31         l[i].id = i;
32     int flagUp = 0;
33     int flagDown = 0;
34     for (int i = 0; i < n; i++) {
35         int part = getPart(l[i].v);
36         if (part == 1) flagUp = 1;
37         if (part == 0) flagDown = 1;
38     }
39     if (!flagUp || !flagDown) return -1;
40     for (int i = 0; i < n; i++) {
41         pt v = l[i].v;
42         pt u = l[(i + 1) % n].v;
43         if (equal(0, v * u) && less(v % u, 0)) {
44             pt dir = l[i].v.rotate();
45             if (lessE(l[(i + 1) % n].0 % dir, l[i].0 % dir ←
46             )) return 0;
47             return -1;
48         }
49         if (less(v * u, 0))
50             return -1;
51     }
52     cur = 0;
53     vector<Line> st(n * 2);
54     for (int tt = 0; tt < 2; tt++) {
55         for (int i = 0; i < n; i++) {
56             for (; cur >= 2; cur--) {
57                 pt G = st[cur - 1] * l[i];
58                 if (!lessE(st[cur - 2].v * (G - st[cur - 2]. ←
59                 0), 0)) break;
60             }
61             st[cur++] = l[i];
62             if (cur >= 2 && lessE(st[cur - 2].v * st[cur ←
63             1].v, 0)) return 0;
64         }
65     }
66     vector<int> use(n, -1);
67     int left = -1, right = -1;
68     for (int i = 0; i < n; i++) {
69         if (use[st[i].id] == -1) {
70             use[st[i].id] = i;
71         }
72         else {
73             left = use[st[i].id];
74             right = i;
75             break;
76         }
77     }
78     vector<Line> tmp;
79     for (int i = left; i < right; i++)
80         tmp.pb(st[i]);
81 }

```

```

83 vector < pt > res;
84 for (int i = 0; i < (int)tmp.size(); i++)
85     res.pb(tmp[i] * tmp[(i + 1) % tmp.size()]);
86 double area = 0;
87 for (int i = 0; i < (int)res.size(); i++)
88     area += res[i] * res[(i + 1) % res.size()];
89 return area / 2;
90 }

```

commonTangents

```

1
2
3 vector<Line> commonTangents(pt A, dbl rA, pt B, dbl rB) {
4     vector<Line> res;
5     pt C = B - A;
6     dbl z = C.len2();
7     for (int i = -1; i <= 1; i += 2) {
8         for (int j = -1; j <= 1; j += 2) {
9             dbl r = rB * j - rA * i;
10            dbl d = z - r * r;
11            if (ls(d, 0)) continue;
12            d = sqrt(max(0.01, d));
13            pt magic = pt(r, d) / z;
14            pt v(magic % C, magic * C);
15            dbl CC = (rA * i - v % A) / v.len2();
16            pt O = v * -CC;
17            res.pb(Line(0, 0 + v.rotate()));
18        }
19    }
20    return res;
21 }
22
23 // HOW TO USE ::
24 // --- *D*-----*F*
25 // --- *...*- - -...*
26 // --- *.....* - - *.....*
27 // --- *.....* - - *.....*
28 // --- *...A...* --- *...B...*
29 // --- *.....* - - *.....*
30 // --- *.....* - - *.....*
31 // --- *...*- - -...*
32 // --- *C*-----*E*
33 // --- res = {CE, CF, DE, DF}

```

minDisc

```

1
2 pair<pt, dbl> minDisc(vector<pt> p) {
3     int n = p.size();
4     pt O = pt(0, 0);
5     dbl R = 0;
6     random_shuffle(all(p));
7     for (int i = 0; i < n; i++) {
8         if (ls(R, (O - p[i]).len())) {
9             O = p[i];
10            R = 0;
11            for (int j = 0; j < i; j++) {
12                if (ls(R, (O - p[j]).len())) {
13                    O = (p[i] + p[j]) / 2;
14                    R = (p[i] - p[j]).len() / 2;
15                    for (int k = 0; k < j; k++) {
16                        if (ls(R, (O - p[k]).len())) {
17                            Line l1((p[i] + p[j]) / 2, (p[i] + p[j]
18                                ) / 2 + (p[i] - p[j]).rotate());
19                            Line l2((p[k] + p[j]) / 2, (p[k] + p[j]
20                                ) / 2 + (p[k] - p[j]).rotate());
21                            O = l1 * l2;
22                            R = (p[i] - O).len();
23                        }
24                    }
25                }
26            }
27        }
28    }
29    return {O, R};
30 }

```

polygonArcCut

```

1
2 struct Meta {
3     int type; // 0 - seg, 1 - circle
4     pt O;
5     dbl R;
6 };
7
8 const Meta SEG = {0, pt(0, 0), 0};
9
10 vector<pair<pt, Meta>> cut(vector<pair<pt, Meta>> p,
11     Line l) {
12     vector<pair<pt, Meta>> res;
13     int n = p.size();
14     for (int i = 0; i < n; i++) {
15         pt A = p[i].F;
16         pt B = p[(i + 1) % n].F;
17         if (le(0, l.v * (A - l.O))) {
18             if (eq(0, l.v * (A - l.O)) && p[i].S.type == 1)
19                 res.pb({A, SEG});
20             else
21                 res.pb(p[i]);
22         }
23         if (p[i].S.type == 0) {
24             if (sign(l.v * (A - l.O)) * sign(l.v * (B - l.O))
25                 == -1) {
26                 pt FF = Line(A, B) * l;
27                 res.pb(make_pair(FF, SEG));
28             }
29         }
30         else {
31             pt E, F;
32             if (intCL(p[i].S.O, p[i].S.R, l, E, F)) {
33                 if (onArc(p[i].S.O, A, E, B))
34                     res.pb({E, SEG});
35                 if (onArc(p[i].S.O, A, F, B))
36                     res.pb({F, p[i].S});
37             }
38         }
39     }
40     return res;
41 }

```

hash_table

```

1 template <const int max_size, class HashType, class
2     Data, const Data default_value>
3 struct hashTable {
4     HashType hash[max_size];
5     Data f[max_size];
6     int size;
7
8     int position(HashType H) const {
9         int i = H % max_size;
10        while (hash[i] && hash[i] != H)
11            i += 1;
12        return i;
13    }
14
15    Data & operator [] (HashType H) {
16        assert(H != 0);
17        int i = position(H);
18        if (!hash[i]) {
19            hash[i] = H;
20            f[i] = default_value;
21            size++;
22        }
23        return f[i];
24    }
25 };
26
27 hashTable<13, int, int, 0> h;

```

hungary

```

1 namespace hungary
2 {
3     const int N = 210;
4
5     int a[N][N];
6     int ans[N];
7
8     int calc(int n, int m)
9     {
10         ++n, ++m;
11         vi u(n), v(m), p(m), prev(m);
12         for (int i = 1; i < n; ++i)
13         {
14             p[0] = i;
15             int x = 0;
16             vi mn(m, inf);
17             vi was(m, 0);
18             while (p[x])
19             {
20                 was[x] = 1;
21                 int ii = p[x], dd = inf, y = 0;
22                 for (int j = 1; j < m; ++j) if (!was[j])
23                 {
24                     int cur = a[ii][j] - u[ii] - v[j];
25                     if (cur < mn[j]) mn[j] = cur, prev[j] = x;
26                     if (mn[j] < dd) dd = mn[j], y = j;
27                 }
28                 forn(j, m)
29                 {
30                     if (was[j]) u[p[j]] += dd, v[j] -= dd;
31                     else mn[j] -= dd;
32                 }
33                 x = y;
34             }
35             while (x)
36             {
37                 int y = prev[x];
38                 p[x] = p[y];
39                 x = y;
40             }
41         }
42         for (int j = 1; j < m; ++j)
43         {
44             ans[p[j]] = j;
45         }
46         return -v[0];
47     }
48     // HOW TO USE ::
49     // — set values to a[1..n][1..m] (n <= m)
50     // — run calc(n, m) to find MINIMUM
51     // — to restore permutation use ans[]
52     // — everything works on negative numbers
53     //
54     // !! i don't understand this code, it's ←
55     // copped from e-maxx (and rewrited by enot110←
56 }

```

modReverseOneLine

```

1 int rev(int x, int m)
2 {
3     if (x == 1) return 1;
4     return (1 - rev(m % x, x) * (ll)m) / x + m;
5 }

```

optimizations

```

1 // from anta code http://codeforces.com/contest/755/←
2 // submission/23864531
3 #pragma GCC optimize ("O3")
4 #pragma GCC target ("sse4")
5 inline void fasterLLDivMod(unsigned long long x, ←
6     unsigned y, unsigned &out_d, unsigned &out_m) {
7     unsigned xh = (unsigned)(x >> 32), xl = (unsigned)←
8     x, d, m;
9 #ifdef __GNUC__
10     asm(
11         "divl %4; \n\t"
12         : "=a" (d), "=d" (m)

```

```

11         : "d" (xh), "a" (xl), "r" (y)
12     );
13 #else
14     __asm {
15         mov edx, dword ptr[xh];
16         mov eax, dword ptr[xl];
17         div dword ptr[y];
18         mov dword ptr[d], eax;
19         mov dword ptr[m], edx;
20     };
21 #endif
22     out_d = d; out_m = m;
23 }
24
25 // have no idea what sse flags are really cool; list←
26 // of some of them
27 // — very good with bitsets
28 #pragma GCC optimize("O3")
29 #pragma GCC target("sse,sse2,sse3,ssse3,sse4,popcnt,←
30     abm,mmx")

```

plane3DInt

```

1 // (A, v) * (B, u) -> (O, n)
2
3 pt n = v * u;
4 pt m = v * n;
5 double t = (B - A) % u / (u % m);
6 pt O = A - m * t;

```

simplex

```

1 namespace simplex {
2     const int MAX_N = -1; // number of variables
3     const int MAX_M = -1; // number of inequalities
4     dbl a[MAX_M][MAX_N];
5     dbl b[MAX_M];
6     dbl c[MAX_N];
7     dbl v;
8     ll n, m;
9     int left[MAX_M];
10    int up[MAX_N];
11    int pos[MAX_N];
12    dbl res[MAX_N];
13
14    void init(int nn, int mm) {
15        n = nn;
16        m = mm;
17        v = 0;
18        for (int i = 0; i < m; i++)
19            for (int j = 0; j < n; j++)
20                a[i][j] = 0;
21        for (int i = 0; i < m; i++)
22            b[i] = 0;
23        for (int i = 0; i < n; i++)
24            c[i] = 0;
25    }
26
27    void pivot(int x, int y) {
28        swap(left[x], up[y]);
29        dbl k = a[x][y];
30        a[x][y] = 1;
31        b[x] /= k;
32        int cur = 0;
33        for (int i = 0; i < n; i++) {
34            a[x][i] = a[x][i] / k;
35            if (!eq(a[x][i], 0))
36                pos[cur++] = i;
37        }
38
39        for (int i = 0; i < m; i++) {
40            if (i == x || eq(a[i][y], 0)) continue;
41            dbl cof = a[i][y];
42            b[i] -= cof * b[x];
43            a[i][y] = 0;
44            for (int j = 0; j < cur; j++)
45                a[i][pos[j]] -= cof * a[x][pos[j]];
46        }
47        dbl cof = c[y];

```

```

49 v += cof * b[x];
50 c[y] = 0;
51 for (int i = 0; i < cur; i++) {
52     c[pos[i]] -= cof * a[x][pos[i]];
53 }
54 }
55
56 void solve() {
57     for (int i = 0; i < n; i++)
58         up[i] = i;
59     for (int i = 0; i < m; i++)
60         left[i] = i + n;
61
62     while (1) {
63         int x = -1;
64         for (int i = 0; i < m; i++)
65             if (ls(b[i], 0) && (x == -1 || b[i] < b[x])) x = i;
66     }
67     if (x == -1) break;
68     int y = -1;
69     for (int j = 0; j < n; j++)
70         if (ls(a[x][j], 0)) {
71             y = j;
72             break;
73         }
74     if (y == -1) {
75         assert(false); // no solution
76     }
77     pivot(x, y);
78
79     while (1) {
80         int y = -1;
81         for (int i = 0; i < n; i++)
82             if (ls(0, c[i]) && (y == -1 || (c[i] > c[y]))) {
83                 y = i;
84             }
85         if (y == -1) break;
86
87         int x = -1;
88         for (int i = 0; i < m; i++) {
89             if (ls(0, a[i][y])) {
90                 if (x == -1 || (b[i] / a[i][y] < b[x] / a[x][y])) {
91                     x = i;
92                 }
93             }
94         }
95         if (y == -1) {
96             assert(false); // infinite solution
97         }
98         pivot(x, y);
99     }
100
101     memset(res, 0, sizeof(res));
102
103     for (int i = 0; i < m; i++) {
104         if (left[i] < n) {
105             res[left[i]] = b[i];
106         }
107     }
108 }
109
110 // HOW TO USE ::
111 // — call init(n, m)
112 // — call solve()
113 // — variables in "up" equals to zero
114 // — variables in "left" equals to b
115 // — max: c * x
116 // — b[i] >= a[i] * x
117 // — answer in "v"
118 // — sertificate in "res"
119 };

```

std_rb_tree

```

1 #include "ext/pb_ds/assoc_container.hpp"
2 using namespace __gnu_pbds;
3
4 template <typename T> using ordered_set = tree<T, ←
    null_type, less<T>, rb_tree_tag, ←
    tree_order_statistics_node_update>;
5 template <typename K, typename V> using ordered_map ←
    = tree<K, V, less<K>, rb_tree_tag, ←
    tree_order_statistics_node_update>;
6

```

```

7 // HOW TO USE ::
8 // — order_of_key(10) returns the number of ←
9 // — elements in set/map strictly less than 10
10 // — *find_by_order(10) returns 10-th smallest ←
11 // — element in set/map (0-based)

```

Суффиксный автомат

```

1 namespace SA {
2     const int MAXN = 1 << 18;
3     const int SIGMA = 26;
4
5     int sz, last;
6     int nxt[MAXN][SIGMA];
7     int link[MAXN], len[MAXN], pos[MAXN];
8
9     void init() {
10         memset(nxt, -1, sizeof(nxt));
11         memset(link, -1, sizeof(link));
12         memset(len, 0, sizeof(len));
13         last = 0;
14         sz = 1;
15     }
16
17     void add(int c) {
18         int cur = sz++;
19         len[cur] = len[last] + 1;
20         pos[cur] = len[cur];
21         int p = last;
22         last = cur;
23         for (; p != -1 && nxt[p][c] == -1; p = link[p]) ←
24             nxt[p][c] = cur;
25         if (p == -1) {
26             link[cur] = 0;
27             return;
28         }
29         int q = nxt[p][c];
30         if (len[p] + 1 == len[q]) {
31             link[cur] = q;
32             return;
33         }
34         int clone = sz++;
35         memcpy(nxt[clone], nxt[q], sizeof(nxt[q]));
36         len[clone] = len[p] + 1;
37         pos[clone] = pos[q];
38         link[clone] = link[q];
39         link[q] = link[cur] = clone;
40         for (; p != -1 && nxt[p][c] == q; p = link[p]) ←
41             nxt[p][c] = clone;
42     }
43
44     int n;
45     string s;
46     int l[MAXN], r[MAXN];
47     int e[MAXN][SIGMA];
48
49     void getSufTree(string _s) {
50         memset(e, -1, sizeof(e));
51         s = _s;
52         n = s.length();
53         reverse(s.begin(), s.end());
54         init();
55         for (int i = 0; i < n; i++) add(s[i] - 'a');
56         reverse(s.begin(), s.end());
57         for (int i = 1; i < sz; i++) {
58             int j = link[i];
59             l[i] = n - pos[i] + len[j];
60             r[i] = n - pos[i] + len[i];
61             e[j][s[l[i]] - 'a'] = i;
62         }
63     }
64 }

```

generalMatching

```

1 namespace GeneralMatching {
2     const int MAXN = 256;
3     int n;
4     vector<int> g[MAXN];
5     int match[MAXN], p[MAXN], base[MAXN], q[MAXN];
6     bool used[MAXN], blossom[MAXN];

```

```

7
8 int lca (int a, int b) {
9     bool used[MXN] = { 0 };
10    for (;;) {
11        a = base[a];
12        used[a] = true;
13        if (match[a] == -1) break;
14        a = p[match[a]];
15    }
16    for (;;) {
17        b = base[b];
18        if (used[b]) return b;
19        b = p[match[b]];
20    }
21 }
22
23 void mark_path (int v, int b, int children) {
24     while (base[v] != b) {
25         blossom[base[v]] = blossom[base[match[v]]] = true;
26         p[v] = children;
27         children = match[v];
28         v = p[match[v]];
29     }
30 }
31
32 int find_path (int root) {
33     memset (used, 0, sizeof used);
34     memset (p, -1, sizeof p);
35     for (int i=0; i<n; ++i)
36         base[i] = i;
37
38     used[root] = true;
39     int qh=0, qt=0;
40     q[qt++] = root;
41     while (qh < qt) {
42         int v = q[qh++];
43         for (size_t i=0; i<g[v].size(); ++i) {
44             int to = g[v][i];
45             if (base[v] == base[to] || match[v] == to) continue;
46             if (to == root || (match[to] != -1 && p[match[to]] != -1)) {
47                 int curbase = lca (v, to);
48                 memset (blossom, 0, sizeof blossom);
49                 mark_path (v, curbase, to);
50                 mark_path (to, curbase, v);
51                 for (int i=0; i<n; ++i)
52                     if (blossom[base[i]]) {
53                         base[i] = curbase;
54                         if (!used[i]) {
55                             used[i] = true;
56                             q[qt++] = i;
57                         }
58                     }
59             }
60             else if (p[to] == -1) {
61                 p[to] = v;
62                 if (match[to] == -1)
63                     return to;
64                 to = match[to];
65                 used[to] = true;
66                 q[qt++] = to;
67             }
68         }
69     }
70     return -1;
71 }
72
73 vector<pair<int, int>> solve(int _n, vector<pair<int, int>> edges) {
74     n = _n;
75     for (int i = 0; i < n; i++) g[i].clear();
76     for (auto o : edges) {
77         g[o.first].push_back(o.second);
78         g[o.second].push_back(o.first);
79     }
80     memset (match, -1, sizeof match);
81     for (int i=0; i<n; ++i) {
82         if (match[i] == -1) {
83             int v = find_path (i);
84             while (v != -1) {
85                 int pv = p[v], ppv = match[pv];
86                 match[v] = pv, match[pv] = v;
87                 v = ppv;
88             }
89         }
90     }
91     vector<pair<int, int>> ans;
92     for (int i = 0; i < n; i++) {
93         if (match[i] > i) {
94             ans.push_back(make_pair(i, match[i]));
95         }
96     }

```

```

96     }
97     return ans;
98 }
99 }

```

dinica

```

1 namespace flow
2 {
3     const int maxn = 1e5 + 10;
4     const int maxe = 2 * maxn;
5
6     int head[maxn], next[maxe], to[maxe], f[maxe], ec ←
7     = 1;
8     int ST, EN, N = maxn;
9
10    inline void setN(int n)
11    {
12        ST = n;
13        EN = n + 1;
14        N = n + 2;
15    }
16
17    inline void _add(int x, int y, int ff)
18    {
19        ++ec;
20        to[ec] = y;
21        next[ec] = head[x];
22        head[x] = ec;
23        f[ec] = ff;
24    }
25
26    inline int add(int x, int y, int ff)
27    {
28        _add(x, y, ff);
29        _add(y, x, 0);
30        return ec - 1;
31    }
32
33    void clear()
34    {
35        forn(i, N) head[i] = 0;
36        ec = 1;
37    }
38
39    int d[maxn];
40    int q[maxn], st = 0, en = 0;
41
42    int bfs()
43    {
44        forn(i, N) d[i] = 1e9;
45        st = 0, en = 0;
46        d[ST] = 0;
47        q[en++] = ST;
48        while (st < en)
49        {
50            int x = q[st++];
51            if (x == EN) return 1;
52            for (int e = head[x]; e; e = next[e])
53            {
54                int y = to[e];
55                if (d[y] == 1e9 && f[e])
56                {
57                    d[y] = d[x] + 1;
58                    q[en++] = y;
59                }
60            }
61        }
62        return 0;
63    }
64
65    int pushed;
66    int fst[maxn];
67
68    int dfs(int x, int flow = 1e9)
69    {
70        if (x == EN)
71        {
72            pushed = flow;
73            return 1;
74        }
75        for (; fst[x]; fst[x] = next[fst[x]])
76        {
77            int e = fst[x];
78            int y = to[e];
79            if (d[y] == d[x] + 1 && f[e] && dfs(y, min(f[e] ←
80            ], flow)))

```

```

79     {
80         f[e] -= pushed;
81         f[e ^ 1] += pushed;
82         return 1;
83     }
84 }
85 return 0;
86 }
87
88
89 ll calcFlow()
90 {
91     ll res = 0;
92     while (bfs())
93     {
94         forn(i, N) fst[i] = head[i];
95         while (dfs(ST))
96         {
97             res += pushed;
98         }
99     }
100     return res;
101 }
102
103 // HOW TO USE ::
104 // — set maxn and maxe (special for izban)
105 // — add adges using add(x, y, f), call setN(n)
106 // — run calcFlow
107 }

```

max-flow-min-cost

```

1 namespace flow
2 {
3     const int maxn = 2e5 + 10;
4     const int maxe = 2 * maxn;
5
6     int head[maxn], next[maxe], to[maxe], flow[maxe], ←
7         cost[maxe], ec = 1;
8     int ST, EN, N = maxn;
9
10    inline void setN(int n)
11    {
12        ST = n;
13        EN = n + 1;
14        N = n + 2;
15    }
16
17    inline void _add(int x, int y, int f, int c)
18    {
19        ++ec;
20        to[ec] = y;
21        next[ec] = head[x];
22        head[x] = ec;
23        flow[ec] = f;
24        cost[ec] = c;
25    }
26
27    inline int add(int x, int y, int f, int c)
28    {
29        _add(x, y, f, c);
30        _add(y, x, 0, -c);
31        return ec - 1;
32    }
33
34    void clear()
35    {
36        forn(i, N) head[i] = 0;
37        ec = 1;
38    }
39
40    ll d[maxn], p[maxn];
41    int last[maxn];
42    int used[maxn];
43
44    pair<ll, ll> _calc(int flag)
45    {
46        const ll INF = 1e12;
47        forn(i, N) p[i] = INF;
48        p[ST] = 0;
49        forn(_, N) forn(x, N) for (int e = head[x]; e; e ←
50            = next[e]) if (flow[e] > 0)
51        {
52            int y = to[e];
53            if (p[y] > p[x] + cost[e])
54                p[y] = p[x] + cost[e];
55        }
56    }
57
58    ll resFlow = 0, resCost = 0;
59    while (1)
60    {
61        forn(i, N) d[i] = INF, used[i] = 0;
62        d[ST] = 0;
63        forn(_, N)
64        {
65            int x = -1;
66            forn(i, N) if (!used[i] && (x == -1 || d[x] ←
67                > d[i])) x = i;
68            used[x] = 1;
69            if (d[x] == INF) break;
70            for (int e = head[x]; e; e = next[e]) if (←
71                flow[e] > 0)
72            {
73                int y = to[e];
74                ll len = cost[e] + p[x] - p[y];
75                if (d[y] > d[x] + len)
76                {
77                    d[y] = d[x] + len;
78                    last[y] = e;
79                }
80            }
81
82            if (d[EN] == INF) break;
83
84            ll realCost = d[EN] + p[EN] - p[ST];
85            if (flag && realCost > 0) break;
86
87            int pushed = inf;
88            int x = EN;
89            while (x != ST)
90            {
91                int e = last[x];
92                pushed = min(pushed, flow[e]);
93                x = to[e ^ 1];
94            }
95
96            resCost += realCost * pushed;
97            resFlow += pushed;
98
99            x = ST;
100            while (x != EN)
101            {
102                int e = last[x];
103                flow[e] -= pushed;
104                flow[e ^ 1] += pushed;
105                x = to[e ^ 1];
106            }
107
108            forn(i, N) p[i] += d[i];
109        }
110        return mp(resFlow, resCost);
111    }
112
113    pair<ll, ll> maxFlow()
114    {
115        return _calc(0);
116    }
117
118    pair<ll, ll> minCost()
119    {
120        return _calc(1);
121    }
122
123    // HOW TO USE::
124    // — add adges using add(x, y, f, c), call setN(n ←
125    // — run maxFlow/minCost, returns pair(flow, cost ←
126    // )
127 }

```

```

54 }
55 }
56
57 ll resFlow = 0, resCost = 0;
58 while (1)
59 {
60     forn(i, N) d[i] = INF, used[i] = 0;
61     d[ST] = 0;
62     forn(_, N)
63     {
64         int x = -1;
65         forn(i, N) if (!used[i] && (x == -1 || d[x] ←
66             > d[i])) x = i;
67         used[x] = 1;
68         if (d[x] == INF) break;
69         for (int e = head[x]; e; e = next[e]) if (←
70             flow[e] > 0)
71         {
72             int y = to[e];
73             ll len = cost[e] + p[x] - p[y];
74             if (d[y] > d[x] + len)
75             {
76                 d[y] = d[x] + len;
77                 last[y] = e;
78             }
79         }
80
81         if (d[EN] == INF) break;
82
83         ll realCost = d[EN] + p[EN] - p[ST];
84         if (flag && realCost > 0) break;
85
86         int pushed = inf;
87         int x = EN;
88         while (x != ST)
89         {
90             int e = last[x];
91             pushed = min(pushed, flow[e]);
92             x = to[e ^ 1];
93         }
94
95         resCost += realCost * pushed;
96         resFlow += pushed;
97
98         x = ST;
99         while (x != EN)
100         {
101             int e = last[x];
102             flow[e] -= pushed;
103             flow[e ^ 1] += pushed;
104             x = to[e ^ 1];
105         }
106
107         forn(i, N) p[i] += d[i];
108     }
109     return mp(resFlow, resCost);
110 }
111
112 pair<ll, ll> maxFlow()
113 {
114     return _calc(0);
115 }
116
117 pair<ll, ll> minCost()
118 {
119     return _calc(1);
120 }
121
122 // HOW TO USE::
123 // — add adges using add(x, y, f, c), call setN(n ←
124 // — run maxFlow/minCost, returns pair(flow, cost ←
125 // )
126 }

```

poly

```

1 struct poly
2 {
3     vi v;
4     poly() {}
5     poly(vi vv)
6     {
7         v = vv;
8     }
9     int size()

```



```

10 {
11     return (int)v.size();
12 }
13 poly cut(int maxLen)
14 {
15     if (maxLen < sz(v)) v.resize(maxLen);
16     return *this;
17 }
18 poly norm()
19 {
20     while (sz(v) > 1 && v.back() == 0) v.pop_back();
21     return *this;
22 }
23 inline int& operator [] (int i)
24 {
25     return v[i];
26 }
27 void out(string name="")
28 {
29     stringstream ss;
30     if (sz(name)) ss << name << "=";
31     int fst = 1;
32     forn(i, sz(v)) if (v[i])
33     {
34         int x = v[i];
35         int sgn = 1;
36         if (x > mod / 2) x = mod - x, sgn = -1;
37         if (sgn == -1) ss << "-";
38         else if (!fst) ss << "+";
39         fst = 0;
40         if (!i || x != 1)
41         {
42             ss << x;
43             if (i > 0) ss << "*x";
44             if (i > 1) ss << "^" << i;
45         }
46         else
47         {
48             ss << "x";
49             if (i > 1) ss << "^" << i;
50         }
51     }
52     if (fst) ss << "0";
53     string s;
54     ss >> s;
55     eprintf("%s\n", s.data());
56 }
57 };
58
59 poly operator + (poly A, poly B)
60 {
61     poly C;
62     C.v = vi(max(sz(A), sz(B)));
63     forn(i, sz(C))
64     {
65         if (i < sz(A)) C[i] = (C[i] + A[i]) % mod;
66         if (i < sz(B)) C[i] = (C[i] + B[i]) % mod;
67     }
68     return C.norm();
69 }
70
71 poly operator - (poly A, poly B)
72 {
73     poly C;
74     C.v = vi(max(sz(A), sz(B)));
75     forn(i, sz(C))
76     {
77         if (i < sz(A)) C[i] = (C[i] + A[i]) % mod;
78         if (i < sz(B)) C[i] = (C[i] + mod - B[i]) % mod;
79     }
80     return C.norm();
81 }
82
83 poly operator * (poly A, poly B)
84 {
85     poly C;
86     C.v = vi(sz(A) + sz(B) - 1);
87
88     forn(i, sz(A)) fft::A[i] = A[i];
89     forn(i, sz(B)) fft::B[i] = B[i];
90     fft::multMod(sz(A), sz(B), mod);
91     forn(i, sz(C)) C[i] = fft::C[i];
92     return C.norm();
93 }
94
95 poly inv(poly A, int n) // returns A^{-1} mod x^n
96 {
97     assert(sz(A) && A[0] != 0);
98     A.cut(n);
99
100     auto cutPoly = [](poly &from, int l, int r)
101     {
102         poly R;

```

```

103     R.v.resize(r - 1);
104     for (int i = 1; i < r; ++i)
105     {
106         if (i < sz(from)) R[i - 1] = from[i];
107     }
108     return R;
109 };
110
111 function<int(int, int)> rev = [&rev](int x, int m)←
112     →int
113 {
114     if (x == 1) return 1;
115     return (1 - rev(m % x, x) * (ll)m) / x + m;
116 };
117
118 poly R({rev(A[0], mod)});
119 for (int k = 1; k < n; k <= 1)
120 {
121     poly A0 = cutPoly(A, 0, k);
122     poly A1 = cutPoly(A, k, 2 * k);
123     poly H = A0 * R;
124     H = cutPoly(H, k, 2 * k);
125     poly R1 = ((A1 * R).cut(k) + H) * (poly({0}) - ←
126     R).cut(k);
127     R.v.resize(2 * k);
128     forn(i, k) R[i + k] = R1[i];
129 }
130 return R.cut(n).norm();
131 }
132
133 pair<poly, poly> divide(poly A, poly B)
134 {
135     if (sz(A) < sz(B)) return {poly({0}), A};
136
137     auto rev = [](poly f)
138     {
139         reverse(all(f.v));
140         return f;
141     };
142
143     poly q = rev((inv(rev(B), sz(A) - sz(B) + 1) * rev←
144     (A)).cut(sz(A) - sz(B) + 1));
145     poly r = A - B * q;
146
147     return {q, r};
148 }

```

retro

```

1 namespace retro
2 {
3     const int N = 4e5 + 10;
4
5     vi v[N];
6     vi vrev[N];
7
8     void add(int x, int y)
9     {
10         v[x].pb(y);
11         vrev[y].pb(x);
12     }
13
14     const int UD = 0;
15     const int WIN = 1;
16     const int LOSE = 2;
17
18     int res[N];
19     int moves[N];
20     int deg[N];
21     int q[N], st, en;
22
23     void calc(int n)
24     {
25         forn(i, n) deg[i] = sz(v[i]);
26         st = en = 0;
27         forn(i, n) if (!deg[i])
28         {
29             q[en++] = i;
30             res[i] = LOSE;
31         }
32         while (st < en)
33         {
34             int x = q[st++];
35             for (int y : vrev[x])
36             {
37                 if (res[y] == UD && (res[x] == LOSE || (←
38                 deg[y] == 0 && res[x] == WIN)))

```

```
38         {  
39             res[y] = 3 - res[x];  
40             moves[y] = moves[x] + 1;  
41             q[en++] = y;  
42         }  
43     }  
44 }  
45 }  
46 }
```