

## Содержание

1	final/template/vimrc.txt
2	final/template/template.cpp
3	Practice round
4	final/template/fastIO.cpp
5	final/template/hashTable.cpp
6	final/template/optimizations.cpp
7	final/template/useful.cpp
8	final/template/Template.java
9	final/template/bitset.cpp
10	final/numeric/fft.cpp
11	final/numeric/fftint.cpp
12	final/numeric/blackbox.cpp
13	final/numeric/crt.cpp
14	final/numeric/mulMod.cpp
15	final/numeric/modReverse.cpp
16	final/numeric/pollard.cpp
17	final/numeric/poly.cpp
18	final/numeric/simplex.cpp
19	final/numeric/sumLine.cpp
20	final/numeric/berlekamp.cpp
21	final/numeric/integrate.cpp
22	final/geom/commonTangents.cpp
23	final/geom/halfplaneIntersection.cpp
24	final/geom/minDisc.cpp
25	final/geom/convexHull3D-N2.cpp
26	final/geom/polygonArcCut.cpp
27	final/geom/polygonTangent.cpp
28	final/geom/checkPlaneInt.cpp
29	final/geom/furthestPoints.cpp
30	final/strings/eertree.cpp
31	final/strings/sufAutomaton.cpp
32	final/strings/sufArray.cpp
33	final/strings/duval.cpp
34	final/graphs/centroid.cpp
35	final/graphs/dominatorTree.cpp
36	final/graphs/generalMatching.cpp
37	final/graphs/heavyLight.cpp
38	final/graphs/hungary.cpp
39	final/graphs/minCostNegCycle.cpp
40	final/graphs/retro.cpp
41	final/graphs/smith.cpp
42	final/graphs/mincut.cpp
43	final/graphs/twoChineseFast.cpp
44	final/graphs/linkcut.cpp
45	final/graphs/chordaltree.cpp
46	final/graphs/minimization.cpp
47	final/graphs/matroidIntersection.cpp

## final/template/vimrc.txt

```

1
1
2 1 map <F9> :wall! <CR> :!g++ -Wall -Wextra -Wshadow -<
Wno-unused-result -o %:r % -std=c++14 -DHOME -<
D_GLIBCXX_DEBUG -fsanitize=address <CR>
2 2 map <F7> :wall! <CR> :!g++ -Wall -Wextra -Wshadow -<
Wno-unused-result -o %:r % -std=c++14 -DHOME -<
O2 <CR>
2 3 map <F8> :wall! <CR> :!ulimit -s 500000 && ./%:r <CR>
>
2 4 map <F10> :wall! <CR> :!g++ -Wall -Wextra -Wshadow -<
Wno-unused-result -o %:r % -std=c++14 -DHOME -<
D_GLIBCXX_DEBUG -fsanitize=address -g && gdb <
./%:r <CR>
3
5
6 inoremap {<CR> {<CR>}<ESC>O
7
8 map <c-a> ggVG
9
10 set nu
11 set rnu
12 syntax on
13
14 map <c-t> :tabnew <CR>
15 map <c-l> :tabn <CR>
16 map <c-h> :tabp <CR>
17
18 set cin
19 set sw=4
20 set so=99
21 set bs=2
22 set et
23 set sts=4

```

## final/template/template.cpp

```

1 // team : SPb ITMO University 1
2 #include <bits/stdc++.h>
3
4 #define F first
5 #define S second
6 #define X first
7 #define Y second
8 #define pb push_back
9 #define sz(a) (int)(a).size()
10 #define all(a) (a).begin(), a.end()
11 #define pw(x) (1LL<<(x))
12
13 #define db(x) cerr << #x << " = " << x << endl
14 #define db2(x, y) cerr << "(" << #x << ", " << #y << "<
") = (" << x << ", " << y << ")<n";
15 #define db3(x, y, z) cerr << "(" << #x << ", " << #y <<
"< ", " << #z << ") = (" << x << ", " << y << "<
", " << z << ")<n";
16 #define dbv(a) cerr << #a << " = "; for (auto xxxx: <
a) cerr << xxxx << " "; cerr << endl
17
18 using namespace std;
19
20 typedef long long ll;
21 typedef double dbl;
22 const int INF = 1.01e9;
23
24
25
26 int main() {
27 #define TASK ""
28 #ifndef HOME
29     assert(freopen(TASK".in", "r", stdin));
30 #endif
31
32
33
34
35 #ifndef HOME
36     cerr << "time: " << clock() * 1.0 / CLOCKS_PER_SEC<
<< endl;
37 #endif
38     return 0;
39 }

```

## Practice round

1. Посаботити задачи каждому человеку
2. Печать
3. IDE для джавы
4. Сравнить скорость локального компьютера и сервера
5. Проверить \_\_int128
6. Проверить прагмы (например на битсетах)
7. Узнать максимально возможный размер отправляемого кода

### final/template/fastIO.cpp

```

1 #include <cstdio>
2 #include <algorithm>
3
4 /** Interface */
5
6 inline int readInt();
7 inline int readUInt();
8 inline bool isEof();
9
10 /** Read */
11
12 static const int buf_size = 100000;
13 static char buf[buf_size];
14 static int buf_len = 0, pos = 0;
15
16 inline bool isEof() {
17     if (pos == buf_len) {
18         pos = 0, buf_len = fread(buf, 1, buf_size, stdin);
19     }
20     if (pos == buf_len) return 1;
21     return 0;
22 }
23
24 inline int getChar() { return isEof() ? -1 : buf[pos++]; }
25
26 inline int readChar() {
27     int c = getChar();
28     while (c != -1 && c <= 32) c = getChar();
29     return c;
30 }
31
32 inline int readUInt() {
33     int c = readChar(), x = 0;
34     while ('0' <= c && c <= '9') x = x * 10 + c - '0', c = getChar();
35     return x;
36 }
37
38 inline int readInt() {
39     int s = 1, c = readChar();
40     int x = 0;
41     if (c == '-') s = -1, c = getChar();
42     while ('0' <= c && c <= '9') x = x * 10 + c - '0', c = getChar();
43     return s == 1 ? x : -x;
44 }
45
46 // 10M int [0..1e9]
47 // cin 3.02
48 // scanf 1.2
49 // cin sync_with_stdio(false) 0.71
50 // fastRead getchar 0.53
51 // fastRead fread 0.15

```

### final/template/hashTable.cpp

```

1 template <const int max_size, class HashType, class Data, const Data default_value>
2 struct hashTable {
3     HashType hash[max_size];
4     Data f[max_size];
5     int size;
6
7     int position(HashType H) const {
8         int i = H % max_size;
9         while (hash[i] && hash[i] != H)
10             if (++i == max_size)
11                 i = 0;
12         return i;
13     }
14
15     Data & operator [] (HashType H) {
16         assert(H != 0);
17         int i = position(H);
18         if (!hash[i]) {
19             hash[i] = H;
20             f[i] = default_value;
21             size++;
22         }
23         return f[i];
24     }
25 };
26
27 hashTable<13, int, int, 0> h;

```

### final/template/optimizations.cpp

```

1 inline void fasterLLDivMod(unsigned long long x, unsigned y, unsigned &out_d, unsigned &out_m) {
2     unsigned xh = (unsigned)(x >> 32), xl = (unsigned)x, d, m;
3     #ifdef __GNUC__
4         asm(
5             "divl %4; \n\t"
6             : "=a" (d), "=d" (m)
7             : "d" (xh), "a" (xl), "r" (y)
8         );
9     #else
10         __asm {
11             mov edx, dword ptr[xh];
12             mov eax, dword ptr[xl];
13             div dword ptr[y];
14             mov dword ptr[d], eax;
15             mov dword ptr[m], edx;
16         };
17     #endif
18     out_d = d; out_m = m;
19 }
20
21 // have no idea what sse flags are really cool; list of some of them
22 // -- very good with bitsets
23 #pragma GCC optimize("O3")
24 #pragma GCC target("sse, sse2, sse3, ssse3, sse4, popcnt, abm, mmx")

```

### final/template/useful.cpp

```

1 #include "ext/pb_ds/assoc_container.hpp"
2 using namespace __gnu_pbds;
3
4 template <typename T> using ordered_set = tree<T, null_type, less<T>, rb_tree_tag, tree_order_statistics_node_update>;
5 template <typename K, typename V> using ordered_map = tree<K, V, less<K>, rb_tree_tag, tree_order_statistics_node_update>;
6
7 // HOW TO USE ::
8 // -- order_of_key(10) returns the number of elements in set/map strictly less than 10
9 // -- *find_by_order(10) returns 10-th smallest element in set/map (0-based)
10
11 bitset<N> a;
12 for (int i = a._Find_first(); i != a.size(); i = a._Find_next(i)) {

```

```

13 cout << i << endl;
14 }

```

## final/template/Template.java

```

1 import java.util.*;
2 import java.io.*;
3
4 public class Template {
5     FastScanner in;
6     PrintWriter out;
7
8     public void solve() throws IOException {
9         int n = in.nextInt();
10        out.println(n);
11    }
12
13    public void run() {
14        try {
15            in = new FastScanner();
16            out = new PrintWriter(System.out);
17
18            solve();
19
20            out.close();
21        } catch (IOException e) {
22            e.printStackTrace();
23        }
24    }
25
26    class FastScanner {
27        BufferedReader br;
28        StringTokenizer st;
29
30        FastScanner() {
31            br = new BufferedReader(new InputStreamReader(↵
32            System.in));
33        }
34
35        String next() {
36            while (st == null || !st.hasMoreTokens()) {
37                try {
38                    st = new StringTokenizer(br.readLine());
39                } catch (IOException e) {
40                    e.printStackTrace();
41                }
42            }
43            return st.nextToken();
44        }
45
46        int nextInt() {
47            return Integer.parseInt(next());
48        }
49
50        public static void main(String[] arg) {
51            new Template().run();
52        }
53    }

```

```

20 int get(int pos) {
21     return (data[pos >> SZ] >> (pos & MOD)) & 1;
22 }
23 // k > 0 -> (*this) << k
24 // k < 0 -> (*this) >> (-k)
25 Bitset shift (int k) {
26     Bitset res;
27     res.resize(n);
28     int s = k / BASE;
29     int rem = k % BASE;
30     if (rem < 0) {
31         rem += BASE;
32         s--;
33     }
34     int p1 = BASE - rem;
35     T mask = (p1 == 64)? -1: pw(p1) - 1;
36     for (int i = max(0, -s); i < sz(data) - max(s, ↵
37         0); i++) {
38         res.data[i + s] |= (data[i] & mask) << rem;
39     }
40     if (rem != 0) {
41         for (int i = max(0, -s - 1); i < sz(data) - ↵
42             max(s + 1, 0); i++) {
43             res.data[i + s + 1] |= (data[i] >> p1) & (pw↵
44                 (rem) - 1);
45         }
46     }
47     int cc = data.size() * BASE - n;
48     res.data.back() <<= cc;
49     res.data.back() >>= cc;
50     return res;
51 }

```

## final/template/bitset.cpp

```

1
2 const int SZ = 6;
3 const int BASE = pw(SZ);
4 const int MOD = BASE - 1;
5
6 struct Bitset {
7     typedef unsigned long long T;
8     vector<T> data;
9     int n;
10    void resize(int nn) {
11        n = nn;
12        data.resize((n + BASE - 1) / BASE);
13    }
14    void set(int pos, int val) {
15        int id = pos >> SZ;
16        int rem = pos & MOD;
17        data[id] ^= data[id] & pw(rem);
18        data[id] |= val * pw(rem);
19    }

```

## final/numeric/fft.cpp

```

1 namespace fft
2 {
3     const int maxBase = 21;
4     const int maxN = 1 << maxBase;
5
6     struct num
7     {
8         dbl x, y;
9         num() {}
10        num(dbl xx, dbl yy): x(xx), y(yy) {}
11        num(dbl alp): x(cos(alp)), y(sin(alp)) {}
12    };
13
14    inline num operator + (num a, num b) { return num(←
15        a.x + b.x, a.y + b.y); }
16    inline num operator - (num a, num b) { return num(←
17        a.x - b.x, a.y - b.y); }
18    inline num operator * (num a, num b) { return num(←
19        a.x * b.x - a.y * b.y, a.x * b.y + a.y * b.x); }
20    inline num conj(num a) { return num(a.x, -a.y); }
21
22    const dbl PI = acos(-1);
23
24    num root[maxN];
25    int rev[maxN];
26    bool rootsPrepared = false;
27
28    void prepRoots()
29    {
30        if (rootsPrepared) return;
31        rootsPrepared = true;
32        root[1] = num(1, 0);
33        for (int k = 1; k < maxBase; ++k)
34        {
35            num x(2 * PI / pw(k + 1));
36            for (int i = pw(k - 1); i < pw(k); ++i)
37            {
38                root[2 * i] = root[i];
39                root[2 * i + 1] = root[i] * x;
40            }
41        }
42
43        int base = N;
44
45        int lastRevN = -1;
46        void prepRev()
47        {
48            if (lastRevN == N) return;
49            lastRevN = N;
50            for (int i = 0; i < N; i += 2 * k) for (int j = 0; j < N; j += 2 * k)
51            {
52                num z = f[i + j + k] * root[j + k];
53                f[i + j + k] = f[i + j] - z;
54                f[i + j] = f[i + j] + z;
55            }
56        }
57
58        num a[maxN], b[maxN], f[maxN], g[maxN];
59        ll A[maxN], B[maxN], C[maxN];
60
61        void _multMod(int mod)
62        {
63            for (int i = 0; i < N; i += 2 * k) for (int j = 0; j < N; j += 2 * k)
64            {
65                int x = A[i] % mod;
66                a[i] = num(x & (pw(15) - 1), x >> 15);
67            }
68            for (int i = 0; i < N; i += 2 * k) for (int j = 0; j < N; j += 2 * k)
69            {
70                int x = B[i] % mod;
71                b[i] = num(x & (pw(15) - 1), x >> 15);
72            }
73            fft(a, f);
74            fft(b, g);
75
76            for (int i = 0; i < N; i += 2 * k) for (int j = 0; j < N; j += 2 * k)
77            {
78                int j = (N - i) & (N - 1);
79            }
80        }
81    }
82

```

```

83        num a1 = (f[i] + conj(f[j])) * num(0.5, 0);
84        num a2 = (f[i] - conj(f[j])) * num(0, -0.5);
85        num b1 = (g[i] + conj(g[j])) * num(0.5 / N, 0);
86        num b2 = (g[i] - conj(g[j])) * num(0, -0.5 / N);
87        a[j] = a1 * b1 + a2 * b2 * num(0, 1);
88        b[j] = a1 * b2 + a2 * b1;
89    }
90
91    fft(a, f);
92    fft(b, g);
93
94    for (int i = 0; i < N; i += 2 * k) for (int j = 0; j < N; j += 2 * k)
95    {
96        ll aa = f[i].x + 0.5;
97        ll bb = g[i].x + 0.5;
98        ll cc = f[i].y + 0.5;
99        C[i] = (aa + bb % mod * pw(15) + cc % mod * pw(30)) % mod;
100    }
101
102    void prepAB(int n1, int n2)
103    {
104        base = 1;
105        N = 2;
106        while (N < n1 + n2) base++, N <= 1;
107
108        for (int i = n1; i < N; ++i) A[i] = 0;
109        for (int i = n2; i < N; ++i) B[i] = 0;
110
111        prepRoots();
112        prepRev();
113    }
114
115    void mult(int n1, int n2)
116    {
117        prepAB(n1, n2);
118        for (int i = 0; i < N; i += 2 * k) for (int j = 0; j < N; j += 2 * k)
119        {
120            int j = (N - i) & (N - 1);
121            a[i] = (f[j] * f[j] - conj(f[i] * f[i])) * num(←
122                0, -0.25 / N);
123        }
124        fft(a, f);
125        for (int i = 0; i < N; i += 2 * k) for (int j = 0; j < N; j += 2 * k)
126        {
127            C[i] = (ll)round(f[i].x);
128        }
129    }
130
131    void multMod(int n1, int n2, int mod)
132    {
133        prepAB(n1, n2);
134        _multMod(mod);
135    }
136
137    int D[maxN];
138
139    void multLL(int n1, int n2)
140    {
141        prepAB(n1, n2);
142
143        int mod1 = 1.5e9;
144        int mod2 = mod1 + 1;
145
146        _multMod(mod1);
147
148        for (int i = 0; i < N; i += 2 * k) for (int j = 0; j < N; j += 2 * k)
149        {
150            C[i] = D[i] + (C[i] - D[i] + (ll)mod2) * (ll)←
151                mod1 % mod2 * mod1;
152        }
153    }
154
155    // HOW TO USE ::
156    // — set correct maxBase
157    // — use mult(n1, n2), multMod(n1, n2, mod) and ←
158    // — input : A[], B[]
159    // — output : C[]
160
161    }
162

```

## final/numeric/fftint.cpp

```

1 namespace fft {
2     const int MOD = 998244353;
3     const int base = 20;
4     const int N = 1 << base;
5     const int ROOT = 646;
6
7     int root[N];
8     int rev[N];
9
10    ll inv(ll a, ll m = MOD) {
11        if (a == 0) return 0;
12        return ((1 - inv(m % a, a) * m) / a + m) % m;
13    }
14
15    void init() {
16        for (int i = 0; i < N; i++) rev[i] = (rev[i >> 1] >> 1) + ((i & 1) << (base - 1));
17        int NN = N >> 1;
18        int z = 1;
19        for (int i = 0; i < NN; i++) {
20            root[i + NN] = z;
21            z = z * (ll)ROOT % MOD;
22        }
23        for (int i = NN - 1; i > 0; --i) root[i] = root[2 * i];
24    }
25
26    void fft(int *a, int *f) {
27        for (int i = 0; i < N; i++) f[i] = a[rev[i]];
28        for (int k = 1; k < N; k <= 1) {
29            for (int i = 0; i < N; i += 2 * k) {
30                for (int j = 0; j < k; j++) {
31                    int z = f[i + j + k] * (ll)root[j + k] % MOD;
32                    f[i + j + k] = (f[i + j] - z + MOD) % MOD;
33                    f[i + j] = (f[i + j] + z) % MOD;
34                }
35            }
36        }
37    }
38
39    int A[N], B[N], C[N];
40    int F[N], G[N];
41
42    void _mult(int eq) {
43        fft(A, F);
44        if (eq)
45            for (int i = 0; i < N; i++)
46                G[i] = F[i];
47        else fft(B, G);
48        int invN = inv(N);
49        for (int i = 0; i < N; i++) A[i] = F[i] * (ll)G[i] % MOD * invN % MOD;
50        reverse(A + 1, A + N);
51        fft(A, C);
52    }
53
54    void mult(int n1, int n2, int eq = 0) {
55        for (int i = n1; i < N; ++i) A[i] = 0;
56        for (int i = n2; i < N; ++i) B[i] = 0;
57
58        _mult(eq);
59
60        //for(i, n1 + n2) C[i] = 0;
61        //for(i, n1) for(j, n2) C[i + j] = (C[i + j] + A[i] * (ll)B[j]) % mod;
62    }
63 }

```

## final/numeric/blackbox.cpp

```

1 namespace blackbox
2 {
3     int A[N];
4     int B[N];
5     int C[N];
6
7     int magic(int k, int x)
8     {
9         B[k] = x;
10        C[k] = (C[k] + A[0] * (ll)B[k]) % mod;
11        int z = 1;
12        if (k == N - 1) return C[k];
13        while ((k & (z - 1)) == (z - 1))
14        {
15            //mult B[k - z + 1 ... k] x A[z .. 2 * z - 1]
16            for(i, z) fft::A[i] = A[z + i];

```

```

17        for(i, z) fft::B[i] = B[k - z + 1 + i];
18        fft::multMod(z, z, mod);
19        for(i, 2 * z - 1) C[k + 1 + i] = (C[k + 1 + i] +
20            fft::C[i]) % mod;
21        z <= 1;
22    }
23    return C[k];
24 }
25 // A — constant array
26 // magic(k, x):: B[k] = x, returns C[k]
27 // !! WARNING !! better to set N twice the size needed

```

## final/numeric/crt.cpp

```

1 int CRT(int a1, int m1, int a2, int m2) {
2     return (a1 - a2 % m1 + m1) * (ll)rev(m2, m1) % m1 +
3         * m2 + a2;
4 }

```

## final/numeric/mulMod.cpp

```

1 ll mul(ll a, ll b, ll m) { // works for MOD 8e18
2     ll k = (ll)((long double)a * b / m);
3     ll r = a * b - m * k;
4     if (r < 0) r += m;
5     if (r >= m) r -= m;
6     return r;
7 }

```

## final/numeric/modReverse.cpp

```

1 int rev(int x, int m) {
2     if (x == 1) return 1;
3     return (1 - rev(m % x, x) * (ll)m) / x + m;
4 }

```

## final/numeric/pollard.cpp

```

1 namespace pollard
2 {
3     using math::p;
4
5     vector<pair<ll, int>> getFactors(ll N)
6     {
7         vector<ll> primes;
8
9         const int MX = 1e5;
10        const ll MX2 = MX * (ll)MX;
11
12        assert(MX <= math::maxP && math::pc > 0);
13
14        function<void(ll)> go = [&go, &primes](ll n)
15        {
16            for (ll x : primes) while (n % x == 0) n /= x;
17            if (n == 1) return;
18            if (n > MX2)
19            {
20                auto F = [&](ll x) {
21                    ll k = ((long double)x * x) / n;
22                    ll r = (x * x - k * n + 3) % n;
23                    return r < 0 ? r + n : r;
24                };
25                ll x = mt19937_64()() % n, y = x;
26                const int C = 3 * pow(n, 0.25);
27
28                ll val = 1;
29                for(it, C)

```

```

30 {
31     x = F(x), y = F(F(y));
32     if (x == y) continue;
33     ll delta = abs(x - y);
34     ll k = ((long double)val * delta) / n;
35     val = (val * delta - k * n) % n;
36     if (val < 0) val += n;
37     if (val == 0)
38     {
39         ll g = __gcd(delta, n);
40         go(g), go(n / g);
41         return;
42     }
43     if ((it & 255) == 0)
44     {
45         ll g = __gcd(val, n);
46         if (g != 1)
47         {
48             go(g), go(n / g);
49             return;
50         }
51     }
52 }
53 }
54 primes.pb(n);
55 };
56
57 ll n = N;
58
59 for (int i = 0; i < math::pc && p[i] < MX; ++i) ←
60 if (n % p[i] == 0)
61 {
62     primes.pb(p[i]);
63     while (n % p[i] == 0) n /= p[i];
64 }
65
66 go(n);
67
68 sort(primes.begin(), primes.end());
69
70 vector<pair<ll, int>> res;
71 for (ll x : primes)
72 {
73     int cnt = 0;
74     while (N % x == 0)
75     {
76         cnt++;
77         N /= x;
78     }
79     res.push_back({x, cnt});
80 }
81 return res;
82 }

```

## final/numeric/poly.cpp

```

1 struct poly
2 {
3     vi v;
4     poly() {}
5     poly(vi vv)
6     {
7         v = vv;
8     }
9     int size()
10    {
11        return (int)v.size();
12    }
13    poly cut(int maxLen)
14    {
15        if (maxLen < sz(v)) v.resize(maxLen);
16        return *this;
17    }
18    poly norm()
19    {
20        while (sz(v) > 1 && v.back() == 0) v.pop_back();
21        return *this;
22    }
23    inline int& operator [] (int i)
24    {
25        return v[i];
26    }
27    void out(string name="")
28    {
29        stringstream ss;
30        if (sz(name)) ss << name << "=";

```

```

31    int fst = 1;
32    forn(i, sz(v)) if (v[i])
33    {
34        int x = v[i];
35        int sgn = 1;
36        if (x > mod / 2) x = mod - x, sgn = -1;
37        if (sgn == -1) ss << "-";
38        else if (!fst) ss << "+";
39        fst = 0;
40        if (!i || x != 1)
41        {
42            ss << x;
43            if (i > 0) ss << "*x";
44            if (i > 1) ss << "^" << i;
45        }
46        else
47        {
48            ss << "x";
49            if (i > 1) ss << "^" << i;
50        }
51    }
52    if (fst) ss << "0";
53    string s;
54    ss >> s;
55    eprintf("%s\n", s.data());
56 }
57 };
58
59 poly operator + (poly A, poly B)
60 {
61     poly C;
62     C.v = vi(max(sz(A), sz(B)));
63     forn(i, sz(C))
64     {
65         if (i < sz(A)) C[i] = (C[i] + A[i]) % mod;
66         if (i < sz(B)) C[i] = (C[i] + B[i]) % mod;
67     }
68     return C.norm();
69 }
70
71 poly operator - (poly A, poly B)
72 {
73     poly C;
74     C.v = vi(max(sz(A), sz(B)));
75     forn(i, sz(C))
76     {
77         if (i < sz(A)) C[i] = (C[i] + A[i]) % mod;
78         if (i < sz(B)) C[i] = (C[i] + mod - B[i]) % mod;
79     }
80     return C.norm();
81 }
82
83 poly operator * (poly A, poly B)
84 {
85     poly C;
86     C.v = vi(sz(A) + sz(B) - 1);
87
88     forn(i, sz(A)) fft::A[i] = A[i];
89     forn(i, sz(B)) fft::B[i] = B[i];
90     fft::multMod(sz(A), sz(B), mod);
91     forn(i, sz(C)) C[i] = fft::C[i];
92     return C.norm();
93 }
94
95 poly inv(poly A, int n) // returns A^{-1} mod x^n
96 {
97     assert(sz(A) && A[0] != 0);
98     A.cut(n);
99
100    auto cutPoly = [](poly &from, int l, int r)
101    {
102        poly R;
103        R.v.resize(r - l);
104        for (int i = l; i < r; ++i)
105        {
106            if (i < sz(from)) R[i - l] = from[i];
107        }
108        return R;
109    };
110
111    function<int(int, int)> rev = [&rev](int x, int m) ←
112    → int
113    {
114        if (x == 1) return 1;
115        return (1 - rev(m % x, x) * (ll)m) / x + m;
116    };
117
118    poly R({rev(A[0], mod)});
119    for (int k = 1; k < n; k <= 1)
120    {
121        poly A0 = cutPoly(A, 0, k);
122        poly A1 = cutPoly(A, k, 2 * k);
123        poly H = A0 * R;

```

```

123     H = cutPoly(H, k, 2 * k);
124     poly R1 = (((A1 * R).cut(k) + H) * (poly({0}) - ←
125     R)).cut(k);
126     R.v.resize(2 * k);
127     forn(i, k) R[i + k] = R1[i];
128 }
129 return R.cut(n).norm();
130 }
131 pair<poly, poly> divide(poly A, poly B)
132 {
133     if (sz(A) < sz(B)) return {poly({0}), A};
134
135     auto rev = [(poly f)
136     {
137         reverse(all(f.v));
138         return f;
139     }];
140
141     poly q = rev((inv(rev(B), sz(A) - sz(B) + 1) * rev←
142     (A)).cut(sz(A) - sz(B) + 1));
143     poly r = A - B * q;
144
145     return {q, r};
146 }

```

## final/numeric/simplex.cpp

```

1 vector<double> simplex(vector<vector<double>> a) {
2     int n = a.size() - 1;
3     int m = a[0].size() - 1;
4     vector<int> left(n + 1), up(m + 1);
5     iota(up.begin(), up.end(), 0);
6     iota(left.begin(), left.end(), m);
7     auto pivot = [&](int x, int y) {
8         swap(left[x], up[y]);
9         double k = a[x][y];
10        a[x][y] = 1;
11        vector<int> vct;
12        for (int j = 0; j <= m; j++) {
13            a[x][j] /= k;
14            if (!eq(a[x][j], 0)) vct.push_back(j);
15        }
16        for (int i = 0; i <= n; i++) {
17            if (eq(a[i][y], 0) || i == x) continue;
18            k = a[i][y];
19            a[i][y] = 0;
20            for (int j : vct) a[i][j] -= k * a[x][j];
21        }
22    };
23    while (1) {
24        int x = -1;
25        for (int i = 1; i <= n; i++) if (ls(a[i][0], 0) ←
26        && (x == -1 || a[i][0] < a[x][0])) x = i;
27        if (x == -1) break;
28        int y = -1;
29        for (int j = 1; j <= m; j++) if (ls(a[x][j], 0) ←
30        && (y == -1 || a[x][j] < a[x][y])) y = j;
31        if (y == -1) assert(0); // infeasible
32        pivot(x, y);
33    }
34    while (1) {
35        int y = -1;
36        for (int j = 1; j <= m; j++) if (ls(0, a[0][j]) ←
37        && (y == -1 || a[0][j] > a[0][y])) y = j;
38        if (y == -1) break;
39        int x = -1;
40        for (int i = 1; i <= n; i++) if (ls(0, a[i][y]) ←
41        && (x == -1 || a[i][0] / a[i][y] < a[x][0] / a[←
42        x][y])) x = i;
43        if (x == -1) assert(0); // unbounded
44        pivot(x, y);
45    }
46    vector<double> ans(m + 1);
47    for (int i = 1; i <= n; i++) if (left[i] <= m) ans←
48    [left[i]] = a[i][0];
49    ans[0] = -a[0][0];
50    return ans;
51 }
52 // j=1..m: x[j]>=0
53 // i=1..n: sum(j=1..m) A[i][j]*x[j] <= A[i][0]
54 // max sum(j=1..m) A[0][j]*x[j]
55 // res[0] is answer
56 // res[1..m] is certificate

```

## final/numeric/sumLine.cpp

```

1 // sum(i=0..n-1) (a+b*i) div m
2 ll solve(ll n, ll a, ll b, ll m) {
3     if (b == 0) return n * (a / m);
4     if (a >= m) return n * (a / m) + solve(n, a % m, b ←
5     , m);
6     if (b >= m) return n * (n - 1) / 2 * (b / m) + ←
7     solve(n, a, b % m, m);
8     return solve((a + b * n) / m, (a + b * n) % m, m, ←
9     b);
10 }

```

## final/numeric/berlekamp.cpp

```

1 vector<int> berlekamp(vector<int> s) {
2     int l = 0;
3     vector<int> la(1, 1);
4     vector<int> b(1, 1);
5     for (int r = 1; r <= (int)s.size(); r++) {
6         int delta = 0;
7         for (int j = 0; j <= l; j++) {
8             delta = (delta + 1LL * s[r - 1 - j] * la[j]) % ←
9             MOD;
10        }
11        b.insert(b.begin(), 0);
12        if (delta != 0) {
13            vector<int> t(max(la.size(), b.size()));
14            for (int i = 0; i < (int)t.size(); i++) {
15                if (i < (int)la.size()) t[i] = (t[i] + la[i] ←
16                ) % MOD;
17                if (i < (int)b.size()) t[i] = (t[i] - 1LL * ←
18                delta * b[i] % MOD + MOD) % MOD;
19            }
20            if (2 * l <= r - 1) {
21                b = la;
22                int od = inv(delta);
23                for (int &x : b) x = 1LL * x * od % MOD;
24                l = r - 1;
25            }
26            la = t;
27        }
28        assert((int)la.size() == l + 1);
29        assert(l * 2 + 30 < (int)s.size());
30        reverse(la.begin(), la.end());
31        return la;
32    }
33 }
34 vector<int> mul(vector<int> a, vector<int> b) {
35     vector<int> c(a.size() + b.size() - 1);
36     for (int i = 0; i < (int)a.size(); i++) {
37         for (int j = 0; j < (int)b.size(); j++) {
38             c[i + j] = (c[i + j] + 1LL * a[i] * b[j]) % ←
39             MOD;
40        }
41    }
42     vector<int> res(c.size());
43     for (int i = 0; i < (int)res.size(); i++) res[i] = ←
44     c[i] % MOD;
45     return res;
46 }
47 vector<int> mod(vector<int> a, vector<int> b) {
48     if (a.size() < b.size()) a.resize(b.size() - 1);
49
50     int o = inv(b.back());
51     for (int i = (int)a.size() - 1; i >= (int)b.size() ←
52     - 1; i--) {
53         if (a[i] == 0) continue;
54         int coef = 1LL * o * (MOD - a[i]) % MOD;
55         for (int j = 0; j < (int)b.size(); j++) {
56             a[i - (int)b.size() + 1 + j] = (a[i - (int)b. ←
57             size() + 1 + j] + 1LL * coef * b[j]) % MOD;
58        }
59    }
60     while (a.size() >= b.size()) {
61         assert(a.back() == 0);
62         a.pop_back();
63     }
64     return a;
65 }
66 vector<int> bin(int n, vector<int> p) {

```

```

63 vector<int> res(1, 1);
64 vector<int> a(2); a[1] = 1;
65 while (n) {
66     if (n & 1) res = mod(mul(res, a), p);
67     a = mod(mul(a, a), p);
68     n >>= 1;
69 }
70 return res;
71 }
72
73 int f(vector<int> t, int m) {
74     vector<int> v = berlekamp(t);
75     vector<int> o = bin(m - 1, v);
76     int res = 0;
77     for (int i = 0; i < (int)o.size(); i++) res = (res <-
78         + 1LL * o[i] * t[i]) % MOD;
79     return res;
}

```

## final/numeric/integrate.cpp

```

1 function<dbl>(dbl, dbl, function<dbl>(dbl)>> f = [&](dbl L, dbl R, function<dbl>(dbl)> g) {
2     const int ITTERS = 1000000;
3     dbl ans = 0;
4     dbl step = (R - L) * 1.0 / ITTERS;
5     for (int it = 0; it < ITTERS; it++) {
6         double x1 = L + step * it;
7         double xr = L + step * (it + 1);
8         dbl x1 = (x1 + xr) / 2;
9         dbl x0 = x1 - (x1 - x1) * sqrt(3.0 / 5);
10        dbl x2 = x1 + (x1 - x1) * sqrt(3.0 / 5);
11        ans += (5 * g(x0) + 8 * g(x1) + 5 * g(x2)) / 18 <-
12            * step;
13    }
14    return ans;
};

```

## final/geom/commonTangents.cpp

```

1
2
3 vector<Line> commonTangents(pt A, dbl rA, pt B, dbl rB) {
4     vector<Line> res;
5     pt C = B - A;
6     dbl z = C.len2();
7     for (int i = -1; i <= 1; i += 2) {
8         for (int j = -1; j <= 1; j += 2) {
9             dbl r = rB * j - rA * i;
10            dbl d = z - r * r;
11            if (ls(d, 0)) continue;
12            d = sqrt(max(0.01, d));
13            pt magic = pt(r, d) / z;
14            pt v(magic % C, magic * C);
15            dbl CC = (rA * i - v % A) / v.len2();
16            pt O = v * -CC;
17            res.pb(Line(0, 0 + v.rotate()));
18        }
19    }
20    return res;
21 }
22
23 // HOW TO USE ::
24 // --- *D*-----*F*
25 // --- *...* - - *...*
26 // --- *.....* - - *.....*
27 // --- *.....* - - *.....*
28 // --- *...A...* - - *...B...*
29 // --- *.....* - - *.....*
30 // --- *.....* - - *.....*
31 // --- *...* - - *...*
32 // --- *C*-----*E*
33 // --- res = {CE, CF, DE, DF}

```

## final/geom/halfplaneIntersection.cpp

```

1 int getPart(pt v) {
2     return ls(v.y, 0) || (eq(0, v.y) && ls(v.x, 0));
3 }
4
5 int cmpV(pt a, pt b) {
6     int partA = getPart(a);
7     int partB = getPart(b);
8     if (partA < partB) return 1;
9     if (partA > partB) return -1;
10    if (eq(0, a * b)) return 0;
11    if (0 < a * b) return -1;
12    return 1;
13 }
14
15 double planeInt(vector<Line> l) {
16     sort(all(l), [](Line a, Line b) {
17         int r = cmpV(a.v, b.v);
18         if (r != 0) return r < 0;
19         return a.0 % a.v.rotate() > b.0 % a.v.rotate() <-
20             });
21
22     l.resize(unique(all(l), [](Line A, Line B) { <-
23         return cmpV(A.v, B.v) == 0; }) - l.begin());
24     for (int i = 0; i < sz(l); i++)
25         l[i].id = i;
26
27     // if an infinite answer is possible
28     int flagUp = 0;
29     int flagDown = 0;
30     for (int i = 0; i < sz(l); i++) {
31         int part = getPart(l[i].v);
32         if (part == 1) flagUp = 1;
33         if (part == 0) flagDown = 1;
34     }
35     if (!flagUp || !flagDown) return -1;
36
37     for (int i = 0; i < sz(l); i++) {
38         pt v = l[i].v;
39         pt u = l[(i + 1) % sz(l)].v;
40         if (eq(0, v * u) && ls(v % u, 0)) {
41             pt dir = l[i].v.rotate();
42             if (le(l[(i + 1) % sz(l)].0 % dir, l[i].0 % <-
43                 dir)) return 0;
44             return -1;
45         }
46     }
47 }

```



```

43     }
44     if (ls(v * u, 0))
45         return -1;
46 }
47 // main part
48 vector<Line> st;
49 for (int tt = 0; tt < 2; tt++) {
50     for (auto L: l) {
51         for (; sz(st) >= 2 && le(st[sz(st) - 2].v * (←
52             st.back() * L - st[sz(st) - 2].0), 0); st.←
53             pop_back();
54         st.pb(L);
55         if (sz(st) >= 2 && le(st[sz(st) - 2].v * st.←
56             back().v, 0)) return 0; // useless line
57     }
58     vector<int> use(sz(l), -1);
59     int left = -1, right = -1;
60     for (int i = 0; i < sz(st); i++) {
61         if (use[st[i].id] == -1) {
62             use[st[i].id] = i;
63         }
64         else {
65             left = use[st[i].id];
66             right = i;
67             break;
68         }
69     }
70     vector<Line> tmp;
71     for (int i = left; i < right; i++)
72         tmp.pb(st[i]);
73     vector<pt> res;
74     for (int i = 0; i < (int)tmp.size(); i++)
75         res.pb(tmp[i] * tmp[(i + 1) % tmp.size()]);
76     double area = 0;
77     for (int i = 0; i < (int)res.size(); i++)
78         area += res[i] * res[(i + 1) % res.size()];
79     return area / 2;

```

## final/geom/minDisc.cpp

```

1 pair<pt, dbl> minDisc(vector<pt> p) {
2     int n = p.size();
3     pt O = pt(0, 0);
4     dbl R = 0;
5     random_shuffle(all(p));
6     for (int i = 0; i < n; i++) {
7         if (ls(R, (O - p[i]).len())) {
8             O = p[i];
9             R = 0;
10            for (int j = 0; j < i; j++) {
11                if (ls(R, (O - p[j]).len())) {
12                    O = (p[i] + p[j]) / 2;
13                    R = (p[i] - p[j]).len() / 2;
14                    for (int k = 0; k < j; k++) {
15                        if (ls(R, (O - p[k]).len())) {
16                            Line l1((p[i] + p[j]) / 2, (p[i] + p[j]←
17                                ]) / 2 + (p[i] - p[j]).rotate());
18                            Line l2((p[k] + p[j]) / 2, (p[k] + p[j]←
19                                ]) / 2 + (p[k] - p[j]).rotate());
20                            O = l1 * l2;
21                            R = (p[i] - O).len();
22                        }
23                    }
24                }
25            }
26        }
27        return {O, R};
28    }

```

## final/geom/convexHull3D-N2.cpp

```

1 struct Plane {
2     pt O, v;
3     vector<int> id;
4 };
5
6

```

```

7 vector<Plane> convexHull3(vector<pt> p) {
8     vector<Plane> res;
9     int n = p.size();
10    for (int i = 0; i < n; i++)
11        p[i].id = i;
12    for (int i = 0; i < 4; i++) {
13        vector<pt> tmp;
14        for (int j = 0; j < 4; j++)
15            if (i != j)
16                tmp.pb(p[j]);
17        res.pb({tmp[0], (tmp[1] - tmp[0]) * (tmp[2] - ←
18            tmp[0]), {tmp[0].id, tmp[1].id, tmp[2].id}});
19        if ((p[i] - res.back().0) % res.back().v > 0) {
20            res.back().v = res.back().v * -1;
21            swap(res.back().id[0], res.back().id[1]);
22        }
23    }
24    vector<vector<int>> use(n, vector<int>(n, 0));
25    int tnr = 0;
26    for (int i = 4; i < n; i++) {
27        int cur = 0;
28        tnr++;
29        vector<pair<int, int>> curEdge;
30        for (int j = 0; j < sz(res); j++) {
31            if ((p[i] - res[j].0) % res[j].v > 0) {
32                for (int t = 0; t < 3; t++) {
33                    int v = res[j].id[t];
34                    int u = res[j].id[(t + 1) % 3];
35                    use[v][u] = tnr;
36                    curEdge.pb({v, u});
37                }
38            }
39            else {
40                res[cur++] = res[j];
41            }
42        }
43        res.resize(cur);
44        for (auto x: curEdge) {
45            if (use[x.S][x.F] == tnr) continue;
46            res.pb({p[i], (p[x.F] - p[i]) * (p[x.S] - p[i]←
47                )), {x.F, x.S, i}});
48        }
49    }
50    return res;
51 }
52 // plane in 3d
53 // (A, v) * (B, u) -> (O, n)
54 pt n = v * u;
55 pt m = v * n;
56 double t = (B - A) % u / (u % m);
57 pt O = A - m * t;

```

## final/geom/polygonArcCut.cpp

```

1 struct Meta {
2     int type; // 0 - seg, 1 - circle
3     pt O;
4     dbl R;
5 };
6
7
8 const Meta SEG = {0, pt(0, 0), 0};
9
10 vector<pair<pt, Meta>> cut(vector<pair<pt, Meta>> p, ←
11     Line l) {
12     vector<pair<pt, Meta>> res;
13     int n = p.size();
14     for (int i = 0; i < n; i++) {
15         pt A = p[i].F;
16         pt B = p[(i + 1) % n].F;
17         if (le(0, l.v * (A - l.0))) {
18             if (eq(0, l.v * (A - l.0)) && p[i].S.type == 1←
19                 && ls(0, l.v % (p[i].S.0 - A)))
20                 res.pb({A, SEG});
21             else
22                 res.pb(p[i]);
23         }
24         if (p[i].S.type == 0) {
25             if (sign(l.v * (A - l.0)) * sign(l.v * (B - l.←
26                 0)) == -1) {
27                 pt FF = Line(A, B) * l;
28                 res.pb(make_pair(FF, SEG));
29             }
30         }
31     }
32     return res;
33 }

```

```

29     pt E, F;
30     if (intCL(p[i].S.O, p[i].S.R, l, E, F)) {
31         if (onArc(p[i].S.O, A, E, B))
32             res.pb({E, SEG});
33         if (onArc(p[i].S.O, A, F, B))
34             res.pb({F, p[i].S});
35     }
36 }
37 }
38 return res;
39 }

```

```

2     int n = p.size();
3     int cur = 1;
4     ll answer = 0;
5     for (int i = 0; i < n; i++) {
6         for (; (p[(i + 1) % n] - p[i]) * (p[(cur + 1) % n] - p[cur]) > 0; cur = (cur + 1) % n);
7             answer = max(answer, (p[i] - p[cur]).len2());
8     }
9     return answer;
10 }

```

## final/geom/polygonTangent.cpp

```

1 pt tangent(vector<pt>& p, pt O, int cof) {
2     int step = 1;
3     for (; step < (int)p.size(); step *= 2);
4     int pos = 0;
5     int n = p.size();
6     for (; step > 0; step /= 2) {
7         int best = pos;
8         for (int dx = -1; dx <= 1; dx += 2) {
9             int id = ((pos + step * dx) % n + n) % n;
10            if ((p[id] - O) * (p[best] - O) * cof > 0)
11                best = id;
12        }
13        pos = best;
14    }
15    return p[pos];
16 }

```

## final/geom/checkPlaneInt.cpp

```

1 bool checkPoint(vector<Line> l, pt& ret) {
2     random_shuffle(all(l));
3     pt A = l[0].O;
4     for (int i = 1; i < sz(l); i++) {
5         if (!le(0, l[i].v * (A - l[i].O))) {
6             dbl mn = -INF;
7             dbl mx = INF;
8             for (int j = 0; j < i; j++) {
9                 if (eq(l[j].v * l[i].v, 0)) {
10                    if (l[j].v % l[i].v < 0 && (l[j].O - l[i].O) % l[i].v < 0) {
11                        return false;
12                    }
13                }
14                else {
15                    pt u = l[j].v.rotate();
16                    dbl proj = (l[j].O - l[i].O) % u / (l[i].v % u);
17                    if (l[i].v * l[j].v > 0) {
18                        mx = min(mx, proj);
19                    }
20                    else {
21                        mn = max(mn, proj);
22                    }
23                }
24            }
25            if (mn <= mx) {
26                A = l[i].O + l[i].v * mn;
27            }
28            else {
29                return false;
30            }
31        }
32    }
33    ret = A;
34    return true;
35 }
36 }

```

## final/geom/furthestPoints.cpp

```

1 ll furthestPoints(vector<pt> p) {

```

## final/strings/eertree.cpp

```

1 namespace eertree {
2     const int INF = 1e9;
3     const int N = 5e6 + 10;
4     char _s[N];
5     char *s = _s + 1;
6     int to[N][2];
7     int suf[N], len[N];
8     int sz, last;
9
10    const int odd = 1, even = 2, blank = 3;
11
12    void go(int &u, int pos) {
13        while (u != blank && s[pos - len[u] - 1] != s[pos]) {
14            u = suf[u];
15        }
16    }
17
18    int add(int pos) {
19        go(last, pos);
20        int u = suf[last];
21        go(u, pos);
22        int c = s[pos] - 'a';
23        int res = 0;
24        if (!to[last][c]) {
25            res = 1;
26            to[last][c] = sz;
27            len[sz] = len[last] + 2;
28            suf[sz] = to[u][c];
29            sz++;
30        }
31        last = to[last][c];
32        return res;
33    }
34
35    void init() {
36        to[blank][0] = to[blank][1] = even;
37        len[blank] = suf[blank] = INF;
38        len[even] = 0, suf[even] = odd;
39        len[odd] = -1, suf[odd] = blank;
40        last = even;
41        sz = 4;
42    }
43 }

```

## final/strings/sufAutomaton.cpp

```

1 namespace SA {
2     const int MAXN = 1 << 18;
3     const int SIGMA = 26;
4
5     int sz, last;
6     int nxt[MAXN][SIGMA];
7     int link[MAXN], len[MAXN], pos[MAXN];
8
9     void init() {
10        memset(nxt, -1, sizeof(nxt));
11        memset(link, -1, sizeof(link));
12        memset(len, 0, sizeof(len));
13        last = 0;
14        sz = 1;
15    }
16
17    void add(int c) {
18        int cur = sz++;
19        len[cur] = len[last] + 1;
20        pos[cur] = len[cur];
21        int p = last;

```

```

22     last = cur;
23     for (; p != -1 && nxt[p][c] == -1; p = link[p]) ←
24         nxt[p][c] = cur;
25     if (p == -1) {
26         link[cur] = 0;
27         return;
28     }
29     int q = nxt[p][c];
30     if (len[p] + 1 == len[q]) {
31         link[cur] = q;
32         return;
33     }
34     int clone = sz++;
35     memcpy(nxt[clone], nxt[q], sizeof(nxt[q]));
36     len[clone] = len[p] + 1;
37     pos[clone] = pos[q];
38     link[clone] = link[q];
39     link[q] = link[cur] = clone;
40     for (; p != -1 && nxt[p][c] == q; p = link[p]) ←
41         nxt[p][c] = clone;
42 }
43
44 int n;
45 string s;
46 int l[MXN], r[MXN];
47 int e[MXN][SIGMA];
48
49 void getSufTree(string _s) {
50     memset(e, -1, sizeof(e));
51     s = _s;
52     n = s.length();
53     reverse(s.begin(), s.end());
54     init();
55     for (int i = 0; i < n; i++) add(s[i] - 'a');
56     reverse(s.begin(), s.end());
57     for (int i = 1; i < sz; i++) {
58         int j = link[i];
59         l[i] = n - pos[i] + len[j];
60         r[i] = n - pos[i] + len[i];
61         e[j][s[l[i]] - 'a'] = i;
62     }
63 }

```

```

36 int z = 0;
37 for (int i = 0; i < n; i++) {
38     int j = o[i];
39     if (j == n - 1) {
40         z = 0;
41     } else {
42         while (s[i + z] == s[p[j + 1] + z]) z++;
43     }
44     lcp[j] = z;
45     z = !!z;
46 }
47 }

```

## final/strings/duval.cpp

```

1 void duval(string s) {
2     int n = (int) s.length();
3     int i=0;
4     while (i < n) {
5         int j=i+1, k=i;
6         while (j < n && s[k] <= s[j]) {
7             if (s[k] < s[j])
8                 k = i;
9             else
10                ++k;
11            ++j;
12        }
13        while (i <= k) {
14            cout << s.substr(i, j-k) << ' ';
15            i += j - k;
16        }
17    }
18 }

```

## final/strings/sufArray.cpp

```

1 int n;
2 char s[N];
3 int p[N], pn[N], c[N], cn[N], cnt[N];
4 int o[N];
5 int lcp[N];
6
7 void build() {
8     for (int i = 0; i < 256; i++) cnt[i] = 0;
9     for (int i = 0; i < n; i++) cnt[(int)s[i]]++;
10    for (int i = 1; i < 256; i++) cnt[i] += cnt[i - ←
11        1];
12    for (int i = n - 1; i >= 0; i--) p[--cnt[(int)s[i] ←
13        ]] = i;
14    int cl = 1;
15    c[p[0]] = 0;
16    for (int i = 1; i < n; i++) {
17        cl += s[p[i]] != s[p[i - 1]];
18        c[p[i]] = cl - 1;
19    }
20
21    for (int len = 1; len < n; len <= 1) {
22        for (int i = 0; i < cl; i++) cnt[i] = 0;
23        for (int i = 0; i < n; i++) cnt[c[i]]++;
24        for (int i = 1; i < cl; i++) cnt[i] += cnt[i - ←
25            1];
26        for (int i = 0; i < n; i++) pn[i] = (p[i] - len ←
27            + n) % n;
28        for (int i = n - 1; i >= 0; i--) p[--cnt[c[pn[i] ←
29            ]]] = pn[i];
30        cl = 1;
31        cn[p[0]] = 0;
32        for (int i = 1; i < n; i++) {
33            cl += c[p[i]] != c[p[i - 1]] || c[(p[i] + len) ←
34                % n] != c[(p[i - 1] + len) % n];
35            cn[p[i]] = cl - 1;
36        }
37        for (int i = 0; i < n; i++) c[i] = cn[i];
38    }
39
40    for (int i = 0; i < n; i++) o[p[i]] = i;
41 }

```

## final/graphs/centroid.cpp

```

1 // original author: burunduk1, rewritten by me (←
2 // !!! warning !!! this code is not tested well
3 const int N = 1e5, K = 17;
4
5 int pivot, level[N], parent[N];
6 vector<int> v[N];
7
8 int get_pivot( int x, int xx, int n ) {
9     int size = 1;
10    for ( int y : v[x] )
11    {
12        if ( y != xx && level[y] == -1 ) size += get_pivot(
13            y, x, n );
14    }
15    if ( pivot == -1 && ( size * 2 >= n || xx == -1 ) ) ←
16        pivot = x;
17    return size;
18 }
19
20 void build( int x, int xx, int dep, int size ) {
21     assert( dep < K );
22     pivot = -1;
23     get_pivot( x, -1, size );
24     x = pivot;
25     level[x] = dep, parent[x] = xx;
26     for ( int y : v[x] ) if ( level[y] == -1 )
27     {
28         build( y, x, dep + 1, size / 2 );
29     }
30 }

```

## final/graphs/dominatorTree.cpp

```

1 namespace domtree {
2     const int K = 18;
3     const int N = 1 << K;
4
5     int n, root;
6     vector<int> e[N], g[N];
7     int sdom[N], dom[N];
8     int p[N][K], h[N], pr[N];
9     int in[N], out[N], tmr, rev[N];
10
11     void init( int _n, int _root ) {
12         n = _n;
13         root = _root;
14         tmr = 0;
15         for ( int i = 0; i < n; i++ ) {
16             e[i].clear();
17             g[i].clear();
18             in[i] = -1;
19         }
20     }
21
22     void addEdge( int u, int v ) {
23         e[u].push_back( v );
24         g[v].push_back( u );
25     }
26
27     void dfs( int v ) {
28         in[v] = tmr++;
29         for ( int to : e[v] ) {
30             if ( in[to] != -1 ) continue;
31             pr[to] = v;
32             dfs( to );
33         }
34         out[v] = tmr - 1;
35     }
36
37     int lca( int u, int v ) {
38         if ( h[u] < h[v] ) swap( u, v );
39         for ( int i = 0; i < K; i++ ) if ( (h[u] - h[v]) & ←
40             (1 << i) ) u = p[u][i];
41         if ( u == v ) return u;
42         for ( int i = K - 1; i >= 0; i-- ) {
43             if ( p[u][i] != p[v][i] ) {
44                 u = p[u][i];
45                 v = p[v][i];
46             }
47         }
48         return p[u][0];
49     }
50 }

```

```

48 }
49
50 void solve( int _n, int _root, vector<pair<int, int ←
51 >> _edges ) {
52     init( _n, _root );
53     for ( auto ed : _edges ) addEdge( ed.first, ed. ←
54         second );
55
56     dfs( root );
57     for ( int i = 0; i < n; i++ ) if ( in[i] != -1 ) rev ←
58         [in[i]] = i;
59     segtree tr( tmr ); // a[i] := min( a[i], x ) and return ←
60         a[i]
61     for ( int i = tmr - 1; i >= 0; i-- ) {
62         int v = rev[i];
63         int cur = i;
64         for ( int to : g[v] ) {
65             if ( in[to] == -1 ) continue;
66             if ( in[to] < in[v] ) cur = min( cur, in[to] );
67             else cur = min( cur, tr.get( in[to] ) );
68         }
69         sdom[v] = rev[cur];
70         tr.upd( in[v], out[v], in[sdom[v]] );
71     }
72     for ( int i = 0; i < tmr; i++ ) {
73         int v = rev[i];
74         if ( i == 0 ) {
75             dom[v] = v;
76             h[v] = 0;
77         } else {
78             dom[v] = lca( sdom[v], pr[v] );
79             h[v] = h[dom[v]] + 1;
80         }
81         p[v][0] = dom[v];
82         for ( int j = 1; j < K; j++ ) p[v][j] = p[p[v][j ←
83             - 1][j - 1];
84     }
85     for ( int i = 0; i < n; i++ ) if ( in[i] == -1 ) dom ←
86         [i] = -1;
87 }
88 }

```

## final/graphs/generalMatching.cpp

```

1 //COPYPASTED FROM E-MAXX
2 namespace GeneralMatching {
3     const int MAXN = 256;
4     int n;
5     vector<int> g[MAXN];
6     int match[MAXN], p[MAXN], base[MAXN], q[MAXN];
7     bool used[MAXN], blossom[MAXN];
8
9     int lca( int a, int b ) {
10         bool used[MAXN] = { 0 };
11         for ( ;; ) {
12             a = base[a];
13             used[a] = true;
14             if ( match[a] == -1 ) break;
15             a = p[match[a]];
16         }
17         for ( ;; ) {
18             b = base[b];
19             if ( used[b] ) return b;
20             b = p[match[b]];
21         }
22     }
23
24     void mark_path( int v, int b, int children ) {
25         while ( base[v] != b ) {
26             blossom[base[v]] = blossom[base[match[v]]] = ←
27                 true;
28             p[v] = children;
29             children = match[v];
30             v = p[match[v]];
31         }
32     }
33
34     int find_path( int root ) {
35         memset( used, 0, sizeof used );
36         memset( p, -1, sizeof p );
37         for ( int i = 0; i < n; ++i )
38             base[i] = i;
39
40         used[root] = true;
41         int qh = 0, qt = 0;
42         q[qt++] = root;
43         while ( qh < qt ) {

```

```

43     int v = q[qh++];
44     for (size_t i=0; i<g[v].size(); ++i) {
45         int to = g[v][i];
46         if (base[v] == base[to] || match[v] == to) ←
47             continue;
48         if (to == root || (match[to] != -1 && p[←
49             match[to]] != -1)) {
50             int curbase = lca(v, to);
51             memset(blossom, 0, sizeof blossom);
52             mark_path(v, curbase, to);
53             mark_path(to, curbase, v);
54             for (int i=0; i<n; ++i)
55                 if (blossom[base[i]]) {
56                     base[i] = curbase;
57                     if (!used[i]) {
58                         used[i] = true;
59                         q[qt++] = i;
60                     }
61                 }
62             else if (p[to] == -1) {
63                 p[to] = v;
64                 if (match[to] == -1)
65                     return to;
66                 to = match[to];
67                 used[to] = true;
68                 q[qt++] = to;
69             }
70         }
71     }
72     return -1;
73 }
74
75 vector<pair<int, int>> solve(int _n, vector<pair<←
76     int, int>> edges) {
77     n = _n;
78     for (int i = 0; i < n; i++) g[i].clear();
79     for (auto o : edges) {
80         g[o.first].push_back(o.second);
81         g[o.second].push_back(o.first);
82     }
83     memset(match, -1, sizeof match);
84     for (int i=0; i<n; ++i) {
85         if (match[i] == -1) {
86             int v = find_path(i);
87             while (v != -1) {
88                 int pv = p[v], ppv = match[pv];
89                 match[v] = pv, match[pv] = v;
90                 v = ppv;
91             }
92         }
93     }
94     vector<pair<int, int>> ans;
95     for (int i = 0; i < n; i++) {
96         if (match[i] > i) {
97             ans.push_back(make_pair(i, match[i]));
98         }
99     }
100     return ans;
}

```

## final/graphs/heavyLight.cpp

```

1 namespace hld {
2     const int N = 1 << 17;
3     int par[N], heavy[N], h[N];
4     int root[N], pos[N];
5     int n;
6     vector<vector<int>> e;
7     segtree tree;
8
9     int dfs(int v) {
10         int sz = 1, mx = 0;
11         for (int to : e[v]) {
12             if (to == par[v]) continue;
13             par[to] = v;
14             h[to] = h[v] + 1;
15             int cur = dfs(to);
16             if (cur > mx) heavy[v] = to, mx = cur;
17             sz += cur;
18         }
19         return sz;
20     }
21
22     template <typename T>
23     void path(int u, int v, T op) {

```

```

24         for (; root[u] != root[v]; v = par[root[v]]) {
25             if (h[root[u]] > h[root[v]]) swap(u, v);
26             op(pos[root[v]], pos[v] + 1);
27         }
28         if (h[u] > h[v]) swap(u, v);
29         op(pos[u], pos[v] + 1);
30     }
31
32     void init(vector<vector<int>> _e) {
33         e = _e;
34         n = e.size();
35         tree = segtree(n);
36         memset(heavy, -1, sizeof(heavy[0]) * n);
37         par[0] = -1;
38         h[0] = 0;
39         dfs(0);
40         for (int i = 0, cpos = 0; i < n; i++) {
41             if (par[i] == -1 || heavy[par[i]] != i) {
42                 for (int j = i; j != -1; j = heavy[j]) {
43                     root[j] = i;
44                     pos[j] = cpos++;
45                 }
46             }
47         }
48     }
49
50     void add(int v, int x) {
51         tree.add(pos[v], x);
52     }
53
54     int get(int u, int v) {
55         int res = 0;
56         path(u, v, [&](int l, int r) {
57             res = max(res, tree.get(l, r));
58         });
59         return res;
60     }
61 }

```

## final/graphs/hungary.cpp

```

1 namespace hungary
2 {
3     const int N = 210;
4
5     int a[N][N];
6     int ans[N];
7
8     int calc(int n, int m)
9     {
10         ++n, ++m;
11         vi u(n), v(m), p(m), prev(m);
12         for (int i = 1; i < n; ++i)
13         {
14             p[0] = i;
15             int x = 0;
16             vi mn(m, inf);
17             vi was(m, 0);
18             while (p[x])
19             {
20                 was[x] = 1;
21                 int ii = p[x], dd = inf, y = 0;
22                 for (int j = 1; j < m; ++j) if (!was[j])
23                 {
24                     int cur = a[ii][j] - u[ii] - v[j];
25                     if (cur < mn[j]) mn[j] = cur, prev[j] = x;
26                     if (mn[j] < dd) dd = mn[j], y = j;
27                 }
28                 forn(j, m)
29                 {
30                     if (was[j]) u[p[j]] += dd, v[j] -= dd;
31                     else mn[j] -= dd;
32                 }
33                 x = y;
34             }
35             while (x)
36             {
37                 int y = prev[x];
38                 p[x] = p[y];
39                 x = y;
40             }
41         }
42         for (int j = 1; j < m; ++j)
43         {
44             ans[p[j]] = j;
45         }
46         return -v[0];

```

```

47 }
48 // HOW TO USE ::
49 // — set values to a[1..n][1..m] (n <= m)
50 // — run calc(n, m) to find MINIMUM
51 // — to restore permutation use ans[]
52 // — everything works on negative numbers
53 //
54 // !! i don't understand this code, it's ←
55 // copypasted from e-maxx (and rewrited by enot110←
56 )
57 }

```

## final/graphs/minCostNegCycle.cpp

```

1 struct Edge {
2     int from, to, cap, flow;
3     double cost;
4 };
5
6
7 struct Graph {
8     int n;
9     vector<Edge> edges;
10    vector<vector<int>> > e;
11
12    Graph(int _n) {
13        n = _n;
14        e.resize(n);
15    }
16
17    void addEdge(int from, int to, int cap, double ←
18        cost) {
19        e[from].push_back(edges.size());
20        edges.push_back({ from, to, cap, 0, cost });
21        e[to].push_back(edges.size());
22        edges.push_back({ to, from, 0, 0, -cost });
23    }
24
25    void maxflow() {
26        while (1) {
27            queue<int> q;
28            vector<int> d(n, INF);
29            vector<int> pr(n, -1);
30            q.push(0);
31            d[0] = 0;
32            while (!q.empty()) {
33                int v = q.front();
34                q.pop();
35                for (int i = 0; i < (int)e[v].size(); i++) {
36                    Edge cur = edges[e[v][i]];
37                    if (d[cur.to] > d[v] + 1 && cur.flow < cur.←
38                        .cap) {
39                        d[cur.to] = d[v] + 1;
40                        pr[cur.to] = e[v][i];
41                        q.push(cur.to);
42                    }
43                }
44                if (d[n - 1] == INF) break;
45                int v = n - 1;
46                while (v) {
47                    edges[pr[v]].flow++;
48                    edges[pr[v] ^ 1].flow--;
49                    v = edges[pr[v]].from;
50                }
51            }
52
53            bool findcycle() {
54                int iters = n;
55                vector<int> changed;
56                for (int i = 0; i < n; i++) changed.push_back(i)←
57                    ;
58                vector<vector<double>> d(iters + 1, vector<←
59                    double>(n, INF));
60                vector<vector<int>> p(iters + 1, vector<int>(n, ←
61                    -1));
62                d[0].assign(n, 0);
63                for (int it = 0; it < iters; it++) {
64                    d[it + 1] = d[it];
65                    vector<int> nchanged(n, 0);
66                    for (int v : changed) {
67                        for (int id : e[v]) {
68                            Edge cur = edges[id];
69                            if (d[it + 1][cur.to] > d[it][v] + cur.←
70                                cost && cur.flow < cur.cap) {

```

```

68                d[it + 1][cur.to] = d[it][v] + cur.cost;
69                p[it + 1][cur.to] = id;
70                nchanged[cur.to] = 1;
71            }
72        }
73    }
74    changed.clear();
75    for (int i = 0; i < n; i++) if (nchanged[i]) ←
76        changed.push_back(i);
77    if (changed.empty()) return 0;
78
79    int bestU = 0, bestK = 1;
80    double bestAns = INF;
81    for (int u = 0; u < n; u++) {
82        double curMax = -INF;
83        for (int k = 0; k < iters; k++) {
84            double curVal = (d[iters][u] - d[k][u]) / (←
85                iters - k);
86            curMax = max(curMax, curVal);
87        }
88        if (bestAns > curMax) {
89            bestAns = curMax;
90            bestU = u;
91        }
92    }
93    int v = bestU;
94    int it = iters;
95    vector<int> was(n, -1);
96    while (was[v] == -1) {
97        was[v] = it;
98        v = edges[p[it][v]].from;
99        it--;
100    }
101    int vv = v;
102    it = was[v];
103    double sum = 0;
104    do {
105        edges[p[it][v]].flow++;
106        sum += edges[p[it][v]].cost;
107        edges[p[it][v] ^ 1].flow--;
108        v = edges[p[it][v]].from;
109        it--;
110    } while (v != vv);
111    return 1;
112 }
113 };

```

## final/graphs/retro.cpp

```

1 namespace retro
2 {
3     const int N = 4e5 + 10;
4
5     vi v[N];
6     vi vrev[N];
7
8     void add(int x, int y)
9     {
10         v[x].pb(y);
11         vrev[y].pb(x);
12     }
13
14     const int UD = 0;
15     const int WIN = 1;
16     const int LOSE = 2;
17
18     int res[N];
19     int moves[N];
20     int deg[N];
21     int q[N], st, en;
22
23     void calc(int n)
24     {
25         forn(i, n) deg[i] = sz(v[i]);
26         st = en = 0;
27         forn(i, n) if (!deg[i])
28         {
29             q[en++] = i;
30             res[i] = LOSE;
31         }
32         while (st < en)
33         {
34             int x = q[st++];
35             for (int y : vrev[x])
36             {

```

```

37     if (res[y] == UD && (res[x] == LOSE || (--deg[
38         deg[y] == 0 && res[x] == WIN)))
39     {
40         res[y] = 3 - res[x];
41         moves[y] = moves[x] + 1;
42         q[en++] = y;
43     }
44 }
45 }
46 }

```

## final/graphs/smith.cpp

```

1  const int N = 1e5 + 10;
2
3  struct graph
4  {
5      int n;
6
7      vi v[N];
8      vi vrev[N];
9
10     void read()
11     {
12         int m;
13         scanf("%d%d", &n, &m);
14         forn(i, m)
15         {
16             int x, y;
17             scanf("%d%d", &x, &y);
18             --x, --y;
19             v[x].pb(y);
20             vrev[y].pb(x);
21         }
22     }
23
24     int deg[N], cnt[N], used[N], f[N];
25     int q[N], st, en;
26
27     set<int> s[N];
28
29     void calc()
30     {
31         forn(x, n) f[x] = -1, cnt[x] = 0;
32         int val = 0;
33         while (1)
34         {
35             st = en = 0;
36             forn(x, n)
37             {
38                 deg[x] = 0;
39                 used[x] = 0;
40                 for (int y : v[x]) if (f[y] == -1) deg[x]++;
41             }
42             forn(x, n) if (!deg[x] && f[x] == -1 && cnt[x] <= val)
43             {
44                 q[en++] = x;
45                 f[x] = val;
46             }
47             if (!en) break;
48             while (st < en)
49             {
50                 int x = q[st];
51                 st++;
52                 for (int y : vrev[x])
53                 {
54                     if (used[y] == 0 && f[y] == -1)
55                     {
56                         used[y] = 1;
57                         cnt[y]++;
58                         for (int z : vrev[y])
59                         {
60                             deg[z]--;
61                             if (f[z] == -1 && deg[z] == 0 && cnt[z] <= val)
62                             {
63                                 f[z] = val;
64                                 q[en++] = z;
65                             }
66                         }
67                     }
68                 }
69                 val++;
70             }
71         }

```

```

72     forn(x, n) eprintf("%d%c", f[x], " \n"[x + 1 == n]);
73     forn(x, n) if (f[x] == -1)
74     {
75         for (int y : v[x]) if (f[y] != -1) s[x].insert(f[y]);
76     }
77 }
78 g1, g2;
79
80 string get(int x, int y)
81 {
82     int f1 = g1.f[x], f2 = g2.f[y];
83     if (f1 == -1 && f2 == -1) return "draw";
84     if (f1 == -1) {
85         if (g1.s[x].count(f2)) return "first";
86         return "draw";
87     }
88     if (f2 == -1) {
89         if (g2.s[y].count(f1)) return "first";
90         return "draw";
91     }
92     if (f1 < f2) return "first";
93     return "second";
94 }

```

## final/graphs/mincut.cpp

```

1  const int MAXN = 500;
2  int n, g[MAXN][MAXN];
3  int best_cost = 1000000000;
4  vector<int> best_cut;
5
6  void mincut() {
7      vector<int> v[MAXN];
8      for (int i=0; i<n; ++i)
9          v[i].assign(1, i);
10     int w[MAXN];
11     bool exist[MAXN], in_a[MAXN];
12     memset(exist, true, sizeof exist);
13     for (int ph=0; ph<n-1; ++ph) {
14         memset(in_a, false, sizeof in_a);
15         memset(w, 0, sizeof w);
16         for (int it=0, prev; it<n-ph; ++it) {
17             int sel = -1;
18             for (int i=0; i<n; ++i)
19                 if (exist[i] && !in_a[i] && (sel == -1 || w[sel] < w[i]))
20                     sel = i;
21             if (it == n-ph-1) {
22                 if (w[sel] < best_cost)
23                     best_cost = w[sel], best_cut = v[sel];
24                 v[prev].insert(v[prev].end(), v[sel].begin(), v[sel].end());
25                 for (int i=0; i<n; ++i)
26                     g[prev][i] = g[i][prev] + g[sel][i];
27                 exist[sel] = false;
28             }
29             else {
30                 in_a[sel] = true;
31                 for (int i=0; i<n; ++i)
32                     w[i] += g[sel][i];
33                 prev = sel;
34             }
35         }
36     }
37 }

```

## final/graphs/twoChineseFast.cpp

```

1  namespace twoc {
2      struct Heap {
3          static Heap* null;
4          ll x, xadd;
5          int ver, h;
6          /* ANS */ int ei;
7          Heap *l, *r;
8          Heap(ll xx, int vv) : x(xx), xadd(0), ver(vv), h(1), l(null), r(null) {}
9          Heap(const char*) : x(0), xadd(0), ver(0), h(0), l(this), r(this) {}

```

```

10 void add(ll a) { x += a; xadd += a; }
11 void push() {
12     if (l != null) l->add(xadd);
13     if (r != null) r->add(xadd);
14     xadd = 0;
15 }
16 };
17 Heap *Heap::null = new Heap("wqeqw");
18 Heap* merge(Heap *l, Heap *r) {
19     if (l == Heap::null) return r;
20     if (r == Heap::null) return l;
21     l->push(); r->push();
22     if (l->x > r->x)
23         swap(l, r);
24     l->r = merge(l->r, r);
25     if (l->l->h < l->r->h)
26         swap(l->l, l->r);
27     l->h = l->r->h + 1;
28     return l;
29 }
30 Heap *pop(Heap *h) {
31     h->push();
32     return merge(h->l, h->r);
33 }
34 const int N = 666666;
35 struct DSU {
36     int p[N];
37     void init(int nn) { iota(p, p + nn, 0); }
38     int get(int x) { return p[x] == x ? x : p[x] = ←
39         get(p[x]); }
40     void merge(int x, int y) { p[get(y)] = get(x); }
41     dsu;
42     Heap *eb[N];
43     int n;
44     /* ANS */ struct Edge {
45     /* ANS */ int x, y;
46     /* ANS */ ll c;
47     /* ANS */ };
48     /* ANS */ vector<Edge> edges;
49     /* ANS */ int answer[N];
50     void init(int nn) {
51         n = nn;
52         dsu.init(n);
53         fill(eb, eb + n, Heap::null);
54         edges.clear();
55     }
56     void addEdge(int x, int y, ll c) {
57         Heap *h = new Heap(c, x);
58         /* ANS */ h->ei = sz(edges);
59         /* ANS */ edges.push_back({x, y, c});
60         eb[y] = merge(eb[y], h);
61     }
62     ll solve(int root = 0) {
63         ll ans = 0;
64         static int done[N], pv[N];
65         memset(done, 0, sizeof(int) * n);
66         done[root] = 1;
67         int tt = 1;
68         /* ANS */ int cnum = 0;
69         /* ANS */ static vector<ipair> eout[N];
70         /* ANS */ for (int i = 0; i < n; ++i) eout[i].←
71             clear();
72         for (int i = 0; i < n; ++i) {
73             int v = dsu.get(i);
74             if (done[v])
75                 continue;
76             ++tt;
77             while (true) {
78                 done[v] = tt;
79                 int nv = -1;
80                 while (eb[v] != Heap::null) {
81                     nv = dsu.get(eb[v]->ver);
82                     if (nv == v) {
83                         eb[v] = pop(eb[v]);
84                         continue;
85                     }
86                     break;
87                 }
88                 if (nv == -1)
89                     return LINF;
90                 ans += eb[v]->x;
91                 eb[v]->add(-eb[v]->x);
92                 /* ANS */ int ei = eb[v]->ei;
93                 /* ANS */ eout[edges[ei].x].push_back({++←
94                     cnum, ei});
95                 if (!done[nv]) {
96                     pv[v] = nv;
97                     v = nv;
98                     continue;
99                 }
100                 if (done[nv] != tt)
101                     break;
102                 int v1 = nv;

```

```

100 while (v1 != v) {
101     eb[v] = merge(eb[v], eb[v1]);
102     dsu.merge(v, v1);
103     v1 = dsu.get(pv[v1]);
104 }
105 }
106 }
107 /* ANS */ memset(answer, -1, sizeof(int) * n);
108 /* ANS */ answer[root] = 0;
109 /* ANS */ set<ipair> es(all(eout[root]));
110 /* ANS */ while (!es.empty()) {
111     /* ANS */ auto it = es.begin();
112     /* ANS */ int ei = it->second;
113     /* ANS */ es.erase(it);
114     /* ANS */ int nv = edges[ei].y;
115     /* ANS */ if (answer[nv] != -1)
116         continue;
117     /* ANS */ answer[nv] = ei;
118     /* ANS */ es.insert(all(eout[nv]));
119 }
120 /* ANS */ answer[root] = -1;
121 return ans;
122 }
123 /* Usage: twoc::init(vertex_count);
124 * twoc::addEdge(v1, v2, cost);
125 * twoc::solve(root); - returns cost or LINF
126 * twoc::answer contains index of ingoing edge for←
127 each vertex
128 */

```

## final/graphs/linkcut.cpp

```

1 #include <iostream>
2 #include <cstdio>
3 #include <cassert>
4
5 using namespace std;
6
7 // BEGIN ALGO
8
9 const int MAXN = 110000;
10
11 typedef struct _node {
12     _node *l, *r, *p, *pp;
13     int size; bool rev;
14     _node();
15     explicit _node(nullptr_t) {
16         l = r = p = pp = this;
17         size = rev = 0;
18     }
19     void push() {
20         if (rev) {
21             l->rev ^= 1; r->rev ^= 1;
22             rev = 0; swap(l, r);
23         }
24     }
25     void update();
26 } * node;
27 node None = new _node(nullptr);
28 node v2n[MAXN];
29 _node::_node() {
30     l = r = p = pp = None;
31     size = 1; rev = false;
32 }
33 void _node::update() {
34     size = (this != None) + l->size + r->size;
35     l->p = r->p = this;
36 }
37 void rotate(node v) {
38     assert(v != None && v->p != None);
39     assert(!v->rev); assert(!v->p->rev);
40     node u = v->p;
41     if (v == u->l)
42         u->l = v->r, v->r = u;
43     else
44         u->r = v->l, v->l = u;
45     swap(u->p, v->p); swap(v->pp, u->pp);
46     if (v->p != None) {
47         assert(v->p->l == u || v->p->r == u);
48         if (v->p->r == u) v->p->r = v;
49         else v->p->l = v;
50     }
51     u->update(); v->update();
52 }
53 void bigRotate(node v) {
54     assert(v->p != None);

```



```

55 v->p->p->push();
56 v->p->push();
57 v->push();
58 if (v->p->p != None){
59     if ((v->p->l == v) ^ (v->p->p->r == v->p))
60         rotate(v->p);
61     else
62         rotate(v);
63 }
64 rotate(v);
65 }
66 inline void Splay(node v){
67     while (v->p != None) bigRotate(v);
68 }
69 inline void splitAfter(node v){
70     v->push();
71     Splay(v);
72     v->r->p = None;
73     v->r->pp = v;
74     v->r = None;
75     v->update();
76 }
77 void expose(int x){
78     node v = v2n[x];
79     splitAfter(v);
80     while (v->pp != None){
81         assert(v->p == None);
82         splitAfter(v->pp);
83         assert(v->pp->r == None);
84         assert(v->pp->p == None);
85         assert(!v->pp->rev);
86         v->pp->r = v;
87         v->pp->update();
88         v = v->pp;
89         v->r->pp = None;
90     }
91     assert(v->p == None);
92     Splay(v2n[x]);
93 }
94 inline void makeRoot(int x){
95     expose(x);
96     assert(v2n[x]->p == None);
97     assert(v2n[x]->pp == None);
98     assert(v2n[x]->r == None);
99     v2n[x]->rev ^= 1;
100 }
101 inline void link(int x,int y){
102     makeRoot(x); v2n[x]->pp = v2n[y];
103 }
104 inline void cut(int x,int y){
105     expose(x);
106     Splay(v2n[y]);
107     if (v2n[y]->pp != v2n[x]){
108         swap(x,y);
109         expose(x);
110         Splay(v2n[y]);
111         assert(v2n[y]->pp == v2n[x]);
112     }
113     v2n[y]->pp = None;
114 }
115 inline int get(int x,int y){
116     if (x == y) return 0;
117     makeRoot(x);
118     expose(y); expose(x);
119     Splay(v2n[y]);
120     if (v2n[y]->pp != v2n[x]) return -1;
121     return v2n[y]->size;
122 }
123 // END ALGO
124
125 _node mem[MAXN];
126
127 int main(){
128     freopen("linkcut.in","r",stdin);
129     freopen("linkcut.out","w",stdout);
130
131     int n,m;
132     scanf("%d %d",&n,&m);
133
134     for (int i = 0; i < n; i++){
135         v2n[i] = &mem[i];
136     }
137
138     for (int i = 0; i < m; i++){
139         int a,b;
140         if (scanf(" link %d %d",&a,&b) == 2)
141             link(a-1,b-1);
142         else if (scanf(" cut %d %d",&a,&b) == 2)
143             cut(a-1,b-1);
144         else if (scanf(" get %d %d",&a,&b) == 2)
145             printf("%d\n",get(a-1,b-1));
146         else
147             assert(false);

```

```

148 }
149 return 0;
150 }

```

## final/graphs/chordaltree.cpp

```

1 void chordaltree(vector<vector<int>> e) {
2     int n = e.size();
3
4     vector<int> mark(n);
5     set<pair<int, int>> st;
6     for (int i = 0; i < n; i++) st.insert({-mark[i], i});
7
8     vector<int> vct(n);
9     vector<pair<int, int>> ted;
10    vector<vector<int>> who(n);
11    vector<vector<int>> verts(1);
12    vector<int> cliq(n, -1);
13    cliq.push_back(0);
14    vector<int> last(n + 1, n);
15    int prev = n + 1;
16    for (int i = n - 1; i >= 0; i--) {
17        int x = st.begin()->second;
18        st.erase(st.begin());
19        if (mark[x] <= prev) {
20            vector<int> cur = who[x];
21            cur.push_back(x);
22            verts.push_back(cur);
23            ted.push_back({cliq[last[x]], (int)verts.size()-1});
24        } else {
25            verts.back().push_back(x);
26        }
27        for (int y : e[x]) {
28            if (cliq[y] != -1) continue;
29            who[y].push_back(x);
30            st.erase({-mark[y], y});
31            mark[y]++;
32            st.insert({-mark[y], y});
33            last[y] = x;
34        }
35        prev = mark[x];
36        vct[i] = x;
37        cliq[x] = (int)verts.size() - 1;
38    }
39
40    int k = verts.size();
41    vector<int> pr(k);
42    vector<vector<int>> g(k);
43    for (auto o : ted) {
44        pr[o.second] = o.first;
45        g[o.first].push_back(o.second);
46    }
47 }

```

## final/graphs/minimization.cpp

```

1 namespace mimimi /* ^ ^ */ {
2     const int N = 100555;
3     const int S = 3;
4     int e[N][S];
5     int label[N];
6     vector<int> eb[N][S];
7     int ans[N];
8     void solve(int n) {
9         for (int i = 0; i < n; ++i)
10             for (int j = 0; j < S; ++j)
11                 eb[i][j].clear();
12         for (int i = 0; i < n; ++i)
13             for (int j = 0; j < S; ++j)
14                 eb[e[i][j]][j].push_back(i);
15         vector<unordered_set<int>> classes(*max_element(eb.begin(), eb.end(), [](const vector<int>& a, const vector<int>& b) { return a.size() < b.size(); }));
16         for (int i = 0; i < n; ++i)
17             classes[label[i]].insert(i);
18         for (int i = 0; i < sz(classes); ++i)
19             if (classes[i].empty()) {
20                 classes[i].swap(classes.back());
21                 classes.pop_back();
22                 --i;

```

```

23     }
24     for (int i = 0; i < sz(classes); ++i)
25         for (int v : classes[i])
26             ans[v] = i;
27     for (int i = 0; i < sz(classes); ++i)
28         for (int c = 0; c < S; ++c) {
29             unordered_map<int, unordered_set<int>> ←
involved;
30             for (int v : classes[i])
31                 for (int nv : eb[v][c])
32                     involved[ans[nv]].insert(nv);
33             for (auto &pp : involved) {
34                 int cl = pp.X;
35                 auto &cls = classes[cl];
36                 if (sz(pp.Y) == sz(cls))
37                     continue;
38                 for (int x : pp.Y)
39                     cls.erase(x);
40                 if (sz(cls) < sz(pp.Y))
41                     cls.swap(pp.Y);
42                 for (int x : pp.Y)
43                     ans[x] = sz(classes);
44                 classes.push_back(move(pp.Y));
45             }
46         }
47     }
48     /* Usage: initialize edges: e[vertex][character]
49                labels: label[vertex]
50                solve(n)
51                ans[] - classes
52     */
53 }

```

```

53         for (int to : e[i]) {
54             if (nd[to] > make_pair(d[i].first + w[to], ←
d[i].second + 1)) {
55                 nd[to] = make_pair(d[i].first + w[to], d←
[i].second + 1);
56                 pr[to] = i;
57             }
58         }
59     }
60     if (d == nd) break;
61     d = nd;
62 }
63 int v = -1;
64 for (int i = 0; i < m; i++) {
65     if ((d[i].first < INF && (type[i] & 2)) && (v ←
== -1 || d[i] < d[v])) v = i;
66 }
67 if (v == -1) break;
68 while (v != -1) {
69     sum += w[v];
70     taken[v] ^= 1;
71     v = pr[v];
72 }
73 ans[--cnt] = sum;
74 }

```

## final/graphs/matroidIntersection.cpp

```

1  // check(ctaken, 1) — first matroid
2  // check(ctaken, 2) — second matroid
3  vector<char> taken(m);
4  while (1) {
5      vector<vector<int>> e(m);
6      for (int i = 0; i < m; i++) {
7          for (int j = 0; j < m; j++) {
8              if (taken[i] && !taken[j]) {
9                  auto ctaken = taken;
10                 ctaken[i] = 0;
11                 ctaken[j] = 1;
12                 if (check(ctaken, 2)) {
13                     e[i].push_back(j);
14                 }
15             }
16             if (!taken[i] && taken[j]) {
17                 auto ctaken = taken;
18                 ctaken[i] = 1;
19                 ctaken[j] = 0;
20                 if (check(ctaken, 1)) {
21                     e[i].push_back(j);
22                 }
23             }
24         }
25     }
26     vector<int> type(m);
27     // 0 — cant, 1 — can in \2, 2 — can in \1
28     for (int i = 0; i < m; i++) {
29         if (!taken[i]) {
30             auto ctaken = taken;
31             ctaken[i] = 1;
32             if (check(ctaken, 2)) type[i] |= 1;
33         }
34         if (!taken[i]) {
35             auto ctaken = taken;
36             ctaken[i] = 1;
37             if (check(ctaken, 1)) type[i] |= 2;
38         }
39     }
40     vector<int> w(m);
41     for (int i = 0; i < m; i++) {
42         w[i] = taken[i] ? ed[i].c : -ed[i].c;
43     }
44     vector<pair<int, int>> d(m, {INF, 0});
45     for (int i = 0; i < m; i++) {
46         if (type[i] & 1) d[i] = {w[i], 0};
47     }
48     vector<int> pr(m, -1);
49     while (1) {
50         vector<pair<int, int>> nd = d;
51         for (int i = 0; i < m; i++) {
52             if (d[i].first == INF) continue;

```

```
dbl Simpson() { return (F(-1) + 4 * F(0) + F(1)) / 6;
} dbl Runge2() { return (F(sqrt(1.0 / 3)) + F(sqrt(1.0 /
3))) / 2; } dbl Runge3() { return (F(sqrt(3.0 / 5)) * 5 +
F(0) * 8 + F(sqrt(3.0 / 5)) * 5) / 18; }
```

Simpson и Runge2 – точны для полиномов степени  $\leq 3$   
Runge3 – точен для полиномов степени  $\leq 5$

Явный Рунге-Кутты четвертого порядка, ошибка  $O(h^4)$

```
y' = f(x, y) y_(n+1) = y_n + (k1 + 2 * k2 + 2 * k3 +
k4) * h / 6
```

```
k1 = f(xn, yn) k2 = f(xn + h/2, yn + h/2 * k1) k3 =
f(xn + h/2, yn + h/2 * k2) k4 = f(xn + h, yn + h * k3)
```

Методы Адамса-Башфорта

```
y_n+3 = y_n+2 + h * (23/12 * f(x_n+2, y_n+2)
- 4/3 * f(x_n+1, y_n+1) + 5/12 * f(x_n, y_n)) y_n+4
= y_n+3 + h * (55/24 * f(x_n+3, y_n+3) - 59/24
* f(x_n+2, y_n+2) + 37/24 * f(x_n+1, y_n+1) - 3/8
* f(x_n, y_n)) y_n+5 = y_n+4 + h * (1901/720 *
f(x_n+4, y_n+4) - 1387/360 * f(x_n+3, y_n+3) + 109/30
* f(x_n+2, y_n+2) - 637/360 * f(x_n+1, y_n+1) +
251/720 * f(x_n, y_n))
```

Извлечение корня по простому модулю (от Сережи) 3  
 $\leq p$ ,  $1 \leq a < p$ , найти  $x^2 = a$

1) Если  $a^{(p-1)/2} \neq 1$ , return -1 2) Выбрать случайный  $1 \leq i < p$  3)  $T(x) = (x+i)^{(p-1)/2} \bmod (x^2 - a) = bx + c$  4) Если  $b \neq 0$  то вернуть  $c/b$ , иначе к шагу 2)

Иногда вместо того чтобы считать первообразный у простого числа, можно написать чекер ответа и перебирать случайный первообразный.

Иногда можно представить ответ в виде многочлена и вместо подсчета самих  $k$ -тов посчитать значения и проинтерполировать

Лемма Бернсайда:

Группа  $G$  действует на множество  $X$  Тогда число классов эквивалентности  $= (\sum |f(g)| \text{ for } g \text{ in } G) / |G|$  где  $f(g) = \text{число } x \text{ (из } X) : g(x) = x$

Число простых быстрее  $O(n)$ :

$dp(n, k)$  – число чисел от 1 до  $n$  в которых все простые  $\geq p[k]$   
 $dp(n, 1) = n$   
 $dp(n, j) = dp(n, j+1) + dp(n / p[j], j)$ , т. е.  $dp(n, j+1) = dp(n, j) - dp(n / p[j], j)$

Если  $p[j], p[k] > \sqrt{n}$  то  $dp(n, j) + j = dp(n, k) + k$

Хуяришь все оптимайзы сверху, но не считаешь глубже  $dp(n, k)$ ,  $n < K$  Потом фенвиком+сортировкой подсчитываешь за  $(K+Q)\log$  все эти запросы Хуяришь во второй раз, но на этот раз берешь прекальканные значения

Если  $\sqrt{n} < p[k] < n$  то (число простых до  $n$ )  $= dp(n, k) + k - 1$

$\sum_{k=1..n} k^2 = n(n+1)(2n+1)/6$

$\sum_{k=1..n} k^3 = n^2(n+1)^2/4$

Чиселки:

Фибоначчи 45: 1134903170 46: 1836311903  
47: 2971215073 91: 4660046610375530309 92:  
7540113804746346429 93: 12200160415121876738

Числа с кучей делителей 20:  $d(12)=6$  50:  $d(48)=10$   
100:  $d(60)=12$  1000:  $d(840)=32$   $10^4$ :  $d(9240)=64$   $10^5$ :  
 $d(83160)=128$   $10^6$ :  $d(720720)=240$   $10^7$ :  $d(8648640)=448$   
 $10^8$ :  $d(91891800)=768$   $10^9$ :  $d(931170240)=1344$   $10^{11}$ :  
 $d(97772875200)=4032$   $10^{12}$ :  $d(963761198400)=6720$   
 $10^{15}$ :  $d(866421317361600)=26880$   $10^{18}$ :  
 $d(897612484786617600)=103680$

Bell numbers: 0:1, 1:1, 2:2, 3:5, 4:15, 5:52, 6:203, 7:877, 8:4140, 9:21147, 10:115975, 11:678570, 12:4213597, 13:27644437, 14:190899322, 15:1382958545, 16:10480142147, 17:82864869804, 18:682076806159, 19:5832742205057, 20:51724158235372, 21:474869816156751, 22:4506715738447323, 23:44152005855084346

Catalan numbers: 0:1, 1:1, 2:2, 3:5, 4:14, 5:42, 6:132, 7:429, 8:1430, 9:4862, 10:16796, 11:58786, 12:208012, 13:742900, 14:2674440, 15:9694845, 16:35357670, 17:129644790, 18:477638700, 19:1767263190, 20:6564120420, 21:24466267020, 22:91482563640, 23:343059613650, 24:1289904147324, 25:4861946401452

Partitions numbers: 0:1, 1:1, 2:2, 3:3, 4:5, 5:7, 6:11, 7:15, 8:22, 9:30, 10:42, 20:627, 30:5604, 40:37338, 50:204226, 60:966467, 70:4087968, 80:15796476, 90:56634173, 100:190569292

$\prod_{k=1..+\infty} (1-x^k) = \sum_{q=-\infty..+\infty} (-1)^q x^{((3q^2-2q)/2)}$

## Table of Integrals\*

## Basic Forms

$$\int x^n dx = \frac{1}{n+1} x^{n+1} \quad (1)$$

$$\int \frac{1}{x} dx = \ln |x| \quad (2)$$

$$\int u dv = uv - \int v du \quad (3)$$

$$\int \frac{1}{ax+b} dx = \frac{1}{a} \ln |ax+b| \quad (4)$$

## Integrals of Rational Functions

$$\int \frac{1}{(x+a)^2} dx = -\frac{1}{x+a} \quad (5)$$

$$\int (x+a)^n dx = \frac{(x+a)^{n+1}}{n+1}, n \neq -1 \quad (6)$$

$$\int x(x+a)^n dx = \frac{(x+a)^{n+1}((n+1)x-a)}{(n+1)(n+2)} \quad (7)$$

$$\int \frac{1}{1+x^2} dx = \tan^{-1} x \quad (8)$$

$$\int \frac{1}{a^2+x^2} dx = \frac{1}{a} \tan^{-1} \frac{x}{a} \quad (9)$$

$$\int \frac{x}{a^2+x^2} dx = \frac{1}{2} \ln |a^2+x^2| \quad (10)$$

$$\int \frac{x^2}{a^2+x^2} dx = x - a \tan^{-1} \frac{x}{a} \quad (11)$$

$$\int \frac{x^3}{a^2+x^2} dx = \frac{1}{2} x^2 - \frac{1}{2} a^2 \ln |a^2+x^2| \quad (12)$$

$$\int \frac{1}{ax^2+bx+c} dx = \frac{2}{\sqrt{4ac-b^2}} \tan^{-1} \frac{2ax+b}{\sqrt{4ac-b^2}} \quad (13)$$

$$\int \frac{1}{(x+a)(x+b)} dx = \frac{1}{b-a} \ln \frac{a+x}{b+x}, a \neq b \quad (14)$$

$$\int \frac{x}{(x+a)^2} dx = \frac{a}{a+x} + \ln |a+x| \quad (15)$$

$$\int \frac{x}{ax^2+bx+c} dx = \frac{1}{2a} \ln |ax^2+bx+c| - \frac{b}{a\sqrt{4ac-b^2}} \tan^{-1} \frac{2ax+b}{\sqrt{4ac-b^2}} \quad (16)$$

## Integrals with Roots

$$\int \sqrt{x-ax} dx = \frac{2}{3} (x-a)^{3/2} \quad (17)$$

$$\int \frac{1}{\sqrt{x \pm a}} dx = 2\sqrt{x \pm a} \quad (18)$$

$$\int \frac{1}{\sqrt{a-x}} dx = -2\sqrt{a-x} \quad (19)$$

$$\int x\sqrt{x-ax} dx = \frac{2}{3} a(x-a)^{3/2} + \frac{2}{5} (x-a)^{5/2} \quad (20)$$

$$\int \sqrt{ax+bdx} = \left( \frac{2b}{3a} + \frac{2x}{3} \right) \sqrt{ax+b} \quad (21)$$

$$\int (ax+b)^{3/2} dx = \frac{2}{5a} (ax+b)^{5/2} \quad (22)$$

$$\int \frac{x}{\sqrt{x \pm a}} dx = \frac{2}{3} (x \mp 2a) \sqrt{x \pm a} \quad (23)$$

$$\int \sqrt{\frac{x}{a-x}} dx = -\sqrt{x(a-x)} - a \tan^{-1} \frac{\sqrt{x(a-x)}}{x-a} \quad (24)$$

$$\int \sqrt{\frac{x}{a+x}} dx = \sqrt{x(a+x)} - a \ln [\sqrt{x} + \sqrt{x+a}] \quad (25)$$

$$\int x\sqrt{ax+bdx} = \frac{2}{15a^2} (-2b^2 + abx + 3a^2x^2) \sqrt{ax+b} \quad (26)$$

$$\int \sqrt{x(ax+b)} dx = \frac{1}{4a^{3/2}} \left[ (2ax+b) \sqrt{ax(ax+b)} - b^2 \ln |a\sqrt{x} + \sqrt{a(ax+b)}| \right] \quad (27)$$

$$\int \sqrt{x^3(ax+b)} dx = \left[ \frac{b}{12a} - \frac{b^2}{8a^2x} + \frac{x}{3} \right] \sqrt{x^3(ax+b)} + \frac{b^3}{8a^{5/2}} \ln |a\sqrt{x} + \sqrt{a(ax+b)}| \quad (28)$$

$$\int \sqrt{x^2 \pm a^2} dx = \frac{1}{2} x \sqrt{x^2 \pm a^2} \pm \frac{1}{2} a^2 \ln |x + \sqrt{x^2 \pm a^2}| \quad (29)$$

$$\int \sqrt{a^2 - x^2} dx = \frac{1}{2} x \sqrt{a^2 - x^2} + \frac{1}{2} a^2 \tan^{-1} \frac{x}{\sqrt{a^2 - x^2}} \quad (30)$$

$$\int x\sqrt{x^2 \pm a^2} dx = \frac{1}{3} (x^2 \pm a^2)^{3/2} \quad (31)$$

$$\int \frac{1}{\sqrt{x^2 \pm a^2}} dx = \ln |x + \sqrt{x^2 \pm a^2}| \quad (32)$$

$$\int \frac{1}{\sqrt{a^2 - x^2}} dx = \sin^{-1} \frac{x}{a} \quad (33)$$

$$\int \frac{x}{\sqrt{x^2 \pm a^2}} dx = \sqrt{x^2 \pm a^2} \quad (34)$$

$$\int \frac{x}{\sqrt{a^2 - x^2}} dx = -\sqrt{a^2 - x^2} \quad (35)$$

$$\int \frac{x^2}{\sqrt{x^2 \pm a^2}} dx = \frac{1}{2} x \sqrt{x^2 \pm a^2} \mp \frac{1}{2} a^2 \ln |x + \sqrt{x^2 \pm a^2}| \quad (36)$$

$$\int \sqrt{ax^2+bx+cdx} = \frac{b+2ax}{4a} \sqrt{ax^2+bx+c} + \frac{4ac-b^2}{8a^{3/2}} \ln |2ax+b+2\sqrt{a(ax^2+bx+c)}| \quad (37)$$

$$\int x\sqrt{ax^2+bx+c} = \frac{1}{48a^{5/2}} \left( 2\sqrt{a}\sqrt{ax^2+bx+c} \times (-3b^2+2abx+8a(c+ax^2)) + 3(b^3-4abc) \ln |b+2ax+2\sqrt{a}\sqrt{ax^2+bx+c}| \right) \quad (38)$$

$$\int \frac{1}{\sqrt{ax^2+bx+c}} dx = \frac{1}{\sqrt{a}} \ln |2ax+b+2\sqrt{a(ax^2+bx+c)}| \quad (39)$$

$$\int \frac{x}{\sqrt{ax^2+bx+c}} dx = \frac{1}{a} \sqrt{ax^2+bx+c} - \frac{b}{2a^{3/2}} \ln |2ax+b+2\sqrt{a(ax^2+bx+c)}| \quad (40)$$

$$\int \frac{dx}{(a^2+x^2)^{3/2}} = \frac{x}{a^2\sqrt{a^2+x^2}} \quad (41)$$

## Integrals with Logarithms

$$\int \ln ax dx = x \ln ax - x \quad (42)$$

$$\int \frac{\ln ax}{x} dx = \frac{1}{2} (\ln ax)^2 \quad (43)$$

$$\int \ln(ax+b) dx = \left( x + \frac{b}{a} \right) \ln(ax+b) - x, a \neq 0 \quad (44)$$

$$\int \ln(x^2+a^2) dx = x \ln(x^2+a^2) + 2a \tan^{-1} \frac{x}{a} - 2x \quad (45)$$

$$\int \ln(x^2-a^2) dx = x \ln(x^2-a^2) + a \ln \frac{x+a}{x-a} - 2x \quad (46)$$

$$\int \ln(ax^2+bx+c) dx = \frac{1}{a} \sqrt{4ac-b^2} \tan^{-1} \frac{2ax+b}{\sqrt{4ac-b^2}} - 2x + \left( \frac{b}{2a} + x \right) \ln(ax^2+bx+c) \quad (47)$$

$$\int x \ln(ax+b) dx = \frac{bx}{2a} - \frac{1}{4} x^2 + \frac{1}{2} \left( x^2 - \frac{b^2}{a^2} \right) \ln(ax+b) \quad (48)$$

$$\int x \ln(a^2-b^2x^2) dx = -\frac{1}{2} x^2 + \frac{1}{2} \left( x^2 - \frac{a^2}{b^2} \right) \ln(a^2-b^2x^2) \quad (49)$$

## Integrals with Exponentials

$$\int e^{ax} dx = \frac{1}{a} e^{ax} \quad (50)$$

$$\int \sqrt{x} e^{ax} dx = \frac{1}{a} \sqrt{x} e^{ax} + \frac{i\sqrt{\pi}}{2a^{3/2}} \operatorname{erf}(i\sqrt{ax}), \text{ where } \operatorname{erf}(x) = \frac{2}{\sqrt{\pi}} \int_0^x e^{-t^2} dt \quad (51)$$

$$\int x e^x dx = (x-1)e^x \quad (52)$$

$$\int x e^{ax} dx = \left( \frac{x}{a} - \frac{1}{a^2} \right) e^{ax} \quad (53)$$

$$\int x^2 e^x dx = (x^2 - 2x + 2) e^x \quad (54)$$

$$\int x^2 e^{ax} dx = \left( \frac{x^2}{a} - \frac{2x}{a^2} + \frac{2}{a^3} \right) e^{ax} \quad (55)$$

$$\int x^3 e^x dx = (x^3 - 3x^2 + 6x - 6) e^x \quad (56)$$

$$\int x^n e^{ax} dx = \frac{x^n e^{ax}}{a} - \frac{n}{a} \int x^{n-1} e^{ax} dx \quad (57)$$

$$\int x^n e^{ax} dx = \frac{(-1)^n}{a^{n+1}} \Gamma[1+n, -ax], \text{ where } \Gamma(a, x) = \int_x^\infty t^{a-1} e^{-t} dt \quad (58)$$

$$\int e^{ax^2} dx = -\frac{i\sqrt{\pi}}{2\sqrt{a}} \operatorname{erf}(i\sqrt{a}x) \quad (59)$$

$$\int e^{-ax^2} dx = \frac{\sqrt{\pi}}{2\sqrt{a}} \operatorname{erf}(x\sqrt{a}) \quad (60)$$

$$\int x e^{-ax^2} dx = -\frac{1}{2a} e^{-ax^2} \quad (61)$$

$$\int x^2 e^{-ax^2} dx = \frac{1}{4} \sqrt{\frac{\pi}{a^3}} \operatorname{erf}(x\sqrt{a}) - \frac{x}{2a} e^{-ax^2} \quad (62)$$

\*© 2014. From <http://integral-table.com>, last revised June 14, 2014. This material is provided as is without warranty or representation about the accuracy, correctness or suitability of the material for any purpose, and is licensed under the Creative Commons Attribution-NonCommercial-ShareAlike 3.0 United States License. To view a copy of this license, visit <http://creativecommons.org/licenses/by-nc-sa/3.0/> or send a letter to Creative Commons, 171 Second Street, Suite 300, San Francisco, California, 94105, USA.

**Integrals with Trigonometric Functions**

$$\int \sin ax dx = -\frac{1}{a} \cos ax \quad (63)$$

$$\int \sin^2 ax dx = \frac{x}{2} - \frac{\sin 2ax}{4a} \quad (64)$$

$$\int \sin^n ax dx = -\frac{1}{a} \cos ax {}_2F_1 \left[ \frac{1}{2}, \frac{1-n}{2}, \frac{3}{2}, \cos^2 ax \right] \quad (65)$$

$$\int \sin^3 ax dx = -\frac{3 \cos ax}{4a} + \frac{\cos 3ax}{12a} \quad (66)$$

$$\int \cos ax dx = \frac{1}{a} \sin ax \quad (67)$$

$$\int \cos^2 ax dx = \frac{x}{2} + \frac{\sin 2ax}{4a} \quad (68)$$

$$\int \cos^p ax dx = -\frac{1}{a(1+p)} \cos^{1+p} ax \times {}_2F_1 \left[ \frac{1+p}{2}, \frac{1}{2}, \frac{3+p}{2}, \cos^2 ax \right] \quad (69)$$

$$\int \cos^3 ax dx = \frac{3 \sin ax}{4a} + \frac{\sin 3ax}{12a} \quad (70)$$

$$\int \cos ax \sin bxdx = \frac{\cos[(a-b)x]}{2(a-b)} - \frac{\cos[(a+b)x]}{2(a+b)}, a \neq b \quad (71)$$

$$\int \sin^2 ax \cos bxdx = -\frac{\sin[(2a-b)x]}{4(2a-b)} + \frac{\sin bx}{2b} - \frac{\sin[(2a+b)x]}{4(2a+b)} \quad (72)$$

$$\int \sin^2 x \cos x dx = \frac{1}{3} \sin^3 x \quad (73)$$

$$\int \cos^2 ax \sin bxdx = \frac{\cos[(2a-b)x]}{4(2a-b)} - \frac{\cos bx}{2b} - \frac{\cos[(2a+b)x]}{4(2a+b)} \quad (74)$$

$$\int \cos^2 ax \sin ax dx = -\frac{1}{3a} \cos^3 ax \quad (75)$$

$$\int \sin^2 ax \cos^2 bxdx = \frac{x}{4} - \frac{\sin 2ax}{8a} - \frac{\sin[2(a-b)x]}{16(a-b)} + \frac{\sin 2bx}{8b} - \frac{\sin[2(a+b)x]}{16(a+b)} \quad (76)$$

$$\int \sin^2 ax \cos^2 ax dx = \frac{x}{8} - \frac{\sin 4ax}{32a} \quad (77)$$

$$\int \tan ax dx = -\frac{1}{a} \ln \cos ax \quad (78)$$

$$\int \tan^2 ax dx = -x + \frac{1}{a} \tan ax \quad (79)$$

$$\int \tan^n ax dx = \frac{\tan^{n+1} ax}{a(1+n)} \times {}_2F_1 \left( \frac{n+1}{2}, 1, \frac{n+3}{2}, -\tan^2 ax \right) \quad (80)$$

$$\int \tan^3 ax dx = \frac{1}{a} \ln \cos ax + \frac{1}{2a} \sec^2 ax \quad (81)$$

$$\int \sec x dx = \ln |\sec x + \tan x| = 2 \tanh^{-1} \left( \tan \frac{x}{2} \right) \quad (82)$$

$$\int \sec^2 ax dx = \frac{1}{a} \tan ax \quad (83)$$

$$\int \sec^3 x dx = \frac{1}{2} \sec x \tan x + \frac{1}{2} \ln |\sec x + \tan x| \quad (84)$$

$$\int \sec x \tan x dx = \sec x \quad (85)$$

$$\int \sec^2 x \tan x dx = \frac{1}{2} \sec^2 x \quad (86)$$

$$\int \sec^n x \tan x dx = \frac{1}{n} \sec^n x, n \neq 0 \quad (87)$$

$$\int \csc x dx = \ln \left| \tan \frac{x}{2} \right| = \ln |\csc x - \cot x| + C \quad (88)$$

$$\int \csc^2 ax dx = -\frac{1}{a} \cot ax \quad (89)$$

$$\int \csc^3 x dx = -\frac{1}{2} \cot x \csc x + \frac{1}{2} \ln |\csc x - \cot x| \quad (90)$$

$$\int \csc^n x \cot x dx = -\frac{1}{n} \csc^n x, n \neq 0 \quad (91)$$

$$\int \sec x \csc x dx = \ln |\tan x| \quad (92)$$

**Products of Trigonometric Functions and Monomials**

$$\int x \cos x dx = \cos x + x \sin x \quad (93)$$

$$\int x \cos ax dx = \frac{1}{a^2} \cos ax + \frac{x}{a} \sin ax \quad (94)$$

$$\int x^2 \cos x dx = 2x \cos x + (x^2 - 2) \sin x \quad (95)$$

$$\int x^2 \cos ax dx = \frac{2x \cos ax}{a^2} + \frac{a^2 x^2 - 2}{a^3} \sin ax \quad (96)$$

$$\int x^n \cos x dx = -\frac{1}{2} (i)^{n+1} [\Gamma(n+1, -ix) + (-1)^n \Gamma(n+1, ix)] \quad (97)$$

$$\int x^n \cos ax dx = \frac{1}{2} (ia)^{1-n} [(-1)^n \Gamma(n+1, -iax) - \Gamma(n+1, iax)] \quad (98)$$

$$\int x \sin x dx = -x \cos x + \sin x \quad (99)$$

$$\int x \sin ax dx = -\frac{x \cos ax}{a} + \frac{\sin ax}{a^2} \quad (100)$$

$$\int x^2 \sin x dx = (2 - x^2) \cos x + 2x \sin x \quad (101)$$

$$\int x^2 \sin ax dx = \frac{2 - a^2 x^2}{a^3} \cos ax + \frac{2x \sin ax}{a^2} \quad (102)$$

$$\int x^n \sin x dx = -\frac{1}{2} (i)^n [\Gamma(n+1, -ix) - (-1)^n \Gamma(n+1, -ix)] \quad (103)$$

**Products of Trigonometric Functions and Exponentials**

$$\int e^x \sin x dx = \frac{1}{2} e^x (\sin x - \cos x) \quad (104)$$

$$\int e^{bx} \sin ax dx = \frac{1}{a^2 + b^2} e^{bx} (b \sin ax - a \cos ax) \quad (105)$$

$$\int e^x \cos x dx = \frac{1}{2} e^x (\sin x + \cos x) \quad (106)$$

$$\int e^{bx} \cos ax dx = \frac{1}{a^2 + b^2} e^{bx} (a \sin ax + b \cos ax) \quad (107)$$

$$\int x e^x \sin x dx = \frac{1}{2} e^x (\cos x - x \cos x + x \sin x) \quad (108)$$

$$\int x e^x \cos x dx = \frac{1}{2} e^x (x \cos x - \sin x + x \sin x) \quad (109)$$

**Integrals of Hyperbolic Functions**

$$\int \cosh ax dx = \frac{1}{a} \sinh ax \quad (110)$$

$$\int e^{ax} \cosh bxdx = \begin{cases} \frac{e^{ax}}{a^2 - b^2} [a \cosh bx - b \sinh bx] & a \neq b \\ \frac{e^{2ax}}{4a} + \frac{x}{2} & a = b \end{cases} \quad (111)$$

$$\int \sinh ax dx = \frac{1}{a} \cosh ax \quad (112)$$

$$\int e^{ax} \sinh bxdx = \begin{cases} \frac{e^{ax}}{a^2 - b^2} [-b \cosh bx + a \sinh bx] & a \neq b \\ \frac{e^{2ax}}{4a} - \frac{x}{2} & a = b \end{cases} \quad (113)$$

$$\int e^{ax} \tanh bxdx = \begin{cases} \frac{e^{(a+2b)x}}{(a+2b)} {}_2F_1 \left[ 1 + \frac{a}{2b}, 1, 2 + \frac{a}{2b}, -e^{2bx} \right] - \frac{1}{a} e^{ax} {}_2F_1 \left[ \frac{a}{2b}, 1, 1E, -e^{2bx} \right] & a \neq b \\ \frac{e^{ax} - 2 \tan^{-1}[e^{ax}]}{a} & a = b \end{cases} \quad (114)$$

$$\int \tanh ax dx = \frac{1}{a} \ln \cosh ax \quad (115)$$

$$\int \cos ax \cosh bxdx = \frac{1}{a^2 + b^2} [a \sin ax \cosh bx + b \cos ax \sinh bx] \quad (116)$$

$$\int \cos ax \sinh bxdx = \frac{1}{a^2 + b^2} [b \cos ax \cosh bx + a \sin ax \sinh bx] \quad (117)$$

$$\int \sin ax \cosh bxdx = \frac{1}{a^2 + b^2} [-a \cos ax \cosh bx + b \sin ax \sinh bx] \quad (118)$$

$$\int \sin ax \sinh bxdx = \frac{1}{a^2 + b^2} [b \cosh bx \sin ax - a \cos ax \sinh bx] \quad (119)$$

$$\int \sinh ax \cosh ax dx = \frac{1}{4a} [-2ax + \sinh 2ax] \quad (120)$$

$$\int \sinh ax \cosh bxdx = \frac{1}{b^2 - a^2} [b \cosh bx \sinh ax - a \cosh ax \sinh bx] \quad (121)$$

