

Содержание

1	final/template/vimrc.txt
2	final/template/template.cpp
3	final/template/fastIO.cpp
4	final/template/hashTable.cpp
5	final/template/optimizations.cpp
6	final/template/Template.java
7	final/numeric/fft.cpp
8	final/numeric/fftint.cpp
9	final/numeric/blackbox.cpp
10	final/numeric/crt.cpp
11	final/numeric/pollard.cpp
12	final/numeric/poly.cpp
13	final/numeric/simplex.cpp
14	final/geom/commonTangents.cpp
15	final/geom/halfplaneIntersection.cpp
16	final/geom/minDisc.cpp
17	final/geom/convexHull3D-N2.cpp
18	final/geom/polygonArcCut.cpp
19	final/strings/eertree.cpp
20	final/strings/sufAutomaton.cpp
21	final/graphs/centroid.cpp
22	final/graphs/dinica.cpp
23	final/graphs/dominatorTree.cpp
24	final/graphs/fenwick-min.cpp
25	final/graphs/generalMatching.cpp
26	final/graphs/heavyLight.cpp
27	final/graphs/hungary.cpp
28	final/graphs/max-flow-min-cost.cpp
29	final/graphs/retro.cpp
30	final/graphs/smith.cpp
31	final/graphs/twoChinese.cpp
32	final/graphs/linkcut.cpp

final/template/vimrc.txt

```

1  map <F9> :wall! <CR> :!g++ -Wall -Wextra -Wshadow -<
    Wno-unused-result -o %:r % -std=c++14 -DHOME -<
    D_GLIBCXX_DEBUG -fsanitize=address <CR>
2  map <F7> :wall! <CR> :!g++ -Wall -Wextra -Wshadow -<
    Wno-unused-result -o %:r % -std=c++14 -DHOME -<
    O2 <CR>
3  map <F8> :wall! <CR> :!ulimit -s 500000 && ./%:r <CR>
    >
4
5  inoremap {<CR> {<CR>}<ESC>O
2  6  map <c-a> ggVG
7
8  set nu
2  9  set rnu
10 syntax on
11
12 map <c-t> :tabnew <CR>
13 map <c-l> :tabn <CR>
4  14 map <c-h> :tabp <CR>
15
16
4  17 set cin
18 set sw=4
19 set so=99
5  20 set bs=2
21 set et
    set sts=4

```

final/template/template.cpp

```

7  1  // team : SPb ITMO University 1
2  #include <bits/stdc++.h>
3
4  #define F first
5  #define S second
6  #define pb push_back
8  7  #define forn(i, n) for(int i = 0 ; (i) < (n) ; ++i)
8  #define eprintf(...) fprintf(stderr, __VA_ARGS__) ,<
    fflush(stderr)
8  9  #define sz(a) ((int)(a).size())
10 #define all(a) (a).begin(), a.end()
9  11 #define pw(x) (1LL<<(x))
12
13 using namespace std;
9  14
15 typedef long long ll;
16 typedef double dbl;
10 17 typedef vector<int> vi;
18 typedef pair<int, int> pi;
19
10 20 const int INF = 1.01e9;
21 const dbl eps = 1e-9;
10 22
23 /* — main part — */
24
11 25
26
27
11 28
29
30
12 31 int main()
32 {
12 33 #define TASK ""
34 #ifdef home
35     assert(freopen(TASK".in", "r", stdin));
12 36     //assert(freopen(TASK".out", "w", stdout));
37 #endif
38
13 39
40
14 41
42
43 #ifdef home
14 44     eprintf("time = %d ms\n", (int)(clock() * 1000. / <
        CLOCKS_PER_SEC));
45 #endif
46     return 0;
15 47 }

```

final/template/fastIO.cpp

```

1 #include <stdio>
2 #include <algorithm>
3
4 /** Interface */
5
6 inline int readInt();
7 inline int readUInt();
8 inline bool isEof();
9
10 /** Read */
11
12 static const int buf_size = 100000;
13 static char buf[buf_size];
14 static int buf_len = 0, pos = 0;
15
16 inline bool isEof() {
17     if (pos == buf_len) {
18         pos = 0, buf_len = fread(buf, 1, buf_size, stdin);
19     }
20     if (pos == buf_len) return 1;
21     return 0;
22 }
23
24 inline int getChar() { return isEof() ? -1 : buf[pos++]; }
25
26 inline int readChar() {
27     int c = getChar();
28     while (c != -1 && c <= 32) c = getChar();
29     return c;
30 }
31
32 inline int readUInt() {
33     int c = readChar(), x = 0;
34     while ('0' <= c && c <= '9') x = x * 10 + c - '0', c = getChar();
35     return x;
36 }
37
38 inline int readInt() {
39     int s = 1, c = readChar();
40     int x = 0;
41     if (c == '-') s = -1, c = getChar();
42     while ('0' <= c && c <= '9') x = x * 10 + c - '0', c = getChar();
43     return s == 1 ? x : -x;
44 }
45
46 // 10M int [0..1e9]
47 // cin 3.02
48 // scanf 1.2
49 // cin_sync_with_stdio(false) 0.71
50 // fastRead getchar 0.53
51 // fastRead fread 0.15
52

```

```

23     return f[i];
24 }
25 };
26
27 hashTable<13, int, int, 0> h;
28
29 #include "ext/pb_ds/assoc_container.hpp"
30 using namespace __gnu_pbds;
31
32 template <typename T> using ordered_set = tree<T, ←
    null_type, less<T>, rb_tree_tag, ←
    tree_order_statistics_node_update>;
33 template <typename K, typename V> using ordered_map ←
    = tree<K, V, less<K>, rb_tree_tag, ←
    tree_order_statistics_node_update>;
34
35 // HOW TO USE ::
36 // -- order_of_key(10) returns the number of ←
    elements in set/map strictly less than 10
37 // -- *find_by_order(10) returns 10-th smallest ←
    element in set/map (0-based)

```

final/template/optimizations.cpp

```

1 // from anta code http://codeforces.com/contest/755/←
    submission/23864531
2
3 #pragma GCC optimize ("O3")
4 #pragma GCC target ("sse4")
5 inline void fasterLLDivMod(unsigned long long x, ←
    unsigned y, unsigned &out_d, unsigned &out_m) {
6     unsigned xh = (unsigned)(x >> 32), xl = (unsigned)←
    x, d, m;
7 #ifdef __GNUC__
8     asm(
9         "divl %4; \n\t"
10        : "=a" (d), "=d" (m)
11        : "d" (xh), "a" (xl), "r" (y)
12        );
13 #else
14     __asm {
15         mov edx, dword ptr[xh];
16         mov eax, dword ptr[xl];
17         div dword ptr[y];
18         mov dword ptr[d], eax;
19         mov dword ptr[m], edx;
20     };
21 #endif
22     out_d = d; out_m = m;
23 }
24
25
26 // have no idea what sse flags are really cool; list ←
    of some of them
27 // -- very good with bitsets
28 #pragma GCC optimize("O3")
29 #pragma GCC target("sse,sse2,sse3,ssse3,sse4,popcnt,←
    abm,mmx")

```

final/template/hashTable.cpp

```

1 template <const int max_size, class HashType, class ←
    Data, const Data default_value>
2 struct hashTable {
3     HashType hash[max_size];
4     Data f[max_size];
5     int size;
6
7     int position(HashType H) const {
8         int i = H % max_size;
9         while (hash[i] && hash[i] != H)
10             if (++i == max_size)
11                 i = 0;
12         return i;
13     }
14
15     Data & operator [] (HashType H) {
16         assert(H != 0);
17         int i = position(H);
18         if (!hash[i]) {
19             hash[i] = H;
20             f[i] = default_value;
21             size++;
22         }
23     }
24 }

```

final/template/Template.java

```

1 import java.util.*;
2 import java.io.*;
3
4 public class Template {
5     FastScanner in;
6     PrintWriter out;
7
8     public void solve() throws IOException {
9         int n = in.nextInt();
10        out.println(n);
11    }
12
13    public void run() {
14        try {
15            in = new FastScanner();
16            out = new PrintWriter(System.out);
17
18            solve();
19
20            out.close();
21        }
22    }
23 }

```

```

21     } catch (IOException e) {
22         e.printStackTrace();
23     }
24 }
25
26 class FastScanner {
27     BufferedReader br;
28     StringTokenizer st;
29
30     FastScanner() {
31         br = new BufferedReader(new InputStreamReader(↵
32             System.in));
33     }
34
35     String next() {
36         while (st == null || !st.hasMoreTokens()) {
37             try {
38                 st = new StringTokenizer(br.readLine());
39             } catch (IOException e) {
40                 e.printStackTrace();
41             }
42         }
43         return st.nextToken();
44     }
45
46     int nextInt() {
47         return Integer.parseInt(next());
48     }
49 }
50
51 public static void main(String[] arg) {
52     new Template().run();
53 }

```

final/numeric/fft.cpp

```

1  namespace fft
2  {
3      const int maxBase = 21;
4      const int maxN = 1 << maxBase;
5
6      struct num
7      {
8          dbl x, y;
9          num() {}
10         num(dbl xx, dbl yy): x(xx), y(yy) {}
11         num(dbl alp): x(cos(alp)), y(sin(alp)) {}
12     };
13
14     inline num operator + (num a, num b) { return num(↵
15         a.x + b.x, a.y + b.y); }
16     inline num operator - (num a, num b) { return num(↵
17         a.x - b.x, a.y - b.y); }
18     inline num operator * (num a, num b) { return num(↵
19         a.x * b.x - a.y * b.y, a.x * b.y + a.y * b.x); ↵
20     }
21     inline num conj(num a) { return num(a.x, -a.y); }
22
23     const dbl PI = acos(-1);
24
25     num root[maxN];
26     int rev[maxN];
27     bool rootsPrepared = false;
28
29     void prepRoots()
30     {
31         if (rootsPrepared) return;
32         rootsPrepared = true;
33         root[1] = num(1, 0);
34         for (int k = 1; k < maxBase; ++k)
35         {
36             num x(2 * PI / pw(k + 1));
37             for (int i = pw(k - 1); i < pw(k); ++i)
38             {
39                 root[2 * i] = root[i];
40                 root[2 * i + 1] = root[i] * x;
41             }
42         }
43     }
44
45     int base, N;
46
47     int lastRevN = -1;
48     void prepRev()
49     {
50         if (lastRevN == N) return;
51         lastRevN = N;
52         forn(i, N) rev[i] = (rev[i >> 1] >> 1) + ((i & ↵
53             1) << (base - 1));
54     }
55
56     void fft(num *a, num *f)
57     {
58         forn(i, N) f[i] = a[rev[i]];
59         for (int k = 1; k < N; k <= 1) for (int i = 0; ↵
60             i < N; i += 2 * k) forn(j, k)
61         {
62             num z = f[i + j + k] * root[j + k];
63             f[i + j + k] = f[i + j] - z;
64             f[i + j] = f[i + j] + z;
65         }
66     }
67
68     num a[maxN], b[maxN], f[maxN], g[maxN];
69     ll A[maxN], B[maxN], C[maxN];
70
71     void _multMod(int mod)
72     {
73         forn(i, N)
74         {
75             int x = A[i] % mod;
76             a[i] = num(x & (pw(15) - 1), x >> 15);
77         }
78         forn(i, N)
79         {
80             int x = B[i] % mod;
81             b[i] = num(x & (pw(15) - 1), x >> 15);
82         }
83         fft(a, f);
84         fft(b, g);
85
86         forn(i, N)
87         {
88             int j = (N - i) & (N - 1);
89

```

```

83     num a1 = (f[i] + conj(f[j])) * num(0.5, 0);
84     num a2 = (f[i] - conj(f[j])) * num(0, -0.5);
85     num b1 = (g[i] + conj(g[j])) * num(0.5 / N, 0) ←
;
86     num b2 = (g[i] - conj(g[j])) * num(0, -0.5 / N ←
);
87     a[j] = a1 * b1 + a2 * b2 * num(0, 1);
88     b[j] = a1 * b2 + a2 * b1;
89 }
90
91 fft(a, f);
92 fft(b, g);
93
94 forn(i, N)
95 {
96     ll aa = f[i].x + 0.5;
97     ll bb = g[i].x + 0.5;
98     ll cc = f[i].y + 0.5;
99     C[i] = (aa + bb % mod * pw(15) + cc % mod * pw ←
(30)) % mod;
100 }
101
102
103 void prepAB(int n1, int n2)
104 {
105     base = 1;
106     N = 2;
107     while (N < n1 + n2) base++, N <= 1;
108
109     for (int i = n1; i < N; ++i) A[i] = 0;
110     for (int i = n2; i < N; ++i) B[i] = 0;
111
112     prepRoots();
113     prepRev();
114 }
115
116 void mult(int n1, int n2)
117 {
118     prepAB(n1, n2);
119     forn(i, N) a[i] = num(A[i], B[i]);
120     fft(a, f);
121     forn(i, N)
122     {
123         int j = (N - i) & (N - 1);
124         a[i] = (f[j] * f[j] - conj(f[i] * f[i])) * num ←
(0, -0.25 / N);
125     }
126     fft(a, f);
127     forn(i, N) C[i] = (ll)round(f[i].x);
128 }
129
130
131 void multMod(int n1, int n2, int mod)
132 {
133     prepAB(n1, n2);
134     _multMod(mod);
135 }
136
137 int D[maxN];
138
139 void multLL(int n1, int n2)
140 {
141     prepAB(n1, n2);
142
143     int mod1 = 1.5e9;
144     int mod2 = mod1 + 1;
145
146     _multMod(mod1);
147
148     forn(i, N) D[i] = C[i];
149
150     _multMod(mod2);
151
152     forn(i, N)
153     {
154         C[i] = D[i] + (C[i] - D[i] + (ll)mod2) * (ll) ←
mod1 % mod2 * mod1;
155     }
156 }
157 // HOW TO USE ::
158 // — set correct maxBase
159 // — use mult(n1, n2), multMod(n1, n2, mod) and ←
multLL(n1, n2)
160 // — input : A[], B[]
161 // — output : C[]
162 }

```

final/numeric/fftint.cpp

```

1 namespace fft
2 {
3     const int mod = 998244353;
4     const int base = 20;
5     const int N = 1 << base;
6     const int ROOT = 646;
7
8     int root[N];
9     int rev[N];
10
11 void init()
12 {
13     forn(i, N) rev[i] = (rev[i >> 1] >> 1) + ((i & ←
1) << (base - 1));
14     int NN = N >> 1;
15     int z = 1;
16     forn(i, NN)
17     {
18         root[i + NN] = z;
19         z = z * (ll)ROOT % mod;
20     }
21     for (int i = NN - 1; i > 0; --i) root[i] = root ←
[2 * i];
22 }
23
24 void fft(int *a, int *f)
25 {
26     forn(i, N) f[i] = a[rev[i]];
27     for (int k = 1; k < N; k <= 1) for (int i = 0; ←
i < N; i += 2 * k) forn(j, k)
28     {
29         int z = f[i + j + k] * (ll)root[j + k] % mod;
30         f[i + j + k] = (f[i + j] - z + mod) % mod;
31         f[i + j] = (f[i + j] + z) % mod;
32     }
33 }
34
35 int A[N], B[N], C[N];
36 int F[N], G[N];
37
38 void _mult(int eq)
39 {
40     fft(A, F);
41     if (eq) forn(i, N) G[i] = F[i];
42     else fft(B, G);
43     int invN = inv(N);
44     forn(i, N) A[i] = F[i] * (ll)G[i] % mod * invN % ←
mod;
45     reverse(A + 1, A + N);
46     fft(A, C);
47 }
48
49 void mult(int n1, int n2, int eq = 0)
50 {
51     for (int i = n1; i < N; ++i) A[i] = 0;
52     for (int i = n2; i < N; ++i) B[i] = 0;
53
54     _mult(eq);
55
56     //forn(i, n1 + n2) C[i] = 0;
57     //forn(i, n1) forn(j, n2) C[i + j] = (C[i + j] + ←
A[i] * (ll)B[j]) % mod;
58 }
59 }

```

final/numeric/blackbox.cpp

```

1 namespace blackbox
2 {
3     int A[N];
4     int B[N];
5     int C[N];
6
7     int magic(int k, int x)
8     {
9         B[k] = x;
10        C[k] = (C[k] + A[0] * (ll)B[k]) % mod;
11        int z = 1;
12        if (k == N - 1) return C[k];
13        while ((k & (z - 1)) == (z - 1))
14        {
15            //mult B[k - z + 1 ... k] x A[z .. 2 * z - 1]
16            forn(i, z) fft::A[i] = A[z + i];
17            forn(i, z) fft::B[i] = B[k - z + 1 + i];
18            fft::multMod(z, z, mod);
19            forn(i, 2 * z - 1) C[k + 1 + i] = (C[k + 1 + i] ←
+ fft::C[i]) % mod;

```

```

20     z <=<= 1;
21 }
22 return C[k];
23 }
24 // A — constant array
25 // magic(k, x):: B[k] = x, returns C[k]
26 // !! WARNING !! better to set N twice the size ←
27 // needed

```

final/numeric/crt.cpp

```

1 int rev(int x, int m)
2 {
3     if (x == 1) return 1;
4     return (1 - rev(m % x, x) * (ll)m) / x + m;
5 }
6
7 int CRT(int a1, int m1, int a2, int m2)
8 {
9     return (a1 - a2 % m1 + m1) * (ll)rev(m2, m1) % m1 ←
10     * m2 + a2;

```

```

56 ll n = N;
57
58
59 for (int i = 0; i < math::pc && p[i] < MX; ++i) ←
60 if (n % p[i] == 0)
61 {
62     primes.pb(p[i]);
63     while (n % p[i] == 0) n /= p[i];
64 }
65
66 go(n);
67
68 sort(primes.begin(), primes.end());
69
70 vector<pair<ll, int>> res;
71 for (ll x : primes)
72 {
73     int cnt = 0;
74     while (N % x == 0)
75     {
76         cnt++;
77         N /= x;
78     }
79     res.push_back({x, cnt});
80 }
81 return res;
82 }

```

final/numeric/pollard.cpp

```

1 namespace pollard
2 {
3     using math::p;
4
5     vector<pair<ll, int>> getFactors(ll N)
6     {
7         vector<ll> primes;
8
9         const int MX = 1e5;
10        const ll MX2 = MX * (ll)MX;
11
12        assert(MX <= math::maxP && math::pc > 0);
13
14        function<void(ll)> go = [&go, &primes](ll n)
15        {
16            for (ll x : primes) while (n % x == 0) n /= x;
17            if (n == 1) return;
18            if (n > MX2)
19            {
20                auto F = [&](ll x) {
21                    ll k = ((long double)x * x) / n;
22                    ll r = (x * x - k * n + 3) % n;
23                    return r < 0 ? r + n : r;
24                };
25                ll x = mt19937_64()() % n, y = x;
26                const int C = 3 * pow(n, 0.25);
27
28                ll val = 1;
29                forn(it, C)
30                {
31                    x = F(x), y = F(F(y));
32                    if (x == y) continue;
33                    ll delta = abs(x - y);
34                    ll k = ((long double)val * delta) / n;
35                    val = (val * delta - k * n) % n;
36                    if (val < 0) val += n;
37                    if (val == 0)
38                    {
39                        ll g = __gcd(delta, n);
40                        go(g), go(n / g);
41                        return;
42                    }
43                    if ((it & 255) == 0)
44                    {
45                        ll g = __gcd(val, n);
46                        if (g != 1)
47                        {
48                            go(g), go(n / g);
49                            return;
50                        }
51                    }
52                }
53            }
54            primes.pb(n);
55        };

```

final/numeric/poly.cpp

```

1 struct poly
2 {
3     vi v;
4     poly() {}
5     poly(vi vv)
6     {
7         v = vv;
8     }
9     int size()
10    {
11        return (int)v.size();
12    }
13    poly cut(int maxLen)
14    {
15        if (maxLen < sz(v)) v.resize(maxLen);
16        return *this;
17    }
18    poly norm()
19    {
20        while (sz(v) > 1 && v.back() == 0) v.pop_back();
21        return *this;
22    }
23    inline int& operator [] (int i)
24    {
25        return v[i];
26    }
27    void out(string name="")
28    {
29        stringstream ss;
30        if (sz(name)) ss << name << " = ";
31        int fst = 1;
32        forn(i, sz(v)) if (v[i])
33        {
34            int x = v[i];
35            int sgn = 1;
36            if (x > mod / 2) x = mod - x, sgn = -1;
37            if (sgn == -1) ss << "-";
38            else if (!fst) ss << "+";
39            fst = 0;
40            if (!i || x != 1)
41            {
42                ss << x;
43                if (i > 0) ss << "*x";
44                if (i > 1) ss << "^" << i;
45            }
46            else
47            {
48                ss << "x";
49                if (i > 1) ss << "^" << i;
50            }
51        }
52        if (fst) ss << "0";
53        string s;
54        ss >> s;
55        eprintf("%s\n", s.data());
56    }

```

```

57 };
58
59 poly operator + (poly A, poly B)
60 {
61     poly C;
62     C.v = vi(max(sz(A), sz(B)));
63     forn(i, sz(C))
64     {
65         if (i < sz(A)) C[i] = (C[i] + A[i]) % mod;
66         if (i < sz(B)) C[i] = (C[i] + B[i]) % mod;
67     }
68     return C.norm();
69 }
70
71 poly operator - (poly A, poly B)
72 {
73     poly C;
74     C.v = vi(max(sz(A), sz(B)));
75     forn(i, sz(C))
76     {
77         if (i < sz(A)) C[i] = (C[i] + A[i]) % mod;
78         if (i < sz(B)) C[i] = (C[i] + mod - B[i]) % mod;
79     }
80     return C.norm();
81 }
82
83 poly operator * (poly A, poly B)
84 {
85     poly C;
86     C.v = vi(sz(A) + sz(B) - 1);
87
88     forn(i, sz(A)) fft::A[i] = A[i];
89     forn(i, sz(B)) fft::B[i] = B[i];
90     fft::multMod(sz(A), sz(B), mod);
91     forn(i, sz(C)) C[i] = fft::C[i];
92     return C.norm();
93 }
94
95 poly inv(poly A, int n) // returns A^{-1} mod x^n
96 {
97     assert(sz(A) && A[0] != 0);
98     A.cut(n);
99
100     auto cutPoly = [](poly &from, int l, int r)
101     {
102         poly R;
103         R.v.resize(r - l);
104         for (int i = l; i < r; ++i)
105         {
106             if (i < sz(from)) R[i - l] = from[i];
107         }
108         return R;
109     };
110
111     function<int(int, int)> rev = [&rev](int x, int m) ←
112     → int
113     {
114         if (x == 1) return 1;
115         return (1 - rev(m % x, x) * (ll)m) / x + m;
116     };
117
118     poly R({rev(A[0], mod)});
119     for (int k = 1; k < n; k <= 1)
120     {
121         poly A0 = cutPoly(A, 0, k);
122         poly A1 = cutPoly(A, k, 2 * k);
123         poly H = A0 * R;
124         H = cutPoly(H, k, 2 * k);
125         poly R1 = (((A1 * R).cut(k) + H) * (poly({0}) - ←
126         R)).cut(k);
127         R.v.resize(2 * k);
128         forn(i, k) R[i + k] = R1[i];
129     }
130     return R.cut(n).norm();
131 }
132
133 pair<poly, poly> divide(poly A, poly B)
134 {
135     if (sz(A) < sz(B)) return {poly({0}), A};
136
137     auto rev = [](poly f)
138     {
139         reverse(all(f.v));
140         return f;
141     };
142
143     poly q = rev((inv(rev(B), sz(A) - sz(B) + 1) * rev ←
144     (A)).cut(sz(A) - sz(B) + 1));
145     poly r = A - B * q;
146
147     return {q, r};
148 }

```

final/numeric/simplex.cpp

```

1
2 namespace simplex {
3     const int MAX_N = -1; // number of variables
4     const int MAX_M = -1; // number of inequalities
5     dbl a[MAX_M][MAX_N];
6     dbl b[MAX_M];
7     dbl c[MAX_N];
8     dbl v;
9     ll n, m;
10    int left[MAX_M];
11    int up[MAX_N];
12    int pos[MAX_N];
13    dbl res[MAX_N];
14
15    void init(int nn, int mm) {
16        n = nn;
17        m = mm;
18        v = 0;
19        for (int i = 0; i < m; i++)
20            for (int j = 0; j < n; j++)
21                a[i][j] = 0;
22        for (int i = 0; i < m; i++)
23            b[i] = 0;
24        for (int i = 0; i < n; i++)
25            c[i] = 0;
26    }
27
28    void pivot(int x, int y) {
29        swap(left[x], up[y]);
30        dbl k = a[x][y];
31        a[x][y] = 1;
32        b[x] /= k;
33        int cur = 0;
34        for (int i = 0; i < n; i++) {
35            a[x][i] = a[x][i] / k;
36            if (!eq(a[x][i], 0))
37                pos[cur++] = i;
38        }
39
40        for (int i = 0; i < m; i++) {
41            if (i == x || eq(a[i][y], 0)) continue;
42            dbl cof = a[i][y];
43            b[i] -= cof * b[x];
44            a[i][y] = 0;
45            for (int j = 0; j < cur; j++)
46                a[i][pos[j]] -= cof * a[x][pos[j]];
47        }
48        dbl cof = c[y];
49        v += cof * b[x];
50        c[y] = 0;
51        for (int i = 0; i < cur; i++) {
52            c[pos[i]] -= cof * a[x][pos[i]];
53        }
54    }
55
56    void solve() {
57        for (int i = 0; i < n; i++)
58            up[i] = i;
59        for (int i = 0; i < m; i++)
60            left[i] = i + n;
61
62        while (1) {
63            int x = -1;
64            for (int i = 0; i < m; i++)
65                if (ls(b[i], 0) && (x == -1 || b[i] < b[x])) ←
66            {
67                x = i;
68            }
69            if (x == -1) break;
70            int y = -1;
71            for (int j = 0; j < n; j++)
72                if (ls(a[x][j], 0)) {
73                    y = j;
74                    break;
75                }
76            if (y == -1) {
77                assert(false); // no solution
78            }
79            pivot(x, y);
80        }
81        while (1) {
82            int y = -1;
83            for (int i = 0; i < n; i++)
84                if (ls(0, c[i]) && (y == -1 || (c[i] > c[y]) ←
85            )) {
86                y = i;
87            }
88            if (y == -1) break;
89        }
90    }
91 }

```

```

87
88     int x = -1;
89     for (int i = 0; i < m; i++) {
90         if (ls(0, a[i][y])) {
91             if (x == -1 || (b[i] / a[i][y] < b[x] / a[←
x][y])) {
92                 x = i;
93             }
94         }
95     }
96     if (y == -1) {
97         assert(false); // infinite solution
98     }
99     pivot(x, y);
100 }
101
102 memset(res, 0, sizeof(res));
103
104 for (int i = 0; i < m; i++) {
105     if (left[i] < n) {
106         res[left[i]] = b[i];
107     }
108 }
109
110 // HOW TO USE ::
111 // — call init(n, m)
112 // — call solve()
113 // — variables in "up" equals to zero
114 // — variables in "left" equals to b
115 // — max: c * x
116 // — b[i] >= a[i] * x
117 // — answer in "v"
118 // — sertificate in "res"
119 };

```

final/geom/commonTangents.cpp

```

1
2
3 vector<Line> commonTangents(pt A, dbl rA, pt B, dbl ←
rB) {
4     vector<Line> res;
5     pt C = B - A;
6     dbl z = C.len2();
7     for (int i = -1; i <= 1; i += 2) {
8         for (int j = -1; j <= 1; j += 2) {
9             dbl r = rB * j - rA * i;
10            dbl d = z - r * r;
11            if (ls(d, 0)) continue;
12            d = sqrt(max(0.01, d));
13            pt magic = pt(r, d) / z;
14            pt v(magic % C, magic * C);
15            dbl CC = (rA * i - v % A) / v.len2();
16            pt O = v * -CC;
17            res.pb(Line(0, 0 + v.rotate()));
18        }
19    }
20    return res;
21 }
22
23 // HOW TO USE ::
24 // — *D*—————*F*
25 // — *...* — — *...*
26 // — *.....* — — *.....*
27 // — *.....* — — *.....*
28 // — *...A...* — — *...B...*
29 // — *.....* — — *.....*
30 // — *.....* — — *.....*
31 // — *...* — — *...*
32 // — *C*—————*E*
33 // — res = {CE, CF, DE, DF}

```

final/geom/halfplaneIntersection.cpp

```

1 int getPart(pt v) {
2     return less(0, v.y) || (equal(0, v.y) && less(v.x, ←
0));
3 }
4
5 int cmpV(pt a, pt b) {
6     int partA = getPart(a);
7     int partB = getPart(b);
8     if (partA < partB) return -1;
9     if (partA > partB) return 1;
10    if (equal(0, a * b)) return 0;
11    if (0 < a * b) return -1;
12    return 1;
13 }
14
15 double planeInt(vector<Line> l) {
16     int n = l.size();
17     sort(all(l), [](Line a, Line b) {
18         int r = cmpV(a.v, b.v);
19         if (r != 0) return r < 0;
20         return a.O % a.v.rotate() < b.O % a.v.rotate() ←
;
21     });
22
23     int cur = 0;
24     for (int i = 0; i < n; ) {
25         int j = i;
26         for (; i < n && cmpV(l[j].v, l[i].v) == 0 && ←
cmpV(l[i].v, l[j].v) == 0; i++);
27         l[cur++] = l[i - 1];
28     }
29     n = cur;
30
31     for (int i = 0; i < n; i++)
32         l[i].id = i;
33
34     int flagUp = 0;
35     int flagDown = 0;
36     for (int i = 0; i < n; i++) {
37         int part = getPart(l[i].v);
38         if (part == 1) flagUp = 1;
39         if (part == 0) flagDown = 1;
40     }
41     if (!flagUp || !flagDown) return -1;
42 }

```

```

43 for (int i = 0; i < n; i++) {
44     pt v = l[i].v;
45     pt u = l[(i + 1) % n].v;
46     if (equal(0, v * u) && less(v % u, 0)) {
47         pt dir = l[i].v.rotate();
48         if (lessE(l[(i + 1) % n].0 % dir, l[i].0 % dir ←
49     )) return 0;
50     return -1;
51 }
52 if (less(v * u, 0))
53     return -1;
54 }
55
56 cur = 0;
57 vector<Line> st(n * 2);
58 for (int tt = 0; tt < 2; tt++) {
59     for (int i = 0; i < n; i++) {
60         for (; cur >= 2; cur--) {
61             pt G = st[cur - 1] * l[i];
62             if (!lessE(st[cur - 2].v * (G - st[cur - 2]. ←
63         0), 0))
64                 break;
65             st[cur++] = l[i];
66             if (cur >= 2 && lessE(st[cur - 2].v * st[cur ←
67         1].v, 0)) return 0;
68         }
69     }
70     vector<int> use(n, -1);
71     int left = -1, right = -1;
72     for (int i = 0; i < cur; i++) {
73         if (use[st[i].id] == -1) {
74             use[st[i].id] = i;
75         }
76         else {
77             left = use[st[i].id];
78             right = i;
79             break;
80         }
81     }
82     vector<Line> tmp;
83     for (int i = left; i < right; i++)
84         tmp.pb(st[i]);
85     vector<pt> res;
86     for (int i = 0; i < (int)tmp.size(); i++)
87         res.pb(tmp[i] * tmp[(i + 1) % tmp.size()]);
88     double area = 0;
89     for (int i = 0; i < (int)res.size(); i++)
90         area += res[i] * res[(i + 1) % res.size()];
91     return area / 2;
92 }

```

final/geom/minDisc.cpp

```

1 pair<pt, dbl> minDisc(vector<pt> p) {
2     int n = p.size();
3     pt 0 = pt(0, 0);
4     dbl R = 0;
5     random_shuffle(all(p));
6     for (int i = 0; i < n; i++) {
7         if (ls(R, (0 - p[i]).len())) {
8             0 = p[i];
9             R = 0;
10            for (int j = 0; j < i; j++) {
11                if (ls(R, (0 - p[j]).len())) {
12                    0 = (p[i] + p[j]) / 2;
13                    R = (p[i] - p[j]).len() / 2;
14                    for (int k = 0; k < j; k++) {
15                        if (ls(R, (0 - p[k]).len())) {
16                            Line l1((p[i] + p[j]) / 2, (p[i] + p[j] ←
17                )) / 2 + (p[i] - p[j]).rotate();
18                            Line l2((p[k] + p[j]) / 2, (p[k] + p[j] ←
19                )) / 2 + (p[k] - p[j]).rotate();
20                            0 = l1 * l2;
21                            R = (p[i] - 0).len();
22                        }
23                    }
24                }
25            }
26        }
27        return {0, R};
28    }

```

final/geom/convexHull3D-N2.cpp

```

1 struct Plane {
2     pt 0, v;
3     vector<int> id;
4 };
5
6 vector<Plane> convexHull3(vector<pt> p) {
7     vector<Plane> res;
8     int n = p.size();
9     for (int i = 0; i < n; i++)
10         p[i].id = i;
11     for (int i = 0; i < 4; i++) {
12         vector<pt> tmp;
13         for (int j = 0; j < 4; j++)
14             if (i != j)
15                 tmp.pb(p[j]);
16         res.pb({tmp[0], (tmp[1] - tmp[0]) * (tmp[2] - ←
17         tmp[0]), {tmp[0].id, tmp[1].id, tmp[2].id}});
18         if ((p[i] - res.back().0) % res.back().v > 0) {
19             res.back().v = res.back().v * -1;
20             swap(res.back().id[0], res.back().id[1]);
21         }
22     }
23     vector<vector<int>> use(n, vector<int>(n, 0));
24     int tnr = 0;
25     for (int i = 4; i < n; i++) {
26         int cur = 0;
27         tnr++;
28         vector<pair<int, int>> curEdge;
29         for (int j = 0; j < sz(res); j++) {
30             if ((p[i] - res[j].0) % res[j].v > 0) {
31                 for (int t = 0; t < 3; t++) {
32                     int v = res[j].id[t];
33                     int u = res[j].id[(t + 1) % 3];
34                     use[v][u] = tnr;
35                     curEdge.pb({v, u});
36                 }
37             }
38             else {
39                 res[cur++] = res[j];
40             }
41         }
42         res.resize(cur);
43         for (auto x: curEdge) {
44             if (use[x.S][x.F] == tnr) continue;
45             res.pb({p[i], (p[x.F] - p[i]) * (p[x.S] - p[i] ←
46             )), {x.F, x.S, i}});
47         }
48     }
49     return res;
50 }
51
52 // plane in 3d
53 // (A, v) * (B, u) -> (O, n)
54 pt n = v * u;
55 pt m = v * n;
56 double t = (B - A) % u / (u % m);
57 pt 0 = A - m * t;

```

final/geom/polygonArcCut.cpp

```

1 struct Meta {
2     int type; // 0 - seg, 1 - circle
3     pt 0;
4     dbl R;
5 };
6
7 const Meta SEG = {0, pt(0, 0), 0};
8
9 vector<pair<pt, Meta>> cut(vector<pair<pt, Meta>> p, ←
10     Line l) {
11     vector<pair<pt, Meta>> res;
12     int n = p.size();
13     for (int i = 0; i < n; i++) {
14         pt A = p[i].F;
15         pt B = p[(i + 1) % n].F;
16         if (le(0, l.v * (A - l.0))) {
17             if (eq(0, l.v * (A - l.0)) && p[i].S.type == 1 ←
18             && ls(0, l.v % (p[i].S.0 - A)))
19                 res.pb({A, SEG});
20         }
21     }
22 }

```



```

19     else
20         res.pb(p[i]);
21     }
22     if (p[i].S.type == 0) {
23         if (sign(l.v * (A - l.0)) * sign(l.v * (B - l.0)) == -1) {
24             pt FF = Line(A, B) * l;
25             res.pb(make_pair(FF, SEG));
26         }
27     }
28     else {
29         pt E, F;
30         if (intCL(p[i].S.0, p[i].S.R, l, E, F)) {
31             if (onArc(p[i].S.0, A, E, B))
32                 res.pb({E, SEG});
33             if (onArc(p[i].S.0, A, F, B))
34                 res.pb({F, p[i].S});
35         }
36     }
37     return res;
38 }

```

final/strings/eertree.cpp

```

1 namespace eertree {
2     const int INF = 1e9;
3     const int N = 5e6 + 10;
4     char _s[N];
5     char *s = _s + 1;
6     int to[N][2];
7     int suf[N], len[N];
8     int sz, last;
9
10     const int odd = 1, even = 2, blank = 3;
11
12     void go(int &u, int pos) {
13         while (u != blank && s[pos - len[u] - 1] != s[pos]) {
14             u = suf[u];
15         }
16     }
17
18     int add(int pos) {
19         go(last, pos);
20         int u = suf[last];
21         go(u, pos);
22         int c = s[pos] - 'a';
23         int res = 0;
24         if (!to[last][c]) {
25             res = 1;
26             to[last][c] = sz;
27             len[sz] = len[last] + 2;
28             suf[sz] = to[u][c];
29             sz++;
30         }
31         last = to[last][c];
32         return res;
33     }
34
35     void init() {
36         to[blank][0] = to[blank][1] = even;
37         len[blank] = suf[blank] = INF;
38         len[even] = 0, suf[even] = odd;
39         len[odd] = -1, suf[odd] = blank;
40         last = even;
41         sz = 4;
42     }
43 }

```

```

10     memset(nxt, -1, sizeof(nxt));
11     memset(link, -1, sizeof(link));
12     memset(len, 0, sizeof(len));
13     last = 0;
14     sz = 1;
15 }
16
17 void add(int c) {
18     int cur = sz++;
19     len[cur] = len[last] + 1;
20     pos[cur] = len[cur];
21     int p = last;
22     last = cur;
23     for (; p != -1 && nxt[p][c] == -1; p = link[p]) ←
24         nxt[p][c] = cur;
25     if (p == -1) {
26         link[cur] = 0;
27         return;
28     }
29     int q = nxt[p][c];
30     if (len[p] + 1 == len[q]) {
31         link[cur] = q;
32         return;
33     }
34     int clone = sz++;
35     memcpy(nxt[clone], nxt[q], sizeof(nxt[q]));
36     len[clone] = len[p] + 1;
37     pos[clone] = pos[q];
38     link[clone] = link[q];
39     link[q] = link[cur] = clone;
40     for (; p != -1 && nxt[p][c] == q; p = link[p]) ←
41         nxt[p][c] = clone;
42 }
43
44 int n;
45 string s;
46 int l[MAXN], r[MAXN];
47 int e[MAXN][SIGMA];
48
49 void getSufTree(string _s) {
50     memset(e, -1, sizeof(e));
51     s = _s;
52     n = s.length();
53     reverse(s.begin(), s.end());
54     init();
55     for (int i = 0; i < n; i++) add(s[i] - 'a');
56     reverse(s.begin(), s.end());
57     for (int i = 1; i < sz; i++) {
58         int j = link[i];
59         l[i] = n - pos[i] + len[j];
60         r[i] = n - pos[i] + len[i];
61         e[j][s[l[i]] - 'a'] = i;
62     }
63 }
64
65 namespace duval {
66     string s;
67     int n = (int) s.length();
68     int i = 0;
69     while (i < n) {
70         int j = i + 1, k = i;
71         while (j < n && s[k] <= s[j]) {
72             if (s[k] < s[j])
73                 k = i;
74             else
75                 ++k;
76             ++j;
77         }
78         while (i <= k) {
79             cout << s.substr(i, j - k) << ' ';
80             i += j - k;
81         }
82     }
83 }

```

final/strings/sufAutomaton.cpp

```

1 namespace SA {
2     const int MAXN = 1 << 18;
3     const int SIGMA = 26;
4
5     int sz, last;
6     int nxt[MAXN][SIGMA];
7     int link[MAXN], len[MAXN], pos[MAXN];
8
9     void init() {

```

final/graphs/centroid.cpp

```

1 // original author: burunduk1, rewritten by me (←
  enot110)
2 // !!! warning !!! this code is not tested well
3 const int N = 1e5, K = 17;
4
5 int pivot, level[N], parent[N];
6 vector<int> v[N];
7
8 int get_pivot( int x, int xx, int n ) {
9     int size = 1;
10    for (int y : v[x])
11    {
12        if (y != xx && level[y] == -1) size += get_pivot(
13            (y, x, n));
14    }
15    if (pivot == -1 && (size * 2 >= n || xx == -1)) ←
16        pivot = x;
17    return size;
18 }
19
20 void build( int x, int xx, int dep, int size ) {
21     assert(dep < K);
22     pivot = -1;
23     get_pivot(x, -1, size);
24     x = pivot;
25     level[x] = dep, parent[x] = xx;
26     for (int y : v[x]) if (level[y] == -1)
27     {
28         build(y, x, dep + 1, size / 2);
29     }
30 }

```

final/graphs/dinica.cpp

```

1 namespace flow
2 {
3     const int maxn = 1e5 + 10;
4     const int maxe = 2 * maxn;
5
6     int head[maxn], next[maxe], to[maxe], f[maxe], ec ←
7     = 1;
8     int ST, EN, N = maxn;
9
10    inline void setN(int n)
11    {
12        ST = n;
13        EN = n + 1;
14        N = n + 2;
15    }
16
17    inline void _add(int x, int y, int ff)
18    {
19        ++ec;
20        to[ec] = y;
21        next[ec] = head[x];
22        head[x] = ec;
23        f[ec] = ff;
24    }
25
26    inline int add(int x, int y, int ff)
27    {
28        _add(x, y, ff);
29        _add(y, x, 0);
30        return ec - 1;
31    }
32
33    void clear()
34    {
35        forn(i, N) head[i] = 0;
36        ec = 1;
37    }
38
39    int d[maxn];
40    int q[maxn], st = 0, en = 0;
41
42    int bfs()
43    {
44        forn(i, N) d[i] = 1e9;
45        st = 0, en = 0;
46        d[ST] = 0;
47        q[en++] = ST;
48        while (st < en)

```

```

48    {
49        int x = q[st++];
50        if (x == EN) return 1;
51        for (int e = head[x]; e; e = next[e])
52        {
53            int y = to[e];
54            if (d[y] == 1e9 && f[e])
55            {
56                d[y] = d[x] + 1;
57                q[en++] = y;
58            }
59        }
60    }
61    return 0;
62 }
63
64 int pushed;
65 int fst[maxn];
66
67 int dfs(int x, int flow = 1e9)
68 {
69     if (x == EN)
70     {
71         pushed = flow;
72         return 1;
73     }
74     for (; fst[x]; fst[x] = next[fst[x]])
75     {
76         int e = fst[x];
77         int y = to[e];
78         if (d[y] == d[x] + 1 && f[e] && dfs(y, min(f[e] ←
79             ], flow)))
80         {
81             f[e] -= pushed;
82             f[e ^ 1] += pushed;
83             return 1;
84         }
85     }
86     return 0;
87 }
88
89 ll calcFlow()
90 {
91     ll res = 0;
92     while (bfs())
93     {
94         forn(i, N) fst[i] = head[i];
95         while (dfs(ST))
96         {
97             res += pushed;
98         }
99     }
100    return res;
101 }
102
103 // HOW TO USE ::
104 // — set maxn and maxe (special for izban)
105 // — add adges using add(x, y, f), call setN(n)
106 // — run calcFlow
107 }

```

final/graphs/dominatorTree.cpp

```

1 namespace domtree {
2     const int MAXN = 300100;
3     int n;
4     vector<int> e[MAXN];
5     vector<int> g[MAXN];
6     int par[MAXN];
7     int in[MAXN], rin[MAXN], tnr;
8     int dom[MAXN], sdom[MAXN], cmn[MAXN];
9     int p[MAXN];
10    int adom[MAXN];
11    vector<int> vct[MAXN];
12
13    void init(int _n) {
14        n = _n;
15        for (int i = 0; i < n; i++) {
16            e[i].clear();
17        }
18    }
19
20    void addEdge(int from, int to) {
21        e[from].push_back(to);
22    }
23 }

```

```

24 void dfs(int v) {
25     in[v] = tmr++;
26     rin[in[v]] = v;
27     for (int to : e[v]) {
28         if (in[to] == -1) {
29             dfs(to);
30             par[in[to]] = in[v];
31         }
32         g[in[to]].push_back(in[v]);
33     }
34 }
35
36 int get(int u, int x = 0) {
37     if (u == p[u]) return x ? -1 : u;
38     int v = get(p[u], x + 1);
39     if (v < 0) return u;
40     if (sdom[cmn[p[u]]] < sdom[cmn[u]]) cmn[u] = cmn[←
41         [p[u]];
42     p[u] = v;
43     return x ? v : cmn[u];
44 }
45
46 void uni(int u, int v) {
47     p[v] = u;
48 }
49
50 void calc() {
51     for (int i = 0; i < n; i++) {
52         in[i] = -1;
53         adom[i] = -1;
54         dom[i] = sdom[i] = p[i] = cmn[i] = i;
55         vct[i].clear();
56         g[i].clear();
57     }
58     tmr = 0;
59     dfs(0);
60     for (int i = tmr - 1; i >= 0; i--) {
61         for (int to : g[i]) sdom[i] = min(sdom[i], ←
62             sdom[get(to)]);
63         if (i > 0) vct[sdom[i]].push_back(i);
64         for (int w : vct[i]) {
65             int v = get(w);
66             if (sdom[v] == sdom[w]) dom[w] = sdom[w];
67             else dom[w] = v;
68         }
69         if (i > 0) uni(par[i], i);
70     }
71     for (int i = 1; i < tmr; i++) {
72         if (dom[i] != sdom[i]) dom[i] = dom[dom[i]];
73         adom[rin[i]] = rin[dom[i]];
74     }
75 }

```

final/graphs/fenwick-min.cpp

```

1 const int inf = 1.01e9;
2 const int maxn = 1e5;
3
4 namespace fenwick
5 {
6     const int N = maxn + 1;
7
8     int a[N], l[N], r[N];
9
10 void modify(int q, int v) {
11     q++;
12     a[q] = min(a[q], v);
13     int x = q;
14     while (x < N) {
15         l[x] = min(l[x], v);
16         x = (x | (x - 1)) + 1;
17     }
18     x = q;
19     while (x > 0) {
20         r[x] = min(r[x], v);
21         x &= x - 1;
22     }
23 }
24
25 int find_min(int ll, int rr) {
26     ll++;
27     rr++;
28     int res = inf;
29     int x = ll;
30     while ((x | (x - 1)) + 1 <= rr) {
31         res = min(res, r[x]);

```

```

32     x = (x | (x - 1)) + 1;
33 }
34 res = min(res, a[x]);
35 x = rr;
36 while ((x & (x - 1)) >= ll) {
37     res = min(res, l[x]);
38     x &= x - 1;
39 }
40 return res;
41 }
42
43 // indexes 0 .. maxn-1
44 // (!) to init fill (a, l, r) with INF
45 // (!) modify supports only decreasing of the ←
46     value
47 // find_min [l, r] (both inclusive)

```

final/graphs/generalMatching.cpp

```

1 //COPYPASTED FROM E-MAXX
2 namespace GeneralMatching {
3     const int MAXN = 256;
4     int n;
5     vector<int> g[MAXN];
6     int match[MAXN], p[MAXN], base[MAXN], q[MAXN];
7     bool used[MAXN], blossom[MAXN];
8
9     int lca (int a, int b) {
10         bool used[MAXN] = { 0 };
11         for (;;) {
12             a = base[a];
13             used[a] = true;
14             if (match[a] == -1) break;
15             a = p[match[a]];
16         }
17         for (;;) {
18             b = base[b];
19             if (used[b]) return b;
20             b = p[match[b]];
21         }
22     }
23
24 void mark_path (int v, int b, int children) {
25     while (base[v] != b) {
26         blossom[base[v]] = blossom[base[match[v]]] = ←
27             true;
28         p[v] = children;
29         children = match[v];
30         v = p[match[v]];
31     }
32 }
33
34 int find_path (int root) {
35     memset (used, 0, sizeof used);
36     memset (p, -1, sizeof p);
37     for (int i=0; i<n; ++i)
38         base[i] = i;
39
40     used[root] = true;
41     int qh=0, qt=0;
42     q[qt++] = root;
43     while (qh < qt) {
44         int v = q[qh++];
45         for (size_t i=0; i<g[v].size(); ++i) {
46             int to = g[v][i];
47             if (base[v] == base[to] || match[v] == to) ←
48                 continue;
49             if (to == root || (match[to] != -1 && p[←
50                 match[to]] != -1)) {
51                 int curbase = lca (v, to);
52                 memset (blossom, 0, sizeof blossom);
53                 mark_path (v, curbase, to);
54                 mark_path (to, curbase, v);
55                 for (int i=0; i<n; ++i)
56                     if (blossom[base[i]]) {
57                         base[i] = curbase;
58                         if (!used[i]) {
59                             used[i] = true;
60                             q[qt++] = i;
61                         }
62                     }
63             }
64             else if (p[to] == -1) {
65                 p[to] = v;
66                 if (match[to] == -1)
67                     return to;

```

```

65         to = match[to];
66         used[to] = true;
67         q[qt++] = to;
68     }
69 }
70 }
71 return -1;
72 }
73
74 vector<pair<int, int>> solve(int _n, vector<pair<int, int>> edges) {
75     n = _n;
76     for (int i = 0; i < n; i++) g[i].clear();
77     for (auto o : edges) {
78         g[o.first].push_back(o.second);
79         g[o.second].push_back(o.first);
80     }
81     memset (match, -1, sizeof match);
82     for (int i=0; i<n; ++i) {
83         if (match[i] == -1) {
84             int v = find_path (i);
85             while (v != -1) {
86                 int pv = p[v], ppv = match[pv];
87                 match[v] = pv, match[pv] = v;
88                 v = ppv;
89             }
90         }
91     }
92     vector<pair<int, int>> ans;
93     for (int i = 0; i < n; i++) {
94         if (match[i] > i) {
95             ans.push_back(make_pair(i, match[i]));
96         }
97     }
98     return ans;
99 }
100 }

```

final/graphs/heavyLight.cpp

```

1 namespace hld {
2     const int N = 1 << 17;
3     int par[N], heavy[N], h[N];
4     int root[N], pos[N];
5     int n;
6     vector<vector<int>> e;
7     segtree tree;
8
9     int dfs(int v) {
10         int sz = 1, mx = 0;
11         for (int to : e[v]) {
12             if (to == par[v]) continue;
13             par[to] = v;
14             h[to] = h[v] + 1;
15             int cur = dfs(to);
16             if (cur > mx) heavy[v] = to, mx = cur;
17             sz += cur;
18         }
19         return sz;
20     }
21
22     template <typename T>
23     void path(int u, int v, T op) {
24         for (; root[u] != root[v]; v = par[root[v]]) {
25             if (h[root[u]] > h[root[v]]) swap(u, v);
26             op(pos[root[v]], pos[v] + 1);
27         }
28         if (h[u] > h[v]) swap(u, v);
29         op(pos[u], pos[v] + 1);
30     }
31
32     void init(vector<vector<int>> _e) {
33         e = _e;
34         n = e.size();
35         tree = segtree(n);
36         memset(heavy, -1, sizeof(heavy[0]) * n);
37         par[0] = -1;
38         h[0] = 0;
39         dfs(0);
40         for (int i = 0, cpos = 0; i < n; i++) {
41             if (par[i] == -1 || heavy[par[i]] != i) {
42                 for (int j = i; j != -1; j = heavy[j]) {
43                     root[j] = i;
44                     pos[j] = cpos++;
45                 }
46             }
47         }
48     }
49 }

```

```

48     }
49
50     void add(int v, int x) {
51         tree.add(pos[v], x);
52     }
53
54     int get(int u, int v) {
55         int res = 0;
56         path(u, v, [&](int l, int r) {
57             res = max(res, tree.get(l, r));
58         });
59         return res;
60     }
61 }

```

final/graphs/hungary.cpp

```

1 namespace hungary
2 {
3     const int N = 210;
4
5     int a[N][N];
6     int ans[N];
7
8     int calc(int n, int m)
9     {
10         ++n, ++m;
11         vi u(n), v(m), p(m), prev(m);
12         for (int i = 1; i < n; ++i)
13         {
14             p[0] = i;
15             int x = 0;
16             vi mn(m, inf);
17             vi was(m, 0);
18             while (p[x])
19             {
20                 was[x] = 1;
21                 int ii = p[x], dd = inf, y = 0;
22                 for (int j = 1; j < m; ++j) if (!was[j])
23                 {
24                     int cur = a[ii][j] - u[ii] - v[j];
25                     if (cur < mn[j]) mn[j] = cur, prev[j] = x;
26                     if (mn[j] < dd) dd = mn[j], y = j;
27                 }
28                 forn(j, m)
29                 {
30                     if (was[j]) u[p[j]] += dd, v[j] -= dd;
31                     else mn[j] -= dd;
32                 }
33                 x = y;
34             }
35             while (x)
36             {
37                 int y = prev[x];
38                 p[x] = p[y];
39                 x = y;
40             }
41         }
42         for (int j = 1; j < m; ++j)
43         {
44             ans[p[j]] = j;
45         }
46         return -v[0];
47     }
48
49     // HOW TO USE ::
50     // — set values to a[1..n][1..m] (n <= m)
51     // — run calc(n, m) to find MINIMUM
52     // — to restore permutation use ans[]
53     // — everything works on negative numbers
54     // !! i don't understand this code, it's ←
55     // cypasted from e-maxx (and rewritten by enot110←)
56 }

```

final/graphs/max-flow-min-cost.cpp

```

1 namespace flow
2 {
3     const int maxn = 2e5 + 10;
4     const int maxe = 2 * maxn;
5 }

```

```

5
6 int head[maxn], next[maxe], to[maxe], flow[maxe], ←
  cost[maxe], ec = 1;
7 int ST, EN, N = maxn;
8
9 inline void setN(int n)
10 {
11     ST = n;
12     EN = n + 1;
13     N = n + 2;
14 }
15
16 inline void _add(int x, int y, int f, int c)
17 {
18     ++ec;
19     to[ec] = y;
20     next[ec] = head[x];
21     head[x] = ec;
22     flow[ec] = f;
23     cost[ec] = c;
24 }
25
26 inline int add(int x, int y, int f, int c)
27 {
28     _add(x, y, f, c);
29     _add(y, x, 0, -c);
30     return ec - 1;
31 }
32
33 void clear()
34 {
35     forn(i, N) head[i] = 0;
36     ec = 1;
37 }
38
39 ll d[maxn], p[maxn];
40 int last[maxn];
41 int used[maxn];
42
43 pair<ll, ll> _calc(int flag)
44 {
45     const ll INF = 1e12;
46     forn(i, N) p[i] = INF;
47     p[ST] = 0;
48     forn(_, N) forn(x, N) for (int e = head[x]; e; e ←
49         = next[e]) if (flow[e] > 0)
50     {
51         int y = to[e];
52         if (p[y] > p[x] + cost[e])
53         {
54             p[y] = p[x] + cost[e];
55         }
56     }
57     ll resFlow = 0, resCost = 0;
58     while (1)
59     {
60         forn(i, N) d[i] = INF, used[i] = 0;
61         d[ST] = 0;
62         forn(_, N)
63         {
64             int x = -1;
65             forn(i, N) if (!used[i] && (x == -1 || d[x] ←
66                 > d[i])) x = i;
67             used[x] = 1;
68             if (d[x] == INF) break;
69             for (int e = head[x]; e; e = next[e]) if (←
70                 flow[e] > 0)
71             {
72                 int y = to[e];
73                 ll len = cost[e] + p[x] - p[y];
74                 if (d[y] > d[x] + len)
75                 {
76                     d[y] = d[x] + len;
77                     last[y] = e;
78                 }
79             }
80             if (d[EN] == INF) break;
81
82             ll realCost = d[EN] + p[EN] - p[ST];
83             if (flag && realCost > 0) break;
84
85             int pushed = inf;
86             int x = EN;
87             while (x != ST)
88             {
89                 int e = last[x];
90                 pushed = min(pushed, flow[e]);
91                 x = to[e ^ 1];
92             }
93

```

```

94     resCost += realCost * pushed;
95     resFlow += pushed;
96
97     x = EN;
98     while (x != ST)
99     {
100         int e = last[x];
101         flow[e] -= pushed;
102         flow[e ^ 1] += pushed;
103         x = to[e ^ 1];
104     }
105
106     forn(i, N) p[i] += d[i];
107 }
108 return mp(resFlow, resCost);
109 }
110
111 pair<ll, ll> maxFlow()
112 {
113     return _calc(0);
114 }
115
116 pair<ll, ll> minCost()
117 {
118     return _calc(1);
119 }
120
121 // HOW TO USE::
122 // — add adges using add(x, y, f, c), call setN(n ←
123 // — run maxFlow/minCost, returns pair(flow, cost ←
124 }

```

final/graphs/retro.cpp

```

1 namespace retro
2 {
3     const int N = 4e5 + 10;
4
5     vi v[N];
6     vi vrev[N];
7
8     void add(int x, int y)
9     {
10         v[x].pb(y);
11         vrev[y].pb(x);
12     }
13
14     const int UD = 0;
15     const int WIN = 1;
16     const int LOSE = 2;
17
18     int res[N];
19     int moves[N];
20     int deg[N];
21     int q[N], st, en;
22
23     void calc(int n)
24     {
25         forn(i, n) deg[i] = sz(v[i]);
26         st = en = 0;
27         forn(i, n) if (!deg[i])
28         {
29             q[en++] = i;
30             res[i] = LOSE;
31         }
32         while (st < en)
33         {
34             int x = q[st++];
35             for (int y : vrev[x])
36             {
37                 if (res[y] == UD && (res[x] == LOSE || (←
38                     deg[y] == 0 && res[x] == WIN)))
39                 {
40                     res[y] = 3 - res[x];
41                     moves[y] = moves[x] + 1;
42                     q[en++] = y;
43                 }
44             }
45         }
46     }

```

final/graphs/smith.cpp

```

1  const int N = 1e5 + 10;
2
3  struct graph
4  {
5      int n;
6
7      vi v[N];
8      vi vrev[N];
9
10     void read()
11     {
12         int m;
13         scanf("%d%d", &n, &m);
14         forn(i, m)
15         {
16             int x, y;
17             scanf("%d%d", &x, &y);
18             --x, --y;
19             v[x].pb(y);
20             vrev[y].pb(x);
21         }
22     }
23
24     int deg[N], cnt[N], used[N], f[N];
25     int q[N], st, en;
26
27     set<int> s[N];
28
29     void calc()
30     {
31         forn(x, n) f[x] = -1, cnt[x] = 0;
32         int val = 0;
33         while (1)
34         {
35             st = en = 0;
36             forn(x, n)
37             {
38                 deg[x] = 0;
39                 used[x] = 0;
40                 for (int y : v[x]) if (f[y] == -1) deg[x]++;
41             }
42             forn(x, n) if (!deg[x] && f[x] == -1 && cnt[x] <= val)
43             {
44                 q[en++] = x;
45                 f[x] = val;
46             }
47             if (!en) break;
48             while (st < en)
49             {
50                 int x = q[st];
51                 st++;
52                 for (int y : vrev[x])
53                 {
54                     if (used[y] == 0 && f[y] == -1)
55                     {
56                         used[y] = 1;
57                         cnt[y]++;
58                         for (int z : vrev[y])
59                         {
60                             deg[z]--;
61                             if (f[z] == -1 && deg[z] == 0 && cnt[z] <= val)
62                             {
63                                 f[z] = val;
64                                 q[en++] = z;
65                             }
66                         }
67                     }
68                 }
69                 val++;
70             }
71         }
72         forn(x, n) eprintf("%d%c", f[x], " \n"[x + 1 == n]);
73         forn(x, n) if (f[x] == -1)
74         {
75             for (int y : v[x]) if (f[y] != -1) s[x].insert(f[y]);
76         }
77     }
78     g1, g2;
79
80     string get(int x, int y)
81     {
82         int f1 = g1.f[x], f2 = g2.f[y];
83         if (f1 == -1 && f2 == -1) return "draw";
84         if (f1 == -1) {

```

```

85         if (g1.s[x].count(f2)) return "first";
86         return "draw";
87     }
88     if (f2 == -1) {
89         if (g2.s[y].count(f1)) return "first";
90         return "draw";
91     }
92     if (f1 ^ f2) return "first";
93     return "second";
94 }

```

final/graphs/twoChinese.cpp

```

1  const int INF = 1e9;
2  struct Edge {
3      int from, to, w, id;
4  };
5  namespace dmst {
6      int n;
7      vector<int> p;
8      vector<Edge> edges;
9
10     int get(int x) {
11         if (x == p[x]) return x;
12         return p[x] = get(p[x]);
13     }
14
15     void uni(int u, int v) {
16         p[get(v)] = get(u);
17     }
18
19     vector<Edge> solve() {
20         vector<int> id(n, -1);
21         vector<int> vert;
22         int cn = 0;
23         for (int i = 0; i < n; i++) if (get(i) == i) {
24             vert.push_back(i);
25             id[i] = cn++;
26         }
27         if (cn == 1) return vector<Edge>();
28
29         vector<vector<int>> e(cn);
30         for (int i = 0; i < (int)edges.size(); i++) {
31             if (get(edges[i].to) != get(edges[i].from)) {
32                 e[id[get(edges[i].to)]].push_back(i);
33             }
34         }
35
36         vector<int> nxtId(cn, -1);
37         for (int i = 0; i < cn; i++) {
38             int mn = INF;
39             for (int id : e[i]) mn = min(mn, edges[id].w);
40             for (int id : e[i]) {
41                 edges[id].w -= mn;
42                 if (edges[id].w == 0) nxtId[i] = id;
43             }
44         }
45
46         vector<char> vis(cn);
47         vis[0] = 1;
48         int cur = 1;
49         while (!vis[cur]) {
50             vis[cur] = 1;
51             cur = id[get(edges[nxtId[cur]].from)];
52         }
53         vector<Edge> ans;
54         if (cur == 0) {
55             for (int i = 0; i < cn; i++) {
56                 if (vis[i] && i != 0) {
57                     ans.push_back(edges[nxtId[i]]);
58                     uni(0, vert[i]);
59                 }
60             }
61             auto nans = solve();
62             for (auto ee : nans) ans.push_back(ee);
63             return ans;
64         }
65         vector<int> cp = p;
66         int o = cur;
67         while (1) {
68             uni(vert[o], vert[cur]);
69             ans.push_back(edges[nxtId[cur]]);
70             int to = id[get(edges[nxtId[cur]].from)];
71             if (to == o) break;
72             cur = to;
73         }
74         vector<Edge> nedges = solve();

```

```

75     p = cp;
76     vector<char> covered(cn);
77     for (auto ee : nedges) covered[id[get(ee.to)]] ←
78         1;
79     for (auto ee : ans) if (!covered[id[get(ee.to)]] ←
80         []) nedges.push_back(ee);
81     return nedges;
82 }
83 // root is 0
84 vector<Edge> getMst(int _n, vector<Edge> _edges) {
85     n = _n;
86     edges = _edges;
87     p.resize(n);
88     for (int i = 0; i < n; i++) p[i] = i;
89     return solve();
90 }
91 }

```

final/graphs/linkcut.cpp

```

1  #include <iostream>
2  #include <cstdio>
3  #include <cassert>
4
5  using namespace std;
6
7  // BEGIN ALGO
8
9  const int MAXN = 110000;
10
11  typedef struct _node{
12     _node *l, *r, *p, *pp;
13     int size; bool rev;
14     _node();
15     explicit _node(nullptr_t){
16         l = r = p = pp = this;
17         size = rev = 0;
18     }
19     void push(){
20         if (rev){
21             l->rev ^= 1; r->rev ^= 1;
22             rev = 0; swap(l,r);
23         }
24     }
25     void update();
26 }* node;
27 node None = new _node(nullptr);
28 node v2n[MAXN];
29 _node::_node(){
30     l = r = p = pp = None;
31     size = 1; rev = false;
32 }
33 void _node::update(){
34     size = (this != None) + l->size + r->size;
35     l->p = r->p = this;
36 }
37 void rotate(node v){
38     assert(v != None && v->p != None);
39     assert(!v->rev); assert(!v->p->rev);
40     node u = v->p;
41     if (v == u->l)
42         u->l = v->r, v->r = u;
43     else
44         u->r = v->l, v->l = u;
45     swap(u->p, v->p); swap(v->pp, u->pp);
46     if (v->p != None){
47         assert(v->p->l == u || v->p->r == u);
48         if (v->p->r == u) v->p->r = v;
49         else v->p->l = v;
50     }
51     u->update(); v->update();
52 }
53 void bigRotate(node v){
54     assert(v->p != None);
55     v->p->p->push();
56     v->p->push();
57     v->push();
58     if (v->p->p != None){
59         if ((v->p->l == v) ^ (v->p->p->r == v->p))
60             rotate(v->p);
61         else
62             rotate(v);
63     }
64     rotate(v);
65 }

```

```

66 inline void Splay(node v){
67     while (v->p != None) bigRotate(v);
68 }
69 inline void splitAfter(node v){
70     v->push();
71     Splay(v);
72     v->r->p = None;
73     v->r->pp = v;
74     v->r = None;
75     v->update();
76 }
77 void expose(int x){
78     node v = v2n[x];
79     splitAfter(v);
80     while (v->pp != None){
81         assert(v->p == None);
82         splitAfter(v->pp);
83         assert(v->pp->r == None);
84         assert(v->pp->p == None);
85         assert(!v->pp->rev);
86         v->pp->r = v;
87         v->pp->update();
88         v = v->pp;
89         v->r->pp = None;
90     }
91     assert(v->p == None);
92     Splay(v2n[x]);
93 }
94 inline void makeRoot(int x){
95     expose(x);
96     assert(v2n[x]->p == None);
97     assert(v2n[x]->pp == None);
98     assert(v2n[x]->r == None);
99     v2n[x]->rev ^= 1;
100 }
101 inline void link(int x, int y){
102     makeRoot(x); v2n[x]->pp = v2n[y];
103 }
104 inline void cut(int x, int y){
105     expose(x);
106     Splay(v2n[y]);
107     if (v2n[y]->pp != v2n[x]){
108         swap(x,y);
109         expose(x);
110         Splay(v2n[y]);
111         assert(v2n[y]->pp == v2n[x]);
112     }
113     v2n[y]->pp = None;
114 }
115 inline int get(int x, int y){
116     if (x == y) return 0;
117     makeRoot(x);
118     expose(y); expose(x);
119     Splay(v2n[y]);
120     if (v2n[y]->pp != v2n[x]) return -1;
121     return v2n[y]->size;
122 }
123 // END ALGO
124
125 _node mem[MAXN];
126
127
128 int main(){
129     freopen("linkcut.in", "r", stdin);
130     freopen("linkcut.out", "w", stdout);
131
132     int n, m;
133     scanf("%d %d", &n, &m);
134
135     for (int i = 0; i < n; i++)
136         v2n[i] = &mem[i];
137
138     for (int i = 0; i < m; i++){
139         int a, b;
140         if (scanf(" link %d %d", &a, &b) == 2)
141             link(a-1, b-1);
142         else if (scanf(" cut %d %d", &a, &b) == 2)
143             cut(a-1, b-1);
144         else if (scanf(" get %d %d", &a, &b) == 2)
145             printf("%d\n", get(a-1, b-1));
146         else
147             assert(false);
148     }
149     return 0;
150 }

```

```
dbl Simpson() { return (F(-1) + 4 * F(0) + F(1)) / 6;
} dbl Runge2() { return (F(sqrtl(1.0 / 3)) + F(sqrtl(1.0 /
3))) / 2; } dbl Runge3() { return (F(-sqrtl(3.0 / 5)) * 5 +
F(0) * 8 + F(sqrtl(3.0 / 5)) * 5) / 18; }
```

Simpson и Runge2 – точны для полиномов степени ≤ 3
Runge3 – точен для полиномов степени ≤ 5

—
Явный Рунге-Кутт четвертого порядка, ошибка $O(h^4)$

```
y' = f(x, y) y_(n+1) = y_n + (k1 + 2 * k2 + 2 * k3 +
k4) * h / 6
```

```
k1 = f(xn, yn) k2 = f(xn + h/2, yn + h/2 * k1) k3 =
f(xn + h/2, yn + h/2 * k2) k4 = f(xn + h, yn + h * k3)
```

Методы Адамса-Башфорта

```
y_n+3 = y_n+2 + h * (23/12 * f(x_n+2,y_n+2)
- 4/3 * f(x_n+1,y_n+1) + 5/12 * f(x_n,y_n)) y_n+4
= y_n+3 + h * (55/24 * f(x_n+3,y_n+3) - 59/24
* f(x_n+2,y_n+2) + 37/24 * f(x_n+1,y_n+1) - 3/8
* f(x_n,y_n)) y_n+5 = y_n+4 + h * (1901/720 *
f(x_n+4,y_n+4) - 1387/360 * f(x_n+3,y_n+3) + 109/30
* f(x_n+2,y_n+2) - 637/360 * f(x_n+1,y_n+1) +
251/720 * f(x_n,y_n))
```

—
Извлечение корня по простому модулю (от Сережи) $3 \leq p$, $1 \leq a < p$, найти $x^2 = a$

```
1) Если  $a^{((p-1)/2)} \neq 1$ , return -1 2) Выбрать слу-
чайный  $1 \leq i < p$  3)  $T(x) = (x+i)^{((p-1)/2)} \bmod (x^2
-a) = bx + c$  4) Если  $b \neq 0$  то вернуть  $c/b$ , иначе к шагу
2)
```

—
Иногда вместо того чтобы считать первообразный у простого числа, можно написать чекер ответа и перебирать случайный первообразный.

Не заходит FFT по TL-ю – чекнуть что стоит double, а не long double

mt19937 генерит случайный unsigned int, если хочется больше есть mt19937_64

Иногда можно представить ответ в виде многочлена и вместо подсчета самих k-тов посчитать значения и проинтерполировать

Перед сабмитом чекнуть что все выводится в printf, а не eprintf!!!

—
Лемма Бернсайда:

Группа G действует на множество X Тогда число классов эквивалентности $= (\sum |f(g)| \text{ for } g \text{ in } G) / |G|$ где $f(g)$ = число x (из X) : $g(x) = x$

—
Число простых быстрее $O(n)$:

```
dp(n, k) – число чисел от 1 до n в которых все простые
 $\geq p[k]$   $dp(n, 1) = n$   $dp(n, j) = dp(n, j+1) + dp(n / p[j], j)$ , т. е.  $dp(n, j+1) = dp(n, j) - dp(n / p[j], j)$ 
```

Если $p[j], p[k] > \sqrt{n}$ то $dp(n, j) + j == dp(n, k) + k$

Хуяришь все оптимайзы сверху, но не считаешь глубже $dp(n, k)$, $n < K$ Потом фенвиком+сортировкой подсчитываешь за $(K+Q)\log$ все эти запросы Хуяришь во второй раз, но на этот раз берешь прекальканные значения

Если $\sqrt{n} < p[k] < n$ то (число простых до n) $= dp(n, k) + k - 1$

—
Чиселки:

Фибоначчи 45: 1134903170 46: 1836311903
47: 2971215073 91: 4660046610375530309 92:
7540113804746346429 93: 12200160415121876738

Числа с кучей делителей 20: d(12)=6 50: d(48)=10
100: d(60)=12 1000: d(840)=32 10^4 : d(9240)=64 10^5 :
d(83160)=128 10^6 : d(720720)=240 10^7 : d(8648640)=448
 10^8 : d(91891800)=768 10^9 : d(931170240)=1344 10^{11} :
d(97772875200)=4032 10^{12} : d(963761198400)=6720
 10^{15} : d(866421317361600)=26880 10^{18} :
d(897612484786617600)=103680

Bell numbers: 0:1, 1:1, 2:2, 3:5, 4:15,
5:52, 6:203, 7:877, 8:4140, 9:21147, 10:115975,
11:678570, 12:4213597, 13:27644437, 14:190899322,
15:1382958545, 16:10480142147, 17:82864869804,
18:682076806159, 19:5832742205057, 20:51724158235372,
21:474869816156751, 22:4506715738447323,
23:44152005855084346

Catalan numbers: 0:1, 1:1, 2:2, 3:5, 4:14, 5:42,
6:132, 7:429, 8:1430, 9:4862, 10:16796, 11:58786,
12:208012, 13:742900, 14:2674440, 15:9694845,
16:35357670, 17:129644790, 18:477638700, 19:1767263190,
20:6564120420, 21:24466267020, 22:91482563640,
23:343059613650, 24:1289904147324, 25:4861946401452

Table of Integrals*

Basic Forms

$$\int x^n dx = \frac{1}{n+1} x^{n+1} \quad (1)$$

$$\int \frac{1}{x} dx = \ln |x| \quad (2)$$

$$\int u dv = uv - \int v du \quad (3)$$

$$\int \frac{1}{ax+b} dx = \frac{1}{a} \ln |ax+b| \quad (4)$$

Integrals of Rational Functions

$$\int \frac{1}{(x+a)^2} dx = -\frac{1}{x+a} \quad (5)$$

$$\int (x+a)^n dx = \frac{(x+a)^{n+1}}{n+1}, n \neq -1 \quad (6)$$

$$\int x(x+a)^n dx = \frac{(x+a)^{n+1}((n+1)x-a)}{(n+1)(n+2)} \quad (7)$$

$$\int \frac{1}{1+x^2} dx = \tan^{-1} x \quad (8)$$

$$\int \frac{1}{a^2+x^2} dx = \frac{1}{a} \tan^{-1} \frac{x}{a} \quad (9)$$

$$\int \frac{x}{a^2+x^2} dx = \frac{1}{2} \ln |a^2+x^2| \quad (10)$$

$$\int \frac{x^2}{a^2+x^2} dx = x - a \tan^{-1} \frac{x}{a} \quad (11)$$

$$\int \frac{x^3}{a^2+x^2} dx = \frac{1}{2} x^2 - \frac{1}{2} a^2 \ln |a^2+x^2| \quad (12)$$

$$\int \frac{1}{ax^2+bx+c} dx = \frac{2}{\sqrt{4ac-b^2}} \tan^{-1} \frac{2ax+b}{\sqrt{4ac-b^2}} \quad (13)$$

$$\int \frac{1}{(x+a)(x+b)} dx = \frac{1}{b-a} \ln \frac{a+x}{b+x}, a \neq b \quad (14)$$

$$\int \frac{x}{(x+a)^2} dx = \frac{a}{a+x} + \ln |a+x| \quad (15)$$

$$\int \frac{x}{ax^2+bx+c} dx = \frac{1}{2a} \ln |ax^2+bx+c| - \frac{b}{a\sqrt{4ac-b^2}} \tan^{-1} \frac{2ax+b}{\sqrt{4ac-b^2}} \quad (16)$$

Integrals with Roots

$$\int \sqrt{x-ax} dx = \frac{2}{3} (x-a)^{3/2} \quad (17)$$

$$\int \frac{1}{\sqrt{x \pm a}} dx = 2\sqrt{x \pm a} \quad (18)$$

$$\int \frac{1}{\sqrt{a-x}} dx = -2\sqrt{a-x} \quad (19)$$

$$\int x\sqrt{x-ax} dx = \frac{2}{3} a(x-a)^{3/2} + \frac{2}{5} (x-a)^{5/2} \quad (20)$$

$$\int \sqrt{ax+bdx} = \left(\frac{2b}{3a} + \frac{2x}{3} \right) \sqrt{ax+b} \quad (21)$$

$$\int (ax+b)^{3/2} dx = \frac{2}{5a} (ax+b)^{5/2} \quad (22)$$

$$\int \frac{x}{\sqrt{x \pm a}} dx = \frac{2}{3} (x \mp 2a) \sqrt{x \pm a} \quad (23)$$

$$\int \sqrt{\frac{x}{a-x}} dx = -\sqrt{x(a-x)} - a \tan^{-1} \frac{\sqrt{x(a-x)}}{x-a} \quad (24)$$

$$\int \sqrt{\frac{x}{a+x}} dx = \sqrt{x(a+x)} - a \ln [\sqrt{x} + \sqrt{x+a}] \quad (25)$$

$$\int x\sqrt{ax+bdx} = \frac{2}{15a^2} (-2b^2 + abx + 3a^2x^2) \sqrt{ax+b} \quad (26)$$

$$\int \sqrt{x(ax+b)} dx = \frac{1}{4a^{3/2}} \left[(2ax+b) \sqrt{ax(ax+b)} - b^2 \ln |a\sqrt{x} + \sqrt{a(ax+b)}| \right] \quad (27)$$

$$\int \sqrt{x^3(ax+b)} dx = \left[\frac{b}{12a} - \frac{b^2}{8a^2x} + \frac{x}{3} \right] \sqrt{x^3(ax+b)} + \frac{b^3}{8a^{5/2}} \ln |a\sqrt{x} + \sqrt{a(ax+b)}| \quad (28)$$

$$\int \sqrt{x^2 \pm a^2} dx = \frac{1}{2} x \sqrt{x^2 \pm a^2} \pm \frac{1}{2} a^2 \ln |x + \sqrt{x^2 \pm a^2}| \quad (29)$$

$$\int \sqrt{a^2 - x^2} dx = \frac{1}{2} x \sqrt{a^2 - x^2} + \frac{1}{2} a^2 \tan^{-1} \frac{x}{\sqrt{a^2 - x^2}} \quad (30)$$

$$\int x\sqrt{x^2 \pm a^2} dx = \frac{1}{3} (x^2 \pm a^2)^{3/2} \quad (31)$$

$$\int \frac{1}{\sqrt{x^2 \pm a^2}} dx = \ln |x + \sqrt{x^2 \pm a^2}| \quad (32)$$

$$\int \frac{1}{\sqrt{a^2 - x^2}} dx = \sin^{-1} \frac{x}{a} \quad (33)$$

$$\int \frac{x}{\sqrt{x^2 \pm a^2}} dx = \sqrt{x^2 \pm a^2} \quad (34)$$

$$\int \frac{x}{\sqrt{a^2 - x^2}} dx = -\sqrt{a^2 - x^2} \quad (35)$$

$$\int \frac{x^2}{\sqrt{x^2 \pm a^2}} dx = \frac{1}{2} x \sqrt{x^2 \pm a^2} \mp \frac{1}{2} a^2 \ln |x + \sqrt{x^2 \pm a^2}| \quad (36)$$

$$\int \sqrt{ax^2+bx+cdx} = \frac{b+2ax}{4a} \sqrt{ax^2+bx+c} + \frac{4ac-b^2}{8a^{3/2}} \ln |2ax+b+2\sqrt{a(ax^2+bx+c)}| \quad (37)$$

$$\int x\sqrt{ax^2+bx+c} = \frac{1}{48a^{5/2}} \left(2\sqrt{a}\sqrt{ax^2+bx+c} \times (-3b^2+2abx+8a(c+ax^2)) + 3(b^3-4abc) \ln |b+2ax+2\sqrt{a}\sqrt{ax^2+bx+c}| \right) \quad (38)$$

$$\int \frac{1}{\sqrt{ax^2+bx+c}} dx = \frac{1}{\sqrt{a}} \ln |2ax+b+2\sqrt{a(ax^2+bx+c)}| \quad (39)$$

$$\int \frac{x}{\sqrt{ax^2+bx+c}} dx = \frac{1}{a} \sqrt{ax^2+bx+c} - \frac{b}{2a^{3/2}} \ln |2ax+b+2\sqrt{a(ax^2+bx+c)}| \quad (40)$$

$$\int \frac{dx}{(a^2+x^2)^{3/2}} = \frac{x}{a^2\sqrt{a^2+x^2}} \quad (41)$$

Integrals with Logarithms

$$\int \ln ax dx = x \ln ax - x \quad (42)$$

$$\int \frac{\ln ax}{x} dx = \frac{1}{2} (\ln ax)^2 \quad (43)$$

$$\int \ln(ax+b) dx = \left(x + \frac{b}{a} \right) \ln(ax+b) - x, a \neq 0 \quad (44)$$

$$\int \ln(x^2+a^2) dx = x \ln(x^2+a^2) + 2a \tan^{-1} \frac{x}{a} - 2x \quad (45)$$

$$\int \ln(x^2-a^2) dx = x \ln(x^2-a^2) + a \ln \frac{x+a}{x-a} - 2x \quad (46)$$

$$\int \ln(ax^2+bx+c) dx = \frac{1}{a} \sqrt{4ac-b^2} \tan^{-1} \frac{2ax+b}{\sqrt{4ac-b^2}} - 2x + \left(\frac{b}{2a} + x \right) \ln(ax^2+bx+c) \quad (47)$$

$$\int x \ln(ax+b) dx = \frac{bx}{2a} - \frac{1}{4} x^2 + \frac{1}{2} \left(x^2 - \frac{b^2}{a^2} \right) \ln(ax+b) \quad (48)$$

$$\int x \ln(a^2-b^2x^2) dx = -\frac{1}{2} x^2 + \frac{1}{2} \left(x^2 - \frac{a^2}{b^2} \right) \ln(a^2-b^2x^2) \quad (49)$$

Integrals with Exponentials

$$\int e^{ax} dx = \frac{1}{a} e^{ax} \quad (50)$$

$$\int \sqrt{x} e^{ax} dx = \frac{1}{a} \sqrt{x} e^{ax} + \frac{i\sqrt{\pi}}{2a^{3/2}} \operatorname{erf}(i\sqrt{ax}),$$

where $\operatorname{erf}(x) = \frac{2}{\sqrt{\pi}} \int_0^x e^{-t^2} dt$ (51)

$$\int x e^x dx = (x-1)e^x \quad (52)$$

$$\int x e^{ax} dx = \left(\frac{x}{a} - \frac{1}{a^2} \right) e^{ax} \quad (53)$$

$$\int x^2 e^x dx = (x^2 - 2x + 2) e^x \quad (54)$$

$$\int x^2 e^{ax} dx = \left(\frac{x^2}{a} - \frac{2x}{a^2} + \frac{2}{a^3} \right) e^{ax} \quad (55)$$

$$\int x^3 e^x dx = (x^3 - 3x^2 + 6x - 6) e^x \quad (56)$$

$$\int x^n e^{ax} dx = \frac{x^n e^{ax}}{a} - \frac{n}{a} \int x^{n-1} e^{ax} dx \quad (57)$$

$$\int x^n e^{ax} dx = \frac{(-1)^n}{a^{n+1}} \Gamma[1+n, -ax],$$

where $\Gamma(a, x) = \int_x^\infty t^{a-1} e^{-t} dt$ (58)

$$\int e^{ax^2} dx = -\frac{i\sqrt{\pi}}{2\sqrt{a}} \operatorname{erf}(i\sqrt{a}x) \quad (59)$$

$$\int e^{-ax^2} dx = \frac{\sqrt{\pi}}{2\sqrt{a}} \operatorname{erf}(x\sqrt{a}) \quad (60)$$

$$\int x e^{-ax^2} dx = -\frac{1}{2a} e^{-ax^2} \quad (61)$$

$$\int x^2 e^{-ax^2} dx = \frac{1}{4} \sqrt{\frac{\pi}{a^3}} \operatorname{erf}(x\sqrt{a}) - \frac{x}{2a} e^{-ax^2} \quad (62)$$

*© 2014. From <http://integral-table.com>, last revised June 14, 2014. This material is provided as is without warranty or representation about the accuracy, correctness or suitability of the material for any purpose, and is licensed under the Creative Commons Attribution-NonCommercial-ShareAlike 3.0 United States License. To view a copy of this license, visit <http://creativecommons.org/licenses/by-nc-sa/3.0/> or send a letter to Creative Commons, 171 Second Street, Suite 300, San Francisco, California, 94105, USA.

Integrals with Trigonometric Functions

$$\int \sin ax dx = -\frac{1}{a} \cos ax \quad (63)$$

$$\int \sin^2 ax dx = \frac{x}{2} - \frac{\sin 2ax}{4a} \quad (64)$$

$$\int \sin^n ax dx = -\frac{1}{a} \cos ax {}_2F_1 \left[\frac{1}{2}, \frac{1-n}{2}, \frac{3}{2}, \cos^2 ax \right] \quad (65)$$

$$\int \sin^3 ax dx = -\frac{3 \cos ax}{4a} + \frac{\cos 3ax}{12a} \quad (66)$$

$$\int \cos ax dx = \frac{1}{a} \sin ax \quad (67)$$

$$\int \cos^2 ax dx = \frac{x}{2} + \frac{\sin 2ax}{4a} \quad (68)$$

$$\int \cos^p ax dx = -\frac{1}{a(1+p)} \cos^{1+p} ax \times {}_2F_1 \left[\frac{1+p}{2}, \frac{1}{2}, \frac{3+p}{2}, \cos^2 ax \right] \quad (69)$$

$$\int \cos^3 ax dx = \frac{3 \sin ax}{4a} + \frac{\sin 3ax}{12a} \quad (70)$$

$$\int \cos ax \sin bxdx = \frac{\cos[(a-b)x]}{2(a-b)} - \frac{\cos[(a+b)x]}{2(a+b)}, a \neq b \quad (71)$$

$$\int \sin^2 ax \cos bxdx = -\frac{\sin[(2a-b)x]}{4(2a-b)} + \frac{\sin bx}{2b} - \frac{\sin[(2a+b)x]}{4(2a+b)} \quad (72)$$

$$\int \sin^2 x \cos x dx = \frac{1}{3} \sin^3 x \quad (73)$$

$$\int \cos^2 ax \sin bxdx = \frac{\cos[(2a-b)x]}{4(2a-b)} - \frac{\cos bx}{2b} - \frac{\cos[(2a+b)x]}{4(2a+b)} \quad (74)$$

$$\int \cos^2 ax \sin ax dx = -\frac{1}{3a} \cos^3 ax \quad (75)$$

$$\int \sin^2 ax \cos^2 bxdx = \frac{x}{4} - \frac{\sin 2ax}{8a} - \frac{\sin[2(a-b)x]}{16(a-b)} + \frac{\sin 2bx}{8b} - \frac{\sin[2(a+b)x]}{16(a+b)} \quad (76)$$

$$\int \sin^2 ax \cos^2 ax dx = \frac{x}{8} - \frac{\sin 4ax}{32a} \quad (77)$$

$$\int \tan ax dx = -\frac{1}{a} \ln \cos ax \quad (78)$$

$$\int \tan^2 ax dx = -x + \frac{1}{a} \tan ax \quad (79)$$

$$\int \tan^n ax dx = \frac{\tan^{n+1} ax}{a(1+n)} \times {}_2F_1 \left(\frac{n+1}{2}, 1, \frac{n+3}{2}, -\tan^2 ax \right) \quad (80)$$

$$\int \tan^3 ax dx = \frac{1}{a} \ln \cos ax + \frac{1}{2a} \sec^2 ax \quad (81)$$

$$\int \sec x dx = \ln |\sec x + \tan x| = 2 \tanh^{-1} \left(\tan \frac{x}{2} \right) \quad (82)$$

$$\int \sec^2 ax dx = \frac{1}{a} \tan ax \quad (83)$$

$$\int \sec^3 x dx = \frac{1}{2} \sec x \tan x + \frac{1}{2} \ln |\sec x + \tan x| \quad (84)$$

$$\int \sec x \tan x dx = \sec x \quad (85)$$

$$\int \sec^2 x \tan x dx = \frac{1}{2} \sec^2 x \quad (86)$$

$$\int \sec^n x \tan x dx = \frac{1}{n} \sec^n x, n \neq 0 \quad (87)$$

$$\int \csc x dx = \ln \left| \tan \frac{x}{2} \right| = \ln |\csc x - \cot x| + C \quad (88)$$

$$\int \csc^2 ax dx = -\frac{1}{a} \cot ax \quad (89)$$

$$\int \csc^3 x dx = -\frac{1}{2} \cot x \csc x + \frac{1}{2} \ln |\csc x - \cot x| \quad (90)$$

$$\int \csc^n x \cot x dx = -\frac{1}{n} \csc^n x, n \neq 0 \quad (91)$$

$$\int \sec x \csc x dx = \ln |\tan x| \quad (92)$$

Products of Trigonometric Functions and Monomials

$$\int x \cos x dx = \cos x + x \sin x \quad (93)$$

$$\int x \cos ax dx = \frac{1}{a^2} \cos ax + \frac{x}{a} \sin ax \quad (94)$$

$$\int x^2 \cos x dx = 2x \cos x + (x^2 - 2) \sin x \quad (95)$$

$$\int x^2 \cos ax dx = \frac{2x \cos ax}{a^2} + \frac{a^2 x^2 - 2}{a^3} \sin ax \quad (96)$$

$$\int x^n \cos x dx = -\frac{1}{2} (i)^{n+1} [\Gamma(n+1, -ix) + (-1)^n \Gamma(n+1, ix)] \quad (97)$$

$$\int x^n \cos ax dx = \frac{1}{2} (ia)^{1-n} [(-1)^n \Gamma(n+1, -iax) - \Gamma(n+1, iax)] \quad (98)$$

$$\int x \sin x dx = -x \cos x + \sin x \quad (99)$$

$$\int x \sin ax dx = -\frac{x \cos ax}{a} + \frac{\sin ax}{a^2} \quad (100)$$

$$\int x^2 \sin x dx = (2 - x^2) \cos x + 2x \sin x \quad (101)$$

$$\int x^2 \sin ax dx = \frac{2 - a^2 x^2}{a^3} \cos ax + \frac{2x \sin ax}{a^2} \quad (102)$$

$$\int x^n \sin x dx = -\frac{1}{2} (i)^n [\Gamma(n+1, -ix) - (-1)^n \Gamma(n+1, -ix)] \quad (103)$$

Products of Trigonometric Functions and Exponentials

$$\int e^x \sin x dx = \frac{1}{2} e^x (\sin x - \cos x) \quad (104)$$

$$\int e^{bx} \sin ax dx = \frac{1}{a^2 + b^2} e^{bx} (b \sin ax - a \cos ax) \quad (105)$$

$$\int e^x \cos x dx = \frac{1}{2} e^x (\sin x + \cos x) \quad (106)$$

$$\int e^{bx} \cos ax dx = \frac{1}{a^2 + b^2} e^{bx} (a \sin ax + b \cos ax) \quad (107)$$

$$\int x e^x \sin x dx = \frac{1}{2} e^x (\cos x - x \cos x + x \sin x) \quad (108)$$

$$\int x e^x \cos x dx = \frac{1}{2} e^x (x \cos x - \sin x + x \sin x) \quad (109)$$

Integrals of Hyperbolic Functions

$$\int \cosh ax dx = \frac{1}{a} \sinh ax \quad (110)$$

$$\int e^{ax} \cosh bxdx = \begin{cases} \frac{e^{ax}}{a^2 - b^2} [a \cosh bx - b \sinh bx] & a \neq b \\ \frac{e^{2ax}}{4a} + \frac{x}{2} & a = b \end{cases} \quad (111)$$

$$\int \sinh ax dx = \frac{1}{a} \cosh ax \quad (112)$$

$$\int e^{ax} \sinh bxdx = \begin{cases} \frac{e^{ax}}{a^2 - b^2} [-b \cosh bx + a \sinh bx] & a \neq b \\ \frac{e^{2ax}}{4a} - \frac{x}{2} & a = b \end{cases} \quad (113)$$

$$\int e^{ax} \tanh bxdx = \begin{cases} \frac{e^{(a+2b)x}}{(a+2b)} {}_2F_1 \left[1 + \frac{a}{2b}, 1, 2 + \frac{a}{2b}, -e^{2bx} \right] - \frac{1}{a} e^{ax} {}_2F_1 \left[\frac{a}{2b}, 1, 1E, -e^{2bx} \right] & a \neq b \\ \frac{e^{ax} - 2 \tan^{-1}[e^{ax}]}{a} & a = b \end{cases} \quad (114)$$

$$\int \tanh ax dx = \frac{1}{a} \ln \cosh ax \quad (115)$$

$$\int \cos ax \cosh bxdx = \frac{1}{a^2 + b^2} [a \sin ax \cosh bx + b \cos ax \sinh bx] \quad (116)$$

$$\int \cos ax \sinh bxdx = \frac{1}{a^2 + b^2} [b \cos ax \cosh bx + a \sin ax \sinh bx] \quad (117)$$

$$\int \sin ax \cosh bxdx = \frac{1}{a^2 + b^2} [-a \cos ax \cosh bx + b \sin ax \sinh bx] \quad (118)$$

$$\int \sin ax \sinh bxdx = \frac{1}{a^2 + b^2} [b \cosh bx \sin ax - a \cos ax \sinh bx] \quad (119)$$

$$\int \sinh ax \cosh ax dx = \frac{1}{4a} [-2ax + \sinh 2ax] \quad (120)$$

$$\int \sinh ax \cosh bxdx = \frac{1}{b^2 - a^2} [b \cosh bx \sinh ax - a \cosh ax \sinh bx] \quad (121)$$