

VIDEO TUTORIAL



Important!

This replacement procedure can be used for:
BMW X5 (E53) 3.0 d, BMW X5 (E53) 3.0 i

The steps may slightly vary depending on the car design.

REPLACEMENT: BRAKE CALIPER – BMW X5 E53. TOOLS YOU NEED:



- Wire brush
- WD-40 spray
- Brake cleaner
- Copper grease
- Brake caliper guide pins grease
- HEX bit no.H7.
- Flare nut spanner №11
- Wheel impact socket #17
- Ratchet wrench
- Torque wrench
- Flat Screwdriver
- Crow bar
- Brake hose clip
- Brake bleeder kit
- Wheel chock

BUY TOOLS

Replacement: brake caliper – BMW X5 E53. Tip from AUTODOC experts:

- The replacement procedure is identical for the left and right brake calipers on the same axle.
- All work should be done with the engine stopped.

REPLACEMENT: BRAKE CALIPER – BMW X5 E53. USE THE FOLLOWING PROCEDURE:


- 1** Open the bonnet. Unscrew the brake fluid reservoir cap.



- 2** Secure the wheels with chocks.



- 3** Loosen the wheel mounting bolts. Use wheel impact socket #17.



4 Raise the rear of the car and secure on supports.

5 Unscrew the wheel bolts.




AUTODOC recommends:

- Important! Hold the wheel while unscrewing the fastening bolts. BMW X5 E53


6 Remove the wheel.



7.1 Detach the brake caliper retaining spring.



7.2 Use a flat screwdriver.




8 Disconnect the brake pad wear sensor cable.




Please note!

- Some cars are not equipped with the brake pad wear sensor.

9 Remove the dust boot caps of the brake caliper guide pins. Use a flat screwdriver.



10 Clean the area where the brake hose is connected to the caliper, and the guide pins area. Use a brake cleaner.



Replacement: brake caliper – BMW X5 E53. AUTODOC recommends:

- After applying the spray, wait a few minutes.

11

Clamp the brake hose off using a brake hose clamp.



12


Loosen the brake hose fastening. Use a flare nut spanner #11.

13

Clean the brake caliper fasteners. Use a wire brush. Use WD-40 spray.


14

Unscrew the brake caliper fastening. Use HEX No.H7. Use a ratchet wrench.




15

Remove the guide pins from the brake caliper.




16

Spread the brake pads. Use a crowbar.



17


Remove the brake caliper.



Replacement: brake caliper – BMW X5 E53. Professionals recommend:


- When replacing the brake caliper, it is recommended to check the brake hose for damages and, if necessary, to replace it with a new one.
- When replacing a brake caliper it is recommended to replace brake pads, check the state of the brake discs and replace them with new ones if necessary.
- Check the brake caliper bracket, brake caliper guide pins and boots. Clean them. Replace, if necessary.
- Don't press the brake pedal after the brake caliper has been removed. As a result, the piston can fall out from the brake cylinder, and brake fluid leakage and depressurization of the system may occur.

18 Remove the brake pads.




19 Disconnect the brake pads wear sensor. Use a flat screwdriver.

20 Unscrew the brake hose from the brake caliper. Use a flare nut spanner #11.



21 Disconnect the brake hose.




22 Treat the brake hose. Use a brake cleaner.

AUTODOC recommends:

- Replacement: brake caliper – BMW X5 E53. After applying the spray, wait a few minutes.


23

Install and fix the brake hose into a new caliper.



24

Tighten the fastener connecting the brake pipe to the brake caliper. Use a flare nut spanner #11. Use a torque wrench. Tighten it to 40 Nm torque.




25

Remove the brake hose clamp.

26

Connect the brake pads wear sensor.



27


Install the brake pads.

Replacement: brake caliper – BMW X5 E53. Tip:

- If going to use the old brake pads, clean them.

28

Install the brake caliper and fix it.



29

Clean the brake caliper guide pins.



30

Lubricate guide pins with special brake grease.

Replacement: brake caliper – BMW X5 E53. AUTODOC recommends:

- If no new guide pins were supplied in a kit with the new brake calipers, use the old pins.

31

Screw in the guide pins.

