

VIDEO TUTORIAL



important!

This replacement procedure can be used for:

BMW 3 Saloon (E46) 328i 2.8, BMW 3 Saloon (E46) 320d 2.0, BMW 3 Saloon (E46) 323i 2.5, BMW 3 Saloon (E46) 320i 2.0, BMW 3 Coupe (E46) 323Ci 2.5, BMW 3 Coupe (E46) 328Ci 2.8, BMW X3 (E83) xDrive 20 d, BMW X3 (E83) xDrive 30 d, BMW 3 Saloon (E46) 316i 1.9, BMW 3 Touring (E46) 320i 2.0, BMW 3 Coupe (E46) 320Ci 2.0, BMW 3 Coupe (E46) 318Ci 1.9, BMW 3 Touring (E46) 318i 1.9, BMW 3 Touring (E46) 328i 2.8, BMW 3 Touring (E46) 320d 2.0, (+63)

The steps may slightly vary depending on the car design.

CLUB.AUTODOC.CO.UK 1-8









• Fender cover

BUY TOOLS

CLUB.AUTODOC.CO.UK 2-8





- Replace the cabin filter at least once every six months, in early spring and autumn seasons.
- Follow the terms, recommendations and requirements of the part operation provided by the manufacturer.
- If the air flow into the cabin has sharply reduced, replace the filter before a scheduled maintenance.
- All work should be done with the engine stopped.

REPLACEMENT: POLLEN FILTER – BMW E46. TAKE THE FOLLOWING STEPS:

1 Open the hood.



- Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.
- 3 Slide the filter cover clips.



CLUB.AUTODOC.CO.UK 3-8







Raise a little the cabin filter housing cover.



Remove the filter element from the filter housing.



Replacement: pollen filter – BMW E46. Tip:

- To avoid damaging the cabin filter cover, do not remove it before removing the filtering element.
- Clean the cabin filter housing and cover.

Replacement: pollen filter – BMW E46. AUTODOC experts recommend:

- Remove any debris from the cabin filter housing carefully to prevent contamination of the ventilation duct.
- Do not attempt to clean and reuse the filter it will affect the quality of air cleaning inside the car.

CLUB.AUTODOC.CO.UK 4-8







Insert a new filter element into the filter housing. Make sure that the filter edge fits tight to the housing.



Replacement: pollen filter – BMW E46. Tip from AUTODOC experts:

- Follow the air flow direction arrow on the filter.
- Check out the correct location of the filter element. Do not skew.
- Take care to only use quality filters.

Reinstall the cabin filter housing cover.



9 Install the clips.



CLUB.AUTODOC.CO.UK 5-8







Remove the fender protection cover. Close the hood.




- Switch on the ignition. Switch on the air conditioning system. This is necessary in order to make sure that the component operates properly.
- Switch off the ignition.





VIEW MORE TUTORIALS

CLUB.AUTODOC.CO.UK 6-8





AUTODOC — TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE



A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR BMW

POLLEN FILTER: A WIDE SELECTION

CLUB.AUTODOC.CO.UK 7-8