

Лабораторная работа №4

Первоначальное конфигурирование сети

Джахангиров Илгар Залид оглы

Российский университет дружбы народов, Москва, Россия

Информация

- Джахангиров Илгар Залид оглы
- студент
- Российский университет дружбы народов
- [1032225689@pfur.ru]


Провести подготовительную работу по первоначальной настройке коммутаторов сети.

Задание

Требуется сделать первоначальную настройку коммутаторов сети, представленной на схеме L1. Под первоначальной настройкой понимается указание имени устройства, его IP-адреса, настройка доступа по паролю к виртуальным терминалам и консоли, настройка удалённого доступа к устройству по ssh. При выполнении работы необходимо учитывать соглашение об именовании.

1. В логической рабочей области Packet Tracer разместим коммутаторы и оконечные устройства согласно схеме сети L1 и соединим их через соответствующие интерфейсы (рис. ??). Для соединения коммутаторов между собой используем кроссовый кабель, а для подключения коммутаторов к оконечным устройствам возьмем прямой кабель.

Выполнение лабораторной работы



Выполнение лабораторной работы

```
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#hostname msk-donskaya-cahanqirov-sw1
msk-donskaya-cahanqirov-sw1(config)#interface vlan2
msk-donskaya-cahanqirov-sw1(config-if)##no shutdown
^
% Invalid input detected at '^' marker.

msk-donskaya-cahanqirov-sw1(config-if)##no shutdown
^
% Invalid input detected at '^' marker.

msk-donskaya-cahanqirov-sw1(config-if)#no shutdown
msk-donskaya-cahanqirov-sw1(config-if)#ip address 10.128.1.2 255.255.255.0
msk-donskaya-cahanqirov-sw1(config-if)#exit
msk-donskaya-cahanqirov-sw1(config)#ip default gateway 10.128.1.1
^
% Invalid input detected at '^' marker.

msk-donskaya-cahanqirov-sw1(config)#ip default-gateway 10.128.1.1
msk-donskaya-cahanqirov-sw1(config)#line vty 0 4
msk-donskaya-cahanqirov-sw1(config-line)#password cisco
msk-donskaya-cahanqirov-sw1(config-line)#login
msk-donskaya-cahanqirov-sw1(config-line)#exit
msk-donskaya-cahanqirov-sw1(config)#line console 0
msk-donskaya-cahanqirov-sw1(config-line)#password cisco
msk-donskaya-cahanqirov-sw1(config-line)#login
msk-donskaya-cahanqirov-sw1(config-line)#exit
msk-donskaya-cahanqirov-sw1(config)#enable secret cisco
msk-donskaya-cahanqirov-sw1(config)#service password-encryption
msk-donskaya-cahanqirov-sw1(config)#username admin privilege 1 secret cisco
msk-donskaya-cahanqirov-sw1(config)#ip domain name donskeya.rudn.edu
msk-donskaya-cahanqirov-sw1(config)#crypto key generate rsa
The name for the keys will be: msk-donskaya-cahanqirov-sw1.donskeya.rudn.edu
Choose the size of the key modulus in the range of 360 to 2048 for your
General Purpose Keys. Choosing a key modulus greater than 512 may take
a few minutes.

How many bits in the modulus [512]: 2048
% Generating 2048 bit RSA keys, keys will be non-exportable...[OK]

msk-donskaya-cahanqirov-sw1(config)#line vty 0 4
*Mar 1 0:48:35.661: %SSH-5-ENABLED: SSH 1.99 has been enabled
msk-donskaya-cahanqirov-sw1(config-line)#transport input ssh
msk-donskaya-cahanqirov-sw1(config-line)#exit
msk-donskaya-cahanqirov-sw1(config)#exit
msk-donskaya-cahanqirov-sw1#
%SYS-5-CONFIG_I: Configured from console by console

msk-donskaya-cahanqirov-sw1#wr m
Building configuration...
***
```

Выполнение лабораторной работы

```
Switch>enable
Switch#conf t
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#hostname msk-donskaya-cahanqirov-sw-2
msk-donskaya-cahanqirov-sw-2(config)#interface vlan2
msk-donskaya-cahanqirov-sw-2(config-if)#no shutdown
msk-donskaya-cahanqirov-sw-2(config-if)#ip address 10.128.1.3 255.255.255.0
msk-donskaya-cahanqirov-sw-2(config-if)#exit
msk-donskaya-cahanqirov-sw-2(config)#ip default gateway 10.128.1.1
^
% Invalid input detected at '^' marker.

msk-donskaya-cahanqirov-sw-2(config)#ip default-gateway 10.128.1.1
msk-donskaya-cahanqirov-sw-2(config)#line vty 0 4
msk-donskaya-cahanqirov-sw-2(config-line)#password cisco
msk-donskaya-cahanqirov-sw-2(config-line)#login
msk-donskaya-cahanqirov-sw-2(config-line)#exit
msk-donskaya-cahanqirov-sw-2(config)#line console 0
msk-donskaya-cahanqirov-sw-2(config-line)#password cisco
msk-donskaya-cahanqirov-sw-2(config-line)#login
msk-donskaya-cahanqirov-sw-2(config-line)#exit
msk-donskaya-cahanqirov-sw-2(config)#enable secret cisco
msk-donskaya-cahanqirov-sw-2(config)#service password-encryption
msk-donskaya-cahanqirov-sw-2(config)#username admin privilege 1 secret cisco
msk-donskaya-cahanqirov-sw-2(config)#ip domain name donsKaya.rudn.edu
msk-donskaya-cahanqirov-sw-2(config)#crypto key generate rsa
The name for the keys will be: msk-donskaya-cahanqirov-sw-2.donskaya.rudn.edu
Choose the size of the key modulus in the range of 360 to 2048 for your
General Purpose Keys. Choosing a key modulus greater than 512 may take
a few minutes.

How many bits in the modulus [512]: 2048
% Generating 2048 bit RSA keys, keys will be non-exportable...[OK]

msk-donskaya-cahanqirov-sw-2(config)#line vty 0 4
*Mar 1 0:43:41.778: %SSH-5-ENABLED: SSH 1.99 has been enabled
msk-donskaya-cahanqirov-sw-2(config-line)#transport input ssh
msk-donskaya-cahanqirov-sw-2(config-line)#exit
msk-donskaya-cahanqirov-sw-2(config)#exit
msk-donskaya-cahanqirov-sw-2#
%SYS-5-CONFIG_I: Configured from console by console

msk-donskaya-cahanqirov-sw-2#wr m
Building configuration...
[OK]
msk-donskaya-cahanqirov-sw-2#
```

Выполнение лабораторной работы

```
Switch#enable
Switch#conf t
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#hostname msk-donskaya-cahanqirov-sw-3
msk-donskaya-cahanqirov-sw-3(config)#interface vlan2
msk-donskaya-cahanqirov-sw-3(config-if)#no shutdown
msk-donskaya-cahanqirov-sw-3(config-if)#ip address 10.128.1.4 255.255.255.0
msk-donskaya-cahanqirov-sw-3(config-if)#exit
msk-donskaya-cahanqirov-sw-3(config)#ip default gateway 10.128.1.1
^
% Invalid input detected at '^' marker.

msk-donskaya-cahanqirov-sw-3(config)#ip default-gateway 10.128.1.1
msk-donskaya-cahanqirov-sw-3(config)#line vty 0 4
msk-donskaya-cahanqirov-sw-3(config-line)#password cisco
msk-donskaya-cahanqirov-sw-3(config-line)#login
msk-donskaya-cahanqirov-sw-3(config-line)#exit
msk-donskaya-cahanqirov-sw-3(config)#line console 0
msk-donskaya-cahanqirov-sw-3(config-line)#password cisco
msk-donskaya-cahanqirov-sw-3(config-line)#login
msk-donskaya-cahanqirov-sw-3(config-line)#exit
msk-donskaya-cahanqirov-sw-3(config)#enable secret cisco
msk-donskaya-cahanqirov-sw-3(config)#service password-encryption
msk-donskaya-cahanqirov-sw-3(config)#username admin privilege 1 secret cisco
msk-donskaya-cahanqirov-sw-3(config)#ip domain name donskeya.rudn.edu
msk-donskaya-cahanqirov-sw-3(config)#crypto key generate rsa
The name for the keys will be: msk-donskaya-cahanqirov-sw-3.donskeya.rudn.edu
Choose the size of the key modulus in the range of 360 to 2048 for your
  General Purpose Keys. Choosing a key modulus greater than 512 may take
  a few minutes.

How many bits in the modulus [512]: 2048
% Generating 2048 bit RSA keys, keys will be non-exportable...[OK]

msk-donskaya-cahanqirov-sw-3(config)#line vty 0 4
*Mar 1 0:54:3.516: %SSH-5-ENABLED: SSH 1.99 has been enabled
msk-donskaya-cahanqirov-sw-3(config-line)#transport input ssh
msk-donskaya-cahanqirov-sw-3(config-line)#exit
msk-donskaya-cahanqirov-sw-3(config)#exit
msk-donskaya-cahanqirov-sw-3#
%SYS-5-CONFIG_I: Configured from console by console

msk-donskaya-cahanqirov-sw-3#wr m
Building configuration...
[OK]
msk-donskaya-cahanqirov-sw-3#
```

Выполнение лабораторной работы

```
Switch>enable
Switch#conf t
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#hostname msk-donskaya-cahanqirov-sw-4
msk-donskaya-cahanqirov-sw-4(config)#interface vlan2
msk-donskaya-cahanqirov-sw-4(config-if)#no shutdown
msk-donskaya-cahanqirov-sw-4(config-if)#ip address 10.128.1.5 255.255.255.0
msk-donskaya-cahanqirov-sw-4(config-if)#exit
msk-donskaya-cahanqirov-sw-4(config)#ip default-gateway 10.128.1.1
msk-donskaya-cahanqirov-sw-4(config)#line vty 0 4
msk-donskaya-cahanqirov-sw-4(config-line)#password cisco
msk-donskaya-cahanqirov-sw-4(config-line)#login
msk-donskaya-cahanqirov-sw-4(config-line)#exit
msk-donskaya-cahanqirov-sw-4(config)#enable secret cisco
msk-donskaya-cahanqirov-sw-4(config)#service password encryption
^
% Invalid input detected at '^' marker.

msk-donskaya-cahanqirov-sw-4(config)#service password-encryption
msk-donskaya-cahanqirov-sw-4(config)#username admin privilege 1 secret cisco
msk-donskaya-cahanqirov-sw-4(config)#ip domain name donskeya.rudn.edu
msk-donskaya-cahanqirov-sw-4(config)#crypto key generate rsa
The name for the keys will be: msk-donskaya-cahanqirov-sw-4.donskeya.rudn.edu
Choose the size of the key modulus in the range of 360 to 2048 for your
  General Purpose Keys. Choosing a key modulus greater than 512 may take
  a few minutes.

How many bits in the modulus [512]: 2048
% Generating 2048 bit RSA keys, keys will be non-exportable...[OK]

msk-donskaya-cahanqirov-sw-4(config)#line vty 0 4
*Mar 1 1:13:57.248: %SSH-5-ENABLED: SSH 1.99 has been enabled
msk-donskaya-cahanqirov-sw-4(config-line)#transport input ssh
msk-donskaya-cahanqirov-sw-4(config-line)#exit
msk-donskaya-cahanqirov-sw-4(config)#exit
msk-donskaya-cahanqirov-sw-4#
%SYS-5-CONFIG_I: Configured from console by console

msk-donskaya-cahanqirov-sw-4#wr m
Building configuration...
[OK]
msk-donskaya-cahanqirov-sw-4#
```

Выполнение лабораторной работы

```
Switch>enable
Switch#conf t
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#hostname msk-pavlovskaya-cahanqirov-sw-1
msk-pavlovskaya-cahanqirov-sw-1(config)#interface vlan2
msk-pavlovskaya-cahanqirov-sw-1(config-if)#ip address 10.128.1.6 255.255.255.0
msk-pavlovskaya-cahanqirov-sw-1(config-if)#exit
msk-pavlovskaya-cahanqirov-sw-1(config)#ip default gateway 10.128.1.1
^
% Invalid input detected at '^' marker.

msk-pavlovskaya-cahanqirov-sw-1(config)#ip default-gateway 10.128.1.1
msk-pavlovskaya-cahanqirov-sw-1(config)#line vty 0 4
msk-pavlovskaya-cahanqirov-sw-1(config-line)#password cisco
msk-pavlovskaya-cahanqirov-sw-1(config-line)#login
msk-pavlovskaya-cahanqirov-sw-1(config-line)#exit
msk-pavlovskaya-cahanqirov-sw-1(config)#line console 0
msk-pavlovskaya-cahanqirov-sw-1(config-line)#password cisco
msk-pavlovskaya-cahanqirov-sw-1(config-line)#login
msk-pavlovskaya-cahanqirov-sw-1(config-line)#exit
msk-pavlovskaya-cahanqirov-sw-1(config)#enable secret cisco
msk-pavlovskaya-cahanqirov-sw-1(config)#service password-encryption
msk-pavlovskaya-cahanqirov-sw-1(config)#username admin privilege 1 secret cisco
msk-pavlovskaya-cahanqirov-sw-1(config)#ip domain name donskeya.rudn.edu
msk-pavlovskaya-cahanqirov-sw-1(config)#crypto key generate rsa
The name for the keys will be: msk-pavlovskaya-cahanqirov-sw-1.donskeya.rudn.edu
Choose the size of the key modulus in the range of 360 to 2048 for your
  General Purpose Keys. Choosing a key modulus greater than 512 may take
  a few minutes.

How many bits in the modulus [512]: 2048
% Generating 2048 bit RSA keys, keys will be non-exportable...[OK]

msk-pavlovskaya-cahanqirov-sw-1(config)#line vty 0 4
*Mar 1 0:7:34.476: %SSH-5-ENABLED: SSH 1.99 has been enabled
msk-pavlovskaya-cahanqirov-sw-1(config-line)#transport input ssh
msk-pavlovskaya-cahanqirov-sw-1(config-line)#exit
msk-pavlovskaya-cahanqirov-sw-1(config)#exit
msk-pavlovskaya-cahanqirov-sw-1#
%SYS-5-CONFIG_I: Configured from console by console

msk-pavlovskaya-cahanqirov-sw-1#wr m
Building configuration...
[OK]
msk-pavlovskaya-cahanqirov-sw-1#
```

В результате выполнения данной лабораторной работы я провел подготовительную работу по первоначальной настройке коммутаторов сети.