

CS 442/542

Project Starting Point

yacc4

yaccExample.h

```
#include "SymTab.h"  
#include "IOMngr.h"
```

ExprEval.y

```
%{  
#include <stdio.h>  
#include <stdlib.h>  
#include <string.h>  
#include "yaccExample.h"  
#include "Semantics.h"  
#include "CodeGen.h"  
  
extern int yylex(); /* The next token function. */  
extern char *yytext; /* The matched token text. */  
extern int yyleng; /* The token text length. */  
extern int yyparse();  
void dumpTable();  
  
extern struct SymTab *table;  
extern struct SymEntry *entry;  
  
%}
```

ExprEval.y

```
%union {  
    long val;  
    char * string;  
    struct ExprRes * ExprRes;  
    struct InstrSeq * InstrSeq;  
    struct BExprRes * BExprRes;  
}
```

ExprEval.y

```
%type <string> Id
%type <ExprRes> Factor
%type <ExprRes> Term
%type <ExprRes> Expr
%type <InstrSeq> StmtSeq
%type <InstrSeq> Stmt
%type <BExprRes> BExpr
```

```
%token Ident
%token IntLit
%token Int
%token Write
%token IF
%token EQ
```

ExprEval.y

%%

```
Prog      : Declarations StmtSeq {Finish($2); };
Declarations : Dec Declarations { };
Declarations : { };
Dec        : Int Ident {EnterName(table, yytext, &entry); };
StmtSeq    : Stmt StmtSeq {$$ = AppendSeq($1, $2); };
StmtSeq    : {$$ = NULL; };
Stmt       : Write Expr ';' {$$ = doPrint($2); };
Stmt       : Id '=' Expr ';' {$$ = doAssign($1, $3); };
Stmt       : IF '(' BExpr ')' '{' StmtSeq '}' {$$ = doIf($3, $6); };
```

ExprEval.y

```
BExpr      :   Expr EQ Expr          { $$ = doBExpr($1, $3); };
Expr       :   Expr '+' Term         { $$ = doAdd($1, $3); } ;
Expr       :   Term                  { $$ = $1; } ;
Term       :   Term '*' Factor       { $$ = doMult($1, $3); } ;
Term       :   Factor                { $$ = $1; } ;
Factor     :   IntLit                { $$ = doIntLit(yytext); };
Factor     :   Ident                 { $$ = doRval(yytext); };
Id         :   Ident                 { $$ = strdup(yytext); }
```

%%

```
yyerror(char *s) {
    WriteIndicator(GetCurrentColumn());
    WriteMessage("Illegal Character in YACC");
}
```

lex1.l

```
%{  
#include "yaccExample.h"  
#include "y.tab.h"  
  
#define YY_INPUT(buf,result,max_size) \  
    { int c = GetSourceChar(); \  
      result = (c == EOF) ? YY_NULL : (buf[0] = c, 1); \  
    }  
  
%}  
  
letter [A-Za-z]  
digit [0-9]
```


lex1.l

```
%%  
if          {return IF;}  
int         {return Int;}  
print       {return Write;}  
{letter}({letter}|{digit})* {return Ident;}  
{digit}{digit}*           {return IntLit;}  
\=\\=          {return EQ;}  
\=            {return '=';}  
\+           {return '+';}  
\*           {return '*'}  
\;           {return ';'}  
\{           {return '{'}  
\}           {return '}'}  
\(           {return '(';}  
\)           {return ')'};
```

lex1.l

```
[ ]      {}  
\t      {}  
\r      {}  
\n      {}  
  
.  
    {WriteIndicator(GetCurrentColumn());  
      WriteMessage("Illegal Character in lex");}  
  
%%  
  
yywrap () {  
}
```

Semantics.h

```
/* Semantic Records */
struct IdList {
    struct SymEntry * TheEntry;
    struct IdList * Next;
};
struct ExprRes {
    int Reg;
    struct InstrSeq * Instrs;
};
struct ExprResList {
    struct ExprRes * Expr;
    struct ExprResList * Next;
};
struct BExprRes {
    char * Label;
    struct InstrSeq * Instrs;
};
```

Semantics.h

```
/* Semantics Actions */  
extern struct ExprRes * doIntLit(char * digits);  
extern struct ExprRes * doRval(char * name);  
extern struct InstrSeq * doAssign(char * name, struct ExprRes * Res1);  
extern struct ExprRes * doAdd(struct ExprRes * Res1, struct ExprRes * Res2);  
extern struct ExprRes * doMult(struct ExprRes * Res1, struct ExprRes * Res2);  
extern struct InstrSeq * doPrint(struct ExprRes * Expr);  
extern struct BExprRes * doBExpr (struct ExprRes * Res1, struct ExprRes * Res2);  
extern struct InstrSeq * doIf(struct BExprRes * bRes, struct InstrSeq * seq);  
  
extern void    Finish(struct InstrSeq *Code);
```

Semantics.c

```
#include <strings.h>  
#include <stdlib.h>
```

```
#include "CodeGen.h"  
#include "Semantics.h"  
#include "SymTab.h"  
#include "IOMngr.h"
```

```
extern struct SymTab *table;
```

Semantics.c

```
struct ExprRes * doIntLit(char * digits) {  
  
    struct ExprRes *res;  
  
    res = (struct ExprRes *) malloc(sizeof(struct ExprRes));  
    res->Reg = AvailTmpReg();  
    res->Instrs = GenInstr(NULL,"li",TmpRegName(res->Reg),digits,NULL);  
  
    return res;  
}
```

Semantics.c

```
struct ExprRes * doRval(char * name) {  
  
    struct ExprRes *res;  
  
    if (!FindName(table, name)) {  
        WriteIndicator(GetCurrentColumn());  
        WriteMessage("Undeclared variable");  
    }  
    res = (struct ExprRes *) malloc(sizeof(struct ExprRes));  
    res->Reg = AvailTmpReg();  
    res->Instrs = GenInstr(NULL,"lw",TmpRegName(res->Reg),name,NULL);  
  
    return res;  
}
```

Semantics.c

```
struct ExprRes * doAdd(struct ExprRes * Res1, struct ExprRes * Res2) {  
  
    int reg;  
  
    reg = AvailTmpReg();  
    AppendSeq(Res1->Instrs, Res2->Instrs);  
    AppendSeq(Res1->Instrs, GenInstr(NULL, "add",  
                                     TmpRegName(reg),  
                                     TmpRegName(Res1->Reg),  
                                     TmpRegName(Res2->Reg)));  
    ReleaseTmpReg(Res1->Reg);  
    ReleaseTmpReg(Res2->Reg);  
    Res1->Reg = reg;  
    free(Res2);  
    return Res1;  
}
```


Semantics.c

```
struct ExprRes * doMult(struct ExprRes * Res1, struct ExprRes * Res2) {  
  
    int reg;  
  
    reg = AvailTmpReg();  
    AppendSeq(Res1->Instrs, Res2->Instrs);  
    AppendSeq(Res1->Instrs, GenInstr(NULL, "mul",  
                                     TmpRegName(reg),  
                                     TmpRegName(Res1->Reg),  
                                     TmpRegName(Res2->Reg)));  
    ReleaseTmpReg(Res1->Reg);  
    ReleaseTmpReg(Res2->Reg);  
    Res1->Reg = reg;  
    free(Res2);  
    return Res1;  
}
```

Semantics.c

```
struct InstrSeq * doPrint(struct ExprRes * Expr) {  
  
    struct InstrSeq *code;  
    code = Expr->Instrs;  
  
    AppendSeq(code, GenInstr(NULL, "li", "$v0", "1", NULL));  
    AppendSeq(code, GenInstr(NULL, "move", "$a0", TmpRegName(Expr->Reg), NULL));  
    AppendSeq(code, GenInstr(NULL, "syscall", NULL, NULL, NULL));  
  
    AppendSeq(code, GenInstr(NULL, "li", "$v0", "4", NULL));  
    AppendSeq(code, GenInstr(NULL, "la", "$a0", "_nl", NULL));  
    AppendSeq(code, GenInstr(NULL, "syscall", NULL, NULL, NULL));  
  
    ReleaseTmpReg(Expr->Reg);  
    free(Expr);  
  
    return code;  
}
```

Semantics.c

```
struct InstrSeq * doAssign(char *name, struct ExprRes * Expr) {  
  
    struct InstrSeq *code;  
  
    if (!FindName(table, name)) {  
        WriteIndicator(GetCurrentColumn());  
        WriteMessage("Undeclared variable");  
    }  
  
    code = Expr->>Instrs;  
  
    AppendSeq(code, GenInstr(NULL, "sw", TmpRegName(Expr->Reg), name, NULL));  
  
    ReleaseTmpReg(Expr->Reg);  
    free(Expr);  
  
    return code;  
}
```

Semantics.c

```
struct BExprRes * doBExpr(struct ExprRes * Res1, struct ExprRes * Res2) {
    struct BExprRes * bRes;
    AppendSeq(Res1->Instrs, Res2->Instrs);
    bRes = (struct BExprRes *) malloc(sizeof(struct BExprRes));
    bRes->Label = GenLabel();
    AppendSeq(Res1->Instrs,
              GenInstr(NULL, "bne", TmpRegName(Res1->Reg),
                      TmpRegName(Res2->Reg), bRes->Label));

    bRes->Instrs = Res1->Instrs;
    ReleaseTmpReg(Res1->Reg);
    ReleaseTmpReg(Res2->Reg);
    free(Res1);
    free(Res2);
    return bRes;
}
```

Semantics.c

```
struct InstrSeq * dolf(struct BExprRes * bRes, struct InstrSeq * seq) {  
    struct InstrSeq * seq2;  
    seq2 = AppendSeq(bRes->>Instrs, seq);  
    AppendSeq(seq2, GenInstr(bRes->Label, NULL, NULL, NULL, NULL));  
    free(bRes);  
    return seq2;  
}
```

Semantics.c

```
void Finish(struct InstrSeq *Code) {
    struct InstrSeq *code;
    struct SymEntry *entry;
    struct Attr * attr;

    code = GenInstr(NULL, ".text", NULL, NULL, NULL);
    AppendSeq(code, GenInstr(NULL, ".globl", "main", NULL, NULL));
    AppendSeq(code, GenInstr("main", NULL, NULL, NULL, NULL));

    AppendSeq(code, Code);

    AppendSeq(code, GenInstr(NULL, "li", "$v0", "10", NULL));
    AppendSeq(code, GenInstr(NULL, "syscall", NULL, NULL, NULL));
    AppendSeq(code, GenInstr(NULL, ".data", NULL, NULL, NULL));
    AppendSeq(code, GenInstr(NULL, ".align", "4", NULL, NULL));
    AppendSeq(code, GenInstr("_nl", ".asciiz", "\\n\\n\\n\\n", NULL, NULL));
```

Semantics.c

```
entry = FirstEntry(table);
while (entry) {
    AppendSeq(code, GenInstr((char *) GetName(entry), ".word", "0", NULL, NULL));
    entry = NextEntry(table, entry);
}

WriteSeq(code);

return;
}
```

CodeGen.h

```
#include <stdio.h>
```

```
extern FILE *AssmFile;
```

```
struct InstrSeq {  
    char *Label;  
    char *OpCode;  
    char *Oprnd1;  
    char *Oprnd2;  
    char *Oprnd3;  
    struct InstrSeq *Next;  
};
```


CodeGen.h

```
extern void InitCodeGen(char *AFilename);

extern struct InstrSeq * GenInstr(char *Label, char *OpCode,
                                   char *Oprnd1, char *Oprnd2, char *Oprnd3);
extern struct InstrSeq * AppendSeq(struct InstrSeq *Seq1, struct InstrSeq *Seq2);
extern void WriteSeq(struct InstrSeq *ASeq);

extern char *GenLabel();
```

CodeGen.h

```
extern int AvailTmpReg();
extern char *TmpRegName(int RegNum);
extern void ReleaseTmpReg(int ANum);
extern void ResetAllTmpReg();
extern struct InstrSeq * SaveSeq();
extern struct InstrSeq * RestoreSeq();

extern char *Imm(int Val);
extern char *RegOff(int Offset, char * Reg);
```

main.c

```
#include <stdio.h>
#include "Semantics.h"
#include "CodeGen.h"
#include "SymTab.h"
#include "IOMngr.h"

extern int yyparse();
```

main.c

```
struct SymTab *table;
struct SymTab *ProcSymTab;
struct SymEntry *entry;
int inProc =0;
FILE *aFile;

int main(int argc, char * argv[]) {
    table = CreateSymTab(33);
    //assumes there is a listing file
    OpenFiles(argv[1], argv[2]);
    if (argc == 4)
        aFile = fopen(argv[3], "w");
    else
        aFile = stdout;

    yyparse();
}
```

Source Program

```
int num1;  
int num2;  
num1 = 10;  
num2 = 20;  
if (num1+10+10+10 == 2*num2) {  
    print num1;  
    print num2;  
}  
print num1;  
print num2;
```

Assembly Language Program

```
.text
.globl      main
main:
    li      $t0, 10
    sw      $t0, num1
    li      $t0, 20
    sw      $t0, num2
    lw      $t0, num1
    li      $t1, 10
    add     $t2, $t0, $t1
    li      $t0, 10
    add     $t1, $t2, $t0
    li      $t0, 10
    add     $t2, $t1, $t0
    li      $t0, 2
    lw      $t1, num2
    mul     $t3, $t0, $t1
```

Assembly Language Program

```
bne    $t2, $t3, L1
lw     $t0, num1
li     $v0, 1
move   $a0, $t0
syscall
li     $v0, 4
la     $a0, _nl
syscall
lw     $t0, num2
li     $v0, 1
move   $a0, $t0
syscall
li     $v0, 4
la     $a0, _nl
syscall
```

L1:

Assembly Language Program

```
lw      $t0, num1
li      $v0, 1
move    $a0, $t0
syscall

li      $v0, 4
la      $a0, _nl
syscall

lw      $t0, num2
li      $v0, 1
move    $a0, $t0
syscall

li      $v0, 4
la      $a0, _nl
syscall
```


Assembly Language Program

```
        li      $v0, 10
        syscall
        .data
        .align  4
_nl:    .asciiz  "\n"
num1:   .word    0
num2:   .word    0
```

Build the Program

```
> yacc -d ExprEval.y  
> lex lex1.l  
> cc -o comp lex.yy.c y.tab.c SymTab.c Semantics.c CodeGen.c IOMngr.c main.c
```

Execute the Program

```
> ./comp source listing.lst asmCode.asm
```

Where to Start

- Download yacc4ForStudents
- Download the Mars or SPIM MIPS simulator
- Build and test the code with your implementation of SymTab and IOMngr
- Try adding one feature at a time. For example add subtraction
- Try adding another feature such as the less than relational operator
- Keep adding features until you run out of time...
- As you add features keep backup copies of versions that work.
- Have fun!