

SQL Constraints

SQL constraints are used to specify rules for the data in a table.

Constraints are used to limit the type of data that can go into a table. This ensures the accuracy and reliability of the data in the table. If there is any violation between the constraint and the data action, the action is aborted.

Constraints can be column level or table level. Column level constraints apply to a column, and table level constraints apply to the whole table.

The following constraints are commonly used in SQL:

1. **NOT NULL** - Ensures that a column cannot have a NULL value
2. **UNIQUE** - Ensures that all values in a column are different
3. **PRIMARY KEY** - A combination of a NOT NULL and UNIQUE. Uniquely identifies each row in a table
4. **FOREIGN KEY** - Uniquely identifies a row/record in another table
5. **CHECK** - Ensures that all values in a column satisfies a specific condition
6. **DEFAULT** - Sets a default value for a column when no value is specified
7. **INDEX** - Used to create and retrieve data from the database very quickly

SQL NOT NULL on CREATE TABLE

The following SQL ensures that the "ID", "LastName", and "FirstName" columns will NOT accept NULL values when the "Persons" table is created:

Example

```
CREATE TABLE Persons (  
    ID int NOT NULL,  
    LastName varchar(255) NOT NULL,  
    FirstName varchar(255) NOT NULL,  
    Age int  
);
```

SQL UNIQUE Constraint on CREATE TABLE

The following SQL creates a UNIQUE constraint on the "ID" column when the "Persons" table is created:

SQL Server / Oracle / MS Access:

```
CREATE TABLE Persons (  
    ID int NOT NULL UNIQUE,  
    LastName varchar(255) NOT NULL,  
    FirstName varchar(255),  
    Age int  
);
```

SQL PRIMARY KEY Constraint

The PRIMARY KEY constraint uniquely identifies each record in a table.

Primary keys must contain UNIQUE values, and cannot contain NULL values.

A table can have only ONE primary key; and in the table, this primary key can consist of single or multiple columns (fields).

SQL PRIMARY KEY on CREATE TABLE

The following SQL creates a PRIMARY KEY on the "ID" column when the "Persons" table is created:

MySQL:

```
CREATE TABLE Persons (  
    ID int NOT NULL,  
    LastName varchar(255) NOT NULL,  
    FirstName varchar(255),  
    Age int,  
    PRIMARY KEY (ID)  
);
```

SQL Server / Oracle / MS Access:

```
CREATE TABLE Persons (  
    ID int NOT NULL PRIMARY KEY,  
    LastName varchar(255) NOT NULL,  
    FirstName varchar(255),  
    Age int  
);
```

SQL FOREIGN KEY Constraint

A FOREIGN KEY is a key used to link two tables together.

A FOREIGN KEY is a field (or collection of fields) in one table that refers to the PRIMARY KEY in another table.

The table containing the foreign key is called the child table, and the table containing the candidate key is called the referenced or parent table.

Look at the following two tables:

"Persons" table:

PersonID	LastName	FirstName	Age
1	Hansen	Ola	30
2	Svendson	Tove	23
3	Pettersen	Kari	20

"Orders" table:

OrderID	OrderNumber	PersonID
1	77895	3
2	44678	3
3	22456	2
4	24562	1

Notice that the "PersonID" column in the "Orders" table points to the "PersonID" column in the "Persons" table.

The "PersonID" column in the "Persons" table is the PRIMARY KEY in the "Persons" table.

The "PersonID" column in the "Orders" table is a FOREIGN KEY in the "Orders" table.

The FOREIGN KEY constraint is used to prevent actions that would destroy links between tables.

The FOREIGN KEY constraint also prevents invalid data from being inserted into the foreign key column, because it has to be one of the values contained in the table it points to.

SQL FOREIGN KEY on CREATE TABLE

The following SQL creates a FOREIGN KEY on the "PersonID" column when the "Orders" table is created:

MySQL:

```
CREATE TABLE Orders (  
    OrderID int NOT NULL,  
    OrderNumber int NOT NULL,  
    PersonID int,  
    PRIMARY KEY (OrderID),  
    FOREIGN KEY (PersonID) REFERENCES Persons(PersonID)  
);
```

SQL Server / Oracle / MS Access:

```
CREATE TABLE Orders (  
    OrderID int NOT NULL PRIMARY KEY,  
    OrderNumber int NOT NULL,  
    PersonID int FOREIGN KEY REFERENCES Persons(PersonID)  
);
```

SQL CHECK Constraint

The CHECK constraint is used to limit the value range that can be placed in a column.

If you define a CHECK constraint on a single column it allows only certain values for this column.

If you define a CHECK constraint on a table it can limit the values in certain columns based on values in other columns in the row.

SQL CHECK on CREATE TABLE

The following SQL creates a CHECK constraint on the "Age" column when the "Persons" table is created. The CHECK constraint ensures that you can not have any person below 18 years:

MySQL:

```
CREATE TABLE Persons (  
    ID int NOT NULL,  
    LastName varchar(255) NOT NULL,  
    FirstName varchar(255),  
    Age int,  
    CHECK (Age>=18)  
);
```

SQL Server / Oracle / MS Access:

```
CREATE TABLE Persons (  
    ID int NOT NULL,  
    LastName varchar(255) NOT NULL,  
    FirstName varchar(255),  
    Age int CHECK (Age>=18)  
);
```

To allow naming of a CHECK constraint, and for defining a CHECK constraint on multiple columns, use the following SQL syntax:

MySQL / SQL Server / Oracle / MS Access:

```
CREATE TABLE Persons (  
    ID int NOT NULL,  
    LastName varchar(255) NOT NULL,  
    FirstName varchar(255),
```

```
Age int,  
City varchar(255),  
CONSTRAINT CHK_Person CHECK (Age>=18 AND City='Sandnes')  
);
```