

SAFETY DATA SHEET

SECTION 1: IDENTIFICATION OF THE HAZARDOUS CHEMICAL AND OF THE SUPPLIER

PRODUCT : Amoil Celcon 000, 00, 0, 1, 2, 3
 CHEMICAL DESCRIPTION : Greases
 SUPPLIER : Amoil (Malaysia) Sdn. Bhd.
 ADDRESS : 14, Jalan Tembaga SD 5/2, Bandar Sri Damansara,
 Kepong, 52200 Kuala Lumpur, Malaysia.
 TEL : 603-6273 4269 / 6274 6563
 FAX : 603-6276 4267

SECTION 2: HAZARDS IDENTIFICATION

WARNING STATEMENTS:

- ⚠ HANDLE MATERIAL IN PRESSURE EQUIPMENT WITH CARE.
- ⚠ ACCIDENTAL INJECTION CAN CAUSE SERIOUS TISSUE DAMAGE.

EYES:

Expected to cause no more than minor eye irritation characterized by tearing or a burning sensation.

ORAL:

If more than several mouthfuls are swallowed, abdominal discomfort, nausea, and diarrhea may occur.

INHALATION:

When overheated, product may release H₂S gas. Trace amounts may cause an odor. In the unlikely event of conditions causing the accumulation of hazardous levels of H₂S, exposure may result in irritation of the eyes and respiratory tract, headache, dizziness, nausea, vomiting, and diarrhea. At concentrations above 300 ppm, respiratory paralysis, causing unconsciousness and death, can occur. Product not volatile at ambient temperatures. Vapours, mist, or fumes in high concentrations, as generated from spraying or heating in an enclosed space, may cause irritation.

SKIN:

Brief contact may cause slight irritation. Prolonged contact may cause more severe irritation and discomfort, seen as local redness and swelling.

LONG TERM TOXIC EFFECTS:

The base oil component(s) are not expected to be carcinogenic based on IARC criteria. This product has not been tested as a whole for chronic health effects. See Section 11 for additional information.

SECTION 3: COMPOSITION AND INFORMATION OF THE INGREDIENTS OF THE HAZARDOUS CHEMICAL

COMPONENTS	CAS No.	%
Solvent dewaxed heavy paraffinic distillate	64742650	< 75
Solvent deasphalted residual oil	64741953	< 20
Additives which may include thickeners, antioxidants, rust inhibitors, extreme pressure agents, demulsifiers,	Not available	< 10

tackifiers antifoam agent, and corrosion inhibitors.		
Lithium hydroxystearate	7620771	< 8

SECTION 4: FIRST-AID MEASURES

EYES:

Flush eyes immediately with fresh water for at least 15 minutes while holding the eyelids open. If irritation persists, see a doctor.

SKIN:

Wash skin thoroughly with soap and water. If skin irritation persists or a rash develops as a result of excessive contact, see a doctor.

INGESTION:

If swallowed and person is conscious, give water or milk. DO NOT make person vomit except on advice of medical personnel. If advice cannot be obtained, take person with container and label to nearest emergency treatment center. Never give anything by mouth to an unconscious person.

INHALATION:

This material is not expected to be an acute inhalation problem under typical applications. However, if exposed to excessive levels of fumes, mists, or dusts, remove to fresh air and get medical attention.

ADVICE TO DOCTOR:

High-pressure equipment can cause small, often bloodless, puncture wounds where material may have been injected deep into the extremity. Within 24 hours, there is usually extensive swelling, discoloration and intense pain in the affected part. Requires immediate treatment at a surgical emergency centre; else disfigurement or amputation of the affected part may occur.

SECTION 5: FIRE-FIGHTING MEASURES

IGNITION TEMP. (Degrees C) : >300°C
 FLAMMABLE LIMITS (% by volume) : N/D.
 FLASH POINT (degrees C) : >200°C (COC).

FIRE EXTINGUISHING AGENTS:

According to the U.S. National Fire Protection Association Guide, use water fog, dry chemical, foam, or carbon dioxide. Water or foam may cause frothing. Use water to cool fire-exposed containers. If a leak or spill has not ignited, use water spray to disperse the vapours and to provide protection for persons attempting to stop the leak.

EXPLOSION HAZARDS:

For fires involving this material, do not enter any enclosed or confined space without self-contained breathing apparatus to protect against the hazardous effects of combustion products or oxygen deficiency. Hydrogen sulfide (H₂S) may be released when heated.

N/D = Not determine

SECTION 6: ACCIDENTAL RELEASE MEASURES

IN CASE OF SPILL:

Shovel up material and place in disposable container, observing precautions outlined in this MSDS. Scrub contaminated area with detergent and water using stiff broom or mop. Pick up liquid with an absorbent and place in a disposable container. Avoid eye and skin contact. Prevent contamination of groundwater or surface water.

SECTION 7: HANDLING & STORAGE

Minimum feasible handling temperatures should be maintained. Periods of exposure to high temperatures should be minimised. Water contamination should be avoided. Under extreme temperatures or extended storage periods, hydrogen sulfide gas may accumulate in the head-space of container. Misuse of empty containers can be hazardous. DO NOT cut, weld, heat or drill container. Residue may ignite with explosive violence if heated sufficiently. Do not pressurize or expose to open flame or heat. Keep container closed and drum bungs in place.

SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION**EYES:**

Avoid eye contact. The wearing of chemical safety goggles or face shield is recommended.

SKIN:

Exposed employees should exercise reasonable personal cleanliness; this includes cleansing exposed skin several times daily with soap and water and laundering or dry cleaning soiled work clothing at least weekly.

INHALATION:

None required when handling at minimum feasible temperatures.

VENTILATION:

Under normal application of this product, general dilution ventilation is adequate.

EXPOSURE LIMITS:

The ACGIH TLV for mineral oil mists is 5 mg/m³ for a daily 8 hours exposure. A short term exposure limit (STEL) of 10 mg/m³ is recommended. None established for product.

SECTION 9: PHYSICAL & CHEMICAL PROPERTIES

NOTE: The following data may represent a range of approximate or typical values for products in the same family. Precise technical information is provided in Product Bulletins and can be obtained from your Marketing Representative.

NLGI Grade	000	00	0	1	2	3
Appearance	Semi Solid					
Colour	Amber					
Odour	Mild Petroleum Oil Like					
Pour Point	-12°C					
Flash Point	> 250°C (Base Oil)					
Dropping Point, °C min	160	160	190	190	190	200
Viscosity, cSt @ 40°C	150					
Penetration Test at 25°C min	450	415	370	325	280	251

Water Solubility	Insoluble					
Operating Temperature °C	-20 to 130	-20 to 130	-20 to 130	-20 to 150	-20 to 160	-20 to 160

SECTION 10: STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION:

Do not occur.

PRODUCTS OF COMBUSTION:

Carbon monoxide, carbon dioxide, and aldehydes and ketones, combustion products of nitrogen or sulfur. Metal combustion products (oxides and/or sulfides) may be released.

CONDITIONS TO AVOID:

Heat, Strong Oxidizers.

SECTION 11: TOXICOLOGICAL INFORMATION

GENERAL:

This product contains petroleum base oils which may be refined by various processes including severe solvent extraction, hydro cracking and hydro treating. These oils have not been listed in the U.S. National Toxicology Program (NTP) Annual Report nor have they been classified by the International Agency for Research on Cancer (IARC) as carcinogenic or probably carcinogenic to humans.

High-Pressure Equipment Information: Accidental high-velocity injection under the skin of materials of this type may result in serious injury. Seek medical attention at once should an accident like this occur. The initial wound at the injection site may not appear to be serious at first; but, if left untreated, could result in disfigurement or amputation of the affected part. Take this information with you if you seek medical treatment.

SECTION 12: ECOLOGICAL INFORMATION

ENVIRONMENTAL EFFECTS:

This product is expected to have low aquatic toxicity (LD50 > 1000 mg/l) and is not considered to represent a long-term danger to the aquatic environment.

SECTION 13: DISPOSAL INFORMATION

WASTE DISPOSAL:

Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations. Contact local environmental or health authorities for approved disposal of this material.

REMARKS:

None Determined.

SECTION 14: TRANSPORT INFORMATION

TRANSPORT OF DANGEROUS GOODS

UN NUMBER	: Not Applicable
DANGEROUS GOODS CLASS	: Not Applicable
PROPER SHIPPING NAME	: Not Applicable
HAZCHEM CODE	: Not Applicable
ADDITIONAL INFORMATION	: None Determined

SECTION 15: REGULATORY INFORMATION

RESPIRATOR INFORMATION	: None determined.
------------------------	--------------------

SECTION 16: OTHER INFORMATION

To the best of our knowledge, the information provided in this MSDS document is correct. We do not assume any liability for consequences of the use of this information since it may be applied under conditions beyond our control or knowledge. Also, it is possible that additional data could be made available after this MSDS was issued. Certain hazards are described herein; however these may not be the only hazards that exist. All materials may present unknown hazards and should be used with caution.

Customers are encouraged to review this information, follow precautions, and comply with all applicable laws and regulations regarding the use and disposal of this product. For specific technical data or advice concerning this product as supplied in your country please contact your local sales representative. The final determination of the suitability of any material is the sole responsibility of the user.

Date of issue	:	22 October 2017
Date of previous issue	:	22 October 2017
Remark	:	