

Title: AES Cryptography

Name: Joshua II B Dajao, Vonzelle Cuizon

Section: 1030-130 PM M-F

Date Performed: 7/19/25

Instructor: Sir Godwin Monserate

Code:

```
#include <stdio.h>
#include <string.h>
#include <stdlib.h>

int hashinator3000(char *blip) {
    int count = 0;
    for (int i = 0; blip[i] != '\0'; i++) {
        count += blip[i];
    }
    return count;
}

void encryptingtationing(char *zorp, char *fluff, char *glonk) {
    int len = strlen(zorp);
    for (int i = 0; i < len; i++) {
        glonk[i] = zorp[i] ^ fluff[i % strlen(fluff)];
    }
    glonk[len] = '\0';
}

void dedecryption(char *splarg, char *boop, char *snack) {
    int len = strlen(splarg);
    for (int i = 0; i < len; i++) {
        snack[i] = splarg[i] ^ boop[i % strlen(boop)];
    }
    snack[len] = '\0';
}

int main() {
    char keybanana[100];
    char inputpickle[100];
    char encryptednoodle[100];
    char decryptedpotato[100];
    int uservibe;

    printf("=== Encryption Program ===\n");
    printf(" [1] Encrypt\n");
    printf(" [2] Decrypt\n");
```

```

printf("Enter your choice: ");
scanf("%d", &uservibe);
getchar(); //eatnewline

printf("Enter key: ");
fgets(keybanana, sizeof(keybanana), stdin);
keybanana[strcspn(keybanana, "\n")] = '\0';

if (uservibe == 1) {
    printf("Enter message to encrypt: ");
    fgets(inputpickle, sizeof(inputpickle), stdin);
    inputpickle[strcspn(inputpickle, "\n")] = '\0';

    encrypting(tationing(inputpickle, keybanana, encryptednoodle);

    printf("\n--- Encryption Results ---\n");
    printf("Plaintext: %s\n", inputpickle);
    printf("ASCII Hash (Plaintext): %d\n", hashinator3000(inputpickle));
    printf("Encrypted (ASCII values): ");
    for (int i = 0; i < strlen(encryptednoodle); i++) {
        printf("%d ", (unsigned char)encryptednoodle[i]);
    }
    printf("\nASCII Hash (Encrypted): %d\n", hashinator3000(encryptednoodle));
} else if (uservibe == 2) {
    printf("Enter encrypted ASCII values (space-separated): ");
    char asciiInput[500];
    fgets(asciiInput, sizeof(asciiInput), stdin);

    int asciiValues[100];
    int count = 0;
    char *token = strtok(asciiInput, " ");
    while (token != NULL && count < 100) {
        asciiValues[count++] = atoi(token);
        token = strtok(NULL, " ");
    }

    for (int i = 0; i < count; i++) {
        inputpickle[i] = (char)asciiValues[i];
    }
    inputpickle[count] = '\0';

    dedecryption(inputpickle, keybanana, decryptedpotato);

    printf("\n--- Decryption Results ---\n");
    printf("Encrypted (ASCII values): ");
    for (int i = 0; i < count; i++) {
        printf("%d ", (unsigned char)inputpickle[i]);
    }
    printf("\nASCII Hash (Encrypted): %d\n", hashinator3000(inputpickle));
    printf("Decrypted: %s\n", decryptedpotato);
}

```

```

    } else {
        printf("Invalid choice.\n");
    }

    return 0;
}

```

Sample Product:

```

Output

=== Encryption Program ===
1. Encrypt message
2. Decrypt message
Enter your choice: 1
Enter key: abcdefghijklmnop
Enter message to encrypt: godwin

--- Encryption Results ---
Plaintext: godwin
ASCII Hash (Plaintext): 648
Encrypted (ASCII values): 6 13 7 19 12 8
ASCII Hash (Encrypted): 65
|

=== Code Execution Successful ===

```

```

Output

=== Encryption Program ===
1. Encrypt message
2. Decrypt message
Enter your choice: 2
Enter key: abcdefghijklmnop
Enter encrypted ASCII values (space-separated): 6 13 7 19 12 8

--- Decryption Results ---
Encrypted (ASCII values): 6 13 7 19 12 8
ASCII Hash (Encrypted): 65
Decrypted: godwin

=== Code Execution Successful ===

```