

MASTER'S THESIS 2026

Title

Jonatan Haraldsson
Jesper Noord



Department of Industrial and Materials Science
Division of Material and Computational Mechanics
CHALMERS UNIVERSITY OF TECHNOLOGY
Gothenburg, Sweden 2026

Title

© Jonatan Haraldsson & Jesper Noord

Supervisors:

Examiner:

Master's Thesis 2025

Department of Industrial and Materials Science

Division of Material and Computational Mechanics

Chalmers University of Technology

SE-412 96 Gothenburg

Cover:

Typeset in L^AT_EX

Printed by Chalmers Reproservice

Gothenburg, Sweden 2025

Title

Jonatan Haraldsson & Jesper Noord
Department of Industrial and Materials Science
Division of Material and Computational Mechanics
Chalmers University of Technology

Abstract

bla bla

Keywords: *Physics Informed Neural Network, ..., ...*

Acknowledgements

List of Acronyms

EV electric vehicle. 1

PINN physics-informed neural network. 1

RMSE root-mean-squared error. 3

Contents

List of Acronyms	v
1 Introduction	1
1.1 Background	1
1.2 Aim and Scope	1
2 Theory	3
2.1 Overview of Batteries	3
2.2 Neural Networks	3
3 Method	4
4 Results and Discussion	5
5 Conclusion	6
A Appendix A: Extra Stuff	8

1

Introduction

1.1 Background

physics-informed neural network (PINN), electric vehicle (EV)

1.2 Aim and Scope

2

Theory

2.1 Overview of Batteries

- A battery's parts, anode, cathode, electrolyte. Cell vs. module.
- The general working principle: charging and discharging. Potential negative effects that need to be considered. Heat development, or other factors affecting performance of the cell.
- What equations are governing? (Thermodynamics, Mechanics, electric, chemical)

2.2 Neural Networks

- General overview of neural networks. Explain neurons, weights, bias, loss function, different types of NNs. RNN??
- How to make NNs PINNs?
-




FIG 2.1: Schematic view of a neural network where each circle represents a single neuron. An input signal $\mathbf{X} = \{\mathbf{x}_i\}_{i=0}^N$ enters the model in the input layer, proceeds through the hidden layers, and exits from the output layer. This process produces an output $\mathbf{Y} = \{\mathbf{y}_i\}_{i=0}^M$, which can be interpreted as a prediction based on the input data.

Loss function, such as **root-mean-squared error (RMSE)**.

3

Method

Here's the method

4

Results and Discussion

Here are the results

5

Conclusion

Here's the conclusion

Bibliography

- [1] J. Haraldsson, “Msc thesis,” *Chalmers*, vol. 1, no. 1, 2026.

A

Appendix A: Extra Stuff

In FIG. A.1, ...



FIG A.1: hej