```
//20.AVL tree
#include <stdio.h>
#include <stdlib.h>
struct Node {
 int key;
 struct Node *left;
 struct Node *right;
 int height;
};
int max(int a, int b);
int height(struct Node *N) {
 if (N == NULL)
  return 0;
 return N->height;
}
int max(int a, int b) {
 return (a > b) ? a : b;
}
struct Node *newNode(int key) {
 struct Node *node = (struct Node *)
  malloc(sizeof(struct Node));
 node->key = key;
 node->left = NULL;
 node->right = NULL;
 node->height = 1;
 return (node);
}
struct Node *rightRotate(struct Node *y) {
 struct Node *x = y->left;
 struct Node *T2 = x->right;
 x->right = y;
```

```
y->left = T2;
 y->height = max(height(y->left), height(y->right)) + 1;
 x->height = max(height(x->left), height(x->right)) + 1;
return x;
}
struct Node *leftRotate(struct Node *x) {
 struct Node *y = x->right;
 struct Node *T2 = y->left;
 y->left = x;
 x->right = T2;
 x->height = max(height(x->left), height(x->right)) + 1;
 y->height = max(height(y->left), height(y->right)) + 1;
 return y;
}
int getBalance(struct Node *N) {
 if (N == NULL)
  return 0;
 return height(N->left) - height(N->right);
}
struct Node *insertNode(struct Node *node, int key) {
 if (node == NULL)
  return (newNode(key));
 if (key < node->key)
  node->left = insertNode(node->left, key);
 else if (key > node->key)
```

```
node->right = insertNode(node->right, key);
 else
  return node;
 node->height = 1 + max(height(node->left),
        height(node->right));
 int balance = getBalance(node);
 if (balance > 1 && key < node->left->key)
  return rightRotate(node);
 if (balance < -1 && key > node->right->key)
  return leftRotate(node);
 if (balance > 1 && key > node->left->key) {
  node->left = leftRotate(node->left);
  return rightRotate(node);
}
 if (balance < -1 && key < node->right->key) {
  node->right = rightRotate(node->right);
  return leftRotate(node);
}
return node;
}
struct Node *minValueNode(struct Node *node) {
struct Node *current = node;
 while (current->left != NULL)
```

```
current = current->left;
 return current;
}
struct Node *deleteNode(struct Node *root, int key) {
 if (root == NULL)
  return root;
 if (key < root->key)
  root->left = deleteNode(root->left, key);
 else if (key > root->key)
  root->right = deleteNode(root->right, key);
 else {
  if ((root->left == NULL) || (root->right == NULL)) {
   struct Node *temp = root->left ? root->left : root->right;
   if (temp == NULL) {
    temp = root;
    root = NULL;
   } else
    *root = *temp;
   free(temp);
  } else {
   struct Node *temp = minValueNode(root->right);
   root->key = temp->key;
```

```
root->right = deleteNode(root->right, temp->key);
  }
 }
 if (root == NULL)
  return root;
 root->height = 1 + max(height(root->left),
        height(root->right));
 int balance = getBalance(root);
 if (balance > 1 && getBalance(root->left) >= 0)
  return rightRotate(root);
 if (balance > 1 && getBalance(root->left) < 0) {
  root->left = leftRotate(root->left);
  return rightRotate(root);
 }
 if (balance < -1 && getBalance(root->right) <= 0)
  return leftRotate(root);
 if (balance < -1 && getBalance(root->right) > 0) {
  root->right = rightRotate(root->right);
  return leftRotate(root);
 }
 return root;
}
void printPreOrder(struct Node *root) {
```

```
if (root != NULL) {
  printf("%d ", root->key);
  printPreOrder(root->left);
  printPreOrder(root->right);
}
}
int main() {
struct Node *root = NULL;
 root = insertNode(root, 2);
 root = insertNode(root, 1);
 root = insertNode(root, 7);
 root = insertNode(root, 4);
 root = insertNode(root, 5);
 root = insertNode(root, 3);
 root = insertNode(root, 8);
 printPreOrder(root);
 root = deleteNode(root, 3);
 printf("\nAfter deletion: ");
 printPreOrder(root);
return 0;
 4 2 1 3 7 5 8
 After deletion: 4 2 1 7 5 8
 Process exited after 0.03277 seconds with return value 0
```

Press any key to continue . . .