4. Create a Table Book with the fields S No, B Name, Author, Price, and Publisher. Create a **save point** for the table **book** as **B. Rollback** the table **book** after inserting four and five rows respectively. Execute the commands Grant & Revoke and finally Commit the table.

Ans.

```
mysql> CREATE TABLE Workers (
    ->   S_No INT,
    ->   name VARCHAR(50),
    ->   Designation VARCHAR(50),
    ->   Branch VARCHAR(50),
    ->   FOREIGN KEY (S_No) REFERENCES Employee(S_No)
    -> );
Query OK, 0 rows affected (0.88 sec)

mysql> CREATE TABLE Book (
    ->   S_No INT PRIMARY KEY,
    ->   B_Name VARCHAR(50),
    ->   Author VARCHAR(50),
    ->   Price DECIMAL(10,2),
    ->   Publisher VARCHAR(50)
    -> );
Query OK, 0 rows affected (0.13 sec)

mysql> SAVEPOINT B;
Query OK, 0 rows affected (0.00 sec)

mysql> INSERT INTO Book VALUES (1, 'The Great Gatsby', 'F. Scott Fitzgerald', 9.99, 'Scribner');
Query OK, 1 row affected (0.05 sec)

mysql> INSERT INTO Book VALUES (2, 'To Kill a Mockingbird', 'Harper Lee', 8.99, 'J. B. Lippincott & Co.');
Query OK, 1 row affected (0.01 sec)

mysql> INSERT INTO Book VALUES (3, '1984', 'George Orwell', 7.99, 'Secker & Warburg');
Query OK, 1 row affected (0.01 sec)

mysql> INSERT INTO Book VALUES (4, 'Animal Farm', 'George Orwell', 6.99, 'Secker & Warburg');
Query OK, 1 row affected (0.01 sec)

mysql> ROLLBACK TO B;
```