

Damage-Free Versatility

ULTRAVIOLET LASER MARKING SYSTEM

- Versatile in **marking a wide range** of materials
- Perfect for “cold marking,”** where heat-affected zones are damaging or aesthetically unacceptable
- Eliminates additives** when marking plastic or silicon materials
- Reduces risk of micro-fracture** when marking glass micro-mark electronics, circuit boards, microchips, solar panels, gemstones, and medical instruments



Models

UVC

Technology Options

- Vari-Z™ 3-Axis
- iZONIT™ Vision System
- Mark-on-the-Fly Technology

Controllers

U15 External PC

Software

Proprietary Merlin® II LS

Lens Configurations

Diameter	Marking Area				Working Clearance	
103 mm	2.56 in	x	2.56 in	65 mm x 65 mm	5.35 in	136 mm
160 mm	4.33 in	x	4.33 in	110 mm x 110 mm	8.58 in	218 mm
250 mm	6.10 in	x	6.10 in	155 mm x 155 mm	12.2 in	310 mm
255 mm	6.69 in	x	6.69 in	170 mm x 170 mm	12.36 in	314 mm



Dimensions

w/o Vari-Z™	w/ Vari-Z™	
6.7 in	7.06 in	
170 mm	179 mm	

w/o Vari-Z™	w/ Vari-Z™
6.03 in	
153 mm	
w/ Vari-Z™	
7.43 in	
189 mm	

w/o Vari-Z™	w/ Vari-Z™
22.06 in	29.94 in
560 mm	760 mm

DUAL-HEAD

FIBER

VANADATE

GREEN

UV

CO₂

ENCLOSURES