

From the Line Filter to the Anisotropic Stencil Filter

A Step-by-Step Mathematical Walkthrough

J.C. Vaught

1 The Big Picture (Before Any Math)

The whole point of this document is to answer one question: how did we go from the Line Filter (LF), which is slow and memory-hungry, to the Anisotropic Stencil Filter (ASF), which is fast and lean, without changing the answer at all?

The short version is this. The Line Filter does a bunch of steps (gather pixels, build a matrix, solve a system, repeat along a line, weight, sum). Every single one of those steps is a linear operation on the original pixel values. When you chain a bunch of linear operations together, the result is still just one big linear operation. That means the entire LF pipeline, no matter how complicated it looks, is secretly equivalent to “multiply each pixel in a neighborhood by some weight and add them up.” The ASF simply precomputes those weights ahead of time so the GPU only has to do the easy part: gather, multiply, sum. One operation instead of many. Same answer. Much faster.

The rest of this document walks through every step of the math that makes this work, slowly and with lots of explanation.

2 Step 1: What Are We Even Computing?

2.1 The Goal

We have a grayscale image, which is really just a grid of numbers. Each number is a brightness value. We want to find edges, the places where the brightness changes sharply.

To find edges, we need to estimate how fast the brightness is changing at every pixel. In calculus terms, we want the derivative of the image intensity. The bigger the derivative, the stronger the edge.

2.2 The Problem with Simple Approaches

The most obvious way to estimate a derivative is to look at two neighboring pixels and take the difference. This is essentially what Sobel and Prewitt filters do (with some slight averaging). The problem is that if the image is noisy, those two pixels might have random junk in their values, and the difference will be meaningless.

Our approach uses way more pixels (say, 100 instead of 9) and fits a smooth polynomial surface through all of them. The derivative of that smooth surface is our edge estimate. More pixels means more noise averaging, and the polynomial fit means we are not blurring edges the way Gaussian smoothing does.

2.3 Why Direction Matters

An edge has a direction. A vertical edge has a strong horizontal derivative and a weak vertical one. A diagonal edge has strong derivatives in neither the horizontal nor vertical direction individually, but a strong derivative perpendicular to the edge.

Rather than computing derivatives in just two directions (horizontal and vertical) and combining them, we try many candidate directions (say, 18 angles evenly spaced around the circle) and pick the one that gives the biggest response. This is what “anisotropic” means in the name: the filter looks different in different directions.

3 Step 2: The Point Filter (One Pixel, One Direction)

This is the foundation of everything. Before we worry about lines or stencils, we need to understand how to estimate a derivative at a single pixel in a single direction.

3.1 Setting Up Local Coordinates

Pick a target pixel at position (X_0, Y_0) in the image. Pick a candidate edge direction θ_k (one of our 18 angles, for example). We set up a local coordinate system centered on our pixel, rotated so that x points along the normal to the edge (the direction we want the derivative in) and y points along the edge itself.

For any neighbor pixel at (X_i, Y_i) , its local coordinates are:

$$\begin{aligned} x_i &= (X_i - X_0) \cos \theta_k + (Y_i - Y_0) \sin \theta_k \\ y_i &= -(X_i - X_0) \sin \theta_k + (Y_i - Y_0) \cos \theta_k \end{aligned} \quad (1)$$

This is just a coordinate rotation. We are re-expressing each neighbor's position relative to our target pixel, in a coordinate system aligned with the candidate edge direction.

To give a concrete example, suppose our target pixel is at $(50, 50)$ and we are testing $\theta_k = 0^\circ$ (a vertical edge). Then the rotation is trivial: $x_i = X_i - 50$ and $y_i = Y_i - 50$. For $\theta_k = 45^\circ$, the axes are rotated 45 degrees, so the x and y coordinates become mixtures of the horizontal and vertical offsets.

3.2 Fitting a Polynomial Surface

Now we model the image brightness near our target pixel as a polynomial in these local coordinates. Using a Taylor expansion of order d (we typically use $d = 4$):

$$f(x_i, y_i) \approx \underbrace{f^0}_{\text{constant}} + \underbrace{f_x^0 x_i}_{\text{linear in } x} + \underbrace{f_y^0 y_i}_{\text{linear in } y} + \underbrace{\frac{f_{xx}^0}{2} x_i^2}_{\text{quadratic}} + \dots \quad (2)$$

There are $M = (d+1) \frac{d+2}{2}$ unknown coefficients in this expansion. For $d = 4$, that is $M = 15$ unknowns.

What are these unknowns? They are the partial derivatives of the image at our target pixel: the value f^0 , the first derivatives f_x^0 and f_y^0 , the second derivatives f_{xx}^0 , f_{yy}^0 , f_{xy}^0 , and so on up to fourth order. The one we care about most is f_x^0 , the derivative in the normal direction, because that is our edge strength.

3.3 Gathering Neighbors

We select N_p neighbor pixels around our target. These are chosen as the N_p closest integer-coordinate pixels, forming an approximately circular patch. For $N_p = 100$, this circle has a radius of about 6 pixels.

Each neighbor gives us one equation: we know its local coordinates (x_i, y_i) from Equation 1, and we know its brightness $f(X_i, Y_i)$ from the image. Plugging into Equation 2 gives us one equation relating the 15 unknowns to one known brightness value.

With $N_p = 100$ equations and 15 unknowns, we have a heavily overdetermined system. This is good because it means the solution averages out noise.

3.4 The Linear System

Stack all N_p equations into a matrix equation:

$$A_{\theta_k} z = b \quad (3)$$

$$(X_j, Y_j) = (X_0 + j \cos \theta_k, Y_0 + j \sin \theta_k), \quad j \in \{-m, \dots, 0, \dots, m\} \quad (8)$$

For $m = 7$, this gives 15 positions (from $j = -7$ to $j = 7$). At each one, we run the entire point filter: gather N_p neighbors, build the matrix, solve, extract $\hat{f}_x^{(j,k)}$.

Think of it this way. We are sliding a circular patch along the candidate edge direction and measuring the edge strength at each position. If there really is an edge running in that direction, all 15 patches should see it, and the combined evidence is much stronger than any single patch.

4.2 Combining the Estimates

We combine the 15 derivative estimates using a Gaussian-weighted average:

$$R_k = \sum_{j=-m}^m w_j \cdot \hat{f}_x^{(j,k)} \quad (9)$$

where the weights are:

$$w_j = \exp\left(-\frac{j^2}{2\sigma^2}\right), \quad \sigma = \frac{m}{2} \quad (10)$$

The Gaussian weighting means positions near the center (small $|j|$) count more than positions far away (large $|j|$). This is sensible: the target pixel is at $j = 0$, and positions farther away are less relevant.

For $m = 7$, the weights look like this: $w_0 = 1.0$ (center), $w_{\pm 1} \approx 0.92$, $w_{\pm 3} \approx 0.57$, $w_{\pm 7} \approx 0.007$ (almost zero at the ends).

4.3 Why This Is Expensive

Every one of those 15 virtual positions requires its own gather of N_p pixels, its own matrix-vector product with the pseudoinverse, and its own extraction of the derivative. With $N_p = 100$ and $m = 7$:

- $15 \times 100 = 1500$ pixel reads per direction
- 15 separate matrix-vector multiplies
- All repeated for $N_s = 18$ directions

That is $15 \times 100 \times 18 = 27,000$ pixel reads per target pixel, plus thousands of multiply-add operations. For a 1280 x 720 image, that is about 25 billion pixel reads. This is why the naive LF is slow and uses tons of memory.

5 Step 4: The Algebraic Collapse (The Key Step)

Here is where the magic happens. We are going to show that the entire line filter computation, all 15 polynomial fits combined with Gaussian weighting, is equivalent to a single weighted sum over pixel values. No matrices, no pseudoinverses, no loops at runtime.

5.1 Expanding the Line Response

Let us write out what R_k actually computes, in full detail. From Equation 9 and Equation 6:

$$R_k = \sum_{j=-m}^m w_j \cdot \hat{f}_x^{(j,k)} \quad (11)$$

Substituting the definition of $\hat{f}_x^{(j,k)}$:

$$R_k = \sum_{j=-m}^m w_j \cdot \left(\mathbf{p}_{\text{fx}}^{(k)} \cdot \mathbf{b}_j \right) \quad (12)$$

The stencil shape is an elongated, anisotropic pattern that stretches along the candidate edge direction. When you plot the weights, you see a dipole pattern: positive weights on one side of the expected edge, negative weights on the other. This makes sense because the derivative should respond to the difference in brightness across the edge.

At runtime, for each pixel, the GPU kernel loops over the N_s orientations, and for each one, it gathers the pixel values at the stencil offsets, multiplies by the precomputed weights, and sums. The orientation with the largest absolute response wins.

10 Summary

The derivation has four conceptual steps.

The first step is recognizing that the point filter (polynomial fit followed by derivative extraction) is a linear operation on pixel values. The derivative at a single point is just $\mathbf{p}_{\text{fx}}^{(k)} \cdot \mathbf{b}$, a dot product of fixed weights with brightness values.

The second step is recognizing that the line extension (evaluating the point filter at multiple virtual positions and taking a Gaussian-weighted sum) is also linear. You are summing dot products, which is itself a dot product.

The third step is expanding the double sum (over virtual positions j and neighbors i) to get a single sum over (j, i) pairs, each pair contributing $w_j \cdot p_i^{(k)}$ times one pixel value.

The fourth step is deduplication: grouping all (j, i) pairs that reference the same pixel, summing their weights, and storing only the unique positions and fused weights. This compressed stencil is the ASF.

The result is mathematically identical to the original line filter. Same pixels, same weights, same answer. But the computation goes from “build matrices, solve systems, loop over virtual positions” to “gather pixels, multiply by precomputed weights, sum.” This is why the ASF is 18 to 24 times faster and uses 311 times less memory than the naive LF implementation.