Refrigerant Identification Testing

Ford Ecat Electronic Parts Catalog

Refrigerant Identification

1. **NOTE:** *Refrigerant Identification Equipment must be used to identify gas samples taken directly from the refrigeration system or storage containers prior to recovering or charging the refrigerant system.*

   NOTE: *Use Refrigerant Identification Equipment that conforms to SAE J1771 for R-134a or SAE J2912 standard identifies R-134a and R-1234yf.*

   Follow the instructions included with the Refrigerant Identification Equipment to obtain the sample for testing.
   - 198-RI2012yfp A/C Refrigerant Analyzer for use with R134a and R1234yf vehicles Use the General Equipment: Refrigerant Identification Equipment

2. The Refrigerant Identification Equipment displays one of the following:
   - If the purity level of R-134a is 98% or greater by weight, the green PASS LED lights. The weight concentrations of R-134a, R-12, R-22, hydrocarbons and air is displayed on the digital display.
   - If refrigerant R-134a does not meet the 98% purity level, the red FAIL LED lights and an alarm sounds alerting the user of potential hazards. The weight concentrations of R-134a, R-12, R-22 and hydrocarbons are displayed on the digital display.
   - If hydrocarbon concentrations are 2% or greater by weight, the red FAIL LED lights, "Hydrocarbon High" is displayed on the digital display, and an alarm sounds alerting the user of potential hazards. The weight concentrations of R-134a, R-12, R-22 and hydrocarbons are displayed on the digital display.

3. The percentage of air contained in the sample is displayed if the R-134a content is 98% or greater. The Refrigerant Identification Equipment eliminates the effect of air when determining the refrigerant sample content because air is not considered a contaminant, although air can affect A/C system performance. When the Refrigerant Identification Equipment has determined that a refrigerant source is pure (R-134a is 98% or greater by weight) and air concentration levels are 2% or greater by weight, prompts the user if an air purge is desired.

4. If contaminated refrigerant is detected, repeat the refrigerant identification test to verify that the refrigerant is indeed contaminated.