

Specifications



Material		
Item	Specification	Fill Capacity
Motorcraft® A/C Cooling Coil Coating YN-29	—	—
Motorcraft® A/C System Flushing Solvent YN-23	—	—
Motorcraft® PAG Refrigerant Compressor Oil YN-12-D	WSH-M1C231-B	6.2L (2v) Only 177 ml (6 fl oz) 3.5L GTDI, 3.7L or 5.0L (4v) 100 ml (3.4 fl oz)
Motorcraft® R-134a Refrigerant YN-19 (US); CYN-19-R (Canada); MYN-19 (Mexico)	WSH-M17B19-A	0.68 kg (24 oz) (1.5 lb)
Stay-Brite® R-134a Leak Detection Dye 164-R6060 (Rotunda)	—	—

General Specifications

Item	Specification
A/C Compressor Magnetic Clutch	
Air gap clearance	0.3 - 0.6 mm (0.011 - 0.023 in)
A/C Pressure Relief Valve ^a	
Open pressures	3,792-4,137 kPa (550-600 psi)
Evaporator Temperature Sensor	
On/off temperatures	2.2-3.3°C (36-38°F)
Refrigerant System Dye	
R-134a Leak Detection Dye 164-R6060	—

^aManifold gauge set pressures may vary slightly depending on the distance between the service gauge port valve and the A/C pressure relief valve, low charge protection and pressure cutoff switch locations.