

Specifications



General Specifications

Item	Specification
Battery	
Cold Cranking Amps (CCA) measured at -18°C (0°F)	750 CCA
Voltage	12 volts

Torque Specifications

Description	Nm	lb-ft	lb-in
Battery cable body ground terminal bolt	13	—	115
Battery cable chassis ground terminal bolt	20	—	177
Battery cable engine ground terminal nut	25	18	—
Battery cable engine ground terminal stud bolt	47	35	—
Battery cable harness bracket bolt	20	—	177
Battery cable shield nut	12	—	106
Battery cable shield stud bolt	12	—	106
Battery cable terminal nut	5	—	44
Battery hold-down clamp bolt	7	—	62
Battery Junction Box (BJB) harness positive terminal nut	9	—	80
Battery tray bolt	17	—	150
Front axle mounting bolts	115	85	—
Generator B+ cable end nut	17	—	150
Generator B+ cable terminal/Power Distribution Box (PDB) cable terminal nut	9	—	80
Oil filter drip shield bolts	7	—	62
Power Steering Control Module (PSCM) harness positive terminal nut	9	—	80
PSCM skid plate bolts	40	30	—
Skid plate bolts	48	35	—

Description	Nm	lb-ft	lb-in
Starter solenoid positive cable terminal nut	12	—	106
Starter solenoid wire terminal nut	5	—	44
Transmission fluid cooler tube bracket nut	12	—	106