

Specifications



Material		
Item	Specification	Fill Capacity
Dow Urethane Adhesive Betaseal™ Express	—	—
Dow Urethane One Step Glass Primer Betaprime™ 5500 / 5500A / 5500SA	—	—
Foam Core Butyl E69Z-19562-A	WSB-M3G143-B1	—
Motorcraft® Lacquer Touch-Up Paint (match color to exterior grid wire) (PMPC, PMPM, or PMPP)-19500-XXXXX	ESR-M2P100-C	—
Motorcraft® Rear Window Defroster Repair PM-11	—	—
Sika Urethane Adhesive Sika Tack ASAP	—	—
Sika Urethane Metal and Glass Primer Sika 206 G+P	—	—
Motorcraft® Ultra-Clear Spray Glass Cleaner ZC-23	ESR-M14P5-A	—

General Specifications

Item	Specification
Terminal Kit — Back Glass 4F1Z-14421-AA	—

Torque Specifications

Description	Nm	lb-ft	lb-in
B-pillar below belt bracket bolts	11	—	97

Description	Nm	lb-ft	lb-in
C-pillar below belt bracket bolts	11	—	97
Door window glass-to-regulator bolts	11	—	97
Door window regulator fasteners	11	—	97
Rear window glass nuts	4	—	35
Rear window glass regulator and motor assembly screws	11	—	97
Tether anchor bolt	30	22	—