

Specifications



Material		
Item	Specification	Fill Capacity
Motorcraft® Metal Surface Prep ZC-31-B	—	—
Motorcraft® Premium Cooling System Flush VC-1	ESR-M14P7-A	—
Motorcraft® Silicone Gasket Remover ZC-30-A	—	—
Motorcraft® Orange Antifreeze/Coolant Concentrated VC-3-B (US); CVC-3-B2 (Canada)	WSS-M97B44-D	3.5L Gasoline Turbocharged Direct Injection (GTDI) — 15.6L (16.5 qt), 3.7L — 15.1L (16.0 qt), 5.0L — 16.1L (17.0 qt), 6.2L — 18.5L (19.5 qt)
Motorcraft® Orange Antifreeze/Coolant Prediluted VC-3DIL-B (US); CVC-3DIL-B (Canada)	WSS-M97B44-D2	3.5L Gasoline Turbocharged Direct Injection (GTDI) — 15.6L (16.5 qt), 3.7L — 15.1L (16.0 qt), 5.0L — 16.1L (17.0 qt), 6.2L — 18.5L (19.5 qt)

General Specifications

Item	Specification
Pressure Tests	
Complete cooling system maximum pressure	110 kPa (16 psi)
Pressure relief cap	110 kPa (16 psi)
Radiator (out of vehicle)	138 kPa (20 psi)
Thermostat Opening Temperatures — 3.5L Gasoline Turbocharged Direct Injection (GTDI)	
Starts to open	83.8-90.6°C (183-195°F)
Fully open	98.8°C (210°F)
Thermostat Opening Temperatures — 3.7L	

Item	Specification
Starts to open	83.8-90.6°C (183-195°F)
Fully open	98.8°C (210°F)
Thermostat Opening Temperatures — 5.0L	
Starts to open	87.5°C (189.5°F)
Fully open	100°C (212°F)
Thermostat Opening Temperatures — 6.2L (2V)	
Starts to open	88-92°C (190.4-197.6°F)
Fully open	104°C (219.2°F)

Torque Specifications

Description	Nm	lb-ft	lb-in
A/C fitting nut and bolt	15	—	133
Air dam bolts	20	—	177
Air dam nuts	20	—	177
Battery Junction Box (BJB) bolts	10	—	89
Block heater - 5.0L, 6.2L	40	30	—
Block heater bolt - 3.5L Gasoline Turbocharged Direct Injection (GTDI) , 3.7L	6	—	53
Coolant crossover manifold assembly bolts ^a	—	—	—
Coolant expansion tank module bolts	15	—	133
Coolant inlet connector bolt - 3.5L Gasoline Turbocharged Direct Injection (GTDI) , 3.7L, 5.0L	10	—	89
Coolant outlet connection bolts — 6.2L	10	—	89
Coolant pump bolts — 3.5L GTDI , 3.7L ^a	—	—	—
Coolant pump bolts — 5.0L ^a	—	—	—
Coolant pump bolts — 6.2L ^a	—	—	—
Coolant pump pulley bolts	25	18	—
Cooling fan motor and shroud bolts	7	—	62
Cooling module bolts	30	22	—
Degas bottle bolts	17	—	150
Front bumper cover bracket bolts	3	—	27
Front wheel moulding nuts	3	—	27
Front bumper cover bracket bolts	3	—	27
Generator positive cable nut	9	—	80
Heater outlet tube bolt	10	—	89
Hood latch bolts	25	18	—
Hood latch release handle bolt	8	—	71

Description	Nm	lb-ft	lb-in
Intake manifold bolt	10	—	89
LH turbocharger-to-Charge Air Cooler (CAC) tube bracket bolt	6	—	53
LH turbocharger-to-CAC tube clamp	5	—	44
Positive battery cable nut — 6.2L	9	—	80
Power steering fluid reservoir bolt	11	—	97
Radiator bolts	15	—	133
Thermostat housing bolts — 3.5L GTDI , 3.7L ^a	—	—	—
Thermostat housing bolts — 5.0L	10	—	89
Transmission cooler tube bolt — 3.5L GTDI , 3.7L and 5.0L engines	12	—	106

^aRefer to the procedure in this section.