

Specifications



Material		
Item	Specification	Fill Capacity
Motorcraft® SAE 5W-30 Synthetic Blend Motor Oil (US); Motorcraft® SAE 5W-30 Super Premium Motor Oil (Canada) XO-5W30-QSP (US); CXO-5W30-LSP12 (Canada)	WSS-M2C946-A	—

Torque Specifications

Description	Nm	lb-ft	lb-in
A/C compressor bolts	25	18	—
Catalytic converter adapter nuts	40	30	—
Charge Air Cooler (CAC) tube clamp	5	—	44
Skid plate bolts	40	30	—
Turbocharger-to-bracket bolts	28	21	—
Turbocharger bracket-to-cylinder block bolts	10	—	89
Turbocharger exhaust flange stud bolts	40	30	—
Turbocharger coolant supply tube and the turbocharger oil feed tube bolt ^a	—	—	—
Turbocharger coolant supply tube-to-engine block fitting	50	37	—
Turbocharger coolant supply tube-to-turbocharger fitting	18	—	159
Turbocharger coolant return tube-to-cylinder head fitting	18	—	159
Turbocharger coolant return tube-to-turbocharger fitting	18	—	159
Turbocharger exhaust flange stud bolts	40	30	—
Turbocharger heat shield bolts	6	—	53
Turbocharger intake tube clamp	5	—	44
Turbocharger mounting bolts	32	24	—
Turbocharger oil supply tube-to-engine block fitting — LH	48	35	—
Turbocharger oil supply tube-to-engine block fitting — RH	42	31	—
Turbocharger oil tube assembly bolts ^a	—	—	—

^aRefer to the procedure in this section.

