

Specifications



Material		
Item	Specification	Fill Capacity
Motorcraft® High Temperature Nickel Anti-Seize Lubricant XL-2	—	—
Motorcraft® SAE 5W-20 Premium Synthetic Blend Motor Oil (US); Motorcraft® SAE 5W-20 Super Premium Motor Oil (Canada) XO-5W20-QSP (US); CXO-5W20-LSP12 (Canada)	WSS-M2C945-A	—
Motorcraft® Penetrating and Lock Lubricant (US); Motorcraft® Penetrating Fluid (Canada) XL-1 (US); CXC-51-A (Canada)	—	—

Torque Specifications

Description	Nm	lb-ft	lb-in
A/C compressor bolts	25	18	—
Camshaft Position (CMP) sensor bolt	10	—	89
Catalyst Monitor Sensor (CMS) — 3.5L GTDI , 3.7L and 5.0L (4V)	48	35	—
CMS — 6.2L (2V)	46	34	—
Crankshaft Position (CKP) sensor bolt	10	—	89
Cylinder Head Temperature (CHT) sensor — 3.5L Gasoline Turbocharged Direct Injection (GTDI) and 3.7L	10	—	89
CHT sensor — 5.0L (4V) and 6.2L (2V)	11	—	97
Cylinder head heat shield bolts	10	—	89
Cylinder head heat shield nut	10	—	89
Cylinder head heat shield stud bolt	10	—	89
Fuel Rail Pressure (FRP) sensor — 3.5L GTDI	33	24	—
Ground cable nut	9	—	80
Heated Oxygen Sensor (HO2S) — 3.5L GTDI , 3.7L and 5.0L (4V)	48	35	—
HO2S — 6.2L (2V)	46	34	—
Intake Air Temperature (IAT) sensor bolts — 3.5L GTDI	6	—	53

Description	Nm	lb-ft	lb-in
Knock Sensor (KS) bolt	20	—	177
Manifold Absolute Pressure (MAP) /Intake Air Temperature 2 (IAT2) sensor bolt — 3.5L GTDI	6	—	53
Mass Air Flow (MAF) sensor screws — 3.7L, 5.0L (4V) and 6.2L (2V)	2	—	18
Powertrain Control Module (PCM) -to-PCM support bracket bolts — 3.5L GTDI	9	—	80
PCM stud bolts	9	—	80
Turbocharger Boost Pressure (TCBP) /Charge Air Cooler (CAC) Sensor screws — 3.5L GTDI	3	—	27
Variable Camshaft Timing (VCT) solenoid bolt ^a	—	—	—
VCT variable force solenoid bolt ^a	—	—	—

^aRefer to the procedure in this section.