

Specifications



Material		
Item	Specification	Fill Capacity
Motorcraft® SAE 80W-90 Premium Rear Axle Lubricant (US); Motorcraft® SAE 80W-90 Premium Axle Lubricant (Canada) XY-80W90-QL (US); CXY-80W90-1L (Canada)	WSP-M2C197-A	1.66L (3.5 pt)
Motorcraft® Additive Friction Modifier XL-3 (US); CXL-3 (Canada)	EST-M2C118-A	4.0 oz
Motorcraft® Premium Long-Life Grease XG-1-E1	ESA-M1C75-B	—
Motorcraft® Silicone Gasket and Sealant TA-30	WSE-M4G323-A4	—
Motorcraft® Threadlock and Sealer TA-25-B	WSK-M2G351-A5	—

General Specifications

Item	Specification
Backlash Specifications	
Ring gear backlash	0.204-0.305 mm (0.008-0.012 in)
Ring gear maximum backlash between teeth	0.101mm (0.004 in)
Clearance Specifications	
Differential case maximum runout	0.076 mm (0.003 in)
Housing spreader adapter thread engagement	12.5 mm (0.500 in)
Maximum differential housing spread	0.762 mm (0.030 in)
Lubricant Fill Level Checks	
Front axle	
Lubricant level	9.56 mm (0.38 in) below bottom of differential housing fill hole
Rotational Torque Ranges	
Pinion bearing torque preload	1.8-3.3 Nm (16-29 lb-in)

Torque Specifications

Description	Nm	lb-ft
Axle housing tube bolts	73	54
Axle housing tube bushing bolt	175	129
Crossmember bolts and nuts	90	66
Differential bearing cap bolts	105	77
Differential housing cover bolts	32	24
Differential pinion shaft lock bolt	30	22
Fill plug	25	18
Front axle housing bushing bolt	175	129
Rear axle housing bushing bolt	175	129
Ring gear bolts ^a	—	—
Lower steering column shaft-to-steering gear bolt	30	22

^aRefer to the procedure in this section.