

Specifications



Material		
Item	Specification	Fill Capacity
Motorcraft® DOT 4 LV High Performance Motor Vehicle Brake Fluid PM-20	WSS-M6C65-A2	— ^a
Motorcraft® High Performance DOT 3 Motor Vehicle Brake Fluid (US) / Motorcraft® Brake Fluid - Heavy Duty DOT 3 (Canada) PM-1-C (US); CPM-1-C (Canada)	WSS-M6C65-A1	— ^a
Motorcraft® Metal Brake Parts Cleaner (US) / Motorcraft® Brake Parts Cleaner (Canada) PM-4-A or PM-4-B (US); CPM-4 (Canada)	—	—
Motorcraft® Silicone Brake Caliper Grease and Dielectric Compound XG-3-A	ESE-M1C171-A	—

^aRefer to the brake fluid reservoir cap for correct brake fluid application.

General Specifications

Item	Specification
Brake Disc	
Front brake disc minimum thickness	32 mm (1.259 in)
Rear brake disc minimum thickness	23.0 mm (0.906 in)
Brake Pads	
Maximum brake pad taper wear (in any direction)	3.0 mm (0.118 in)
Minimum brake pad thickness	3.0 mm (0.118 in)

Torque Specifications

Description	Nm	lb-ft	lb-in
Brake caliper bleed screw	10	—	89
Master cylinder primary brake tube fittings	28	21	—
Master cylinder secondary brake tube fitting	20	—	177