

Specifications



Material		
Item	Specification	Fill Capacity
Motorcraft® DOT 4 LV High Performance Motor Vehicle Brake Fluid PM-20	WSS-M6C65-A2	— ^a
Motorcraft® High Performance DOT 3 Motor Vehicle Brake Fluid (US) / Motorcraft® Brake Fluid - Heavy Duty DOT 3 (Canada) PM-1-C (US); CPM-1-C (Canada)	WSS-M6C65-A1	— ^a
Motorcraft® Metal Brake Parts Cleaner (US) / Motorcraft® Brake Parts Cleaner (Canada) PM-4-A or PM-4-B (US); CPM-4 (Canada)	—	—

^aRefer to the brake fluid reservoir cap for correct brake fluid application.

General Specifications

Item	Specification
Brake Disc	
Brake disc minimum thickness	32 mm (1.259 in)
Brake Pads	
Brake pad maximum taper wear (in any direction)	3.0 mm (0.118 in)
Brake pad minimum thickness	3.0 mm (0.118 in)

Torque Specifications

Description	Nm	lb-ft	lb-in
Brake caliper anchor plate bolts	250	184	—
Brake caliper flow bolt	35	26	—
Brake caliper guide pin bolts	37	27	—

Description	Nm	lb-ft	lb-in
Brake disc shield bolts	18	—	159
Brake flexible hose bracket-to-wheel knuckle bolt	30	22	—
Brake tube fitting	17	—	150