

Specifications



Material		
Item	Specification	Fill Capacity
Motorcraft® High Performance DOT 3 Motor Vehicle Brake Fluid (US) / Motorcraft® Brake Fluid - Heavy Duty DOT 3 (Canada) PM-1-C (US); CPM-1-C (Canada)	WSS-M6C65-A1	1,420 ml (3.0 pt)
Motorcraft® Metal Brake Parts Cleaner (US) / Motorcraft® Brake Parts Cleaner (Canada) PM-4-A or PM-4-B (US); CPM-4 (Canada)	—	—

General Specifications

Item	Specification
Brake Disc	
Brake disc minimum thickness	23.0 mm (0.906 in)
Brake Pads	
Brake pad maximum taper wear (in any direction)	3.0 mm (0.118 in)
Brake pad minimum thickness	3.0 mm (0.118 in)

Torque Specifications

Description	Nm	lb-ft	lb-in
Axle vent valve	18	—	159
Brake caliper bleeder screw	10	—	89
Brake caliper flow bolt	35	26	—
Brake caliper guide pin bolts	33	24	—
Brake caliper support bracket bolts	150	111	—
Brake flexible hose bracket-to-axle bolt	30	22	—
Brake flexible hose bracket-to-frame bolt	17	—	150
Brake tube fitting	17	—	150

