

Specifications



Material		
Item	Specification	Fill Capacity
Motorcraft® DOT 4 LV High Performance Motor Vehicle Brake Fluid PM-20	WSS-M6C65-A2	— ^a
Motorcraft® High Performance DOT 3 Motor Vehicle Brake Fluid (US) / Motorcraft® Brake Fluid - Heavy Duty DOT 3 (Canada) PM-1-C (US); CPM-1-C (Canada)	WSS-M6C65-A1	— ^a
Motorcraft® Metal Brake Parts Cleaner (US) / Motorcraft® Brake Parts Cleaner (Canada) PM-4-A or PM-4-B (US); CPM-4 (Canada)	—	—

^aRefer to the brake fluid reservoir cap for correct brake fluid application.

Torque Specifications

Description	Nm	lb-ft	lb-in
Brake booster-to-pedal bracket nuts ^b	—	—	—
Brake master cylinder nuts	25	18	—
Brake pedal bracket bolts	25	18	—
Brake pedal control switch screw	3	—	27
Coolant expansion tank/lower Air Cleaner (ACL) housing assembly bolts	15	—	133
Hood switch and bracket nut	6	—	53
Primary brake tube fitting	28	21	—
Secondary brake tube fitting	20	—	177

^bRefer to the procedure in this section.