

Specifications



Material		
Item	Specification	Fill Capacity
Motorcraft® MERCON® LV Automatic Transmission Fluid XT-10-QLVC (US); CXT-10-LV12 (Canada)	MERCON® LV	12.30L (13.0 qt)

General Specifications

Item	Specification
Transmission Fluid	
This transmission fluid is not interchangeable with any other transmission fluids. Check the transmission fluid level indicator to determine the correct transmission fluid.	

Torque Specifications

Description	Nm	lb-ft	lb-in
Axle carrier mounting bushing bolt	115	85	—
Axle shaft housing carrier bushing bolt	115	85	—
Forward skid plate (6 required)	48	35	—
Heat shield nut—Raptor	48	35	—
Heat shield nut—Raptor	23	17	—
Rearward skid plate (4 required)	48	35	—
Selector lever cable splash shield nut	12	—	106
Starter motor ground cable eyelet nut	25	18	—
Starter solenoid B-terminal eyelet nut	12	—	106
Starter solenoid S-terminal eyelet	5	—	44
Sway bar nut (4 required) ^a	—	—	—
Transmission fluid cooler tube bracket bolt	12	—	106
Transmission fluid cooler tube bracket-to-front of the engine nut—3.5L GTDI and 3.7L	12	—	106

Description	Nm	lb-ft	lb-in
Transmission fluid cooler tube bracket-to-front of the engine nut—5.0L (4V)	12	—	106
Transmission fluid cooler tube bracket-to-front of the engine nut—6.2L (2V)	40	30	—
Transmission fluid cooler tube bracket-to-starter motor stud nut—3.5L GTDI and 3.7L	12	—	106
Transmission fluid cooler tubes-to-transmission bolt ^a	—	—	—
Transmission-to-engine bolt—6.2L (2V) and 5.0L (4V)	48	35	—

^aRefer to the procedure in this section.