

Specifications



Material		
Item	Specification	Fill Capacity
Motorcraft® MERCON® LV Automatic Transmission Fluid XT-10-QLVC (US); CXT-10-LV12 (Canada)	MERCON® LV	1.4L (2.9 pt) ^a
Motorcraft® Transfer Case Fluid (US; Canada) XL-12 (US); CXL-12 (Canada)	ESP-M2C166-H	1.4L (2.9 pt) ^b
Motorcraft® Thread Sealant with PTFE TA-24-B	WSK-M2G350-A2	—
Ultra Silicone Sealant TA-29	—	—

^a 2-speed torque-on-demand

^b Electronic Shift-On-The-Fly (ESOF)

Torque Specifications

Description	Nm	lb-ft	lb-in
Crossmember bolts	90	66	—
Drain plug	15	—	133
Exhaust heat shield bolts	15	—	133
Exhaust support bracket bolt	35	26	—
Fill plug	15	—	133
Mode Indication Switch (MIS)	41	30	—
Shift motor bolts	10	—	89
Shift motor nuts	3	—	27
Skid plate bolts	40	30	—
Transfer case bolts ^a	—	—	—
Transfer case field coil nuts	10	—	89
Transfer case-to-transmission bolts ^a	—	—	—

Description	Nm	lb-ft	lb-in
Transmission mount bolts	90	66	—
Transmission mount nuts	103	76	—

^aRefer to the procedure in this section.