

Image Operations

Negative ($s = L-1-r$): Inverts all intensities. Dark becomes bright, bright becomes dark.

Log Transform ($s = c \log(1 + r)$): Compresses high intensities, expands low ones. Reveals detail in dark regions.

Power-Law / Gamma ($s = cr^\gamma$): $\gamma < 1$: brightens dark regions. $\gamma > 1$: darkens image, suppresses low intensities.

Contrast Stretching: Maps a narrow intensity range to the full $[0, L-1]$ range. Increases overall contrast.

Intensity-Level Slicing: Highlights a specific intensity band while suppressing or preserving all others.

Bit-Plane Slicing: Decomposes into 8 binary planes. Higher planes carry structure; lower planes carry fine detail/noise.

Thresholding ($s = 0$ or $L-1$): Produces binary image. Separates foreground from background.

Histogram Equalization: Flattens histogram to use full intensity range. Increases global contrast.

Histogram Matching: Reshapes histogram to match a specified target distribution.

Local Histogram Processing: Applies equalization in sliding neighborhoods. Reveals local detail that global methods miss.

Addition / Averaging: $\bar{g}(x, y) = \frac{1}{K} \sum g_i(x, y)$. Reduces noise variance by $1/K$. Images must be registered.

Subtraction: Highlights differences between two images. Removes static background.

Multiplication / Division: Mask with ROI to isolate regions. Division corrects uneven illumination/shading.

Smoothing (Box / Gaussian): Averages neighborhood pixels. Reduces noise but blurs edges.

Median Filter (nonlinear): Replaces pixel with neighborhood median. Removes salt-and-pepper noise while preserving edges.

Sharpening (Laplacian, Unsharp Mask): Enhances edges and fine detail. Makes transitions crisper.

NOT: swaps foreground/background. **AND**: intersection of two masks. **OR**: union of two masks. **XOR**: pixels in one mask but not both.

Image Overlap

$\cup = \text{OR}$ $\cap = \text{AND}$ $A^c = \text{NOT}$

Filter Kernels

Smoothing (Low-Pass)		
Box	Weighted Avg	Gaussian
$\frac{1}{9} \begin{bmatrix} 1 & 1 & 1 \\ 1 & 1 & 1 \\ 1 & 1 & 1 \end{bmatrix}$	$\frac{1}{16} \begin{bmatrix} 1 & 2 & 1 \\ 2 & 4 & 2 \\ 1 & 2 & 1 \end{bmatrix}$	$h(x, y) = \frac{1}{2\pi\sigma^2} e^{-\frac{x^2+y^2}{2\sigma^2}}$

Sharpening (High-Pass)		
Laplacian	Laplacian (diag)	Unsharp ($k=1$)
$\begin{bmatrix} 0 & 1 & 0 \\ 1 & -4 & 1 \\ 0 & 1 & 0 \end{bmatrix}$	$\begin{bmatrix} 1 & 1 & 1 \\ 1 & -8 & 1 \\ 1 & 1 & 1 \end{bmatrix}$	$\frac{1}{9} \begin{bmatrix} -1 & -1 & -1 \\ -1 & 17 & -1 \\ -1 & -1 & -1 \end{bmatrix}$

Edge Detection (Gradient)		
Sobel G_x	Sobel G_y	Prewitt G_x
$\begin{bmatrix} -1 & 0 & 1 \\ -2 & 0 & 2 \\ -1 & 0 & 1 \end{bmatrix}$	$\begin{bmatrix} -1 & -2 & -1 \\ 0 & 0 & 0 \\ 1 & 2 & 1 \end{bmatrix}$	$\begin{bmatrix} -1 & 0 & 1 \\ -1 & 0 & 1 \\ -1 & 0 & 1 \end{bmatrix}$