

Human-Supervised CFAR Autotuning for Maritime Sensing

Nathan Kirk*, J.C. Vaught†, Douglas Cahl‡, Yi Wang§
University of South Carolina, Columbia, SC, 29208

Maritime domain awareness, search-and-rescue, and coastal monitoring requires robust on-board radar detection under tight size, weight, power, and cost constraints. Tuning Constant False Alarm Rate (CFAR) detectors for littoral scenes is notoriously difficult due to heavy-tailed sea clutter, land/sea transitions, and shoreline multipath, yet remains essential for low-latency situational awareness. We present a human-supervised methodology for tuning CFAR parameters of commercial-off-the-shelf X-band radars in coastal scenes with stationary/persistent objects. The human operator provides bounding boxes around stationary reference objects (e.g., navigation aids, towers, shoreline structures) on one or more radar frames. Then, the system (i) propagates those regions across a frame sequence, (ii) sweeps the parameter spaces of multiple CFAR variants (cell-averaging, order-statistic, censored, and others), and (iii) solves a multi-objective optimization by maximizing true detections inside annotated regions and minimizing false alarms elsewhere under an explicit constraint. The outcome is a scene- and sensor-tailored algorithm and parameter configuration. Performance is evaluated on synthetic heavy-tailed sea-clutter (K/Pareto) and real X-band radar sequences to characterize the detection–false-alarm trade space under explicit constraints, and to illustrate how the resulting scene-tailored configuration differs from default single-algorithm tuning.

I. Introduction

Coastal and port approaches are operationally challenging radar environments due to strong, non-Gaussian sea clutter, land–sea transition edges, multipath from shoreline infrastructure, and mixed cooperative/non-cooperative traffic. Tuning CFAR detector parameters for these scenes is notoriously scene- and sensor-dependent. We propose a *user-in-the-loop* approach in which a human operator selects a few stationary reference objects; the system then seeks CFAR parameters that consistently detect those objects while suppressing clutter-induced false alarms elsewhere.

AIAA motivation. Small unmanned aircraft systems (UAS) and optionally piloted platforms are increasingly tasked with maritime domain awareness, search-and-rescue, and coastal environmental monitoring. Their radars often operate at low grazing angles in littoral airspace with tight size, weight, power, and cost (SWaP-C) constraints. A configurable CFAR stack that can be quickly tuned in-situ to a given shoreline helps enable robust on-board autonomy and low-latency situational awareness.

Contributions. (1) A formal multi-objective objective for CFAR tuning anchored to human-selected stationary references; (2) a solver-agnostic strategy (grid/racing, evolutionary, Bayesian optimization) over algorithm and parameter spaces; (3) a practical evaluation protocol with percentile-robust detection metrics and explicit penalties for out-of-ROI false alarms; (4) reproducible pseudocode and open-source implementation plan.

II. Background and Related Work

A. CFAR Detectors

The CA-CFAR family estimates background power via local training windows and compares the cell-under-test to a scaled statistic to maintain a desired constant false alarm rate P_{FA} [1, 6, 19]. GO- and SO-CFAR improve robustness near clutter edges and in multi-target scenes by partitioning leading/trailing windows and taking greatest-or smallest-of statistics [2, 3]. Order-statistic (OS-) CFAR sorts reference cells and selects a k-th order statistic to resist outliers/interferers [4, 5]. Variability-index and censored/trimmed-mean CFAR further mitigate heterogeneous backgrounds [7, 8].

*Undergraduate Student, Department of Mechanical Engineering, AIAA Student Member, Member ID: 1924156.

†Graduate Student, Department of Mechanical Engineering, AIAA Student Member, Member ID: 1537189.

‡Professor, Department of Mechanical Engineering.

§Professor, Department of Mechanical Engineering.

B. Littoral Sea-Clutter Models

High-resolution maritime clutter is heavy-tailed and spatially nonhomogeneous; K-distribution and Pareto Type I/II models are widely used [9–11]. These models motivate CFAR designs that avoid contamination of training windows across land–sea transitions and surf zones, and inspire OS-/censoring strategies in heterogeneous clutter [12, 18].

C. Parameter Tuning and Compute Considerations

CA-CFAR admits closed-form threshold multipliers as functions of P_{FA} and reference-cell counts, while OS-CFAR trades robustness for sorting cost and tabulated multipliers [13]. Real-time variants, FPGA/HLS implementations, and runtime-reconfigurable CFAR engines demonstrate feasibility for embedded platforms [14, 16]. Recent learning-based approaches (e.g., CFARNet) seek CFAR-like guarantees from data [15], but target-agnostic hyperparameter selection remains an open, scene-specific problem—precisely what our user-anchored objective addresses.

Positioning relative to prior work. CFAR has been widely used across maritime and aerial surveillance owing to its controllable P_{FA} , local-statistics design, and suitability for embedded implementations [6, 8, 10]. Despite numerous efforts to simplify or automate CFAR tuning—ranging from vendor rule-of-thumb guides and interactive GUIs to heuristic or evolutionary search over thresholds for a single CFAR variant [13, 14, 19]—we are not aware of methods that explicitly combine human accuracy (via bounding boxes on stationary reference objects) with computational optimization to both accelerate the process and maintain accuracy in heterogeneous littoral clutter. Therefore, we formulate an ROI-anchored, multi-algorithm parameter search that uses human-provided supervision to define the objective while leveraging modern optimizers to efficiently explore the algorithm–parameter space.

III. Problem Formulation

Let $I_t \in \mathbb{R}^{M \times N}$ denote radar intensity (range–Doppler or range–azimuth) frames, $t = 1, \dots, T$. A user provides B axis-aligned bounding boxes $\{\mathcal{R}_b\}_{b=1}^B$ around stationary objects on a reference frame; we assume platform motion compensation (or a stationary sensor) allows propagation of $\mathcal{R}_b$ across frames.

Consider a CFAR algorithm $a \in \mathcal{A}$ (e.g., CA, GO, SO, OS, VI/censored) with parameter vector θ_a : number of reference cells N_r , guard cells N_g , order k (OS), censoring/variability thresholds, and threshold scaling factor α . Applying (a, θ_a) to frame I_t yields a binary detection map $D_t(a, \theta_a) \in \{0, 1\}^{M \times N}$.

We define in-ROI detection rate

$$\text{TPR}(a, \theta_a) = \text{median}_{b \in [B]} \text{quantile}_{t \in [T]} \left[\frac{\sum_{(i,j) \in \mathcal{R}_b} D_t(i, j)}{|\mathcal{R}_b|}; q \right], \quad (1)$$

with percentile $q \in [0.5, 0.95]$ to emphasize persistent detection. False-alarm density outside ROIs is

$$\text{FAD}(a, \theta_a) = \frac{\sum_t \sum_{(i,j) \notin \cup_b \mathcal{R}_b} D_t(i, j)}{\sum_t |\Omega \setminus \cup_b \mathcal{R}_b|}. \quad (2)$$

We enforce an empirical P_{FA} constraint $\widehat{P}_{FA}(a, \theta_a) \leq P_{FA}^{\max}$ over background-only tiles.

The tuning objective is a weighted scalarization

$$J(a, \theta_a) = \text{TPR}(a, \theta_a) - \lambda \text{FAD}(a, \theta_a), \quad (3)$$

optionally subject to smoothness or compute regularizers (e.g., $\rho \mathbb{I}[a = \text{OS}]$ to price sorting cost).

IV. Optimization Strategy

A. Search Over Algorithms and Parameters

We search jointly over $a \in \mathcal{A}$ and θ_a . For small problems, Latin-hypercube or racing-based grid searches work well. For larger or expensive evaluations (e.g., long sequences), we apply Bayesian optimization (BO) with Gaussian-process surrogates and acquisition functions (EI/LCB), treating a as a categorical variable encoded via one-hot embeddings.

Algorithm 1 User-in-the-Loop CFAR Tuning (High Level)

- 1: **Input:** frames $\{I_t\}_{t=1}^T$, user ROIs $\{\mathcal{R}_b\}_{b=1}^B$, CFAR family $\mathcal{A}$, budget H , weights (λ, q) , $P_{FA}^{\max}$
 - 2: Propagate ROIs across frames (identity or via registration)
 - 3: **for** $h = 1$ to H **do**
 - 4: Propose (a, θ_a) via grid/GA/BO
 - 5: Compute $D_t \leftarrow \text{CFAR}(I_t; a, \theta_a)$ for all t
 - 6: Estimate TPR, FAD, $\hat{P}_{FA}$ on validation frames/tiles
 - 7: If $\hat{P}_{FA} > P_{FA}^{\max}$ then set $J \leftarrow -\infty$ and continue
 - 8: Update incumbent $(a^*, \theta_a^*) \leftarrow \arg \max J$
 - 9: **end for**
 - 10: **Return** (a^*, θ_a^*) and diagnostics (per-stratum metrics, ROC within ROIs)
-

B. Robust Cross-Validation in Littoral Scenes

We divide frames into *shoreline strata* (sea-only, land-only, transition bands) based on a land/sea mask or texture segmentation, and compute J within each stratum. The final score averages across strata with operator-chosen weights. This guards against overfitting to, for example, calm-sea conditions while degrading near surf.

C. Percentile-Robust Metrics and PFA Control

The quantile in TPR emphasizes persistence across frames, while FAD penalizes spurious detections in background. We also report ROC-like curves within ROIs by sweeping α to verify that the chosen configuration meets $P_{FA}^{\max}$ in held-out background tiles.

V. Experimental Design

A. Data

Synthetic. Generate sea clutter with K- and Pareto Type II statistics across sea states and grazing angles; inject stationary point/extended targets (Swerling I/III-like fluctuations). Add shoreline edges by stitching land and sea tiles with step changes.

Real. Fixed-shore radar or UAS-borne FMCW radar sequences of harbors/inlets with persistent aids-to-navigation and towers as ROIs. Annotate 5–10 ROIs per scene.

B. Baselines and Ablations

Compare CA-/GO-/SO-/OS-/censored (trimmed-mean/VI) CFAR. Ablate: (i) no percentile aggregation, (ii) no stratum balancing, (iii) single-algorithm tuning.

C. Metrics

Primary: (i) in-ROI detection percentile at $q \in \{0.5, 0.9\}$, (ii) background FAD, (iii) scene-level F_β with $\beta < 1$ to emphasize precision (false-alarm control), (iv) compute cost per frame. Secondary: per-stratum scores and CFAR loss (dB) vs. reference-cell count.

VI. AIAA Relevance and Use Cases

For maritime UAS, rapidly configurable CFAR improves: (1) on-board detection of fixed navigation aids during autonomous coastal mapping; (2) port approach monitoring and deconfliction; (3) search-and-rescue in surf zones where sea spikes create false alarms. The proposed tuner fits SWaP-C limits by allowing selection of compute-cheaper variants (e.g., CA-/GO-CFAR) when OS-/censoring is too costly.

VII. Discussion and Limitations

Our method assumes (quasi-)stationary reference objects and accurate registration across frames. Extension to moving targets would require track-before-detect or multi-frame association. Future work includes adaptive land/sea transition detection to automatically censor contaminated training windows and joint tuning with tracking/clustering stages.

VIII. Conclusion

We introduced a practical user-in-the-loop CFAR tuning framework tailored to littoral radar scenes, unifying multi-algorithm selection with scene-specific parameter search under explicit P_{FA} control. We expect consistent improvements in persistent detection of operator-specified stationary objects with fewer background alarms, enabling robust maritime sensing on constrained aerial platforms.

A. Implementation Details

A. Parameter Spaces

- CA-/GO-/SO-CFAR: $N_r \in [8, 128]$, $N_g \in [1, 8]$, multiplier α matched to target $P_{FA} \in [10^{-6}, 10^{-3}]$ via closed forms.
- OS-CFAR: $N_r \in [16, 256]$, $k \in \lceil [0.5N_r] \rceil$, $N_r - 1$, α from tables or numerical inversion.
- Censored/VI-CFAR: upper/lower censoring fractions in $[0, 0.2]$, variability gate in $[0.0, 0.5]$.

B. Pseudocode Snippet

Algorithm 2 Score and Constraint Evaluation

- 1: $\text{TPR} \leftarrow \text{Quantile}_t \text{Median}_b \frac{\sum_{(i,j) \in \mathcal{R}_b} D_t(i,j)}{|\mathcal{R}_b|}$
 - 2: $\text{FAD} \leftarrow \frac{\sum_t \sum_{(i,j) \notin \cup_b \mathcal{R}_b} D_t(i,j)}{\sum_t |\Omega \setminus \cup_b \mathcal{R}_b|}$
 - 3: Enforce $\hat{P}_{FA} \leq P_{FA}^{\max}$ using background-only tiles
 - 4: Return $J = \text{TPR} - \lambda \text{FAD}$
-

B. Alternate Title Options

- 1) Scene-Tailored CFAR: User-Annotated Parameter Optimization for Littoral Surveillance Radars
- 2) Tuning CFAR for the Coast: A User-in-the-Loop Multi-Algorithm Search with P_{FA} Guarantees
- 3) Bounding-Box-Guided CFAR Selection for Stationary Targets in Maritime Radar
- 4) Practical CFAR Autotuning for UAS Maritime Sensing in Littoral Environments
- 5) Robust CFAR in Heterogeneous Sea Clutter via Percentile-Robust, Multi-Objective Search

C. Acronyms

CFAR	Constant False Alarm Rate
GO-/SO-/OS-	Greatest-/Smallest-/Order-Statistic
ROI	Region of Interest
UAS	Unmanned Aircraft System
FAD	False Alarm Density

Acknowledgments

The authors thank the University of South Carolina Radar and Autonomy Group for feedback on early prototypes.

References

- [1] H. M. Finn and R. S. Johnson, "Adaptive detection mode with threshold control as a function of spatially sampled clutter level estimates," *RCA Review*, vol. 29, pp. 414–464, Sept. 1968.
- [2] V. G. Hansen and J. H. Ward, "Detection performance of the cell averaging log/CFAR receiver," *IEEE Trans. Aerosp. Electron. Syst.*, vol. AES-8, no. 5, pp. 648–654, Sept. 1972.
- [3] G. V. Trunk, "Range resolution of targets using automatic detectors," *IEEE Trans. Aerosp. Electron. Syst.*, vol. AES-14, no. 5, pp. 750–755, 1978. [SO-CFAR progenitor]
- [4] H. Rohling, "Radar CFAR thresholding in clutter and multiple target situations," *IEEE Trans. Aerosp. Electron. Syst.*, vol. 19, no. 4, pp. 608–621, 1983.
- [5] O. Rimbart and P. V. Meirvenne, "Performance comparison of order statistic CFAR detectors," in *Proc. IET Radar*, 2005, pp. 1–5.
- [6] P. P. Gandhi and S. A. Kassam, "Analysis of CFAR processors in nonhomogeneous background," *IEEE Trans. Aerosp. Electron. Syst.*, vol. 24, no. 4, pp. 427–445, Jul. 1988.
- [7] S. D. Himonas and M. Barkat, "Automatic censored CFAR detection for nonhomogeneous environments," *IEEE Trans. Aerosp. Electron. Syst.*, vol. 28, no. 1, pp. 286–304, 1992.
- [8] A. Farina, "A review of CFAR detection techniques in radar systems," in *DSP for Radar and Communications*, 2005, pp. 1–42.
- [9] E. Jakeman and P. N. Pusey, "A model for non-Rayleigh sea echo," *IEEE Trans. Antennas Propag.*, vol. 24, no. 6, pp. 806–814, 1976.
- [10] K. D. Ward, R. J. A. Tough, and S. Watts, *Sea Clutter: Scattering, the K Distribution and Radar Performance*. IET, 2006.
- [11] G. V. Weinberg, "Examination of classical detection schemes for targets in Pareto distributed clutter," *Signal, Image and Video Processing*, vol. 7, pp. 1333–1345, 2013.
- [12] M. V. Greco, et al., "CFAR detection in heterogeneous K-distributed sea clutter," in *Proc. IET Radar*, 2010. [or similar Cranfield technical report]
- [13] B. Katzlberger, "Object Detection with Automotive Radar Sensors using CFAR Algorithms," B.Sc. thesis, Johannes Kepler Univ., 2018.
- [14] M. Rangaswamy, "Real-Time Implementations of Ordered-Statistic CFAR," *Zenodo* preprint, 2018.
- [15] T. Diskin, Y. Beer, U. Okun, and A. Wiesel, "CFARNet: Deep learning for target detection with constant false alarm rate," arXiv:2208.02474, 2022.
- [16] A. Rostov, "CFAR detector implementation using Vitis HLS," Hackster.io, Jan. 2025.
- [17] G. Farina, "Bayesian optimization," MIT lecture notes, 2024.
- [18] G. V. Weinberg, "Multipulse OS-CFAR in Pareto background," arXiv:1901.03437, 2019.
- [19] MathWorks, "Constant False Alarm Rate (CFAR) Detection," online documentation, accessed Nov. 2025.