

Vision-Based Flow-Front Assessment in Vacuum-Assisted Resin Transfer Molding

J.C. Vaught¹, Marshall Pigford², Declan Johnson³ and Darun Barazanchy⁴
University of South Carolina, Columbia, SC, 29208, USA

Vacuum-Assisted Resin Transfer Molding (VARTM) operators read the visible advance of the resin flow front under the transparent vacuum bag as their primary process indicator. Prior vision systems for VARTM and Liquid Composite Molding use the same classical visual primitives, namely reference-frame differencing, Otsu thresholding, and morphological cleanup, but each system uses a different subset, no system reports the joint and individual contribution of those primitives, and no labeled video benchmark exists against which to attribute that contribution. This work presents an integrated classical computer-vision pipeline that combines a peak-brightness reference, a darken-only difference, region-of-interest restriction, dynamic-lag reference selection, morphological cleanup, and persistence-based temporal locking, evaluated on a fifty-five-frame hand-labeled subset spanning eleven distinct VARTM infusion runs. The integrated configuration reaches mask Intersection-over-Union of $X.XXX$ (95 % bootstrap confidence interval $[a, b]$) and boundary F_1 of $Y.YYY$ (CI $[c, d]$). A per-sample component-removal ablation on the same subset characterizes the marginal IoU effect of each named primitive, both as an eleven-sample mean and broken down per sample so that primitives whose contribution depends on infusion regime are visible rather than averaged away. The pipeline runs at thirty frames per second on a single CPU and at K frames per second on a CUDA implementation across the eleven samples.

I. Nomenclature

F_t	=	converted-colorspace frame at time index t
G_t	=	reference image at time index t
G_t^*	=	effective reference (peak map when peak-reference enabled, otherwise channel-zero of G_t)
P_t	=	per-pixel peak-brightness map at time t
D_t	=	per-pixel response field at time t
R	=	binary region-of-interest mask
H, W	=	frame height and width in pixels
C	=	channel count of the working colorspace
α	=	exponential-moving-average factor for running-reference mode
κ	=	sqrt-area growth factor estimated from calibration frames
ρ	=	target wet-fraction for dynamic reference mode
λ	=	user lag scale factor for dynamic reference
τ_t	=	elapsed time at frame index t in seconds
$\Delta\tau_t$	=	dynamic lag in seconds for the reference frame
w_c	=	channel weight in the delta computation

¹Graduate Research Assistant, Department of Mechanical Engineering, AIAA Student Member.

²Undergraduate Research Assistant, Department of Computer Science and Engineering, AIAA Student Member.

³Graduate Research Assistant, Department of Mechanical Engineering, AIAA Student Member.

⁴Research Assistant Professor, Department of Mechanical Engineering, AIAA Member.

N_{calib}	=	number of calibration frames before dynamic reference activates
f	=	video frame rate in frames per second
IoU	=	Intersection-over-Union mask agreement score
F_1	=	boundary F_1 score, mean across pixel tolerances $\tau \in \{1, 3, 5\}$

II. Introduction

VACUUM-Assisted Resin Transfer Molding (VARTM) is the dominant process for one-off composite laminates from research panels through small-series aerospace structural parts, and the principal observable signal available to the operator during a run is the visible advance of the resin flow front under the transparent vacuum bag [1].

The position, shape, and rate of that front carry process-quality information that other, more instrumented modalities recover only indirectly. Distributed dielectric arrays [2] and area-sensor grids [3] produce excellent local wetness measurements but require sensors embedded in the lay-up, and fiber-optic frequency-domain reflectometry [4] demands instrumentation no operator on a research bench will install for a one-off panel. Direct video of the bag is the one modality that costs nothing extra, sees the entire laminate at once, and is already recorded in most labs as a procedural artifact.

Prior camera-based VARTM and Liquid Composite Molding (LCM) systems agree on the basic recipe. Difference the live frame against a reference image of the dry preform, threshold the response into a binary candidate mask, and clean the mask with morphology [5,6]. They disagree on every detail that controls how well the recipe works. Some systems clip the difference so that only darkening counts as wetting and others do not [6]. Some track a per-pixel running maximum as the reference and others pin a single early frame [5]. Some impose a temporal-locking rule that holds a positive detection through transient dropouts and others operate frame-by-frame [7]. None of these systems reports the joint contribution of the components it uses, the marginal cost of each component it discards, or the agreement of the resulting mask against a labeled video benchmark, because no shared labeled benchmark exists. The practitioner is left to take the recipe at face value.

The work is hard for three concrete reasons that have to be addressed by anything claiming to do it. The vacuum bag produces strong specular reflections from lab lighting that look bright in every channel and shift on every operator move. The bag wrinkles and creases that pre-date the front are static dark features that do not represent wet fabric and must not be mistaken for it. The lighting itself drifts across a multi-minute infusion as lamps warm up and the operator moves equipment. A pipeline that fails to address any one of these will mark unwetted fabric as wet on most frames of most infusions. Prior camera-based systems individually defeat one or two of the three. None reports which component defeats which failure mode, and none reports the price paid for leaving any of them out.

This paper presents an integrated classical-computer-vision pipeline that combines, in one configuration, the visual primitives the prior systems use in isolation. The pipeline restricts the comparison to a region of interest, projects the working frame into the lightness channel of CIELAB, accumulates a per-pixel peak-brightness reference that absorbs lighting drift, computes a darken-only difference that rejects specular highlights, dynamically lags the reference frame against fill rate, thresholds the response with Otsu, cleans the mask with morphological closing and opening followed by connected-components filtering, and locks pixels whose wet label has persisted for several consecutive frames. On a 55-frame hand-labeled subset spanning eleven distinct VARTM infusion runs, the integrated configuration reaches mask Intersection-over-Union (IoU) of $X.XXX$ with a 95 % bootstrap confidence interval of $[a, b]$ and boundary F_1 of $Y.YYY$ with confidence interval $[c, d]$. A per-sample component-removal ablation on the same subset reports the marginal IoU effect of disabling each named primitive in turn. The reported effects are not uniform in sign or magnitude across the eleven samples, which is the empirical content of the ablation rather than a defect, since a primitive that helps a long operator-view recording can be neutral or counterproductive on a high-frame-rate clip whose dynamics it was not tuned for. The pipeline runs at 30 frames per second on a single central-processing-unit (CPU) thread, and a CUDA implementation reaches K frames per second on the same eleven samples.

The contributions of this paper are the following.

1. An integrated VARTM flow-front segmentation pipeline that combines peak-brightness reference, darken-only difference, ROI restriction, dynamic-lag reference selection, Otsu-plus-offset thresholding, morphological

cleanup, and persistence-based temporal locking in one configuration, with mean IoU $X.XXX$ and boundary F_1 $Y.YYY$ reported with 95 % bootstrap confidence intervals on a 55-frame hand-labeled subset spanning eleven distinct infusion runs.

2. A component-removal ablation that quantifies the marginal IoU effect of each named primitive on the same 55-frame subset, both as an eleven-sample mean and as a per-sample breakdown. The breakdown is reported in full because the effect of any one primitive is regime-dependent, so the joint composition is justified by the per-sample evidence rather than by a single mean.

Section 2 places this work among the three families of prior work that touch the problem. Section 3 walks each component of the pipeline and points forward at the ablation evidence. Section 4 documents the labeling protocol and the eleven-sample dataset. Section 5 reports the integrated configuration’s agreement against the labeled subset and the per-component ablation. Section 6 reports CPU and CUDA throughput. Section 7 discusses failure modes and design tradeoffs. Section 8 concludes.

III. Related Work

Prior work on Vacuum-Assisted Resin Transfer Molding (VARTM) and the broader Liquid Composite Molding (LCM) family touches the flow front from three different directions. A first body of work uses flow-front information to act on the process through closed-loop control or fault response. A second body observes the process to characterize it, typically with embedded sensors or auxiliary cameras for offline study. A third body models the underlying Darcy physics or inverts it from sparse measurements. The work in this paper sits at the seam of all three because the integrated pipeline produces the per-frame full-field flow-front mask that the first family assumes is available, that the second family currently approximates with sensor grids, and that the third family typically receives only as a handful of digitized contours from a manual annotation pass. The remainder of this section addresses each family in turn and closes with the specific gap that the integrated pipeline fills.

A. Use: vision and sensors that act on the VARTM process

Closed-loop VARTM controllers have a long lineage. Multi-segment injection-line work coupled point sensors with a finite-element flow model so that valves could be re-sequenced in real time to chase the flow front toward starved regions and away from race-tracks [8]. The control loop is genuinely real time and the empirical results are convincing for plate geometries, but the feedback signal is a sparse vector of resin-arrival times at instrumented locations, which means dry-spot detection only works when a sensor happens to lie inside the dry region. The integrated pipeline differs by treating every pixel inside the bag as a potential sensor, so dry-spot evidence is not gated on instrumentation density.

A more recent line of work replaces point sensors with a top-mounted camera. Mesogitis and co-workers built a webcam-plus-microcontroller rig that segments the resin flow front with classical machine-vision routines and toggles inlet valves on the resulting front position [5]. Mendizabal et al. close a similar loop on resin film infusion, regulating flow-front velocity to a fixed setpoint with a PID over an OpenCV pipeline and reporting tensile-strength gains of up to 18 percent at the optimal velocity window [6]. Both systems demonstrate that vision alone can drive VARTM control, but neither reports the joint or individual contribution of the segmentation primitives they use, neither evaluates the segmentation against a labeled video benchmark, and both treat the segmentation step as a black box that succeeds or fails as a unit. The work in this paper differs by combining the same family of primitives in one configuration and reporting the agreement of the joint configuration and the IoU cost of disabling each component on a labeled subset spanning eleven distinct infusion runs.

Adjacent to control are vision-based defect-detection systems for composites more broadly [9]. These pipelines now lean almost entirely on convolutional or transformer detectors trained on hand-curated defect crops, and a recurring bottleneck across that survey is the cost of pixel-accurate labels. The work in this paper is upstream of that bottleneck. The integrated classical pipeline produces per-pixel front masks deterministically and characterizes which components are responsible for which IoU points, which gives a downstream learned detector [10,11] a labeled-data starting point whose error structure is decomposable rather than monolithic.

B. Observe: sensor-based and vision-based process characterization

A second family treats the flow front as something to be measured rather than acted on. Konstantopoulos and co-authors review the in-line sensing landscape and group the field around dielectric, thermal, ultrasonic, fiber-optic, and electrical-resistance sensors [1]. Dielectric tracking by Yenilmez and Sozer and others gives unsaturated and saturated front positions at each electrode pair, with an installation cost that is hard to beat, but the spatial resolution of the resulting front is limited by the electrode pitch [2]. Matsuzaki and co-workers dramatically improve coverage with an area-sensor array that tiles a polyimide film into a dense capacitive matrix and recovers the impregnated-area ratio per cell, which is the closest sensor-side analogue to a full-field flow-front mask [3]. The resulting front is, however, still a quantized grid that is destructive to instrument inside production tooling and that adds permeability to the stack-up.

Fiber-optic strategies use Fiber Bragg Grating arrays or Optical Frequency Domain Reflectometry to time-stamp resin arrival at every grating along an embedded fiber, and recent distributed-sensing implementations push toward life-cycle structural health monitoring of large CFRP parts [4]. These methods deliver excellent temporal precision and can survive infusion and cure, but the same coupling between sensor density and front fidelity reappears, since arbitrary front shapes between gratings are interpolated, not measured. A small but growing thread fuses dielectric and visual data with learning-based fusion. The recent AI-based dielectric-plus-visual monitor by Esposito and co-workers detects and tracks the front with a YOLO detector trained on labeled video and uses dielectric channels as a redundant signal [7]. That pipeline is closest in spirit to the front producer described here, but it is reported on a single-fabric study, it does not report which preprocessing components carry which IoU points, and the detector is trained rather than classical. The work in this paper differs by combining the classical primitives the prior systems use in isolation, evaluating the joint configuration on a labeled subset spanning eleven infusion runs, and reporting the marginal IoU effect of each component.

Stieber and co-workers show that learning a flow-front “image” from a sparse pressure-sensor grid is a tractable surrogate task and report time-step accuracy near 92 percent on simulated injection runs [12]. A follow-on extends the same approach to material-property inference under a simulation-to-real transfer pretext and shows IoU around 0.50 with transformer backbones [13]. These are excellent demonstrations of what a network can learn given ground-truth flow-front maps. They presume the maps exist, and they obtain them from FEM injection simulations rather than from real video. The work in this paper addresses the upstream half of that pipeline by producing per-pixel front masks from real VARTM video that such networks would need for fine-tuning, and by reporting which components of the upstream segmenter contribute which IoU points.

C. Model: physics-based forward and inverse flow-front formulations

The third family models the front analytically or numerically. Forward Darcy-flow simulators for VARTM now routinely couple a depth-averaged Darcy solver to a level-set front with high-permeability-medium layers and progressive-saturation effects [14], and end-to-end VARTM simulation with reinforcement compaction and post-filling pressure relaxation has been validated experimentally for plate and stiffened-plate geometries [15]. These models predict the flow front given a permeability field and a boundary condition. The inverse direction is harder. Comas-Cardona and co-authors recover an in-plane permeability field by coupling optical areal-weight measurement with central-injection front observation, and similar work by Di Fratta, Klunker, and Ermanni inverts pressure-sensor traces against an analytic front model to update injection parameters online [16,17]. These methods are mathematically careful, but they all depend on having the front geometry as input. In Comas-Cardona that geometry comes from a manually thresholded plate experiment, and in the sensor-based works it comes from arrival-time interpolation. The integrated pipeline lowers the cost of populating that input by producing per-frame, per-pixel front masks directly from the production video stream that is already being recorded for documentation.

Recent work has begun to merge model and learning. Park and co-authors couple electromechanical PZT signals to a tree-plus-GAN model that both identifies the live front and forecasts its near-future position [18], and physics-informed neural permeability inversion has been explored in synthetic Darcy benchmarks [19]. Both are promising for closed-loop VARTM, and both inherit the same dependency on a labeled flow-front signal during training. Without an open, retargetable source of that signal in real video, every group reproducing or extending these methods has to instrument a new bench.

D. Building blocks: classical CV foundations

The integrated pipeline stays deliberately within well-understood classical operators. Otsu’s bimodal threshold provides the wet-versus-dry separation in each frame [20], the Suzuki-Abe topological-border-following algorithm provides hierarchically consistent contour extraction over the resulting binary [21], and the Kim et al. codebook background model handles the slow illumination drift typical of multi-hour infusions without retraining [22]. None of these primitives is novel. The contribution of this paper is the joint composition, the per-stage parameterization, and the per-component evidence that the joint matters on a labeled multi-mold subset. The recent material-defect-detection survey notes that the absence of characterized preprocessing pipelines is a primary bottleneck for deploying deep models in composite quality control [9], and modern detectors such as YOLO illustrate why that bottleneck matters because they are starved for in-domain pixel labels rather than for capacity [23].

E. Where this work fits

The three families above all touch the flow front, but none of them reports the question this paper answers. The control family treats segmentation as a black box and reports downstream control quality, not segmentation quality. The observation family reports excellent agreement at sensor electrodes and gratings, but interpolates between them rather than measuring per-pixel front geometry from video. The modeling family assumes a per-pixel front exists and consumes it, which is precisely the artifact the upstream segmenter must produce. Within the camera-based subset of the observation family, prior systems differ in which subset of the available primitives they use and report only end-to-end behavior on a single mold. None reports the joint contribution of the components in use, none reports the marginal cost of any component left out, and none evaluates against a labeled video benchmark spanning more than one mold. This paper supplies that evidence on eleven distinct infusion runs and on a 55-frame hand-labeled subset.

IV. Method

A. Pipeline overview

The integrated pipeline is built from primitives that each prior camera-based VARTM and LCM system uses in some subset. None of the primitives is novel in isolation. The empirical question this paper supplies evidence for is what each primitive contributes to the joint result on a labeled multi-mold subset, and the method described below is the configuration that supports that question.

The detection algorithm treats each video frame as a comparison against a reference image of the dry preform. Where resin has wetted the fabric, the local appearance darkens, and the absolute change is largest near the advancing flow front. The pipeline first checks for camera motion against the previous frame and, when motion crosses a configured threshold, registers the live frame back into the reference coordinate system before any difference is computed. The registered frame is optionally smoothed with a pre-delta blur whose output feeds both the running peak map and the difference computation, so the reference and the comparison see the same bandwidth-limited input. The pipeline computes the per-pixel difference inside a rectangular region of interest, clips it to admit only darkening so that specular highlights from the vacuum bag are rejected, normalizes the resulting field, thresholds it into a binary candidate mask, cleans the mask with morphological closing and opening, removes small connected components, and finally locks pixels whose wet label has persisted for several consecutive frames. The locked mask is the canonical output, the optional heatmap renders the underlying delta field for visual diagnosis, and the optional overlay draws the mask boundary onto the original Vacuum-Assisted Resin Transfer Molding (VARTM) frame for human review. Figure Fig. 1 shows the fourteen stages in order.




Fig. 1 Fourteen-stage integrated pipeline. Each frame flows from decode through an optional camera-shift registration and pre-delta blur, then through an appearance-difference comparison against a chosen reference, into a thresholded and morphologically cleaned mask, and finally through a temporal lock that stabilizes the boundary across frames. The same mask drives the binary, heatmap, and overlay renderers.

The pipeline is deliberately classical because the empirical claim of this paper is per-component. Every stage is an explicit function of one frame, the chosen reference image, and a small set of scalar parameters, which is the property that makes the component-removal ablation in Section 5 well defined. A learned segmenter would conflate the contributions of the components inside it, and the question this paper asks would not be answerable.

B. Frame decode and colorspace conversion

The first stage decodes each Blue-Green-Red (BGR) frame from the input video. The second projects that frame into a working colorspace. The pipeline supports four options, namely the International Commission on Illumination (CIE) 1976 $L^*a^*b^*$ colorspace (CIELAB), Red-Green-Blue (RGB), Hue-Saturation-Value (HSV), and 8-bit grayscale. The integrated configuration uses CIELAB because for the resin-and-fabric combinations in the eleven samples evaluated here, wetting primarily darkens the lightness channel L^* rather than shifting chrominance, so the single-channel L^* projection used in the difference computation captures most of the signal. The choice is regime-dependent rather than universal. A pigmented resin or a colored fabric could shift the balance of evidence into chrominance and make RGB or HSV preferable, which is why the alternatives remain selectable. The categorical panel of Figure Fig. 9 reports the IoU effect of each alternative on the canonical reference video; the eleven-sample mean and per-sample breakdown are reported in Table Table 6. We denote the converted frame at index t by $F_t \in \mathbb{R}^{H \times W \times C}$, where C is the channel count of the chosen colorspace.

C. Region of interest

A rectangular region of interest excludes the part frame, manifold flange, and bag wrinkles outside the laminate. The user supplies four fractional margins, one per edge, each clamped to the closed interval from zero to forty-nine hundredths of the corresponding side, and the algorithm builds a binary mask R that is one inside the resulting rectangle and zero elsewhere. A single configuration parameter sets all four margins symmetrically, with per-edge overrides available. All subsequent stages operate only on pixels where $R = 1$.

D. Camera-shift detection and registration

A bumped tripod, a thermal expansion of the rig, or a hand brushing the camera in mid-run shifts the projected position of every laminate pixel by some vector that has nothing to do with wetting. The reference frame stops aligning with the live frame, the difference field lights up along high-contrast laminate edges, and the threshold catches that as wet. The pipeline detects the shift and corrects it before the difference is computed. For each frame, a single phase-correlation step on a fixed-resolution downsample of the working channel of the previous and current frames returns a translation (d_x, d_y) and a confidence score. When either the per-frame magnitude $\sqrt{d_x^2 + d_y^2}$ or the cumulative drift across a five-frame rolling window exceeds the configured threshold, an iterative-coplanar-correlation refinement fits a translation or affine warp W_t on a static-edge mask of the current ROI, and the live frame is warped through W_t into the reference coordinate system before all downstream stages. The static-edge mask is recomputed at each shift event so the registration is driven by mold and frame edges that do not move with the wet front rather than by the wet region itself. The peak map is reset on registration so the post-warp pixels do not accumulate against pre-warp brightness. Figure Fig. 2 shows the shift trace and trigger events on the canonical reference video, with one bumped-tripod event near frame 71 that the pipeline catches and corrects.




Fig. 2 Per-frame shift magnitude (garnet) and rolling five-frame cumulative magnitude (atlantic) for the canonical reference video after windowed phase correlation. Red ticks along the time axis mark frames at which the iterative-coplanar-correlation refit triggers. The dominant event near frame 71 is a real bumped-tripod incident; the pipeline’s per-frame and rolling triggers both fire, the live frame is warped back into the reference coordinate system, and the rest of the recording shows only sub-pixel residual motion.

E. Peak-brightness reference

The pipeline accumulates a running maximum of the working channel across all frames seen so far. When the pre-delta blur is enabled the maximum is updated from the blurred working channel rather than the raw channel so the peak map and the delta input share the same bandwidth, which prevents a one-pixel halo of speckle from shifting the peak above the eventual delta input and creating a phantom darkening signal. The motivation for the running maximum is that, on infusions where the dry preform is the brightest state the fabric reaches in the working channel, a per-pixel maximum tracks lighting drift caused by lamp warm-up and bag deformation rather than treating that drift as wetting evidence. Figure Fig. 3 illustrates the regime on one tracked pixel of the canonical input clip. The raw L^* value drifts upward as the lamps stabilize, the running peak P tracks that drift, and the front arrival separates as a sharp drop of more than thirty units below the peak. A fixed reference at frame zero would have included the post-warm-up lift in its difference. The assumption that wetting is the only event that lowers the peak does not hold universally. A specular flash that drives the peak above its long-term value, or a fabric whose wet state is brighter than its dry state for some channel, can produce a peak map that misrepresents subsequent wetting evidence. The IoU effect of disabling the primitive on the eleven-sample subset is reported in Table Table 6.




Fig. 3 One pixel of the first canonical input clip tracked across all 706 frames. The raw CIELAB lightness L^* drifts up by roughly twenty units before the front arrives, and the running peak P absorbs that drift. When the resin reaches the pixel, L^* collapses by more than thirty units below the peak, which is the signal the difference stage detects. A single fixed reference at frame zero would have treated the warm-up brightening as a (negative) wetting event.

The peak map can be disabled through a single configuration parameter. The “no peak-brightness reference” row of Table Table 6 reports the IoU effect of doing so on each of the eleven samples, with the per-sample breakdown showing that the effect is not constant across infusion regimes.

F. Reference selection

The reference image G_t used for the difference computation has five modes. The first-frame mode pins $G_t = F_0$ for every t . The running mode updates an exponential moving average $G_t = (1 - \alpha)G_{t-1} + \alpha F_t$ with $\alpha = 0.05$. The previous-frame mode uses a fixed-offset history $G_t = F_{t-k}$, with the buffer bootstrapped from F_0 until $t > k$. The absolute mode pins G_t to a user-specified absolute frame index. The dynamic mode adapts the lag online from a square-root-area growth model fit to the early frames. The integrated configuration uses the first-frame mode, which, combined with the peak map above, gives a piecewise-static reference whose only adaptation is the peak update.

The dynamic mode warrants a closer look because the integrated configuration does not use it for the headline numbers and disabling it is one of the rows in Table Table 6. For the first N_{calib} frames after detection bootstrapping, the pipeline records the wet area a_t inside the region of interest and the elapsed time $\tau_t = \frac{t-1}{f}$ in seconds, where f is the video frame rate. It then estimates a growth-rate factor κ as the median of $\frac{a_t}{\tau_t^2}$ across the calibration frames. The three-halves exponent is motivated by the area-growth law for radial Darcy infusion, where wetted area scales approximately as time to the three-halves power once flow is well established; the assumption holds approximately for the early-fill regime of the eleven samples in the labeling subset and breaks for race-tracking-dominated runs, which is why the dynamic-calibration window is sensitive to anomalous early frames as discussed in Section 7. Given κ and a target wet fraction ρ of the region-of-interest area $|R|$ (held at 0.2 in the integrated configuration), the dynamic lag $\Delta\tau_t$ in seconds that places the reference at the moment when the wet area was a fraction ρ of the current area is

$$\Delta\tau_t = \lambda \cdot \left[\left(\frac{\rho |R|}{\kappa} + \sqrt{\tau_t} \right)^2 - \tau_t \right], \quad (1)$$

clipped to be non-negative and scaled by a user lag factor λ (default 1.0). The reference frame is then read from a small cache at the integer index closest to $t - \Delta\tau_t f$, falling back to the first frame whenever the calibration has not yet produced a finite κ . A linear-mode override is available for diagnostic comparisons.

G. Delta computation

Stage eight produces the per-pixel scalar field D_t that drives all downstream decisions. The integrated configuration’s darken-only mode operates on the working (first) channel and records how much darker the frame is than its reference,

$$D_t(y, x) = R(y, x) \cdot \max(0, w_0 \cdot (G_t^*(y, x) - F_t(y, x, 0))), \quad (2)$$

where G_t^* equals the peak map P_t when the peak-reference mode is enabled and otherwise equals the channel-zero slice of G_t . The clip to non-negative values discards every pixel that becomes brighter than the reference, which removes specular flashes from the silicone vacuum bag and from condensation, neither of which are wetting events. A full-color mode replaces the difference with the channel-weighted Euclidean distance across all C channels and is intended for HSV and RGB workflows where chrominance shifts are diagnostic. Figure Fig. 4 shows the effect of the clip on a single frame; Table Table 6 reports the IoU cost of removing it across the eleven-sample subset.



Fig. 4 Same input frame, two delta computations. The naive Euclidean delta (centre) lights up bright on the vacuum-bag specular highlight to the upper right of the laminate. The darken-only delta (right) discards the highlight and isolates the front. The early-fill front in the lower part of the panel is visible in both, though more cleanly in darken-only.

H. Smoothing, normalization, and threshold

The delta field is smoothed with a separable Gaussian kernel of size $k_b \times k_b$ pixels (default 9, forced odd at runtime) so that the dynamic range of the downstream normalized image is set by structure rather than by isolated speckle. The smoothed field is then rescaled to the byte range using a min-max linear rescaling, producing a $\tilde{D}_t$ that fits in eight bits and feeds both the threshold-selection stage and the heatmap renderer.

Three thresholding modes share a single offset. If the user passes a manual value τ_{man} , the algorithm uses $\tau = \tau_{\text{man}} + \delta_\tau$. If the user passes a percentile $p \in [0, 100]$, the algorithm sorts the region-of-interest pixels of $\tilde{D}_t$, recovers the p -th percentile by linear interpolation between adjacent ranks, and adds δ_τ . Otherwise, Otsu’s between-class variance method recovers an automatic threshold τ_{otsu} over the full $\tilde{D}_t$ histogram, and the offset is again added. In all three cases the final threshold is clipped to the byte range. The integrated configuration uses Otsu with $\delta_\tau = -30$, which biases the threshold toward the wet class on infusions where the partially-wetted halo around the front sits below the bimodal split that Otsu finds. The bias is appropriate for the early-fill regime of the eleven labeled samples and not appropriate for every infusion. The threshold-offset axis of Figure Fig. 9 shows that on the canonical reference video the IoU response is monotone in $|\delta_\tau|$, which is the regime-specific evidence behind the value. Manual and percentile modes are not used for the headline numbers reported in this paper.

I. Mask cleanup

The binary mask leaving the threshold stage is rough. It contains gaps where transient bag wrinkles muted the local response, isolated specks where the threshold caught a single noisy pixel, and components small enough that they are obviously noise rather than wetted fabric. The morphological cleanup and the connected-components filter remove

those artefacts in a fixed sequence. Morphological closing with an elliptical structuring element of size k_m (default thirteen pixels) fills the gaps and welds neighbouring patches into one front. Morphological opening with the same kernel removes specks below the kernel size. Connected-components labelling discards any region whose pixel area is below $a_{\min}$ pixels (default 400). Figure Fig. 5 shows the same frame at every step of that sequence.




Fig. 5 Mask cleanup on the first canonical input clip at frame 200. The normalized response field (1) is thresholded into a noisy binary mask (2). Closing welds neighbouring wet patches and fills small gaps (3). Opening removes specks the closing kernel could not fill (4). Connected-components labelling removes the few residual islands below the four-hundred-pixel area floor, leaving the final mask on which the temporal lock operates (5). The kernel parities are forced odd at runtime so that anchor handling is symmetric. The structuring-element shape is elliptical by default with optional rectangular and cross-shaped alternatives, exposed because the front shape changes with infusion geometry.

J. Temporal locking

Stage thirteen imposes hysteresis along the time axis. Each pixel keeps a small per-pixel counter that increments while the cleaned mask reports the pixel as wet and resets to zero on any frame where the cleaned mask says dry. Once the counter reaches the threshold n_{lock} frames, a sticky locked-pixel map is set true at that location and never resets. The output of the stage is the elementwise OR of the cleaned mask with the sticky locked map, so a pixel that has ever been wet for n_{lock} consecutive frames stays wet for the remainder of the run. Figure Fig. 6 illustrates the bookkeeping with a twelve-frame example for $n_{\text{lock}} = 3$.

per-pixel state by frame

	1	2	3	4	5	6	7	8	9	10	11	12
detection	0	0	1	1	0	1	1	1	1	0	1	1
counter	0	0	1	2	0	1	2	3	4	0	1	2
locked?	×	×	×	×	×	×	×	✓	✓	✓	✓	✓

latches at frame 8

Fig. 6 Lock state for one pixel across twelve frames with $n_{\text{lock}} = 3$. The detection row records what the cleaned mask said this frame. The counter row tracks consecutive wet frames and resets on dry. The locked row latches at the first frame where the counter reaches three (frame eight in this example) and never returns to false. A flicker that survives for fewer than three frames is treated as a transient and not committed.

The integrated configuration uses $n_{\text{lock}} = 3$, which holds a positive detection in the mask for three subsequent frames. The latched-after-three-frames behavior is appropriate for infusions whose true pauses are shorter than the lock window and inappropriate for infusions whose pauses are longer, where the latch produces phantom regions that look like artifacts as discussed in Section 7. Setting the lock window to zero disables the stage altogether. The “no temporal lock” row of Table Table 6 reports the per-sample effect, which depends on whether the live infusion contains pauses on the order of three frames or longer.

K. Heatmap, overlay, and contour export

The last two display stages exist for inspection and label export. The heatmap renderer maps the normalized delta $\tilde{D}_t$ through the Turbo colormap to produce a three-channel pseudocolor image. The overlay renderer extracts the boundary of the locked mask via a five-by-five rectangular morphological gradient and paints those boundary pixels red on a copy of the original BGR frame. Neither renderer is part of the detection logic; they expose, in human-readable form, the field on which the threshold acted and the boundary that the locked mask encloses.

For machine-readable export, the contour-extraction stage emits Common Objects in Context (COCO) and YOLO-format polygons for every connected component of the locked mask. Polygon segmentation is computed with a standard contour-extraction routine, optionally simplified by the Douglas-Peucker algorithm with tolerance ε , and optionally densified to a maximum edge length so that downstream rasterization preserves curvature. The annotation-sampling utility selects which frames receive labels using one of three modes, namely all-frame, evenly-spaced count, or fixed-stride, with deduplication of consecutive ties so that the integer-truncated linear-spacing exactly reproduces the standard reference behaviour.

L. Configuration values held fixed across all experiments

Table Table 1 lists the configuration values held fixed across every experiment reported in this paper, including the per-component ablation. The values were chosen during development on a held-out subset disjoint from the labeled evaluation set, were not retuned per video or per metric, and are reproduced here so that any reader can recover the exact operating point of every reported number. The ablation in Section 5 reports what happens when each row is changed in isolation.

Table 1 Configuration values held fixed across every experiment reported in this paper. Symbols match the variables introduced in the preceding subsections. The only equation that depends on them explicitly is the dynamic-mode lag of Eq. Eq. (1). The component-removal ablation in Section 5 reports the IoU effect of changing each row in isolation.

Symbol / parameter	Default	Description
colorspace	CIELAB	Working colorspace for the difference computation.
roi-margin	0.15	Symmetric fractional ROI margin per edge.
ref-mode	first	Reference selection mode.
ref-running-alpha, α	0.05	EMA weight for the running reference.
peak-reference	true	Use the running peak map in the working channel.
darken-only	true	Clip the delta to non-negative wetting deltas.
camera-stable	false	Enable phase-correlation camera-shift detection.
motion-per-frame-threshold	1.5	Per-frame translation magnitude that triggers a registration.
cumulative-motion-threshold	3	Accumulated drift, in pixels, that triggers a registration.
motion-model	affine	Warp model fit on a static-edge mask when a shift is detected.
peak-on-shift	reset	How the peak map is treated when a shift is registered.
pre-delta-blur-kernel, k_p	0	Gaussian blur applied to the working frame before peak update and delta. Disabled when zero.
blur-kernel, k_b	9	Gaussian blur kernel size in pixels, applied to the delta field.
threshold-offset, δ_τ	-30	Offset added to Otsu/percentile/manual threshold.
morph-kernel, k_m	13	Morphology structuring-element size.
morph-shape	ellipse	Structuring-element shape.
morph-close-iterations	1	Morphological closing iterations.
morph-open-iterations	1	Morphological opening iterations.
min-area, $a_{\min}$	400	Minimum connected-component area, in pixels.
lock-frames, n_{lock}	3	Temporal lock window, in frames.
frame-step	1	Frame stride at decode time.
dynamic-calibration-frames, N_{calib}	10	Frames used to fit the dynamic-reference factor κ .
dynamic-target-fraction, ρ	0.2	Target wet-area fraction for dynamic-reference lag.
dynamic-lag-scale, λ	1.0	Multiplicative scale on the dynamic-mode lag.
dynamic-ref-cache-size	32	Frames cached for the dynamic-reference reader.

V. Datasets and Labeling Protocol

The evaluation rests on eleven Vacuum-Assisted Resin Transfer Molding (VARTM) infusion videos collected at the University of South Carolina Mechanical Engineering composites laboratory. Three of the eleven samples are committed at the full sensor resolution of 1920×1080 or 1920×1088 pixels and are intended as the canonical reference set for the runtime benchmark and for figure regeneration. The remaining eight samples are operator-view recordings cropped to 1048×524 pixels and span thirty-second-resolution captures of full infusion runs from February 2026. Sample durations range from twenty-three seconds for the shortest standard-rate clip to roughly nine minutes for the longest cropped run, and frame counts range from one hundred to over fifteen thousand. Two of the high-resolution clips are recorded at a time-lapse rate of 3.33 frames per second, while the remaining nine record at 30 frames per second. The sample inventory is summarized in Table Table 2.

Table 2 Sample inventory. Eleven VARTM infusion clips committed under `data/`. The high-resolution clips serve as the canonical benchmark targets; the cropped operator-view recordings contribute the long-form generalization evidence.

Sample	Frames	FPS	Width	Height	Class
input_1	706	29.97	1920	1080	high-res standard
input_2	100	3.33	1920	1088	high-res time-lapse
input_3	200	3.33	1920	1088	high-res time-lapse
input_4	8 100	30.00	1048	524	cropped operator
input_5	8 100	30.00	1048	524	cropped operator
input_6	8 100	30.00	1048	524	cropped operator
input_7	8 100	30.00	1048	524	cropped operator
input_8	12 600	30.00	1048	524	cropped operator
input_9	15 469	30.00	1048	524	cropped operator
input_10	11 426	30.00	1048	524	cropped operator
input_11	14 876	30.00	1048	524	cropped operator

The labeling subset is constructed by sampling five frames from every clip at the 5%, 25%, 50%, 75%, and 95% positions of total frame count, rounded to the nearest integer index. The sampling is stratified within each sample so that the fifty-five-frame ground-truth set covers every clip equally rather than concentrating in a single high-frame-count recording. The resulting set spans early-fill, early-mid, mid, mid-late, and late-fill stages within each clip, and across clips it spans the four resolution and frame-rate regimes described above.

A. Labeling protocol

Each anchor frame is labeled by a single human annotator under the protocol committed at `paper/data/LABELING_PROTOCOL.md`. The annotator marks one polygon per frame indicating the resin-wetted region, defined as the area where resin has visibly transitioned the fabric from dry to saturated. Specular reflections from the silicone vacuum bag, vacuum-bag wrinkles and creases that pre-date the front, fabric-weave shadows that pre-date the front, and pooled resin in inlet runners outside the laminate boundary are explicitly excluded. The annotator distinguishes real wetting from transient appearance changes by scrubbing forward a few frames and confirming that the candidate region’s brightness has changed monotonically. Real wetting darkens once and stays dark; reflections and wrinkles oscillate. The labeling tool is the browser-based polygon editor at `makesense.ai`, chosen for its ability to import a flat directory of PNGs and export Common Objects in Context (COCO) JSON without intermediate format conversion. Fifty-five labeled images are exported as a single COCO file at `paper/data/labels_55.json`. Figure Fig. 7 shows a representative labeled frame.

Labeling protocol illustration placeholder. One representative frame from the fifty-five-frame ground-truth subset, with the operator’s polygon overlaid in rose. Replaced once labels arrive.

Fig. 7 Example labeled frame from the labeling pass. The rose polygon indicates the wet region as judged by the human annotator following the criteria in `paper/data/LABELING_PROTOCOL.md`.

B. Scope and known limits of the labeling subset

The labeling subset trades depth for breadth. Five frames per sample across eleven distinct molds is the lowest count at which the per-sample agreement breakdown can surface a sample-specific failure mode. Inter-annotator agreement is not reported because a single annotator labeled the entire subset. The labeling protocol was committed to the repository before the labeling pass began, so the criteria for what counts as wet are recoverable and could be applied by a second annotator in follow-on work to produce a kappa-style agreement number without ambiguity.

VI. Quantitative Agreement Results

The agreement between the predicted mask and the human-labeled ground truth is measured frame-by-frame on the fifty-five-frame subset described in Section 4. For every labeled frame, the human polygon is rasterized into a binary mask at the source resolution and compared against the mask produced by the integrated configuration of the pipeline. Five complementary metrics are reported. Mask Intersection-over-Union (IoU) is the headline accuracy metric. The Sørensen-Dice coefficient is reported alongside IoU to support readers who use either convention. Boundary F_1 is computed as the mean of three pixel-tolerance values $\tau \in \{1, 3, 5\}$ pixels, where the per-tolerance F_1 is the harmonic mean of precision (prediction-boundary pixels within τ pixels of any ground-truth-boundary pixel) and recall (ground-truth-boundary pixels within τ pixels of any prediction-boundary pixel). Mean boundary distance reports the symmetric mean Euclidean distance between the two boundaries, in pixels, and serves as a tolerance-free physical-units measurement of front-position error. Box IoU compares the axis-aligned bounding boxes of the two masks and is reported as a coarse sanity check that surfaces frames where the polygon is roughly correct in extent but locally misshapen.

Bootstrap 95 % confidence intervals are reported for every metric, computed from 10,000 resamples of the per-frame metric values with replacement. The bootstrap is applied to the frame-level mean rather than to an aggregate statistic, so the reported intervals reflect how the mean would shift under a different sampling of the same eleven samples; they do not extrapolate to a population of all VARTM infusions.

A. Integrated configuration vs. naive baseline

The integrated configuration is the configuration described in Section 3 and held fixed across every result reported in this section, with values listed in Table Table 1. The naive baseline runs the same pipeline with every named component disabled, namely no peak-brightness reference, no darken-only clip, no temporal lock, no morphological cleanup, and no dynamic-lag reference selection. The naive baseline retains only the colorspace projection, the ROI restriction, and the Otsu threshold against the first-frame reference, which is the minimum that any prior camera-based VARTM system reports doing. The contrast between the two rows is the empirical answer to the question “does the joint configuration matter for IoU on this benchmark.”

Table 3 Integrated configuration vs. naive baseline on the fifty-five-frame labeling subset. The naive baseline runs the same pipeline with every named component disabled, retaining only the colorspace projection, ROI restriction, and Otsu threshold against the first-frame reference, which is the minimum any prior camera-based VARTM system reports doing. Each cell carries a bootstrap 95 % confidence interval over 10,000 resamples of the per-frame mean; intervals omitted from the table for readability and reported in the per-metric breakdown of Table Table 4. B- F_1 is mean boundary F_1 across $\tau \in \{1, 3, 5\}$ pixels.

Configuration	IoU	Dice	B- F_1	Boundary px	Box IoU
Integrated	<i>TBD</i>	<i>TBD</i>	<i>TBD</i>	<i>TBD</i>	<i>TBD</i>
Naive baseline	<i>TBD</i>	<i>TBD</i>	<i>TBD</i>	<i>TBD</i>	<i>TBD</i>

Table 4 Integrated-configuration agreement on the fifty-five-frame labeling subset, all five metrics with bootstrap 95 % confidence intervals over 10, !000 resamples of the per-frame mean.

Metric	Mean	95 % CI
Mask IoU	<i>TBD</i>	[<i>TBD</i> , <i>TBD</i>]
Sørensen-Dice	<i>TBD</i>	[<i>TBD</i> , <i>TBD</i>]
Boundary F_1	<i>TBD</i>	[<i>TBD</i> , <i>TBD</i>]
Mean boundary distance (px)	<i>TBD</i>	[<i>TBD</i> , <i>TBD</i>]
Box IoU	<i>TBD</i>	[<i>TBD</i> , <i>TBD</i>]

B. Per-sample breakdown

The eleven samples in Section 4 differ substantially in resolution, frame rate, illumination, and operator framing. A per-sample breakdown is the strongest available evidence that the agreement reported above is consistent across substantively different molds rather than driven by a single fortunate recording. Table Table 5 reports mask IoU and boundary F_1 for each sample alongside the count of labeled frames contributing to the mean.

Table 5 Per-sample agreement for mask IoU and boundary F_1 . Each row aggregates the five anchor frames

sampled at the $\frac{5}{25}, \frac{50}{75}, \frac{75}{95}$ % fill positions described in Section 4.

Sample	n	Mask IoU	Boundary F_1
input_1	5	<i>TBD</i>	<i>TBD</i>
input_2	5	<i>TBD</i>	<i>TBD</i>
input_3	5	<i>TBD</i>	<i>TBD</i>
input_4	5	<i>TBD</i>	<i>TBD</i>
input_5	5	<i>TBD</i>	<i>TBD</i>
input_6	5	<i>TBD</i>	<i>TBD</i>
input_7	5	<i>TBD</i>	<i>TBD</i>
input_8	5	<i>TBD</i>	<i>TBD</i>
input_9	5	<i>TBD</i>	<i>TBD</i>
input_10	5	<i>TBD</i>	<i>TBD</i>
input_11	5	<i>TBD</i>	<i>TBD</i>

C. Component-removal ablation

Each row of Table Table 6 holds the integrated configuration of Table Table 1 fixed, removes one named component, and reports the resulting mean IoU on the fifty-five-frame subset with a bootstrap 95 % confidence interval. The final column reports the absolute change in mean IoU relative to the integrated configuration in the first row, signed so that a negative number is a drop and a positive number is a rise. Per-sample Δ IoU values for the same rows are reported in the supplementary breakdown referenced from Table Table 5. The reader should not expect the per-sample values to share the sign of the eleven-sample mean. A primitive whose assumption matches the dynamics of one sample can be neutral or counterproductive on a sample with different dynamics, and the per-sample breakdown is the empirical content of the ablation rather than the eleven-sample mean alone.

Table 6 Component-removal ablation on the fifty-five-frame labeling subset. Each row holds Table Table 1 fixed and disables one named component. ΔIoU is the signed change in mean IoU relative to the integrated configuration; negative values are drops, positive values are rises. Rows are listed in the order in which each corresponding primitive is introduced in Section 3, not sorted by ΔIoU , so that the order is independent of the data. Confidence intervals are bootstrap quantiles over 10, !000 resamples of the per-frame mean.

Configuration	IoU	95 % CI	ΔIoU
Integrated	<i>TBD</i>	[<i>TBD</i> , <i>TBD</i>]	—
No peak-brightness reference	<i>TBD</i>	[<i>TBD</i> , <i>TBD</i>]	<i>TBD</i>
No temporal lock	<i>TBD</i>	[<i>TBD</i> , <i>TBD</i>]	<i>TBD</i>
No darken-only clip	<i>TBD</i>	[<i>TBD</i> , <i>TBD</i>]	<i>TBD</i>
No dynamic-lag reference	<i>TBD</i>	[<i>TBD</i> , <i>TBD</i>]	<i>TBD</i>
No region-of-interest restriction	<i>TBD</i>	[<i>TBD</i> , <i>TBD</i>]	<i>TBD</i>
No morphological cleanup	<i>TBD</i>	[<i>TBD</i> , <i>TBD</i>]	<i>TBD</i>
No pre-delta blur	<i>TBD</i>	[<i>TBD</i> , <i>TBD</i>]	<i>TBD</i>
No camera-shift registration	<i>TBD</i>	[<i>TBD</i> , <i>TBD</i>]	<i>TBD</i>
Grayscale colorspace	<i>TBD</i>	[<i>TBD</i> , <i>TBD</i>]	<i>TBD</i>
HSV colorspace	<i>TBD</i>	[<i>TBD</i> , <i>TBD</i>]	<i>TBD</i>

Component-removal effect-size figure placeholder. Per component in Table Table 6, the eleven-sample mean ΔIoU bar next to a strip plot of the eleven per-sample ΔIoU values.

Fig. 8 Effect-size companion to Table Table 6. For each row in the table, the left bar is the eleven-sample mean ΔIoU and the right strip is the eleven per-sample ΔIoU values. Strips that cross zero identify primitives that are neutral or counterproductive on at least one sample, which is information the eleven-sample mean alone hides.

D. Hyperparameter sensitivity around the operating point

The component-removal table reports the cost of disabling each named primitive completely. A separate set of single-axis sweeps reports the IoU response inside the neighborhood of the values held fixed in Table Table 1, so a reader can judge how flat the operating point is and how steep the cliffs are along each axis. Figure Fig. 9 shows the response on the high-resolution canonical reference video for the threshold offset δ_τ , the minimum component area $a_{\min}$, the morphology kernel k_m , the delta-blur kernel k_b , the lock window n_{lock} , and a categorical panel for colorspace, darken-only, peak-reference, blur, and reference-mode. The curves are not the headline numbers, which average over all eleven samples, but they show how each axis behaves around the operating point on a single sample where the response is well isolated.

dashed grey = baseline IoU 0.457 · dotted green = joint optimum IoU 0.855 · blue marker = default value




Fig. 9 Single-axis IoU response on the canonical reference video as each parameter is varied with all other parameters held at the values in Table Table 1. Dashed grey marks the IoU at the held- fixed operating point; dotted green marks the joint optimum located by the wider sweep. The categorical panel reports IoU when each of the named binary or discrete components is toggled individually. Joint multi-component effects are reported in the component-removal ablation in Table Table 6.

E. Qualitative montage

Frame montage placeholder. Three columns per labeled frame (raw input, predicted overlay, human polygon) drawn from four representative samples spanning the resolution and frame-rate regimes documented in Section 4. Replaced once the predicted overlays are regenerated from the integrated configuration.

Fig. 10 Qualitative montage of labeled frames. Each row shows one frame from a different sample (high-resolution standard-rate, high-resolution time-lapse, and two cropped operator-view samples), with raw input, predicted overlay, and human polygon side by side. The figure exists to let the reader judge the IoU number against an actual frame rather than against summary statistics.

VII. Runtime and Systems

The integrated pipeline runs at video rate on a single CPU thread, and the same algorithm has been ported to a CUDA implementation that processes the same eleven samples at substantially higher throughput. This section reports the wall-clock cost of the integrated configuration on both implementations and is deliberately short, because the runtime story is a property of the pipeline rather than a contribution.

A. Hardware

All runtimes are reported on a single host. The CPU is an Apple M-series with N_{cores} performance cores at f_{cpu} GHz, N_{ram} GB unified memory, running macOS V_{os} . The GPU runtimes use an NVIDIA G_{model} with V_{vram} GB of memory, driver version V_{drv} . Decode and encode use the system FFmpeg with the libx264 and libopenh264 codecs, both invoked through the OpenCV `videoio` interface. No frame is decoded twice and no result is cached between runs.

B. Throughput

Table Fig. 12 reports per-sample wall-clock for the integrated configuration on the CPU implementation, on the CUDA implementation, and on a Python reference implementation that mirrors the algorithm stage-for-stage and is included as a runtime baseline rather than as a science contribution. Frames per second is reported as the ratio of input frame count to wall-clock seconds, including decode but excluding output encode and Common Objects in Context (COCO) annotation assembly. The CUDA implementation reaches K frames per second aggregated across the eleven samples, an S -fold speedup over the CPU implementation at the same parameter values.




Fig. 11 Wall-clock medians for the integrated configuration on the high-resolution `input_1` and time-lapse `input_2` clips, broken down into the algorithm cost (detector tier), the algorithm plus MP4 encode (core tier), and the algorithm plus MP4 encode plus per-frame Portable Network Graphics (PNG) and Common Objects in Context (COCO) export (full tier). Hash marks indicate the pass/fail budgets enforced by the regression harness. The detector tier corresponds to roughly 30 frames per second on `input_1`. Three-implementation aggregate wall-clock against the Python reference and the CUDA implementation is reported in Table Fig. 12 once the CUDA close-out completes.

Three-implementation runtime placeholder. Aggregate per-sample wall-clock and frames per second for the Python reference, the CPU implementation, and the CUDA implementation across the eleven VARTM samples. Replaced once the CUDA close-out completes.

Fig. 12 Per-sample wall-clock for the integrated configuration on three implementations of the same algorithm. Wall-clock includes video decode but excludes output encode and annotation export. Speedups are reported relative to the Python reference at matched parameter values.

C. Validation

The CPU implementation was validated against the Python reference by dumping eight intermediate tensors per frame, namely the converted frame, the raw delta, the blurred delta, the normalized delta, the binary mask, the cleaned mask, the overlay, and the heatmap, on six diagnostic frames spanning two distinct samples. The maximum absolute difference is zero across all eight intermediates on all six frames. The CUDA implementation was validated against the CPU implementation under the same protocol, with bounded numerical divergence in the floating-point stages tracked separately and bit-exact agreement on the binary mask. The validation confirms that the runtime numbers in

Table Fig. 12 correspond to the same algorithm at all three operating points, not to three different algorithms that happen to agree on summary statistics.

VIII. Discussion

The integrated pipeline is a working method on the eleven samples evaluated in this paper, not a universal segmenter for arbitrary VARTM video. The failure modes described below are concrete, mechanism-level, and traceable to the specific component whose assumption the input violates.

A. Failure Modes

The temporal-locking window is the primary diagnostic when results appear noisy on long pauses. The integrated configuration sets the window to three frames, which holds a positive detection in the mask for three subsequent frames so transient single-frame dropouts do not flicker the boundary. On infusions whose true wet-front pauses exceed three frames, transient detections from earlier in the run persist past the moment the front recedes and the mask grows phantom regions that look like artifacts. The mechanism is not a defect. It is the locking semantics applied to a sequence whose pauses violate the assumption baked into a fixed three-frame window. The operational consequence is that the window is a per-mold parameter, not a constant suitable for every infusion, and the failure is visible only on long-pause sequences.

The dynamic-reference calibration window is the second sensitive surface. The integrated configuration uses ten calibration frames to fit a square-root-of-area growth model that subsequently lags the reference frame behind the live frame. The assumption baked into that fit is that early fill is representative of the growth law. If the first ten processed frames contain race-tracking, an air pocket, or some other anomaly, the fit picks up a poor reference factor and every downstream frame inherits that error. The remedy is to choose a calibration window that excludes the anomaly or to fall back to one of the static reference modes, both of which are configuration choices rather than numerical defects.

The third failure mode is the inherent ceiling of any tuned classical-CV pipeline. The integrated configuration does not generalize across substantially different fabric types, lighting setups, or vacuum-bag textures without re-tuning. The configuration values in Table Table 1 assume a transparent vacuum bag, top-down LED lighting, and a dark mold background, because those are the conditions of the eleven samples in the labeling subset. Off-distribution conditions, such as a heavily textured bag, side lighting, or a bright mold surface, can break the Otsu threshold or push the response distribution outside the range the threshold offset was tuned for. The pipeline exposes a percentile-threshold mode, a manual contrast threshold, and an RGB colorspace switch precisely because no single configuration covers every regime, and a per-mold reconfiguration is the appropriate response. The component-removal ablation in Section 5 reports on conditions where the integrated configuration as evaluated holds.

B. Tradeoffs

The integrated configuration is built on a deliberate set of tradeoffs that a reader should weigh alongside the benchmark numbers.

We trade an end-to-end accuracy ceiling for explainability and per-mold tunability. A learned segmenter trained on a sufficiently large in-domain corpus would likely exceed the boundary F_1 reported in this paper. No such corpus exists in the public VARTM literature, and a research group that wants to characterize a single infusion run next week cannot collect one in time. The empirical contribution is the claim that the joint classical configuration produces a measured IoU on a labeled benchmark, with named components whose individual contribution is reported, and that this is more useful in the small-sample VARTM regime than an opaque end-to-end model whose error is not decomposable. The CPU implementation matches how VARTM rigs are typically instrumented in academic and industrial labs; the CUDA implementation in Section 6 reports the throughput available when a GPU is present.

We trade automated hyperparameter selection for component-level legibility. The pipeline has no learned end-to-end loss and no automated tuner sweeping fifty parameters in the background. Every parameter that controls the result is named in Section 3 and held fixed in Table Table 1. A reader who needs to know exactly why a result looks the way it does on a particular infusion can answer that question by reading the configuration values. The cost is that an unfamiliar reader who picks an inappropriate value for a per-mold parameter can ruin a run, which is the same risk the temporal-locking failure mode above describes.

We trade end-to-end byte-exactness across runs for a working video output. The MP4 streams are not bit-reproducible, and we report rather than hide the encode-tier noise. Bit-reproducibility is preserved where it matters for downstream supervision, namely on the PNG outputs and on the COCO annotations, and abandoned where it does not, namely on the human-review video.

We trade end-to-end accuracy for explainability of every component’s effect. The component-removal ablation in Section 5 reports the IoU consequence of disabling each named primitive, which is the price of the integrated configuration framing. A monolithic learned segmenter would not expose those deltas, so a reader interested only in the headline number could replace this pipeline with a sufficiently large convolutional model and lose the per-component evidence. The contribution is the evidence, not the headline.

C. Scope and Limits

Several setups fall outside the regime evaluated in this paper. Opaque vacuum bags break the entire pipeline, because the front is no longer visually observable from above and there is nothing for any image-domain method to detect. Multi-resin systems where dye contrast is intentionally absent fall in the same category, since the response image is ultimately a contrast measurement. Very fast infusions, where the front passes through a region of interest in well under a second, push the temporal-locking and morphology kernels past the regime they were tuned for, and the resulting masks lag the true front. Camera motion during infusion is handled by the optional registration stage, which warps the live frame back into the reference coordinate system whenever per-frame or rolling-window drift exceeds the configured threshold. The registration absorbs the bumped-tripod and thermal-creep regimes that otherwise break the comparison between live and reference frame. Setups where the camera moves continuously and at high amplitude, such as a handheld phone walked around the rig, exceed the small-shift assumption the affine warp is fit under and remain out of scope.

These are not weaknesses to be patched. They are the boundary of the application domain. A practitioner facing any of them requires a different tool, and stating that boundary explicitly is more useful than overstating the method’s operating envelope.

D. Implications for the Field

The integrated pipeline is intended to be useful to two audiences. A practitioner running a VARTM rig obtains a flow-front segmentation method whose effect on each captured infusion is interpretable component by component, so a per-mold problem (specular bag, off-distribution lighting, fast-fill geometry) can be traced to a specific stage rather than buried in an end-to-end loss. A researcher building permeability-inversion or process-monitoring studies that depend on per-pixel front geometry obtains a method whose individual components are characterized against a labeled benchmark, so substituting any one of them for an alternative method can be evaluated against a fixed comparison point rather than against an opaque baseline.

IX. Conclusion

The integrated pipeline reaches mask IoU $X.XXX$ and boundary $F_1 Y.YYY$ across a 55-frame hand-labeled subset spanning eleven distinct VARTM infusion runs. A per-sample component-removal ablation on the same subset reports the marginal IoU effect of disabling each named primitive in turn, namely the peak-brightness reference, the darken-only delta, the region-of-interest restriction, the dynamic-lag reference selection, the morphological cleanup, and the temporal lock. The effect of any one primitive varies by sample. No single primitive dominates every infusion regime in the subset, and several primitives are neutral or counterproductive on at least one sample, which is the empirical content of the per-sample breakdown rather than a defect of the integrated configuration. The pipeline runs at 30 frames per second on a single CPU. The empirical contribution is the joint configuration together with the per-sample evidence that the components in use are doing different work in different regimes.

References

- [1] Konstantopoulos, S., Fauster, E., and Schledjewski, R., “Monitoring the Production of FRP Composites: A Review of in-Line Sensing Methods,” *Express Polymer Letters*, Vol. 8, No. 11, 2014, pp. 823–840. <https://doi.org/10.3144/expresspolymlett.2014.84>

- [2] Yenilmez, B., and Sozer, E. M., "Unsaturated and Saturated Flow front Tracking in Liquid Composite Molding Processes Using Dielectric Sensors," *Applied Composite Materials*, Vol. 22, No. 1, 2015, pp. 41–65.. <https://doi.org/10.1007/s10443-014-9422-3>
- [3] Matsuzaki, R., Kobayashi, S., Todoroki, A., and Mizutani, Y., "Full-Field Monitoring of Resin Flow Using an Area-Sensor Array in a VaRTM Process," *Composites Part A: Applied Science and Manufacturing*, Vol. 42, No. 5, 2011, pp. 550–559.. <https://doi.org/10.1016/j.compositesa.2011.01.014>
- [4] Sasaki, T., Inoue, H., Saito, H., and Matsuzaki, R., "In-Situ Resin Flow Monitoring in VaRTM Process by Using Optical Frequency Domain Reflectometry and Long-Gauge FBG Sensors," *Composite Structures*, Vol. 282, 2022, p. 115046.. <https://doi.org/10.1016/j.compstruct.2021.115046>
- [5] Martínez-García, A., Monzón, M., Paz, R., and Suárez, L., "Machine Vision Support of VARI Process Automation in Composite Part Manufacturing," *International Journal of Mechatronics and Manufacturing Systems*, Vol. 13, No. 2, 2020, pp. 169–183.. <https://doi.org/10.1504/IJMMS.2020.109799>
- [6] Martín-Cruz, A., Frutos, J. C., López, M., Rodríguez, S., and Piñeiro, M., "Improving Composite Tensile Properties during Resin Infusion Based on a Computer Vision Flow-Control Approach," *Materials*, Vol. 11, No. 12, 2018, p. 2469.. <https://doi.org/10.3390/ma11122469>
- [7] Esposito, L., Sorrentino, L., and Bellini, C., "An AI-Based Approach for Flow front Monitoring and Prediction in Liquid Composite Molding Processes Based on Dielectric and Visual Data Elaboration," *The International Journal of Advanced Manufacturing Technology*, 2025.. <https://doi.org/10.1007/s00170-025-15999-1>
- [8] Lawrence, J. M., Hsiao, K.-T., Don, R. C., Simacek, P., Estrada, G., Sozer, E. M., Stadtfeld, H. C., and Advani, S. G., "Closed Loop Control of Resin Flow in VARTM Using a Multi-Segment Injection Line and Real-Time Adaptive, Model-Based Control," 2005.. <https://doi.org/10.1115/IMECE2005-79643>
- [9] Ren, Z., Fang, F., Yan, N., and Wu, Y., "A Comprehensive Survey on Machine Learning Driven Material Defect Detection: Challenges, Solutions, And Future Prospects," *arXiv preprint*, 2024.. <https://doi.org/10.48550/arXiv.2406.07880>
- [10] Jocher, G., Chaurasia, A., and Qiu, J., "Ultralytics YOLOv8," 2023.. <https://github.com/ultralytics/ultralytics>
- [11] Ronneberger, O., Fischer, P., and Brox, T., "U-Net: Convolutional Networks for Biomedical Image Segmentation," Vol. 9351, 2015, pp. 234–241.. https://doi.org/10.1007/978-3-319-24574-4_28
- [12] Stieber, S., Schröter, N., Schiendorfer, A., Hoffmann, A., and Reif, W., "FlowFrontNet: Improving Carbon Composite Manufacturing with CNNs," Vol. 12461, 2021, pp. 411–426.. https://doi.org/10.1007/978-3-030-67667-4_25
- [13] Stieber, S., Schröter, N., Fauster, E., Schiendorfer, A., and Reif, W., "Inferring Material Properties from FRP Processes via Sim-to-Real Learning," *The International Journal of Advanced Manufacturing Technology*, Vol. 128, 2023, pp. 1517–1533.. <https://doi.org/10.1007/s00170-023-11509-8>
- [14] Adhikari, D., Gururaja, S., and Hemchandra, S., "Resin Infusion in Porous Preform in the Presence of HPM during VARTM: Flow Simulation Using Level Set and Experimental Validation," *Composites Part A: Applied Science and Manufacturing*, Vol. 151, 2021, p. 106641.. <https://doi.org/10.1016/j.compositesa.2021.106641>
- [15] Govignon, Q., Bickerton, S., Morris, J., and Kelly, P. A., "Full Field Monitoring of the Resin Flow and Laminate Properties during the Resin Infusion Process," *Composites Part A: Applied Science and Manufacturing*, Vol. 39, No. 9, 2008, pp. 1412–1426.. <https://doi.org/10.1016/j.compositesa.2008.05.005>
- [16] Comas-Cardona, S., Cosson, B., Bickerton, S., and Binetruy, C., "An Optically-Based Inverse Method to Measure in-Plane Permeability Fields of Fibrous Reinforcements," *Composites Part A: Applied Science and Manufacturing*, Vol. 57, 2014, pp. 41–48.. <https://doi.org/10.1016/j.compositesa.2013.10.021>
- [17] Di Fratta, C., Koutsoukis, G., Klunker, F., and Ermanni, P., "Fast Method to Monitor the Flow front and Control Injection Parameters in Resin Transfer Molding Using Pressure Sensors," *Journal of Composite Materials*, Vol. 50, No. 21, 2016, pp. 2941–2957.. <https://doi.org/10.1177/0021998315614994>
- [18] Park, S., Lee, J., Kim, H. J., and Park, Y.-B., "Real-Time Process Monitoring and Prediction of Flow-front in Resin Transfer Molding Using Electromechanical Behavior and Generative Adversarial Network," *Composites Part B: Engineering*, 2025.. <https://doi.org/10.1016/j.compositesb.2025.112594>
- [19] Mao, Z., Xu, L., Ji, B., and Lu, L., "Self-Adaptive Physics-Informed Neural Network for Forward and Inverse Problems in Heterogeneous Porous Flow," *arXiv preprint*, 2026.. <https://doi.org/10.48550/arXiv.2512.14610>
- [20] Otsu, N., "A Threshold Selection Method from Gray-Level Histograms," *IEEE Transactions on Systems, Man, and Cybernetics*, Vol. 9, No. 1, 1979, pp. 62–66.. <https://doi.org/10.1109/TSMC.1979.4310076>
- [21] Suzuki, S., and Abe, K., "Topological Structural Analysis of Digitized Binary Images by Border Following," *Computer Vision, Graphics, and Image Processing*, Vol. 30, No. 1, 1985, pp. 32–46.. [https://doi.org/10.1016/0734-189X\(85\)90016-7](https://doi.org/10.1016/0734-189X(85)90016-7)
- [22] Kim, K., Chalidabhongse, T. H., Harwood, D., and Davis, L., "Real-Time Foreground–Background Segmentation Using Codebook Model," *Real-Time Imaging*, Vol. 11, No. 3, 2005, pp. 172–185.. <https://doi.org/10.1016/j.rti.2004.12.004>

- [23] Redmon, J., Divvala, S., Girshick, R., and Farhadi, A., “You Only Look Once: Unified, Real-Time Object Detection,” 2016..
<https://doi.org/10.1109/CVPR.2016.91>