

# TRUECRYPT

FREE OPEN-SOURCE ON-THE-FLY ENCRYPTION

## USER'S GUIDE

### Version Information

TrueCrypt User's Guide, version 2.1a. Released October 1, 2004.

### Licensing Information

Before installing this product (TrueCrypt), you must agree to the license displayed in the TrueCrypt Setup window (the text of the license is also contained in the file *License.txt*).

### Copyright Information

Portions of this software are:

Copyright © 2004 TrueCrypt Foundation. All Rights Reserved.

Copyright © 1998-2000 Paul Le Roux. All Rights Reserved.

Copyright © 2004 TrueCrypt Team. All Rights Reserved.

Copyright © 1995-1997 Eric Young. All Rights Reserved.

Copyright © 2003 Dr. Brian Gladman, Worcester, UK. All Rights Reserved.

Copyright © 2001 Markus Friedl. All Rights Reserved.

For more information, please see the legal notices attached to parts of the source code.

A TrueCrypt Foundation Release

### Limitations

The TrueCrypt Foundation does not warrant that the information contained in this document meets your requirements or that the information is free of errors. The information may include technical inaccuracies or typographical errors.

# CONTENTS

<b>INTRODUCTION.....</b>	<b>4</b>
<b>TRUECRYPT VOLUME.....</b>	<b>4</b>
CREATING A NEW TRUECRYPT VOLUME .....	4
Hash Algorithm.....	5
Quick Format .....	5
Cluster Size .....	5
Auto-Test All Algorithms .....	5
TrueCrypt Volume on CD, DVD, and Other Read-Only Media .....	5
Additional Notes on Volume Creation.....	6
<b>PLAUSIBLE DENIABILITY .....</b>	<b>6</b>
<b>MAIN PROGRAM WINDOW .....</b>	<b>7</b>
Select File.....	7
Select Device.....	7
Mount .....	7
Auto-Mount Partitions .....	7
Dismount.....	8
Dismount All.....	8
Wipe Cache .....	8
Change Password .....	8
Never Save History .....	8
Exit .....	8
PASSWORD ENTRY .....	8
Cache Password in Driver Memory .....	8
<b>PROGRAM MENU .....</b>	<b>9</b>
File -> Exit .....	9
Tools -> Clear Volume History .....	9
Tools -> Preferences .....	9
<b>SUPPORTED OPERATING SYSTEMS.....</b>	<b>10</b>
<b>UNINSTALLING TRUECRYPT.....</b>	<b>10</b>
<b>COMMAND LINE USAGE.....</b>	<b>10</b>
Syntax .....	11
Examples.....	11
<b>ENCRYPTION ALGORITHMS.....</b>	<b>11</b>
<b>TROUBLESHOOTING .....</b>	<b>12</b>
<b>INCOMPATIBILITIES .....</b>	<b>13</b>
<b>DRIVER LIMITATIONS &amp; KNOWN BUGS.....</b>	<b>14</b>
<b>TRUECRYPT SYSTEM FILES.....</b>	<b>14</b>
<b>FREQUENTLY ASKED QUESTIONS.....</b>	<b>15</b>

**TECHNICAL DETAILS.....19**

    ENCRYPTION SCHEME ..... 19

    TRUECRYPT VOLUME FORMAT SPECIFICATION .....20

    HEADER KEY DERIVATION .....20

    SECTOR SCRAMBLING .....21

    RANDOM NUMBER GENERATOR .....22

    COMPLIANCE WITH STANDARDS AND SPECIFICATIONS .....22

**FUTURE DEVELOPMENT .....23**

**ACKNOWLEDGEMENTS.....23**

**VERSION HISTORY .....24**

## PREFACE

This document assumes that the reader is generally familiar with using computer hardware and software. Describing a feature that is usually easily understood has been avoided wherever possible.

## Introduction

TrueCrypt is a software system for establishing and maintaining an on-the-fly-encrypted volume (data storage device). On-the-fly encryption means that data are automatically encrypted or decrypted right before they are loaded or saved, without any user intervention. *No* data stored on an encrypted volume can be read without using the correct password or encryption key. Until decrypted, encrypted volume appears to be nothing more than a series of random numbers. Entire file system is encrypted (i.e. file names, folder names, contents of every file, and free space). *No* unencrypted data are ever stored on any storage device (they are only temporarily kept in RAM during the encryption/decryption process).

## TrueCrypt Volume

There are two basic types of TrueCrypt volumes:

- Container
- Partition/device

A TrueCrypt *container* is a normal file, which can reside on any type of storage device. It contains (hosts) a completely independent encrypted virtual disk device. *Container* is a file-hosted volume.

A TrueCrypt *partition* is a hard disk partition encrypted using TrueCrypt. You can also encrypt floppy disks, ZIP disks, USB hard disks, USB memory sticks, and other types of storage devices.

## Creating a New TrueCrypt Volume

To create a new TrueCrypt file-hosted container or to encrypt a partition/device (requires administrator privileges), click on 'Create Volume' in the main program window. TrueCrypt Volume Creation Wizard should appear. As soon as the Wizard appears, it starts collecting data that will be used in generating the master key, the salt, and the values used to create the IV and 'whitening' values for the new volume. The cors, iaTDvhd0 - pean a serpeac-0.000Wizncludeice (requires

## Hash Algorithm

By setting this option you select which hash algorithm TrueCrypt will use. The selected hash algorithm is used by the random number generator (which generates the master key, salt, and the values used to create IV and 'whitening' values). It is also used in deriving the new volume header key.

TrueCrypt currently supports two hash algorithms: RIPEMD-160, which was designed by an open academic community, and SHA-1 designed by the NSA and NIST.

Note that the output of a hash function is *never* used directly as an encryption key. For more information, please see the section *Technical Details*.

## Quick Format

If unchecked, each sector of the new volume will be formatted. Basically this means that the new volume will be *entirely* filled with random data. Quick format is much faster but may be less secure because until the whole volume has been filled with files, it may be possible to tell how much data it contains (if the space was not filled with random data beforehand). If you are not sure whether to enable or disable Quick Format, we recommend that you leave this option unchecked. Note that Quick Format can only be enabled when encrypting partitions.

## Cluster Size

Cluster is an allocation unit. For example, for a one-byte file, at least one cluster should be allocated on FAT file system. When the file grows beyond the cluster boundary, another cluster is allocated. Theoretically, this means that the bigger the cluster size, the more disk space is wasted; however, the performance is better. If you do not know which value to use, leave the setting at default.

## Auto-Test All Algorithms

The built-in self-test facility, accessible from the Volume Creation Wizard Step 2 window, automatically tests all the encryption algorithms and all the hash algorithms (HMAC's) implemented in TrueCrypt and reports the results. To run these tests, click on the *Auto-Test All Algorithms* button in the test tool window. We recommend that you test the algorithms each time right before creating a new TrueCrypt volume.


## TrueCrypt Volume on CD, DVD, and Other Read-Only Media

If you want a TrueCrypt volume to be stored on a CD, DVD, or other read-only media, first create a file-hosted TrueCrypt container on a hard drive and then burn it onto a CD, DVD, etc., with any CD burning software (or, under Windows XP, with the built-in system tool). Remember that if you need to mount a TrueCrypt volume that is stored on a read-only medium (such as a CD or DVD) under Windows 2000, you must format the volume as FAT (Windows 2000 cannot mount NTFS file system on read-only media).

## Additional Notes on Volume Creation

After you click the 'Format' button in the Volume Creation Wizard window (the last step), there will be a short delay while your system is being polled for additional random data. Afterwards, the master key, header key, salt, and the values used to create the IV and 'whitening' values for the new volume will be generated, and the master key and header key contents will be displayed.

For increased security, the random pool, master key, and header key contents can be prevented from being displayed by unchecking the checkbox in the upper right corner of the corresponding field:



Note that only the first 112 bits of the pool/keys are displayed (not the entire contents).

TrueCrypt volumes can be reformatted as FAT12, FAT16, FAT32, or NTFS anytime. They behave as standard disk devices so you can right-click the device icon and select 'Format'.

*Warning: When encrypting entire hard drive partition or entire device (floppy disk, ZIP disk etc.), all data stored on the device/partition will be lost!*

## Plausible Deniability

It is impossible to identify a TrueCrypt container or partition. Until decrypted, a TrueCrypt volume appears to consist of nothing more than random data (it does not contain any "signature"). Therefore, it is impossible to prove that a file, a partition or a device is a TrueCrypt volume and/or that it has been encrypted.

TrueCrypt container files do not have to have a standard file extension. They can have any file extension you like (for example, .raw, .dat, .iso, .img, .rnd, .tc) or they can have no file extension at all. TrueCrypt ignores file extensions. If you need plausible deniability, make sure your TrueCrypt volumes do not have the .tc file extension (this file extension is 'officially' associated with TrueCrypt).

When formatting a hard disk partition as a TrueCrypt volume, the partition table (including the partition type) is *never* modified. If you intend to use a TrueCrypt partition and you need plausible deniability, follow these steps (Windows XP):

- 1) Make sure you have administrator privileges.
- 2) Right-click *My Computer* icon on your desktop and select *Manage*.
- 3) In the list (on the left) click *Disk Management* (the *Storage* sub-tree).
- 4) If the partition that you want to format as a TrueCrypt has already been created, right-click it and select *Delete Partition...* If the partition has not yet been created, continue with step 4)
- 5) Right-click the free space (should be labeled as *Unallocated*) and select *New Partition...*
- 6) *New Partition Wizard* should appear now. Follow its instructions. On the Wizard page called 'Assign Drive Letter or Path' select 'Do not assign a drive letter or drive path'. Click *Next*.
- 7) Select *Do not format this partition* and click *Next*.
- 8) Click *Finish*.

- 9) The partition now appears to be “reserved” for future use (and future reformatting). As it is unformatted, it can contain any random data, which might, for example, have resided on the hard drive since the last time you repartitioned the hard disk. Therefore, there is no difference between such an *unformatted* partition and a TrueCrypt volume. Now you can format the partition as TrueCrypt (to do that, click *Create Volume* in the main program window and follow the Volume Creation Wizard’s instructions).

Note: if, instead of an *unformatted* partition, you format an NTFS/FAT16/FAT32 partition as TrueCrypt, the partition will then appear to be a corrupted NTFS/FAT16/FAT32 partition.

## Main Program Window

### Select File

Allows you to select a file-hosted TrueCrypt volume. After you select it, you can mount it by clicking ‘Mount’ (see below). It is also possible to select a volume by dragging its icon to the ‘TrueCrypt.exe’ icon (TrueCrypt will be automatically launched then).

### Select Device

Allows you to select a TrueCrypt partition or a storage device (such as floppy disk or ZIP disk). After it is selected, it can be mounted by clicking ‘Mount’ (see below). Note: There is a more comfortable way of mounting TrueCrypt partitions – see ‘Auto-Mount Partitions’ for more information.

### Mount

To mount a TrueCrypt volume, select a free drive letter from the list in the main window. Then select a file or device that hosts the TrueCrypt volume and click ‘Mount’. TrueCrypt will try to mount the volume using cached passwords (if there are any) and if none of them works, it asks you to enter a password. If you enter the correct password, the volume will be mounted.

Note that switching users on Windows XP/2000 does *not* dismount a successfully mounted TrueCrypt volume. Also note that when you exit the TrueCrypt application, the TrueCrypt driver still continues working and no TrueCrypt volumes are dismounted.

### Auto-Mount Partitions

This function allows you to mount TrueCrypt partitions without having to select them manually (by clicking ‘Select Device’). TrueCrypt goes through all available partitions (on all hard drives) one by one and tries to mount each of them as a TrueCrypt volume. Note that TrueCrypt partition cannot be identified, nor the cipher it has been encrypted with. Therefore, the program cannot directly “find” TrueCrypt partitions. Instead, it has to try mounting each (even unencrypted) partition using all encryption algorithms and all cached passwords (if there are any). Therefore, be prepared that this process may take a long time on slow computers. Drive letters will be assigned starting from the one that is selected in the drive list in the main window. If the password you enter is not correct, mounting is tried using cached passwords (if there are any). If you enter empty password, only the cached passwords will be used when attempting to mount partitions.

## **Dismount**

To dismount a TrueCrypt volume basically means to make any access to the data it contains impossible. To do so, select a TrueCrypt volume and click on 'Dismount'.

## **Dismount All**

Dismounts all currently mounted TrueCrypt volumes.

## **Wipe Cache**

Clears any passwords cached in driver memory. When there are no passwords in the cache, this button is disabled. Up to last four successfully mounted TrueCrypt volume passwords can be cached. This allows mounting volumes without having to type their passwords repeatedly. Passwords are *never* saved on any disk – they are only temporarily stored in RAM. Driver memory is never swapped to disk. Password caching can be enabled/disabled in the Preferences (Tools menu).

## **Change Password**

Allows changing the password of the currently selected TrueCrypt volume. The main encryption key remains unchanged. Therefore, reformatting is not necessary and is *not* performed (i.e. *no* data will be lost after changing the password and the password change will only take a few seconds). To change the password of a TrueCrypt volume, click on 'Select File' or 'Select Device', then select the volume, and click on 'Change Password'.

*PKCS-5 PRF Algorithm:* When changing a volume password, you can also select the HMAC hash algorithm that will be used in deriving the new volume header key (for more information, see *Header Key Derivation*) and in generating the new salt (for more information, see *Random Number Generator*).

## **Never Save History**

If checked, the file names and paths of the last eight mounted volumes will not be saved in the history.

## **Exit**

Terminates the TrueCrypt application. The driver continues working and no TrueCrypt volumes are dismounted.

## **Password Entry**

### **Cache Password in Driver Memory**

When checked, the volume password you enter will be cached in driver memory (if the password is correct). Then, later, volumes can be mounted using the cached password without having to type it



again. Up to four passwords can be cached. The passwords are *never* saved on any disk. They are only temporarily stored in RAM. Driver memory is never swapped to disk. Note that turning the password cache off will not clear it (click *Wipe Cache* to do so).

## Program Menu

*Note: Only the menu items that are not self-explanatory are described in this documentation.*

### **File -> Exit**

Terminates the TrueCrypt application. The driver continues working and no TrueCrypt volumes are dismounted.

### **Tools -> Clear Volume History**

Clears the list containing file names and paths of the last eight successfully mounted TrueCrypt volumes.

### **Tools -> Preferences**

#### ***Wipe cached passwords on exit***

If enabled, passwords cached in driver memory will be cleared when exiting TrueCrypt.

#### ***Cache passwords in driver memory***

When checked, up to last four successfully mounted TrueCrypt volume passwords will be cached in driver memory. Then, later, volumes can be mounted using a cached password without having to type it again. The passwords are *never* saved on any disk. They are only temporarily stored in RAM. Driver memory is never swapped to disk.

#### ***Open Explorer window for successfully mounted volume***

If this option is checked, then after a TrueCrypt volume has been successfully mounted, an Explorer window showing the root directory of the volume (e.g. T:\) will be automatically open.

#### ***Close all Explorer windows of volume being dismounted***

Sometimes, dismounting a TrueCrypt volume is not possible due to the fact that some files or folders located on the volume are in use or "locked". This also applies to Explorer windows displaying directories located on TrueCrypt volumes. When this option is checked, all such windows will be automatically closed before dismounting, so that the user does not have to close them manually.

## Supported Operating Systems

TrueCrypt runs on the following operating systems:

- Windows 2003
- Windows XP
- Windows 2000

We recommend Windows XP (at least Service Pack 1) or later as the optimum environment for running TrueCrypt.

## Uninstalling TrueCrypt

To uninstall TrueCrypt, open the Windows control panel and select 'Add/Remove Programs', locate TrueCrypt and click the 'Add/Remove' button.

Normally, all TrueCrypt files, including the device driver, should be removed, and most of the changes made to the registry should be undone. The uninstall will *never* remove any TrueCrypt volume you may have created.

## Command Line Usage

<code>/help</code> or <code>/?</code>	Displays command line help.
<code>/volume</code> or <code>/v</code>	File and path name of a TrueCrypt volume. To mount a hard disk partition, use, for example, <code>/v \Device\Harddisk1\Partition3</code> (to determine the path to a partition, run TrueCrypt and click <i>Select Device</i> ).
<code>/letter</code> or <code>/l</code>	Driver letter to mount the volume as.
<code>/explore</code> or <code>/e</code>	Opens an Explorer window after a volume has been mounted.
<code>/beep</code> or <code>/b</code>	Beeps after a volume has been mounted.
<code>/auto</code> or <code>/a</code>	Automatically mounts the volume.
<code>/dismount</code> or <code>/d</code>	Dismounts the given volume (specified by its drive letter) or when no volume is specified, dismounts all currently mounted TrueCrypt volumes.
<code>/cache</code> or <code>/c</code>	Enables (Y) or disables (N) the password cache. Note that turning the password cache off will not clear it.
<code>/history</code> or <code>/h</code>	Enables (Y) or disables (N) the history.
<code>/wipecache</code> or <code>/w</code>	Wipes any passwords cached in the driver memory.
<code>/password</code> or <code>/p</code>	The volume password. If the password contains spaces, it must be enclosed in quotation marks (e.g., <code>/p "My Password"</code> ). <i>Warning: This method of entering a volume password is not secure, particularly when you save the password in an unencrypted batch file, or when an unencrypted command prompt history log is being saved to disk. Consider using <code>/q /a</code> instead.</i>
<code>/quiet</code> or <code>/q</code>	Quiet mode. When used along with <code>/auto</code> and if no cached password is correct, the password prompt appears (the main TrueCrypt window is not displayed). This could increase the level of privacy in multi-user environments. Program settings are not saved when in quiet mode.

## Syntax

```
truecrypt [[/v] volume] [/d [letter]] [/l letter] [/e] [/b] [/p password]
[/h] [/q] [/c] [/w] [/a]
```

The order of the parameters is not important. Whitespaces between parameters and parameter values do not matter.

## Examples

Mounting a volume called 'myvolume.tc' using the password 'MyPassword', drive letter X, TrueCrypt will open an explorer window and beep, mounting will be automatic:

```
truecrypt /v myvolume.tc /lx /a /p MyPassword /e /b
```

Mounting a volume called ' myvolume.tc' using the password prompt (the main program window will not be displayed):

```
truecrypt /v myvolume.tc /lx /a /q
```

## Encryption Algorithms

TrueCrypt volumes can be encrypted using one of the following algorithms:

Algorithm	Designer(s)	Key Size (Bits)	Block Size (Bits)	Mode
AES	J. Daemen, V. Rijmen	256	128	CBC
Blowfish	B. Schneier	448	64	CBC
CAST5	C. Adams, S. Tavares	128	64	CBC
Triple-DES	IBM, NSA	168	64	Outer-CBC

A random value, unique to each sector and volume, is used as the IV (for more information, please see *Sector Scrambling*).

# Troubleshooting

This section presents possible solutions to common problems that you may run into when using TrueCrypt. If your problem is not listed here, it might be listed in one of the following sections:

*Incompatibilities*  
*Driver Limitations & Known Bugs*  
*Frequently Asked Questions*

---

## PROBLEM:

*I cannot encrypt a partition because it is not displayed in the 'Select Device' window.*

## PROBABLE CAUSE:

The partition is probably in use by the system or a program.

## POSSIBLE SOLUTION:

First close or disable all programs that might be using the partition in any way. If it does not help, right-click the *My Computer* icon on your desktop and select *Manage -> Storage -> Disk Management*. Then right-click the partition that you want to encrypt, and click *Change Drive Letter and Paths*, then click *Remove* and *OK*. Restart your system.

---

## PROBLEM:

*I cannot encrypt a partition because the TrueCrypt Volume Creation Wizard says it is in use.*

## POSSIBLE SOLUTION:

First make sure that you are not trying to encrypt the operating system boot partition (TrueCrypt does not support this). Then close or disable all programs that might be using the partition in any way. If it does not help, right-click the *My Computer* icon on your desktop and select *Manage -> Storage -> Disk Management*. Then right-click the partition that you want to encrypt, and click *Change Drive Letter and Paths*, then click *Remove* and *OK*. Restart your system.

---

## PROBLEM:

*My system crashes when I dismount a TrueCrypt volume.*

## PROBABLE CAUSE:

This is probably caused by an anti-virus program running in the background.

## POSSIBLE SOLUTION:

It usually helps to turn off real-time (on-access) scanning in the preferences of the anti-virus program you use. If it does not help, try disabling or uninstalling the anti-virus program completely.

---

**PROBLEM:**

One of the following problems occurs:

1. *A TrueCrypt volume cannot be mounted*
2. *NTFS TrueCrypt volumes cannot be created*

In addition, the following error may be reported: "*The process cannot access the file because it is being used by another process.*"

**PROBABLE CAUSE:**

This is probably caused by an interfering virus protection software application.

**POSSIBLE SOLUTION:**

It usually helps to turn off real-time (on-access) scanning in the preferences of the virus protection software you use. If it does not help, try temporarily disabling the virus protection software. If this does not help either, try uninstalling it completely.

---

## Incompatibilities

There are a few pieces of software that we know about that might, under certain circumstances, cause problems if run with TrueCrypt.

- *McAfee Antivirus* (Windows 2000 SP4)

If system crashes occur when dismounting a TrueCrypt volume, try disabling the on-access scanner in the McAfee Antivirus preferences before mounting a TrueCrypt volume and leave it disabled while it is mounted.

- *Symantec Norton AntiVirus* (Windows 2000 SP4)

There have been contradicting reports. Most users reported that they had no problems running Symantec Norton AntiVirus with TrueCrypt (and our tests revealed no problems either). If you have Norton AntiVirus installed and system crashes occur when dismounting TrueCrypt volumes, try disabling 'File System Real Time Protection' in the Norton AntiVirus preferences.

- *Nero InCD*

Note that even though this incompatibility has been reported by several users, we cannot confirm it (repeated tests under Windows XP Professional SP1 and Windows 2000 SP4 yielded negative results). However, we believe that the issue might really exist so we have added this piece of software to this list.

## Driver Limitations & Known Bugs

- Network volumes are not supported. A mounted TrueCrypt volume cannot be shared over a network (LAN etc.)
- Raw floppy disk volumes: when a floppy disk is ejected and another one is inserted, garbage will be read/written to the disk, which could lead to data corruption. This affects only 'raw' floppy disk volumes (not file-hosted containers stored on floppy disks).

## TrueCrypt System Files

*WindowsPath*\TrueCryptSetup.exe (uninstaller)

*WindowsPath*\SYSTEM32\DRIVERS\truecrypt.sys (driver)

*WindowsPath*\SYSTEM32\TrueCryptService.exe (service)

The service is necessary to register each newly mounted volume with the operating system (Mount Manager), which then assigns a drive letter to it. The service also allows users without administrator privileges to dismount TrueCrypt volumes.

Note: Replace *WindowsPath* with your Windows installation path (e.g. C:\WINDOWS)

## Frequently Asked Questions

**Q: *I forgot the password – is there any way to recover the files from my TrueCrypt volume?***

A: TrueCrypt does not contain any mechanism or facility that would allow partial or complete recovery of your encrypted data without knowing the correct password or the key used to encrypt the data. The only way to recover your files is to try to 'crack' the password or the key, but it could take thousands or millions of years depending on the length and quality of the password, or on the key size, on the software/hardware efficiency, and on other factors.

**Q: *Is my password stored somewhere?***

A: No.

**Q: *Is some hash of my password stored somewhere?***

A: No.

**Q: *Is the key size limited to 160 bits when I use HMAC-SHA-1 or HMAC-RIPEMD-160?***

A: No, TrueCrypt never uses an output of a hash function directly as an encryption key. See the section 'Header Key Derivation' for more information.

**Q: *What is the maximum possible size of a TrueCrypt volume?***

A: TrueCrypt volumes can be up to 9,223,372,036 GB. However, you need to take into account the following: the limitations of the file system that the container will be stored on, the limitations of the file system of the container itself, the hardware connection standard, and your operating system limitations. Remember that file-hosted containers stored on the FAT32 file system cannot be larger than 4 GB (if you need a larger volume, store it on the NTFS file system or, instead of creating a file-hosted volume, encrypt a partition). Also note that any FAT32 volume, encrypted or not, cannot be larger than 2048 GB (if you need larger volumes, format them as NTFS).

**Q: *Which cipher is the most secure?***

A: Unfortunately, it is impossible to answer this question. However, all ciphers implemented in TrueCrypt are well known and trusted. No weak cipher has been implemented in TrueCrypt.

**Q: *How does TrueCrypt verify that the correct password was entered?***

See section *Technical Details – Encryption Scheme*.

**Q: Is it possible to mount a TrueCrypt container that is stored on a CD or DVD?**

A: Yes, it is. However, if you need to mount a TrueCrypt volume that is stored on a read-only medium (such as a CD or DVD) under Windows 2000, the file system of the TrueCrypt volume must be FAT (Windows 2000 cannot mount NTFS file system on read-only media).

**Q: What will happen if I format a TrueCrypt partition?**

See the question “Is it possible to change the file system of an encrypted volume?”

**Q: Is it possible to change the file system of an encrypted volume?**

A: Yes, when mounted, TrueCrypt volumes can be formatted as FAT12, FAT16, FAT32, or NTFS. The volumes behave as standard disk devices so you can right-click the device icon (for example in ‘My Computer’ list) and select ‘Format’. The actual volume contents will be lost, the whole volume will remain encrypted though. If you format a TrueCrypt-encrypted partition when the TrueCrypt volume that the partition hosts is not mounted, then the volume will be destroyed, and the partition will not be encrypted anymore (it will be empty).

**Q: How do I decrypt a TrueCrypt partition permanently?**

A: If you format a TrueCrypt-encrypted partition when the TrueCrypt volume hosted by the partition is not mounted, then the volume will be destroyed and the partition will not be encrypted anymore (it will be empty). Note that the contents of the TrueCrypt volume will be lost.

**Q: How do I burn a TrueCrypt container larger than 2 GB onto a DVD?**

A: The DVD burning software you use should allow you to select the format of the DVD. If it does, select the UDF format (ISO format does not support files over 2 GB).

**Q: Can I use tools like chkdsk, Defrag, etc. on the contents of a TrueCrypt volume?**

A: Yes, TrueCrypt volumes behave like real physical disk devices, so it is possible to use any filesystem checking/repairing/defragmenting tools on the contents of a mounted TrueCrypt volume.

**Q: Is it possible to encrypt my operating system boot partition?**

A: No, TrueCrypt does not allow this. However, there are ways to ensure that the volume where operating system resides is read-only, which should prevent information leakage (registry, temporary files, etc., are stored in RAM). For more information, see the question “Does TrueCrypt support something like ‘traveller’ mode?”

**Q: Can I mount a TrueCrypt volume stored on another TrueCrypt volume?**

A: Yes, TrueCrypt volumes can be nested without any limitation.



**Q: Can I run TrueCrypt with another on-the-fly disk encryption tool on one system?**

A: We are not aware of any on-the-fly encryption tool that would cause problems when run with TrueCrypt, or vice versa.

**Q: Can I resize a TrueCrypt partition?**

A: Unfortunately, TrueCrypt does not support this. Resizing a TrueCrypt partition using a program such as PartitionMagic will, in most cases, corrupt its contents.

**Q: Will I always be able to mount a TrueCrypt container no matter how fragmented it is?**

A: Yes.

**Q: Is it necessary to restart the computer before copying a TrueCrypt container?**

A: No, it is not necessary.

**Q: Is it secure to create a new container by cloning an existing container?**

A: You should always use the Volume Creation Wizard to create a new TrueCrypt volume. If you copy a container and then start using both this container and its clone in a way that both eventually contain different data, then you could aid cryptanalysis. The reason is that both volumes would share the same key, IVs, whitening values, etc.

**Q: Do I have to “wipe” free space and/or files on a TrueCrypt volume?**

[“Wiping” – secure deletion; overwriting sensitive data to render them unrecoverable.]

A: If you believe that an adversary will be able to decrypt the volume (for example that he will make you reveal the password), then the answer is yes. Otherwise, it is not necessary, because the volume is entirely encrypted.

**Q: Does TrueCrypt support something like ‘traveller’ mode?**

A: If you need to use TrueCrypt on a computer on which you cannot (or do not want to) install TrueCrypt, we recommend using BartPE for this purpose. BartPE stands for “Bart's Preinstalled Environment”, which is essentially the Windows operating system prepared in a way that it can be entirely stored on and booted from a CD/DVD. The freeware [Bart's PE Builder](#) can transform any Windows installation CD into BartPE. In order to include certain applications on a BartPE disk (to make it available to the BartPE system), you need a plug-in for the application. There are several free TrueCrypt plug-ins for BartPE available on the Internet.

**Q: *How is TrueCrypt related to E4M?***

*A: TrueCrypt 1.0 was derived from E4M 2.02a. For information on differences between E4M and TrueCrypt, please see Version History.*

**Q: *Will TrueCrypt be open-source and free forever?***

*A: Yes, it will. No commercial version is planned and never will be. We believe in open-source and free security software.*

*Remark: We know that there are certain individuals trying to distribute TrueCrypt as paid and closed-source software. We are not affiliated with these individuals.*

# Technical Details

## Encryption Scheme

When mounting a TrueCrypt volume (assume there are no cached passwords), the following steps are performed:

1. The first 512 bytes of the volume are read into RAM, out of which the first 64 bytes are the salt.
2. A password entered by the user and the salt read in (1) are passed to the header key derivation function. A HMAC hash algorithm is chosen and the header key derivation function produces a sequence of values (see section *Header Key Derivation*) from which the header encryption key and IV (used to decrypt the volume header) are derived. Note that it is impossible to directly determine the correct HMAC hash algorithm that has to be used in deriving the correct header key (it has to be determined through the process of trial and error).
3. An encryption algorithm is chosen and initialized with the key and IV obtained in (2). Note that it is impossible to directly determine the encryption algorithm that has been used to encrypt the volume (it has to be determined through the process of trial and error).
4. The data read in (1), except the first 64 bytes, are decrypted with the chosen encryption algorithm. Note that now it is still unknown whether the chosen encryption and hash algorithms are correct or not.
5. If the first 4 bytes of the data decrypted in (4) contain the text string "TRUE", then a CRC-32 checksum of the last 256 bytes of the data read in (1) is calculated. If this value matches the value stored at the 8<sup>th</sup> byte (see section *TrueCrypt Volume Format Specification*) of the data decrypted in (4), the process continues with (6). If the values do not match, or the first 4 bytes of the data decrypted in (4) do not contain the text string "TRUE", then the encryption algorithm is assumed to be incorrect. If there is an encryption algorithm that decrypting has not yet been attempted with, the process continues from (3) choosing such encryption algorithm. If there are no encryption algorithms remaining and if there is a HMAC hash algorithm that header key derivation has not yet been attempted with, the process continues from (2) choosing such HMAC hash algorithm. If there are no HMAC hash algorithms and no encryption algorithms remaining to be tested, the password is assumed to be incorrect, and mounting is terminated.
6. Now we know that we have the correct password and the correct encryption and hash algorithms. The minimum program version required to open the volume, stored in data decrypted in (4), is checked. If it is not equal or less than the version of the program that we are using to mount the volume, mounting is terminated.
7. The encryption routine is reinitialized with the master key and IV retrieved from the data decrypted in (4). This key can be used to decrypt any sector of the volume, except the first one (the volume header, which has been encrypted using the header key).  
Note: The master key was generated during the volume creation and cannot be changed later. Volume password change is accomplished by re-encrypting the volume header using a new header key (derived from a new password).
8. The volume is mounted.

For more information pertaining the encryption scheme, see sections *Sector Scrambling* and *Header Key Derivation*.

## TrueCrypt Volume Format Specification

TrueCrypt volume has no “signature”. Until decrypted, it appears to consist of nothing more than random data. Therefore, it is impossible to identify a TrueCrypt container or partition.

TrueCrypt volume format version 1 specification:

Offset (bytes)	Size (bytes)	Encryption Status	Description
0	64	Not Encrypted	Salt *
64	4	Encrypted	ASCII string “TRUE”
68	2	Encrypted	Volume format version
70	2	Encrypted	Minimum program version required to open the volume
72	4	Encrypted	CRC-32 checksum of the (decrypted) bytes 256-511
76	8	Encrypted	Volume creation time
84	8	Encrypted	Header creation/modification time
92	8	Encrypted	Reserved (set to zero)
100	156	Encrypted	Unused
256	32	Encrypted	Data used to generate IV and ‘whitening’ values
288	224	Encrypted	Master encryption key
512	N/A	Encrypted	Data area (actual volume contents)

\*) Note that salt does not need to be encrypted, as it does not have to be kept secret (salt is a sequence of random values).

The bytes 0-63 (salt), bytes 256-287 (data used to generate IV and ‘whitening’ values), and bytes 288-511 (master encryption key), contain random values that have been generated using the built-in random number generator (see section *Random Number Generator*) during the volume creation process.

## Header Key Derivation

Header key is used to decrypt the encrypted area of the TrueCrypt volume header (see sections *Encryption Scheme* and *TrueCrypt Volume Format Specification*). The technique that TrueCrypt uses to generate header keys conforms to PKCS #5 v2.0 (see <ftp://ftp.rsasecurity.com/pub/pkcs/pkcs-5v2/pkcs5v2-0.pdf>). A 64-byte (512-bit) salt is used, which means there are 2 to the power of 512 keys for each password. This significantly decreases vulnerability to ‘off-line’ dictionary attacks (pre-computing all the keys for a dictionary of passwords is very difficult when a salt is used). 2,000 iterations of the key derivation function have to be performed to derive a header key, which significantly increases the time necessary to perform an exhaustive search for passwords (brute force). The header key derivation function is based on

HMAC-SHA-1 or HMAC-RIPEMD-160 (the user selects which). For more information, please see RFC 2104, available at: <http://www.cis.ohio-state.edu/htbin/rfc/rfc2104.html>).

## Sector Scrambling

Each cipher implemented in TrueCrypt operates in CBC mode (Triple-DES in outer-CBC). The IV (initialization vector) is a random value, which is unique to each sector and volume. This value is generated as follows:

1. Bytes 256-263 (or 256-271 for AES) of the decrypted volume header are retrieved (see sections *TrueCrypt Volume Format Specification* and *Encryption Scheme*).
2. Data retrieved in (1) are XORed with the 64-bit sector number (each sector is 512 bytes long; sectors are numbered starting at 0). In case of AES, the upper and lower 64-bit words are XORed with an identical value. The resultant 64-bit value (or 128-bit for AES) is the IV for each 64-bit block of the disk sector (128-bit for AES).

Note: Step (1) is only performed once, right after the volume is mounted. The retrieved value remains in RAM then.

To make obtaining a plaintext/ciphertext pair more difficult, every 8 bytes of each sector (after the sector is encrypted) are XORed with a 64-bit value, which is unique to each sector and volume. The value is generated as follows:

1. Bytes 264-271 (or 272-279 for AES) of the decrypted volume header are retrieved (see sections *TrueCrypt Volume Format Specification* and *Encryption Scheme*).
2. Bytes 272-279 (or 280-287 for AES) of the decrypted volume header are retrieved.
3. Data retrieved in (1) are XORed with the 64-bit sector number (each sector is 512 bytes long; sectors are numbered starting at 0).
4. Data retrieved in (2) are XORed with the 64-bit sector number.
5. A 32-bit CRC-32 value of the first 8 bytes of the resultant value in (3) is calculated.
6. A 32-bit CRC-32 value of the second 8 bytes of the resultant value in (3) is calculated.
7. A 32-bit CRC-32 value of the first 8 bytes of the resultant value in (4) is calculated.
8. A 32-bit CRC-32 value of the second 8 bytes of the resultant value in (4) is calculated.
9. The value calculated in (5) is XORed with the value calculated in (8).
10. The value calculated in (6) is XORed with the value calculated in (7).
11. The 32-bit value calculated in (9) is written to the upper 32-bit word and the value calculated in (10) is written to the lower 32-bit word of the 64-bit 'whitening' value.

## Random Number Generator

The random number generator implemented in TrueCrypt is used to generate the master encryption key, salt, and the values used to create IV and 'whitening' values (see section *Sector Scrambling*).

The random number generator creates a pool of random values in RAM. The pool, which is 256 bytes long, is periodically filled byte by byte with values derived from the following sources:

- Mouse movements (CRC32-hashed coordinates and event delta times)
- Mouse clicks (CRC32-hashed event delta times)
- Key presses (CRC32-hashed key codes and event delta times)
- Network interface statistics (NETAPI32) (collected only once in the beginning)
- Performance statistics of disk devices (collected only once in the beginning)
- Various Win32 handles, time variables, and counters (collected at 250-ms interval)

Random values are written to the pool by adding (not by replacing the old values in the pool). This means that from the moment that a value is written to the pool, it never stops affecting the state of it. Additionally, after a value (byte) is added to the pool, the pool is entirely hashed using a hash function (SHA-1 or RIPEMD-160 – the user selects which).

The described random number generation technique is based on the following:

- *Software Generation of Practically Strong Random Numbers* by Peter Gutmann, (<http://www.cs.auckland.ac.nz/~pgut001/pubs/random.pdf>)
- *Cryptographic Random Numbers* by Carl Ellison, (<http://www.clark.net/pub/cme/P1363/ranno.html>)

## Compliance with Standards and Specifications

TrueCrypt complies with the following standards and specifications:

- PKCS #5 v2.0 (<ftp://ftp.rsasecurity.com/pub/pkcs/pkcs-5v2/pkcs5v2-0.pdf>)
- FIPS 180-2 – SHA-1 ([http://csrc.nist.gov/publications/fips/fips180-2/FIPS180-2\\_changenotice.pdf](http://csrc.nist.gov/publications/fips/fips180-2/FIPS180-2_changenotice.pdf))
- RFC 2104 – HMAC (<http://www.cis.ohio-state.edu/htbin/rfc/rfc2104.html>)
- RFC 2202 – HMAC-SHA-1 (<http://www.cis.ohio-state.edu/htbin/rfc/rfc2202.html>)
- FIPS 46-3 – Triple-DES (<http://csrc.nist.gov/publications/fips/fips46-3/fips46-3.pdf>)
- FIPS 197 – AES (<http://csrc.nist.gov/publications/fips/fips197/fips-197.pdf>)

## Future Development

The following features are planned for a future release:

- 'Hidden' volume
- Twofish
- Serpent
- Linux version
- Hash algorithms conceptually distinct from SHA-1 and RIPEMD-160
- Header key derivation PRF algorithms conceptually distinct from HMAC-SHA-1 and HMAC-RIPEMD-160
- Keyfiles
- Anti-key-logger facilities
- Hotkeys

and more.

## Acknowledgements

Thanks to:

*Paul Le Roux* for making his E4M source code available. TrueCrypt is based on E4M.

*Eric Young* for writing his excellent libdes, libcast, etc., which were the sources of some of the cryptography code used in TrueCrypt.

*Brian Gladman*, who wrote the excellent AES routines.

*Peter Gutmann* for his paper on random numbers, and for creating his cryptlib, which was the source of parts of the random number generator source code used in TrueCrypt.

*Andy Neville* for providing some of the code and inspiration, useful in the implementation of the file-hosted volumes (E4M).

*David Kelvin*, who added the privacy password command line argument, and the quiet mode (E4M).

# Version History

## 2.1a

October 1, 2004

### Removed Features:

- IDEA encryption algorithm removed. This allows non-profit and profit organizations to use TrueCrypt without having to obtain a separate license for IDEA (according to the IDEA license, *any* use of software containing the IDEA algorithm by a non-profit or profit organization is considered as use for commercial purposes, and is subject to a license from MediaCrypt AG).

Important: TrueCrypt volumes encrypted using the IDEA encryption algorithm cannot be mounted using TrueCrypt 2.1a. If you have such a volume, before upgrading to TrueCrypt 2.1a, please create a new TrueCrypt volume using a cipher other than IDEA and move your files to this new volume.

## 2.1

June 21, 2004

### New features:

- RIPEMD-160 hash algorithm added. The user can now select which hash algorithm TrueCrypt will use (SHA-1 or RIPEMD-160).

Note: RIPEMD-160, which was designed by an open academic community, represents a valuable alternative to SHA-1 designed by the NSA and NIST. In the previous versions there was a risk that the whole program would be practically useless, should a major weakness be found in SHA-1. The user-selected hash algorithm is used by the random number generator when creating new volumes, and by the header key derivation function (HMAC based on a hash function, as specified in PKCS #5 v2.0). The random number generator generates the master encryption key, salt, and the values used to create IV and 'whitening' values.

- When changing a volume password, the user can now select the HMAC hash algorithm that will be used in deriving the new volume header key.
- It is now possible to create NTFS TrueCrypt volumes and unformatted TrueCrypt volumes. This enhancement also removes the 2048 GB volume size limit. (Only FAT volumes can be created using the previous versions of TrueCrypt. Any FAT volume, encrypted or not, cannot be over 2,048 GB.)
- Header key content is now displayed in the Volume Creation Wizard window (instead of salt).
- Random pool, master key, and header key contents can be prevented from being displayed in the Volume Creation Wizard window.

### Bug fixes:

- When there is a mounted TrueCrypt container that is stored in another TrueCrypt container, it will be possible to dismount both of them using the 'Dismount All' function, and 'blue screen' errors will not occur upon system shutdown.
- Minor bug fixes to command line handling.



**Improvements:**

- Several minor improvements to the driver.

**Miscellaneous:**

- Released under the original E4M license to avoid potential problems relating to the GPL license (added the IDEA patent information and specific legal notices).

**2.0**

June 7, 2004

**Bug fixes:**

- Data corruption will no longer occur when a TrueCrypt partition is subjected to heavy parallel usage (usually when copying files to or from a TrueCrypt partition). This also fixes the problem with temporarily inaccessible files stored in TrueCrypt partitions.

*Note: File-hosted volumes were not affected by this bug.*

- After dismounting and remounting a volume, its file system will be correctly recognized by the operating system and it will be possible to reuse the same drive letter (*Windows 2000 issue*).
- The main program window will not be displayed when run in quiet mode (*command line usage*).
- Two password entry attempts are no longer necessary to be able to mount a volume (*command line usage*).
- All partitions will be visible to TrueCrypt even if one of them is inaccessible to the operating system (an inaccessible partition made all successive partitions on the hard disk unavailable to TrueCrypt).
- Relative path can be specified when mounting a file-hosted volume (*command line usage*).
- Incorrect passwords are reported when auto-mounting (*command line usage*).

**New features:**

- AES-256 (Rijndael) encryption algorithm.
- The command line option */dismountall* was renamed to */dismount* which can now be also used to dismount a single volume by specifying its drive letter.

**Improvements:**

- Memory pages containing sensitive data are now locked to prevent them from being swapped to the Windows page file.
- The state of the random pool will never be exported directly so the pool contents will not be leaked.

**Miscellaneous:**

- Released under GNU General Public License (GPL)

**1.0a** *(by TrueCrypt Team)*

February 3, 2004

**Removed features:**

- TrueCrypt no longer supports Windows 98/ME.

**1.0** *(by TrueCrypt Team)*

February 2, 2004

*Note: TrueCrypt is based on E4M (Encryption for the Masses). Therefore, the following list contains differences between E4M 2.02a and TrueCrypt 1.0 (minor differences have been omitted).*

**Improvements:**

- Windows XP/2000 support
- The maximum volume size is 18,446,744,073

encryption/decryption).

#### **Bug fixes:**

- Sector scrambling algorithm flaw fixed. Two or more disk sectors to be encrypted consisting of the same values (e.g. filled with zeroes), after being encrypted by E4M, start with the same 8-byte sequence of values (i.e. the first eight bytes of any of these encrypted sectors contain the same values as the first eight bytes of any other of these encrypted sectors). If this had not been fixed, the plausible deniability would not have been possible.
- TrueCrypt volumes can be dismounted (Windows XP issue).
- "Blue screen" errors no longer occur during Windows shutdown when there is one or more mounted TrueCrypt volumes.
- Drive geometry is calculated correctly now (*chkdsk.exe* and *format.exe* do not fail anymore).
- A TrueCrypt volume can be reformatted as FAT32 or NTFS using the Windows built-in format tool (Windows XP/2000 issue).
- Windows Check Disk can now be used on TrueCrypt volumes (Windows XP/2000 issue).
- Windows Disk Defragmenter can now be used on encrypted volumes (Windows XP/2000 issue).

#### **New features:**

- New IV (initialization vector) generation algorithm (see the documentation for more information)
- Every 8 bytes of each sector (after the sector is encrypted) are XORed with a random 64-bit value, which is unique to each sector and volume (sector is 512 bytes long). This makes obtaining a plaintext/ciphertext pair a bit more difficult.
- New function to clear the volume history.
- When selecting a partition/device, the sizes and file system types of available partitions/devices are displayed (Windows XP/2000).
- List of mounted TrueCrypt volumes now contains their sizes and encryption algorithms used (Windows XP/2000).
- Free volume space is reported (in 'My Computer' list etc.)
- Windows XP format facilities do not support formatting volumes larger than 32 GB as FAT32. However, with TrueCrypt Volume Creation Wizard it is now possible to create FAT32 volumes larger than 32 GB.
- New function that allows multiple TrueCrypt partitions to be mounted provided that their correct password(s) has/have been entered (this includes the cached passwords, if there are any).
- Quick format (partitions/devices only)
- Cluster size selection (when creating new volumes)
- Volume properties can now be examined (encryption algorithm, volume creation time, last password change time etc.)
- New function to dismount all mounted TrueCrypt volumes.

- New command line options to dismount all mounted TrueCrypt volumes: /d and /dismountall
- HMAC-SHA1 and CRC-32 algorithm tests are now included in the self-test facility.
- Program menu and Preferences window added.
- Custom user interface fonts supported.
- Optionally, the TrueCrypt installer can now create System Restore points (Windows XP/ME).
- Password input field is wiped after a correct volume password has been entered.
- New graphics, icons, user interface
- New documentation

**Removed features:**

- E4M and SFS volumes are no longer supported.
- DES cipher removed.
- HMAC-MD5 removed (to be replaced by HMAC-RIPEMD-160).