



Windows 10 OpenSSH Equivalent of ssh-copy-id

Christopher Hart on May 24, 2020

2 min read

At the moment, Windows 10's implementation of the OpenSSH client does not have the `ssh-copy-id` command available. However, a PowerShell one-line command can mimic the `ssh-copy-id` command and allow you to copy an SSH public key generated by the `ssh-keygen` command to a remote Linux device for passwordless login.

Generate an SSH Key

Note: If you have already generated an SSH keypair that you would like to use, skip this section and proceed to the [Copy SSH Key to Remote Linux Device](#) section.

First, open a new PowerShell window (*not* a Command Prompt window!) and generate a new SSH keypair with the `ssh-keygen` command. By default, the public and private keys will be placed in the `%USERPROFILE%\.ssh\` directory. The public key file we are interested in is named `id_rsa.pub`.

Plaintext



```
PS C:\Users\Christopher> ssh-keygen
Generating public/private rsa key pair.
Enter file in which to save the key (C:\Users\Christopher\.ssh\id_rsa):
Created directory 'C:\Users\Christopher\.ssh'.
Enter passphrase (empty for no passphrase):
Enter same passphrase again:
Your identification has been saved in C:\Users\Christopher\.ssh\id_rsa.
Your public key has been saved in C:\Users\Christopher\.ssh\id_rsa.pub.
The key fingerprint is:
SHA256:/mjkrJQqbRzCAw1SPYVBNCuxntm/Ms5/MMC15dCRrMc christopher@Christopher-Win10-VM-01
The key's randomart image is:
+---[RSA 2048]---+
|oo.+o==    o.o  |
|. o +. =  o =  |
| o .+. . B    |
|  +..+o o E    |
|   *.S. .     |
|  o +...o     |
|   o =. .o    |
|   o.*o ..    |
|   .=+++      |
+----[SHA256]-----+
PS C:\Users\Christopher>
```

Copy SSH Key to Remote Linux Device

Next, we use the below PowerShell one-line command to copy the contents of the `id_rsa.pub` public key to a remote Linux device. Replace the `{IP-ADDRESS-OR-FQDN}` with the IP address or FQDN (Fully Qualified Domain Name) of the remote Linux device you would like to copy the public key to.

Plaintext





Post



Linux device at IP address 192.168.30.31.

Plaintext



```
PS C:\Users\Christopher> type $env:USERPROFILE\.ssh\id_rsa.pub | ssh 192.168.30.31 "cat >>
.ssh/authorized_keys"
The authenticity of host '192.168.30.31 (192.168.30.31)' can't be established.
ECDSA key fingerprint is SHA256:mTD0/WNCVZ/p/PFSkNDmLJtzIGb5eD7qj6erOQkomjM.
Are you sure you want to continue connecting (yes/no)? yes
Warning: Permanently added '192.168.30.31' (ECDSA) to the list of known hosts.
christopher@192.168.30.31's password:
PS C:\Users\Christopher>
```

Test Passwordless SSH Connectivity to Remote Linux Device

Finally, verify that you can SSH to the remote Linux device with the `ssh` command. An example to a remote Linux device at IP address 192.168.30.31 is shown below. Note how a password did not need to be entered in order for us to establish SSH connectivity to the remote Linux device.

Plaintext



```
PS C:\Users\Christopher> ssh 192.168.30.31
Last login: Sat May 23 12:44:51 2020 from 192.168.10.139
[christopher@linux ~]$ who
christopher pts/0      2020-05-24 19:35 (192.168.10.113)
```

References

The instructions for this blog post were heavily inspired by [Scott Hanselman's blog post](#) on the subject.

This post is licensed under [CC BY 4.0](#) by the author.

Share:

Further Reading

[Sep 24, 2022](#)

[Refactoring Python Network Automation for Unit Tests](#)

[Network operators who embrace automation to streamline their daily wor...](#)

[Sep 24, 2022](#)

[Cisco IOS - 'No matching host key type found' During SSH](#)

[A common issue seen when attempting to SSH into a network device running Cisco...](#)

[Sep 24, 2022](#)

[Cisco IOS - 'No matching key exchange found' During SSH](#)

[A common issue seen when attempting to SSH into a network device running Cisco...](#)

OLDER

[Quick Lab - RIPv2 Auto Summary](#)

NEWER

[Normalizing JSON Data Structure Output on Cisco NX-OS with Python](#)



Post

