

Unix & Linux Stack Exchange is a question and answer site for users of Linux, FreeBSD and other Un\*x-like operating systems. It only takes a minute to sign up.

Sign up to join this community

Anybody can ask a question



Anybody can answer

The best answers are voted up and rise to the top

# UNIX & LINUX

## How to dd a remote disk using SSH on local machine and save to a local disk

Asked 9 years, 8 months ago   Modified 1 year, 6 months ago   Viewed 241k times



How can I create a backup of a remote disk using SSH on my local machine and save it to a local disk?

125



I've tried the following:



```
ssh hostname@my.ip.address "sudo dd if=/dev/sdX " | \  
dd of=/home/username/Documents/filename.image`
```



However, I receive the following error:

By clicking "Accept all cookies", you agree Stack Exchange can store cookies on your device and disclose information in accordance with our [Cookie Policy](#).

Accept all cookies

Necessary cookies only

Customize settings

asked May 31, 2014 at 4:30



QuOrk

1,391

2

10

9

Sorted by:

Highest score (default)





If your intent is to backup a remote computer's **HDD A** via SSH to a single file that's on your local computer's HDD, you could do one of the following.

186



## Examples

*run from remote computer*



```
$ dd if=/dev/sda | gzip -1 - | ssh user@local dd of=image.gz
```



*run from local computer*

```
$ ssh user@remote "dd if=/dev/sda | gzip -1 -" | dd of=image.gz
```

## Live example

```
$ ssh skinner "dd if=/dev/sda5 | gzip -1 -" | dd of=image.gz
208782+0 records in
208782+0 records out
106896384 bytes (107 MB) copied, 22.7608 seconds, 4.7 MB/s
116749+1 records in
116749+1 records out
59775805 bytes (60 MB) copied, 23.9154 s, 2.5 MB/s
```

```
$ ll | grep image.gz
-rw-rw-r--.  1 saml saml  59775805 May 31 01:03 image.gz
```

## Methods for monitoring?

1. Login via `ssh` in another terminal and `ls -l` the file to see what its size is.

2. You can use `pv` to monitor the progress of a large `dd` operation, for instance, for the

```
@local dd of=image.gz
```

ts. Something like:

By clicking "Accept all cookies", you agree Stack Exchange can store cookies on your device and disclose information in accordance with our [Cookie Policy](#).

Accept all cookies

Necessary cookies only

Customize settings

inally left via comments by [@Ryan](#) to make them more obvious.

I tried this for a similar problem (backing up remote computer ONE 's hard drive to remote computer TWO 's storage), like this: `ssh root@TWO dd if=/dev/sda1 | ssh root@TWO dd of=/root/Public/ONE/sda1.img` `<br />[root@ONE]# dd if=/dev/sda1 | ssh root@TWO dd of=/root/Public/ONE/sda1.img` `<br />409600+0 records in 409600+0 records out 209715200 bytes (210 MB) copied, 0.894929 s, 234 MB/s Pseudo-terminal will not be allocated because stdin is not a terminal root@TWO's password: The problem is that the /root/Public/ONE/sda1.img file was created on ONE , not on TWO as expected. How do I fix this? – Urhixidur Jul 15, 2015 at 13:59`

1 Can someone give us an example of using `pvc` from the local machine? Thank you. – [TCB13](#) Dec 16, 2015 at 15:08

it is better to use `lbzip2` or `pigz` insted of `gzip` – [Shimon Doodkin](#) Mar 10, 2016 at 0:15

12 Regarding monitoring: Newer `dd` versions also have the `status=progress` option. Thus, you do not need to run `pskill -USR1 dd` from another terminal anymore. – [Till Schäfer](#) Jan 2, 2018 at 15:23

2 `restore: gunzip -c xxx.gz | pv | dd of=/dev/sda1` – [nobjta\\_9x\\_tq](#) Apr 11, 2020 at 6:12



15



The error you receive is due to the use of `sudo` remotely (you'd be asked for the password but you don't have a `tty` to enter it). On the other hand, as a normal user you can't normally use simply `dd` as suggested in other answer (you don't have the required permissions to the device). You can solve the problem by giving yourself rights to execute `dd` as `sudo` without a password. You can do this by editing the `sudoers` file (on the remote!):



`sudo visudo`



add the following line:

```
userfoo ALL=(ALL) NOPASSWD: /bin/dd if=/dev/sdX
```

`test=test.dd`

...y in `sudoers`, allowing you to run  
permissions to the minimum you

By clicking “Accept all cookies”, you agree Stack Exchange can store cookies on your device and disclose information in accordance with our [Cookie Policy](#).

Accept all cookies

Necessary cookies only

Customize settings

Or, you can just run 'sudo ls' at the applicable end (and type in password), just prior to running the 'sudo dd ...' command – [MikeW](#) Feb 19, 2019 at 11:28



[elfantin](#)

- 1 With newer versions of dd adding status=progress even allows monitoring copy progress. – [sensslen](#) May 21, 2019 at 9:16

This is the correct answer regarding the error message. But you could add these alternatives: use `ssh -t` to execute the command with a `tty` allowing for interactive password input / use `sudo -S` to read password from `stdin` even without a `tty` . – [acran](#) Nov 1, 2020 at 14:34

- 3 @MikeW note that this might not work since by default `sudo` only remembers the authentication for the same console session, see `timeout_type` in `man 5 sudoers` . – [acran](#) Nov 1, 2020 at 14:35



I've just used a modified version on a virtual Linux Mint box to clone a physical hard drive on an aging RedHat server.

8

I ran the following as root on the virtual box:



```
ssh root@192.168.1.5 "dd if=/dev/cciss/c0d0" | dd of=/dev/sdb
```



- 192.168.1.5 is the physical Red Hat Enterprise Linux 2.1 box.
- /dev/sdb is a new virtual disk, which when finished cloning will be the basis of a virtual version of the old dying physical box.

Share Improve this answer

Follow

edited Apr 25, 2016 at 1:01



[slm](#) ♦

368k

121

774

878

answered May 20, 2015 at 4:47

[Fred Nerk](#)

[Nerk!](#) 81 1 1

By clicking “Accept all cookies”, you agree Stack Exchange can store cookies on your device and disclose information in accordance with our [Cookie Policy](#).

Accept all cookies

Necessary cookies only

[Customize settings](#)



Combining these answers allowed me to clone to another Linux host and avoid the 'permission denied' error:

7



- RPI4 SD card ( `/dev/mmcblk0` - this clones the entire card)
- avoid permission issue by prompting for elevated privilege ( `sudo -s` )
- see progress as it copies ( `status=progress` )
- compressing the copy ( `gzip` )
- specify buffer size ( `bs=64k` ) for improved speed. You can specify higher values. please read [this](#)

```
ssh user@1.1.1.1 "sudo -S dd if=/dev/mmcblk0 bs=64k status=progress | gzip -1 -"
| dd of=rpiimg.gz bs=64k
```

Share Improve this answer

Follow

edited Nov 1, 2020 at 0:18



Hummus\_Ful

3 3

answered Nov 28, 2019 at 3:38



Paul Sturm

171 1 3

1 great - works like a charm. – [opinion\\_no9](#) Mar 9, 2023 at 20:12

By clicking “Accept all cookies”, you agree Stack Exchange can store cookies on your device and disclose information in accordance with our [Cookie Policy](#).

Accept all cookies

Necessary cookies only

Customize settings



2



I was in a similar situation recently. The difference for me was, that

- due to security measures `root ssh` access was disabled
- `sudo` was not installed (deliberately)

So what I did was:

1. examine device file permissions (grep for appropriate block device naming scheme (`hd`, `sd`, `nvme`, etc.))

```
user@machine:~$ ls -la /dev/ |grep sd
brw-rw---- 1 root disk      8,  0 Nov 22 13:36 sda
brw-rw---- 1 root disk      8,  1 Nov 22 13:36 sda1
brw-rw---- 1 root disk      8,  2 Nov 22 13:36 sda2
brw-rw---- 1 root disk      8,  5 Nov 22 13:36 sda5
```

2. add the user to the `disk` group

```
root@machine:~$ usermod -aG user disk
```

3. then run the `dd` the same way you already tried (but w/o `sudo`)

```
ssh user@my.ip.address "dd if=/dev/sdX " | dd of=/home/username/Documents/
filename.image
```

(or also chain-in the `gzip` as others suggested)

Share Improve this answer Follow

answered Nov 23, 2020 at 10:03



helvete

151 4

(association bonus) in order to answer this  
from spam and non-answer activity.

By clicking "Accept all cookies", you agree Stack Exchange can store cookies on your device and disclose information in accordance with our [Cookie Policy](#).

Accept all cookies

Necessary cookies only

Customize settings