

MOTOR TYPE	POWER		U _N	n _N	I _N	I _A	η- EFFICIENCY			Cosφ - POWER FACTOR			τ _N	τ _N	AXIAL LOAD
							η - VERİMLİLİK			Cosφ - GÜÇ FAKTÖRÜ					
	GÜÇ						at % load / % yükte			at % load / % yükte					EKSENEL YÜK
MOTOR TİPİ	HP	kW	V	rpm	A	A	50	75	100	50	75	100	Nm	Nm	kN
KM7-30	30	22	380	2880	46.3	183.8	83	84	84	0.76	0.82	0.86	71.9	91.0	26.5
			400	2900	44.5	176.7	82	84	85	0.75	0.81	0.85	71.7	101.6	
			415	2910	43.4	172.3	81	84	85	0.7	0.77	0.83	71.5	109.9	
KM7-35	35	26.5	380	2880	55.1	218.7	84	85	85	0.66	0.75	0.86	86.9	116.2	26.5
			400	2900	52.9	210.0	83	85	85	0.63	0.74	0.85	86.6	129.9	
			415	2910	51.6	204.9	82	85	86	0.61	0.72	0.83	86.4	140.6	
KM7-40	40	30	380	2880	62.4	247.7	85	86	85	0.65	0.74	0.86	98.4	129.9	26.5
			400	2900	59.2	235.0	84	86	86	0.63	0.73	0.85	98.1	145.2	
			415	2910	57.8	229.5	83	86	87	0.61	0.71	0.83	97.8	156.6	
KM7-50	50	37	380	2880	74.3	295.0	85	86	86	0.78	0.85	0.88	121.9	174.2	45
			400	2900	72.2	286.6	84	86	86	0.75	0.82	0.86	121.6	195.7	
			415	2910	70.4	279.5	83	86	87	0.71	0.8	0.84	121.4	212.5	
KM7-60	60	45	380	2870	90.3	358.5	85	86	86	0.76	0.84	0.88	148.7	226.2	45
			400	2890	87.8	348.6	84	86	86	0.75	0.83	0.86	148.5	252.7	
			415	2900	85.7	340.2	83	86	87	0.74	0.8	0.84	148.3	274.9	
KM7-70	70	52	380	2860	105.6	419.2	85	86	86	0.78	0.83	0.87	171.5	260.9	45
			400	2880	102.7	407.7	85	86	86	0.76	0.82	0.85	171.2	291.4	
			415	2890	100.2	397.8	84	86	87	0.73	0.79	0.83	170.8	316.6	
KM7-75	75	55	380	2900	112.9	448.2	85	85	84	0.7	0.84	0.88	181.9	276.7	45
			400	2905	109.8	435.9	84	85	84	0.78	0.83	0.86	181.6	309.0	
			415	2910	107.1	425.2	83	85	85	0.77	0.8	0.84	181.2	335.8	
KM7-80	80	60	380	2900	123.3	489.5	85	85	84	0.76	0.84	0.88	198.6	302.1	45
			400	2905	120.1	476.8	84	85	84	0.75	0.83	0.86	198.3	337.5	
			415	2905	116.9	464.1	83	85	85	0.74	0.8	0.84	198.0	367.0	
KM7-90	90	67	380	2900	137.7	546.7	85	85	84	0.76	0.84	0.88	222.0	337.7	45
			400	2905	133.9	531.6	84	85	84	0.75	0.83	0.86	221.6	377.1	
			415	2905	130.5	518.1	83	85	85	0.74	0.8	0.84	221.2	409.9	
KM7-100	100	75	380	2900	154.8	614.6	83	85	84	0.74	0.8	0.84	284.5	432.8	45
			400	2900	150.4	597.1	83	85	84	0.74	0.8	0.84	284.1	483.5	
			415	2905	146.3	580.8	82	85	85	0.73	0.79	0.83	283.7	525.8	